

Simpleplot 2-15

**SIMPLEPLOT
Reference Manual**

BUSS Ltd.

SIMPLEPLOT Reference Manual (version 2-15)

Copyright © 2000 by

BUSS Ltd.
Business and Innovation Centre
Angel Way
Bradford
West Yorkshire
BD7 1BX
United Kingdom

Telephone 01274 841396
 +44 1274 841396
Fax 01274 841388
 +44 1274 841388

Web Site <http://www.buss.co.uk/buss>
Email info@buss.co.uk

All rights reserved.

Ninth Edition, October 2000

Contents

Preface	v
Introduction	1
Subroutine Specifications	3
Index	421

Preface

SIMPLEPLOT is a library of FORTRAN subroutines for plotting graphs. A wide variety of graphs can be drawn as well as more general pictures and diagrams. Facilities are biased towards the graphical representation of data; in particular, scientific data.

SIMPLEPLOT was originally designed for programmers who wanted to draw pictures of their data with minimum programming effort. Although it still achieves this goal, SIMPLEPLOT has developed into a much more powerful tool for professional software engineers.

Six separate sections constitute the complete SIMPLEPLOT Mark 2:

- The basic package for conventional graph plotting – x - y plots and polar plots.
- Additional subroutines for 3-dimensional plotting – contour maps and surface pictures of 3-D data.
- Additional subroutines for presentation graphics – bar charts, histograms and pie charts.
- *SIMPLEPLOT Volumes* – perspective pictures of 4-dimensional data.
- *SIMPLEPLOT Maps* – for representing data based on geographical coordinate systems.
- *SIMPLEPLOT ViSualization* – for full colour modelling of functions of two, three and four variables.

SIMPLEPLOT-PLUS refers to a SIMPLEPLOT library which is made up from the first three sections and contains many additional facilities.

This manual covers all subroutines supported in the 2-14 release of the library. Further utilities have also been released and are specified in the SIMPLEPLOT Supplement.

Graphics device interface

The SIMPLEPLOT library is independent of any single graphics system but, rather than describe SIMPLEPLOT as either device *independent* or device *dependent*, it is more appropriate to describe it as device *sensitive* with a device independent interface for the user. This means that the user is protected from having to know about the features of the target output device, but SIMPLEPLOT makes as much use of these features as possible.

The SIMPLEPLOT library is usually supplied with the BUSS *Single Entry Point* (S.E.P.) device driver system; this includes interfaces to a large number of graphics devices, and the range of validated device drivers is constantly being extended. Moreover, SIMPLEPLOT can address graphics devices directly, or through a separate low-level graphics systems (*eg.* GKS, CGM) or graphics languages (*eg.* PostScript).

The *SIMPLEPLOT Reference manual* (8th edition) is a comprehensive reference manual for the SIMPLEPLOT library of graph drawing subroutines, and covers sections 1, 2, 4, 7 and SIMPLEPLOT-PLUS. It can be used as a manual in its own right but, for an introduction to SIMPLEPLOT, please refer to the *SIMPLEPLOT Primer*.

Overview

The *SIMPLEPLOT Reference manual* is organized as an alphabetical listing of subroutine specifications, with an introduction, technical appendix and index:

- Introduction to the *SIMPLEPLOT Reference manual*
- Subroutine specifications
- Index

Other appendices, which were listed in previous additions of the *SIMPLEPLOT Reference manual* can now be found in the *SIMPLEPLOT 2-14 Supplement*.

Software version

This manual is based on SIMPLEPLOT Mark 2, version 2-14.

Target audience

The *SIMPLEPLOT Reference manual* has been written with the following readers in mind:

- All users of SIMPLEPLOT who need details of subroutine arguments and behaviour.
- Existing users of SIMPLEPLOT who wish to update their knowledge (and programs) to include the new facilities of SIMPLEPLOT version 2-14.

All readers should be familiar with programming in FORTRAN on their host computer system.

Related documents

Related documents include

- The *SIMPLEPLOT 2-14 Supplement*, which gives appendices and details of the facilities introduced in SIMPLEPLOT version 2-14.
- The *SIMPLEPLOT 2-13 Supplement*, which gives details of the facilities introduced in SIMPLEPLOT version 2-13.
- The *SIMPLEPLOT Primer*, which gives an introduction to SIMPLEPLOT, especially those facilities available for plotting 2-D data.
- *SIMPLEPLOT 3-D*, which describes how to draw representations of 3-D data including the new waterfall charts, stored curve coordinates and labelled curves.
- *SIMPLEPLOT Volumes*, which describes subroutines for drawing perspective volumes of 3-D REAL arrays.

- *SIMPLEPLOT Maps*, which describes subroutines for plotting geographical data.
- *SIMPLEPLOT ViSualization*, which describes subroutines for perspective drawing of functions of two, three and four variables.

How to report problems

If you have any problems with SIMPLEPLOT software or its associated products and services please notify us on one of our Software Performance Report (SPR) forms. One of these should be sent out with every software kit – please photocopy it or contact us if you would like extra copies.

Conventions

The following conventions are used in this manual for subroutine specifications. All specifications are given in a similar format whether they are classified as graphics, specification or auxiliary subroutines.

- Numbers in square brackets, [1], [2], [3] and [4], within subroutine specifications relate to the use of SIMPLEPLOT with plotting devices which have program-selectable pens; these pointers may be reset as often as required (see PEN and SETPNS).
- Subroutines which take text strings as arguments are provided in two forms but both use FORTRAN 77 CHARACTER expressions. The only difference between them is that the routines which have the extra INTEGER argument interpret this number as the exact length of the text string; in this case,
 - There is no removal of trailing spaces.
 - Only the specified number of characters are used; this may lead to truncation of the string itself.
- Potential diagnostic messages are given in each subroutine specification with a number indicating the type of message and therefore at which diagnostic level it is issued. Additional information about individual messages is given in Appendix M in the *SIMPLEPLOT 2-14 Supplement*.

Subroutine Specifications

SUBROUTINE NAME (ARG1, ARG2)

Name

NAME – brief summary line

Availability Section 1, 2, 4, 5, 6, 7 or +, released version 2-*n*.

Arguments Throughout the specifications, arguments of type **INTEGER** have been given names starting with I–N, and arguments of type **REAL** have been given names starting with the letters A–H and O–Z.

IN only arguments are identified as *expression*; a variable name, a constant value or an expression may be used for such arguments.

INOUT or OUT only arguments are identified as *variable*.

RVAL	REAL expression	Expression with floating point value
IVAL	INTEGER expression	Expression with integer value
TORF	LOGICAL expression	Expression with logical value (.TRUE. or .FALSE.)
CHAR	CHARACTER*1	Expression with single character value
CHTYPE	CHARACTER*2	Expression with two character value
CAP	STRING expression	Expression with any length character value
VARX	REAL variable	Variable of type REAL
STR	STRING variable	Variable of type CHARACTER* <i>n</i>
LABARR	STRING array	Array of string values
IARR	INTEGER array	1-dimensional array of INTEGER values
I2ARR	INTEGER 2-D array	2-dimensional array of INTEGER values
DARR	REAL array	1-dimensional array of REAL values
D2ARR	REAL 2-D array	2-dimensional array of REAL values
D3ARR	REAL 3-D array	3-dimensional array of REAL values

Subroutine specifications are listed alphabetically regardless of whether they belong to Section 1, 2, 4, 7 or plus.

**SUBROUTINE ADDCP7 (CAP)
SUBROUTINE ADDCAP (CAP, NCAP)**

Name

ADDCP7 – to draw a caption in a previously defined area.

Availability Section 1, released before version 2-5.

Arguments

CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

ADDCAP/ADDCP7 draws [2] the caption, CAP, in the next position in the area defined by DEFCAP (or DEFKEY).

When a key or caption area is defined, a pointer to the top space in the area is created. As key entries or captions are inserted, the pointer is automatically moved down to the next vacant space.

REAL and INTEGER values can be converted to text strings using the conversion subroutines, KREAL and KNUMB respectively.

Diagnostics

(Caption truncated)²
 (Key/caption area full)²
 (No active key/caption area)²

See also

ADDJST, ADDTOP, BLNKKY, DEFCAP, QKYCAP, RESNXT and TEXTLF.

SUBROUTINE ADDJST (JCHAR)**Name**

ADDJST – to specify how entries in caption areas/keys are to be justified.

Availability Section 4, released before version 2-5.

Argument

JCHAR CHARACTER*1 Justification of key entries/captions

JCHAR *Horizontal justification*

'C' Centred

'L' Left justified

'R' Right justified

'D' Default

Description

By default, captions drawn by ADDCP7 and key entries drawn by *KY/*K7 are left justified within the space available; composite keys drawn by SHKEYS, MPK7H/MPKYH and MPK7V/MPKYV have a centred caption, followed by right-justified numeric key entries (for vertical map keys) or left-justified text entries.

ADDJST changes the justification of key entries and captions. ADDJST also affects the justification of entries in segment labels on pie charts (see PIINCL).

Default

CALL ADDJST('D') restores the default.

See also

ADDCP7, BOTHK7, FILLK7, LINEK7, MARKK7, MPK7H, MPK7V, PIINCL, SHDEK7 and SHKEYS.

SUBROUTINE ADDTOP

Name

ADDTOP – to reset the current key/caption usage pointer to the top of sequence.

Availability Section 4, released before version 2-5.

Arguments

None.

Description

When a key or sequence of captions is set up, a pointer to the top space in the rectangle is created. As key entries or captions are inserted, the pointer is automatically moved down to the next vacant space. **ADDTOP** sets the pointer back to the top.

For example, to produce two sets of captions, left justified and right justified in the same caption area, once the first sequence has filled the area from top to bottom, **ADDJST** can specify right justification, **ADDTOP** sets the pointer back to the top and then the right justified captions can be drawn.

See also

ADDCP7, ADDJST, DEFCAP and DEFKEY.

SUBROUTINE ARHEAD (PROP)**Name**

ARHEAD – to specify the proportional size of arrow heads.

Availability Section 4, released version 2-6.

Argument

PROP REAL expression Proportion of head w.r.t. to shaft

Description

By default, arrows are drawn with heads of a constant size, related to the size of text. ARHEAD specifies variably sized arrow heads such that each head is proportional to the length of the shaft. The ratio of head size to shaft length is indicated by the argument PROP (0.2 gives reasonable results).

Default

CALL ARHEAD(0.0) restores the default.

See also

ARROW, ARSHFT and TEXTSZ.

SUBROUTINE ARROW (XFROM, YFROM, XTO, YTO)**Name**

ARROW – to draw an arrow between two specified points.


Availability Section 4, released version 2-6.

Arguments

XFROM,	REAL expressions	Coordinates of the end of the arrow
YFROM		in units of plotting scales
XTO, YTO	REAL expressions	Coordinates of the head of the
		arrow in units of plotting scales

Description

ARROW draws [1] an arrow from (x_{from}, y_{from}) to (x_{to}, y_{to}) with its head at (x_{to}, y_{to}) . The position and direction of the arrow are completely defined by the four arguments which specify the coordinates of the end and the head of the arrow in terms of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine KXYXY.



If $x_{from} = x_{to}$ and $y_{from} = y_{to}$, nothing is drawn.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

$(**x_1, y_1, x_2, y_2**)^2$

See also

ARHEAD, ARSHFT, CLIPLV and KXYXY.

SUBROUTINE ARSHFT (TORF)**Name**

ARSHFT – to specify whether arrows are to include a shaft.

Availability Section 4, released version 2-6.

Argument

TORF LOGICAL expression Whether shaft is to be included

Description

By default, arrows are drawn with both a shaft and an arrow head but it can be required to draw arrow heads on existing lines. ARSHFT specifies whether or not the shaft is to be drawn by ARROW. The arguments of ARROW are still needed to define the direction of the arrow head and, if variable sized arrow heads have been requested by ARHEAD, to control the size of arrow heads.

Default

CALL ARSHFT(.TRUE.) restores the default.

See also

ARROW and ARHEAD.

SUBROUTINE AXCLR (CHAXIS, ILEVEL)**Name**

AXCLR – to specify the level of annotation drawn with the axis.

Availability Section 1, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 ILEVEL INTEGER expression Level of axis annotation

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

ILEVEL Effect

0	Tick marks and annotation labels are drawn
1	Only axis line drawn

Description

By default, when an axis is drawn it is subdivided and annotated at regular intervals using automatically generated labels. Calling **AXCLR(CHAXIS,1)** before the axis is drawn suppresses the drawing of tick marks and annotation labels; user-defined labels can then be drawn using **AXLAB7** or **AXTXT7**.

A fuller description of the values of **CHAXIS** is given in Appendix T of the *SIMPLEPLOT Supplement*. **AXCLR** can be used for all axis types.

Diagnostics

(Invalid axis type: *XX*)¹

Default

CALL **AXCLR(CHAXIS,0)** returns to automatic annotation of the specified axis.

See also

AXIS7, **AXLAB7** and **AXTXT7**.

SUBROUTINE AXCRSS (CHAXIS, CROSS)**Name**

AXCRSS – to specify the intersection of one axis with its natural pair.

Availability Section 1, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 CROSS REAL expression Position of axis in units of the
 ‘other’ scale

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	√	√	√	√	×	×	×	×	×	√	√	×	×	×	×

Description

By default, a Cartesian or radial axis is positioned such that it intersects the other axis at zero, or the value closest to zero on the scale. An angular axis intersects the radial axis at the outer extreme of the radial scale. AXCRSS specifies an alternative position for an axis. AXCRSS must be called before an axis is drawn.

If the point of intersection lies outside the plotting scale, the axis is drawn at the edge of the picture nearest the intersection.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹

(Invalid axis type: XX)¹

Default

CALL AXCRSS(CHAXIS,0.0) restores the default except for an angular axis for which you must specify the outer radial value or CALL AXLOCN('AP','D').

See also

AXIS7 and AXLOCN.

**SUBROUTINE AXES7 (CAPX, CAPY)
SUBROUTINE AXES (CAPX, NCAPX, CAPY, NCAPY)**

Name

AXES7 – to start a new picture and draw axes.

Availability Section 1, released before version 2-5.

Arguments

CAPX	STRING expression	Caption for horizontal axis
CAPY	STRING expression	Caption for vertical axis
NCAPX	INTEGER expression	Number of characters in CAPX
NCAPY	INTEGER expression	Number of characters in CAPY

Description

AXES7 starts a new picture and draws [1] a pair of axes which are annotated [2] with the scales which exist when the call occurs. The characteristics of these axes can be controlled or augmented by all the other axis subroutines which affect Cartesian or polar axes (see below).

If polar units have been specified by EQSCAL, AXES7 draws a polar framework with one radial axis at the initial θ value, labelled with CAPX; if the angular range is less than a cycle, another radial axis is drawn at the other end of the range, labelled with CAPY; an angular axis is drawn covering the angular range.

If scales are extended to provide similar linear scales in x and y (see EQSCAL), the axes annotate the requested range rather than the extended range. If a box is required to surround these axes, DRAWBX can be used to draw a box on the current picture.

See also

AXIS7, DRAWBX, EQSCAL, NEWPIC and POLAR7.

SUBROUTINE AXGRID (CHAXIS, ILEVEL, LTYPE)**Name**

AXGRID – to specify the style of grids drawn in association with axis subdivisions.

Availability Section 1, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 ILEVEL INTEGER expression Level of grid
 LTYPE INTEGER expression Type of broken line pattern

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	×	×	×	✓	✓	✓	✓	×	×	×	×

ILEVEL *Level of grid*

0	No grid
1	Grid lines drawn [3] at annotated and major unannotated tick marks
2	Grid lines drawn [4] at all tick marks including minor

Description

By default, when an axis is drawn no grid lines are drawn. AXGRID specifies that grid lines are drawn in association with axis subdivisions.

Grids can have any of the available broken line patterns as specified by LTYPE. If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹
 (Invalid axis type: XX)¹

Default

CALL AXGRID(CHAXIS,0,-999) restores the default.

See also

AXIS7, AXLAB7, AXMAJ, AXMIN, AXTXT7 and BUNLPR.

**SUBROUTINE AXIS7 (CHAXIS, CAP)
SUBROUTINE AXIS (CHAXIS, CAP, NCAP)**

Name

AXIS7 – to draw an axis on the current picture.

Availability Section 1, released version 2-11.

Arguments

CHAXIS	CHARACTER*2	Axis type
CAP	STRING expression	Axis caption
NCAP	INTEGER expression	Number of characters in CAP

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	×

Description

AXIS/AXIS7 draws [1] an axis over the current range, annotated [2] according to the scale which exists when the call occurs.

The axis caption, CAP, is drawn [2] in the centre of and parallel to the axis, on the same side of the axis as the axis annotation; the caption is ignored for polar angular axes (CHAXIS='AP').

If AXGRID has been called to requests grids, grid lines are drawn at axis subdivisions.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Invalid axis type: XX)¹

(Inappropriate axis type: XX)²

See also

AXCLR, AXCRSS, AXGRID, AXLBAN, AXLBGP, AXLBJS, AXLBLV, AXLOCN, AXRNGE, AXSBDV, AXSETK and AXSUBS

SUBROUTINE AXLAB7 (CHAXIS, W, CAP)
SUBROUTINE AXLAB (CHAXIS, W, CAP, NCAP)

Name

AXLAB7 – to draw a single axis annotation label and tick mark.

Availability Section 1, released version 2-11.

Arguments

CHAXIS	CHARACTER*2	Axis type
W	REAL expression	Position along axis in units of the plotting scales
CAP	STRING expression	Annotation label
NCAP	INTEGER expression	Number of characters in CAP

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	√	√	√	√	√	√	√	√	×	√	√	√	√	√	×

Description

By default, when an axis is drawn it is subdivided and annotated at regular intervals using automatically generated labels. If additional labels are required on an axis, each one can be drawn by a separate call of AXLAB/AXLAB7. A tick mark is drawn [1] at position *w* along the axis, and labelled [2] with the caption, CAP.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

- (Invalid axis type: XX)¹
- (Inappropriate axis type: XX)²

See also

AXCLR, AXGRID, AXLBAN, AXLBJS, AXLSL, AXSBTK and AXTXT7.

SUBROUTINE AXLBAN (CHAXIS, ACHAR)**Name**

AXLBAN – to specify the style of annotation labels on an axis.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 ACHAR CHARACTER*1 Position of annotation

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ^U	✓ ^U	✓ ^U	×

U: 'P' receding, 'F' following and 'I' inside unavailable

ACHAR Style

'D' Default – towards the outside
 'F' Following axis (in direction of other axis)
 'I' Towards the inside of the picture
 'N' None – annotation labels omitted
 'O' Towards the outside of the picture
 'P' Preceding axis (in direction of other axis)

Description

By default, all axes are annotated towards the outside of the picture if there is room, or towards the inside otherwise. AXLBAN specifies the style of annotation labels according to the value of ACHAR.

If there is insufficient space for labels in the specified location, annotation is drawn elsewhere but is not omitted. If ACHAR='I', 'O', 'P' or 'F', and the annotation request cannot be satisfied, a diagnostic is issued.

A fuller description of the values of CHAXIS and the interpretation of 'P' and 'F' is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(AXLBAN not satisfied)²
 (Invalid axis type: XX)¹

Default

CALL AXLBAN(CHAXIS,'D') restores the default.

See also

AXIS7, AXLAB7, AXLBJS, AXSBTK and AXTXT7.

SUBROUTINE AXLBGP (CHAXIS, ILEVEL)**Name**

AXLBGP – to specify the level of axis annotation near an intersection.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 ILEVEL INTEGER expression Level of annotation at intersection

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	×	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	✓

ILEVEL *Effect*

0	All annotation drawn
1	Annotation omitted near intersection

Description

By default, annotation labels which could be ambiguous or coincident near the intersection of two axes, are omitted from both. CALL AXLBGP(CHAXIS,0) specifies that no gap is to be left in the annotation of the specified axis near an intersection.

AXLBGP must be called before an axis is drawn.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹
 (Invalid axis type: XX)¹

Default

CALL AXLBGP(CHAXIS,1) restores the default.

See also

AXCRSS and AXIS7.

SUBROUTINE AXLBJS (CHAXIS, JCHAR)**Name**

AXLBJS – to specify the justification of axis annotation.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
JCHAR CHARACTER*1 Justification of annotation

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	×	×	×	✓	✓	×	✓	✓	×	×	×	×

JCHAR *Justification of annotation*

'B' Between tick marks (centred)
'C' Centered on the tick mark
'F' Following the tick mark
'P' Preceding the tick mark
'D' Default position

Description

By default, axis annotation labels are drawn preceding the subdivision tick mark with which they are associated. AXLBJS specifies justification of annotation relative to the tick marks.

AXLBJS must be called before an annotation label is drawn (either as part of an axis) or before labels are drawn (using AXLAB7 or AXTXT7).

A fuller description of the possible values of CHAXIS and the interpretation of 'P' and 'F' is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹
(Invalid axis type: XX)¹

Default

CALL AXLBJS(CHAXIS, 'D') restores the default.

See also

AXIS7, AXLAB7, AXLBAN, AXLBSL and AXTXT7.

SUBROUTINE AXLBLV (CHAXIS, ILEV)

Name

AXLBLV – to specify the level of additional annotation on some axes.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 ILEV INTEGER expression Level of annotation

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	\sqrt{NL}	\sqrt{NL}	×	✓	×	×	×	×	×	×	×	×	×	×	×

NL: non-linear scales only

ILEV	<i>Non-linear Cartesian axes</i>	<i>Angular polar axis</i>
0	determined by scales	30°, 60°, 120°, 150°, 210°, 240°, 300°, 330°
1	powers of 10 only	plus 0°, 90°, 180°, 270°
2	3	plus 10° intervals
3	2,5	—
4	1,2,3,4,5,6,7,8,9	—

Description

By default, axes are subdivided and annotated at regular intervals but non-linear axes and angular polar axes may need additional axis annotation due to the small extent of scale displayed. AXLBLV specifies the level of additional labelling.

AXLBLV must be called before an non-linear axis is drawn.

SIMPLEPLOT may omit these labels due to lack of space.

The possible values of CHAXIS are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹

(Invalid axis type: XX)¹

Default

CALL AXLBLV(CHAXIS,0) restores the default.

See also

AXCLR, AXIS7, AXLAB7 and AXTXT7.

SUBROUTINE AXLBSL (CHAXIS, SCHAR)

Name

AXLBSL – to specify the slope of used-defined axis annotation.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 SCHAR CHARACTER*1 Direction of slope of labels

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	×	✓	✓	✓	✓	✓	✓	✓	×	×	×	×

SCHAR *Direction of label*

'H' Horizontal
 'V' Vertical
 'S' Sloping
 'D' Default (different for labels of different lengths)

Description

By default, user-defined axis annotation labels are drawn horizontally for short labels, but long labels are sloped by staggering the characters in an attempt to make efficient use of the limited space. Labels added to axes are considered to be long if they contain six or more characters but no escape sequences. Axis labels which contain active escape sequences are never sloped.

AXLBSL specifies their slope according to the value of SCHAR. AXLBSL must be called before user-defined annotation labels are drawn (using AXLAB7, AXTXT7 or BARC7). Axis labels on an angular axis are always horizontal.

A fuller description of the possible values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹
 (Invalid axis type: XX)¹

Default

CALL AXLBSL(CHAXIS, 'D') restores the default.

See also

AXIS7, AXLAB7, AXLBAN, AXLBJS and AXTXT7.

SUBROUTINE AXLBSP (CHAXIS, CHAR1, CHAR2)**Name**

AXLBSP – to specify separators between label components of *time-date* axis annotation.

Availability Section plus, released version 2-12.

Arguments

CHAXIS CHARACTER*2 Axis type
 CHAR1 CHARACTER*1 Separator between first pair
 CHAR2 CHARACTER*1 Separator between second pair

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	×

Description

Time-date axis annotation labels are built from up to three components. By default, time components are separated by colons (*eg.* 12:00:00) and date components are separated by spaces (*eg.* 30 Mar 1990). AXLBSP specifies alternative single-character separators – CHAR1 between the first and second components, CHAR2 between the second and third components.

In addition to a user-specified character, there are two special codes for separators which can be specified for CHAR1 and/or CHAR2:

CHARi Meaning

'N' No separator, not even a space

'D' Default separator – ':' for Times, ' ' for Dates

Separators should not be confused with the prefix and suffix characters which can be controlled independently by TIMFMT and TIMLDC.

AXLBSP has no effect on numerical axes; it only works after AXLBTP has requested *time-date* scales. A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹

(Invalid axis type: XX)¹

Default

CALL AXLBSP(CHAXIS, 'D', 'D') restores the default.

See also

AX*, TIMFMT, TIMLDA and TIMLDC

SUBROUTINE AXLBTM (CHAXIS, COMP1, COMP2, COMP3)**Name**

AXLBTM – to specify components for *time-date* axis annotation.

Availability Section plus, released version 2-12.

Arguments

CHAXIS CHARACTER*2 Axis type
 COMP1 CHARACTER*2 Component for first label position
 COMP2 CHARACTER*2 Component for second label position
 COMP3 CHARACTER*2 Component for third label position

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	×

Description

By default, SIMPLEPLOT selects components for *time-date* axis labels according to the range of the relevant scale: times are in descending order (*eg.* hour/minute/second) and dates in ascending order (*eg.* day/month/year). AXLBTM specifies the components to be used, in the required order.

For only two components, and set COMP3 to 'NL' or ' '. For only one component, use COMP1, set COMP2 to 'NL' or ' ', and COMP3 is also ignored.

AXLBTM has no effect on numerical axes; it only becomes active after AXLBTP has been called to request *time-date* scales.

A fuller description of the values of CHAXIS and the interpretations of COMP1, COMP2 and COMP3 is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹
 (Invalid axis type: XX)¹
 (AXLBTM cancelled: XX)¹

Default

CALL AXLBTM(CHAXIS,'DF',' ',' ') restores the default.

See also

AX*.

SUBROUTINE AXLBTP (CHAXIS, CHTYPE)**Name**

AXLBTP – to specify *numeric* or *time-date* axis annotation.

Availability Section plus, released version 2-12.

Arguments

CHAXIS CHARACTER*2 Axis type
 CHTYPE CHARACTER*1 Annotation type – 'N'umeric,
 'D'ate or 'T'ime

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	×

CHTYPE *Annotation type*

'N' Numeric (default)
 'D' Date
 'T' Time

Description

By default, SIMPLEPLOT labels an axis with numeric labels representing a continuous **REAL** scale. Encoded times and dates are similar to any other **REAL** values therefore, by default, axis annotation represents numerical values. **AXLBTP** specifies that scale values on the specified axis represent time or date based data according to the value of **CHTYPE**.

A fuller description of the values of **CHAXIS** is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹
 (Invalid axis type: XX)¹

Default

CALL AXLBTP(CHAXIS, 'N') restores the default.

See also

AXIS7, AXLBSP and AXLBTM.

SUBROUTINE AXLOCN (CHAXIS, LCHAR)

Name

AXLOCN – to specify the location of an axis relative to the picture.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
LCHAR CHARACTER*1 Location of axis

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

LCHAR *Location of axis*

'P' Preceding the other axis
'F' Following the other axis
'D' Default

Description

By default, a Cartesian or radial axis is positioned such that it intersects the other axis at zero or at its lowest extreme; a z -axis precedes the x -axis and y -axis; similarly the numeric and labels axes on a bar chart precede one another. AXLOCN specifies the location of the axis with respect to the picture boundary.

AXLOCN must be called before an axis is drawn.

A fuller description of the values of CHAXIS and the interpretation of 'P' and 'F' is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Invalid axis type: XX)¹

Default

CALL AXLOCN(CHAXIS, 'D') restores the default.

See also

AXIS7, AXCRSS and AXLBGP.

SUBROUTINE AXMAJ (CHAXIS, W)**Name**

AXMAJ – to draw a single major axis subdivision.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
W REAL expression Position along axis in units of the plotting scales

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	×

Description

AXMAJ draws [1] a single major unannotated axis subdivision at position w along the specified axis; the tick mark is smaller than those drawn with annotated subdivisions. If grids have been specified, a grid line [3] is drawn.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Invalid axis type: XX)¹

(Inappropriate axis type: XX)²

See also

AXGRID, AXMIN, AXSBDV, AXSBMN, AXSBTK and AXSUBS.

SUBROUTINE AXMIN (CHAXIS, W)

Name

AXMIN – to draw a single minor axis subdivision.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
W REAL expression Position along axis in units of the plotting scales

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	×

Description

AXMIN draws [1] a single minor unannotated axis subdivision at position *w* along the specified axis; the tick mark is smaller than those drawn with annotated and major unannotated subdivisions. If grids have been specified, a grid line [4] is drawn.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Invalid axis type: XX)¹
(Inappropriate axis type: XX)²

See also

AXGRID, AXMAJ, AXSBDV, AXSBMN, AXSBTK and AXSUBS.

SUBROUTINE AXRNGE (CHAXIS, START, STOP)**Name**

AXRNGE – to specify the subrange over which an axis is to be drawn.

Availability Section 1, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
 START REAL expression Start of axis in units of scale
 STOP REAL expression End of axis in units of scale

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	✓

Description

By default, when an axis is drawn it is drawn over the entire range of the scale. AXRNGE specifies an alternative subrange for the specified axis. AXRNGE must be called before the axis is drawn.

This subrange cannot extend the axis beyond the limits of the scale. If one end of the subrange lies beyond the limits of the scale, only part of the subrange is drawn; if the whole of the subrange is outside the limits of the scale, the default applies.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹

(Invalid axis type: XX)¹

Default

The default is restored by calling AXRNGE with a zero range (*ie.* START=STOP). For example, CALL AXRNGE(CHAXIS,0.0,0.0).

See also

AXIS7 and SCALES.

SUBROUTINE AXSBDV (CHAXIS, OFFSET, DELTA)

Name

AXSBDV – to specify the interval at which a linear axis is to be subdivided and annotated.

Availability Section 1, released version 2-11.

Arguments

CHAXIS	CHARACTER*2	Axis type
OFFSET	REAL expression	Offset value for subdivisions
DELTA	REAL expression	Interval between subdivisions of axis in units of the scale

[illegible]

L: Linear scales only

Description

By default, linear axes are subdivided at equal intervals chosen for clarity to give between 5 and 10 subdivisions at multiples of a ‘simple’ number. **AXSBDV** specifies the annotation interval and an offset from which divisions are calculated. **AXSBDV** must be called before an axis is drawn.

If DELTA is less than $1.0E-4 \times$ axis range, the default interval is used instead and, at diagnostic level 2, a diagnostic message is issued (see below).

A fuller description of the values of **CHAXIS** is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹

(Invalid axis type: XX)¹

(Too many axis intervals: default used)¹

Default

CALL AXSBDV(CHAXIS,0.0,0.0) restores the default.

See also

AXIS7 and KSCALE.

SUBROUTINE AXSBMN (CHAXIS, OFFSET, DELTA)**Name**

AXSBMN – to specify the minor subdivisions on a linear axes independently of major subdivisions.

Availability Section 4, released version 2-12.

Arguments

CHAXIS	CHARACTER*2	Axis type
OFFSET	REAL expression	Offset value for minor subdivisions in units of the plotting scale
DELTA	REAL expression	Interval between minor subdivisions in units of the plotting scale

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	\sqrt{L}	\sqrt{L}	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	\times	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$

L: Linear scales only

Description

By default, linear axes are drawn with no minor subdivisions but they can be requested in one of two ways. **AXSUBS** requests minor subdivisions which divide major subdivisions into a specified number of equal parts; **AXSBMN** specifies an offset value and interval independently of the major subdivisions. Minor axis subdivisions are indicated by small tick marks and, when grids of type 2 have been requested, grid lines are also drawn.

AXSBMN and **AXSUBS** provide alternative methods and therefore the most recent call of either cancels any earlier call.

A fuller description of the values of **CHAXIS** is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: *XX*)¹
(Invalid axis type: *XX*)¹

Default

CALL **AXSBMN**(CHAXIS,0.0,0.0) or CALL **AXSUBS**(CHAXIS,0,0) restores the default.

See also

AXGRID, AXIS7, AXMAJ, AXMIN, AXSBDV, AXSBTK and AXSUBS.

SUBROUTINE AXSBTK (CHAXIS, TCHAR)

Name

AXSBTK – to specify the style of tick marks on an axis.

Availability Section 4, released version 2-11.

Arguments

CHAXIS CHARACTER*2 Axis type
TCHAR CHARACTER*1 Direction of tick marks

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ^U	✓ ^U	✓ ^U	✓ ^U

U: 'P' receding, 'F' following and 'I' inside unavailable

TCHAR *Meaning*

'A' Straddling across the axis
'D' Default – towards the outside
'F' Following axis
'I' Towards the inside of the picture
'N' None – tick marks omitted
'O' Towards the outside of the picture
'P' Preceding axis

Description

By default, tick marks are drawn towards the outside of the picture if there is room, or towards the inside otherwise. AXSBTK specifies a new style, and must be called before a tick mark is drawn as part of a composite task, or using AXMAJ, AXMIN, AXLAB7 or AXTXT7.

If there is insufficient space for tick marks in the specified location, they are drawn elsewhere. If TCHAR cannot be satisfied, a diagnostic is issued. A fuller description of the values of CHAXIS and the interpretation of 'P' and 'F' is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(AXSBTK not satisfied)²
(Invalid axis type: XX)¹

Default

CALL AXSBTK(CHAXIS, 'D') restores the default.

See also

AXIS7, AXLAB7, AXMAJ, AXMIN and AXTXT7.

SUBROUTINE AXSUBS (CHAXIS, NMAJOR, NMINOR)**Name**

AXSUBS – to specify the numbers of major and minor subdivisions on linear axes.

Availability Section 4, released version 2-11.

Arguments

CHAXIS	CHARACTER*2	Axis type
NMAJOR	INTEGER expression	Number of major subdivisions
NMINOR	INTEGER expression	Number of minor subdivisions

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	\sqrt{L}	\sqrt{L}	$\sqrt{}$	\times	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$

L: Linear scales only

Description

By default, all linear axes are drawn with no minor subdivisions, and major subdivisions are only used when the space available is too small to fit annotation labels at all tick marks. AXSUBS specifies the intervals between annotated tick marks. These intervals are subdivided into NMAJOR equal major intervals which are each subdivided into NMINOR equal minor intervals. Major tick marks are smaller than annotated tick marks.

AXSUBS must be called before a linear axis is drawn and minor tick marks are smaller than major tick marks.

A fuller description of the values of CHAXIS is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Inappropriate axis type: XX)¹

(Invalid axis type: XX)¹

Default

CALL AXSUBS(CHAXIS,0,0) restores the default.

See also

AXGRID, AXIS7, AXMAJ, AXMIN, AXSBDV and AXSBTK.

**SUBROUTINE AXTXT7 (CHAXIS, W1, STEP, LABARR, NARR)
SUBROUTINE AXTXT (CHAXIS, W1, STEP, LABARR, NARR, NCAP)**

Name

AXTXT7 – to draw a set of axis annotation labels and tick marks.

Availability Section 4, released version 2-11.

Arguments

CHAXIS	CHARACTER*2	Axis type
W1	REAL expression	Position for first label
STEP	REAL expression	Interval between labels
LABARR	STRING array	Set of labels
NARR	INTEGER expression	Number of labels in LABARR
NCAP	INTEGER expression	Maximum number of characters in any label

<i>axis type</i>	Cartesian		Polar		Isometric			Bars		Water		ViSualization			
CHAXIS	XC	YC	RP	AP	XI	YI	ZI	NB	LB	NW	LW	X3	Y3	Z3	U3
	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	×

Description

By default, when an axis is drawn it is subdivided and annotated at regular intervals using automatically generated labels. To draw an axis with user-defined labels, suppress the normal annotation by calling **AXCLR** before the axis is drawn then call **AXTXT/AXTXT7** to draw alternative annotation and tick marks. **LABARR(1)** is positioned at **W1**, **LABARR(2)** is positioned at **W1+STEP** *etc.*

LABARR must be declared with elements large enough for the longest label in the set, *eg.* **CHARACTER*9 LABARR(7)** for a set of 7 labels of up to 9 characters each.

A fuller description of the values of **CHAXIS** is given in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Invalid axis type: **XX**)¹

(Inappropriate axis type: **XX**)²

See also

AXGRID, **AXCLR**, **AXIS7**, **AXLAB7**, **AXLBAN**, **AXLBJS**, **AXLBSL** and **AXSBTK**.

SUBROUTINE BARC HT (D2ARR, LABARR, NARR, NSETS, CAPN, CAPL)

Name

BARC HT – to draw a bar chart on the current picture.

Availability Section 4, released version 2-11.

Arguments

D2ARR	REAL 2-D array	Data values, D2ARR(NARR,NSETS)
LABARR	STRING array	Names of items in each data set
NARR	INTEGER expression	Number of elements in each data set and in LABARR
NSETS	INTEGER expression	Number of data sets
CAPN	STRING expression	Numeric axis caption
CAPL	STRING expression	Label axis caption

Description

BARC HT draws a bar chart on the current picture of data held in the two-dimensional array, D2ARR(NARR,NMAX), where NMAX is greater or equal to the number of data sets to be plotted (NSETS).

BARC HT draws numeric and label axes which can be configured using appropriate **AX*** subroutines with CHAXIS='NB' and 'LB' respectively. By default, the bars are drawn vertically and, if NSETS > 1, bars are clustered side-by-side to represent values from each data set; bars (or clusters of bars) occupy 80% of the space available and are centred within this space; the numeric scale is calculated to accommodate the bar chart exactly and both scales run in the natural direction of the corresponding axis. These default settings can be altered by BARTYP, BARFMT, BARRNG and BARDIR respectively.

BARC HT draws a bar chart on the current 2-D picture and must therefore be preceded by the *new picture* subroutine, NEWPIC.

Diagnostics

(BAR CHART OMITTED: INVALID DIMENSIONS)¹

See also

BARRNG, BARFMT, BARTYP, BARDIR, SHEDGE, SHKEYS and SQSHAD.

SUBROUTINE BARDIR (NBTORF, LBTORF)

Name

BARDIR – to specify the directions of bar chart scales.

Availability Section 4, released version 2-11.

Arguments

NBTORF	LOGICAL expression	Whether to reverse numeric scale
LBTORF	LOGICAL expression	Whether to reverse labels scale

Description

By default, the scales on a bar chart are calculated to fit the data exactly and are configured such that scales go from a small value to a larger value. **BARDIR** can set any combination of scale directions for bar charts by indicating whether to reverse the numeric scale and/or the implicit label scale; the range of the numeric scale can be specified by **BARRNG**.

Default

`CALL BARDIR(.FALSE.,.FALSE.)` restores the default.

See also

BARCHT and **BARRNG**.

SUBROUTINE BARFMT (JCHAR, IVAL)**Name**

BARFMT – to specify how bars in a bar chart occupy the space available.

Availability Section 4, released version 2-11.

Arguments

JCHAR	CHARACTER*1	Justification of bars
IVAL	INTEGER expression	Percentage (1–100%) of space available

JCHAR *Justification of bars*

'P'	Preceding the space – left for vertical bars, bottom for horizontal bars
'C'	Centred within the space
'F'	Following the space – right for vertical bars, top for horizontal bars

Description

By default, bars (or clusters of bars) occupy 80% of the space available and are centred within this space. BARFMT specifies the size and justification of bars on a bar chart.

Default

CALL BARFMT('C',0) restores the default.

See also

BARCMT.

SUBROUTINE BARRNG (VMIN, VMAX)

Name

BARRNG – to specify the range of the numerical scale for bar charts.

Availability Section 4, released version 2-11.

Arguments

VMIN	REAL expression	Minimum scale value
VMAX	REAL expression	Maximum scale value

Description

By default, the numerical scale of bar charts is calculated to accommodate the data exactly. BARRNG specifies alternative range of scales (the direction of scales can be specified separately by BARDIR.)

If the specified scale can not accommodate the entire bar chart, part of the picture cannot be drawn. This contributes to the number of incomplete picture tasks and a diagnostic is issued at the end of the picture.

Default

Calling BARRNG with VMAX less than or equal to VMIN restores the default. *eg.* CALL BARRNG(0.0,0.0).

See also

BARCHT and BARDIR.

SUBROUTINE BARTYP (OCHAR, ITYPE)**Name**

BARTYP – to specify the type of bar chart required.

Availability Section 4, released version 2-11.

Arguments

OCHAR	CHARACTER*1	Orientation of bars
ITYPE	INTEGER expression	Type of bar chart

OCHAR	<i>Orientation of bars</i>
-------	----------------------------

'V'	Vertical bars
-----	---------------

'H'	Horizontal bars
-----	-----------------

ITYPE	<i>Type of bar chart</i>
-------	--------------------------

1	Clustered bars – data sets side-by-side
---	-----------------------------------------

2	Stacked bars – data sets accumulated on same bars
---	---------------------------------------------------

3	Pyramid bars – data sets alternating
---	--------------------------------------

Description

By default, bar charts drawn using **BARCHT** have vertical bars which, if there is more than one data set, are clustered side-by-side. The type of bar chart drawn by **BARCHT** can be changed by a prior call of **BARTYP**.

Orientation can be either horizontal or vertical. If horizontal bars are drawn, the bars and their associated labels are ordered from the top to the bottom of the picture.

Default

CALL BARTYP('V',1) restores the default.

See also

BARCHT.

SUBROUTINE BLNKKY

Name

BLNKKY – to add a blank entry in a key or caption area.

Availability Section 1, released before version 2-5.

Arguments

None.

Description

BLNKKY inserts a blank entry in the next empty space in the current key or caption area (defined by DEFKEY/DEFCAP or selected by RESNXT). All blank entries in a key/caption area are counted towards the total number of entries.

A similar effect can be achieved by increasing the interline spacing (see TEXTLF) or by using embedded sub-commands within text strings (see STRLV and STRCHS).

Diagnostics

(Key/caption area full)²

(No active key/caption area)²

See also

BOTHK7, DEFCAP, DEFKEY, LINEK7, MARKK7, RESNXT, SHDEK7 and FILLK7.

SUBROUTINE BOTHK7 (LTYPE, MKTYPE, CAP)
SUBROUTINE BOTHKY (LTYPE, MKTYPE, CAP, NCAP)

Name

BOTHK7 – to draw an annotated sample of a broken line pattern and marker symbol in a key.

Availability Section 1, released before version 2-5.

Arguments

LTYPE	INTEGER expression	Type of broken line pattern
MKTYPE	INTEGER expression	Type of marker symbol
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

BOTHKY/BOTHK7 inserts a key to a broken line pattern (as used by the BRKN* subroutines) with a marker symbol (as used by MARK*) in the next empty space in the current key or caption area (defined by DEFKEY/DEFCAP or selected by RESNXT).

A sample of the broken line pattern, LTYPE, is drawn [1] on the left of the entry, with the marker symbol, MKTYPE, drawn [3] on the centre of the line; the caption, CAP, is drawn [2] alongside the sample. If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

REAL and INTEGER values can be converted to text strings using the conversion subroutines, KREAL and KNUMB respectively.

Diagnostics

(Caption truncated)²
 (Key/caption area full)²
 (No active key/caption area)²

See also

ADDJST, BLNKKY, BUNLPR, DEFKEY, LINEK7, LINSET, MARKK7 and MKSET.

SUBROUTINE BOXCAP (TORF)**Name**

BOXCAP – to specify whether boxes are to be drawn around caption areas.

Availability Section 4, released before version 2-5.

Argument

TORF LOGICAL expression Whether captions are to be boxed

Description

By default, caption areas defined by DEFCAP are not boxed. BOXCAP specifies whether or not each caption area is to be surrounded by a box.

The box is drawn [1] when the caption area is set up; when this occurs depends on the type of caption area defined by CALL DEFCAP(ITYPE,...):

ITYPE *Box drawn*

-
- | | |
|---|----------------------------------------------|
| 1 | when a new caption area is defined by DEFCAP |
| 2 | when a new caption area is defined by DEFCAP |
| 3 | whenever a new picture is started |
-

Default

CALL BOXCAP(.FALSE.) restores the default.

See also

DEFCAP.

SUBROUTINE BOXGRP (TORF)**Name**

BOXGRP – to specify whether boxes are to be drawn around groups of pictures.

Availability Section 4, released version 2-7.

Argument

TORF LOGICAL expression Whether groups are to be boxed

Description

By default, a group of pictures is not boxed. BOXGRP specifies whether or not a rectangular box is to be drawn around each group of pictures.

The area surrounded by the box is the group of pictures as defined by GROUP including margins but excluding peripheries. If GROUP has not been called (or a 1×1 group has been defined), the box surrounds a single picture and its margin.

The box is drawn [1] when the first picture on the SIMPLEPLOT page is started.

Default

CALL BOXGRP(.FALSE.) restores the default.

See also

BOXPAG, BOXPIC and GROUP.

SUBROUTINE BOXKY (TORF)**Name**

BOXKY – to specify whether boxes are to be drawn around keys.

Availability Section 4, released before version 2-5.

Argument

TORF LOGICAL expression Whether keys are to be boxed

Description

By default, a box is drawn around all key areas. BOXKY specifies whether or not each key area is to be boxed.

The box is drawn [1] when the key is set up; when this occurs depends on the type of key defined by CALL DEFKEY(ITYPE, ...):

ITYPE *Box drawn*

-
- | | |
|---|-------------------------------------|
| 1 | when a new key is defined by DEFKEY |
| 2 | when a new key is defined by DEFKEY |
| 3 | whenever a new picture is started |
-

MPK7H, MPK7V and SHKEYS correspond to ITYPE=2.

Default

CALL BOXKY(.TRUE.) restores the default.

See also

DEFKEY, MPK7H, MPK7V and SHKEYS.

SUBROUTINE BOXPG2 (ITYPE)**Name**

BOXPG2 – to specify how the boundaries of pages are to be drawn.

Availability Section 1, released version 2-14.

Argument

ITYPE INTEGER expression Type of boundary (see below)

ITYPE	Boundary type
0	No drawn boundary (Default)
1	Simple box or parallel line boundary
2	Alternative box with logo

Description

By default, the boundary of the SIMPLEPLOT page is not drawn. BOXPG2 specifies what type of page boundary is required on each SIMPLEPLOT page.

The box [1], and optionally a logo [2] (with BOXPG2(2)), are drawn when the SIMPLEPLOT page is started.

Default

BOXPG2(0) restores the default.

Diagnostics

[Failed to read LOGO file]¹

See also

BOXGRP, BOXPIC and PAGE.

SUBROUTINE BOXPIC (TORF)

Name

BOXPIC – to specify whether boxes are to be drawn around individual pictures.

Availability Section 4, released version 2-7.

Argument

TORF LOGICAL expression Whether pictures are to be boxed

Description

By default, pictures are not boxed. BOXPIC specifies whether or not a rectangular box is to be drawn around every picture (excluding margin).

The box is drawn [1] when a new picture is started.

If scales are extended to provide similar linear scales in x and y (see EQSCAL), the box is drawn around the full extent of the scales at the picture limits. If a box is required to fit the requested range of scales, and the axes drawn to annotate such scales, DRAWBX can be used to draw a box on the current picture.

Default

CALL BOXPIC(.FALSE.) restores the default.

See also

BOXGRP, BOXPAG, DRAWBX and PERIM.

SUBROUTINE BREAK**Name**

BREAK – to force a break between separate sequences of point-by-point plotting.

Availability Section 1, released before version 2-5.

Arguments

None.

Description

A sequence of lines drawn by **BRKNPT**/**JOINPT** is interrupted when any other plotting subroutine is called, and the next call of **BRKNPT**/**JOINPT** is treated as a first call again. **BREAK** explicitly interrupts the sequence without performing any other function. **BREAK** does no drawing.

MARKPT (or **CP7PT**/**CAPPT**) includes the equivalent of **BRKNPT**/**JOINPT** after drawing the symbol (and text), therefore **BREAK** should be called between **MARKPT** and a succeeding **BRKNPT**/**JOINPT** if a line is not required joining symbol and point.

See also

BRKNPT, **CP7PT**, **JOINPT** and **MARKPT**.

SUBROUTINE BRKNAR (X1, DX, DARR, NARR, LTYPE)**Name**

BRKNAR – to draw a curve from an array of values, using a specified broken line pattern.

Availability Section 4, released version 2-11.

Arguments

X1	REAL expression	Value of independent variable for plotting DARR(1)
DX	REAL expression	Independent variable interval between function values
DARR	REAL array	Function values for plotting
NARR	INTEGER expression	Number of points
LTYPE	INTEGER expression	Type of broken line pattern

Description

Using broken line pattern LTYPE, BRKNAR draws [1] the curve which connects the following points:

(X1,DARR(1)), (X1+DX,DARR(2)),...
(X1+(NARR-1)*DX,DARR(NARR))

These points represent a set of values from a single array where the array elements hold function values $y_i = f(x_i)$ and $x_i = x_1 + (i - 1)dx$. The type of curve depends on CVTYPE.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

BRKNCV, BUNLPR, CVTYPE, CLIPLV, MARKAR, RIDDLE and SHDEAR.

SUBROUTINE BRKNBX (X1, Y1, X2, Y2, LTYPE)**Name**

BRKNBX – to draw a box, using a specified broken line pattern.

Availability Section 1, released version 2-8.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of opposite corners of the box, specified in units of the plotting scales
LTYPE	INTEGER expression	Type of broken line pattern

Description

Using broken line pattern LTYPE, BRKNBX draws [1] the box extending from x_1 to x_2 by y_1 to y_2 . If $x_1=x_2$ or $y_1=y_2$, then nothing is drawn.

The points (x_1, y_1) and (x_2, y_2) are specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.



If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(** x_1, y_1, x_2, y_2 **)²
 (Null box, nothing drawn)²

See also

BUNLPR, CLIPLV and SHDEBX.

SUBROUTINE BRKNCL (XCENT, YCENT, RADIUS, LTYPE)**Name**

BRKNCL – to draw a circular function with specified centre, radius and broken line pattern.

Availability Section 1, released before version 2-5.

Arguments

XCENT,	REAL expressions	Coordinates of the centre of the
YCENT		circle in units of the plotting scales
RADIUS	REAL expression	Circle radius in plotting scale units
LTYPE	INTEGER expression	Type of broken line pattern

Description

Using broken line pattern, LTYPE, BRKNCL draws [1] the circle (or the part of the circle which lies within the range of the plotting scales) centred at point (x_{cent}, y_{cent}) , with radius RADIUS. The resulting shape is only geometrically circular when both scales are equal and linear.

The centre point and the radius are both specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

By default, all drawing is restricted by the limits of the picture scales; if it exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Circle exceeds scales)²

See also

BUNLPR, CLIPLV, EQSCAL and SHDECL.

SUBROUTINE BRKNCV (XARR, YARR, NARR, LTYPE)**Name**

BRKNCV – to draw a curve from a set of coordinates, using a specified broken line pattern.

Availability Section 1, released before version 2-5.

Arguments

XARR, YARR	REAL arrays	Coordinates of points, in units of the plotting scales
NARR	INTEGER expression	Number of points
LTYPE	INTEGER expression	Type of broken line pattern

Description

Using broken line pattern LTYPE, BRKNCV draws [1] the curve corresponding to the following points:

(XARR(1), YARR(1)), (XARR(2), YARR(2)), ...
(XARR(NARR), YARR(NARR))

A closed curve can be obtained by using data in which XARR(NARR)=XARR(1) and YARR(NARR)=YARR(1). The type of curve drawn depends on CVTYPE.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

BUNLPR, CLIPLV, CVTYPE, MARKCV, RIDDLE and SHDECV.

SUBROUTINE BRKNFN (FUNX, LTYPE)**Name**

BRKNFN – to draw a curve of a user-defined function, $y = f(x)$, using the specified broken line pattern.

Availability Section 1, released before version 2-5.

Arguments

FUNX	function name	REAL function with one REAL argument, also declared in an EXTERNAL statement
LTYPE	INTEGER expression	Type of broken line pattern

Description

BRKNFN evaluates and draws [1] the curve of the specified function, FUNX, using the specified broken line pattern, LTYPE.

With Cartesian coordinates, the specified function, FUNX, must calculate y given x , and with polar coordinates FUNX must calculate r given θ . The intervals of the independent variable over which BRKNFN evaluates the function, vary with the curvature of the curve.

Care must be taken in the programming of FUNX to ensure that it is continuous and cannot fail for any arguments within the plotting range. Discontinuities may cause SIMPLEPLOT to loop indefinitely.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Function curve exceeds scales)²

See also

BUNLPR, CLIPLV, FNRNGE, POLY, RIDDLE and SHDEFN.

SUBROUTINE BRKNPR (SUBR, T1, T2, LTYPE)**Name**

BRKNPR – to draw the user-defined parametric function using a specified broken line pattern.

Availability Section 4, released version 2-9.

Arguments

SUBR	subroutine name	Subroutine with three REAL arguments, also declared in an EXTERNAL statement
T1, T2	REAL expressions	Values of the function parameter between which curve is to be drawn
LTYPE	INTEGER expression	Type of broken line pattern

Description

BRKNPR evaluates and draws [1] the curve of a user-defined parametric function using the specified broken line pattern, LTYPE.

The parametric function is specified in subroutine SUBR; SUBR must have three **REAL** arguments: T, the value of the function argument, and VARX and VARY, to receive coordinates corresponding to T. SUBR is called by BRKNPR with values of T ranging from T1 to T2.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Parametric function exceeds scales)²

(No. of incomplete picture tasks=n)¹

See also

BUNLPR, CLIPLV, DRAWPR, RIDDLE and SHDEPR.

SUBROUTINE BRKNPT (X, Y, LTYPE)**Name**

BRKNPT – to draw a broken line to the point (x, y) .

Availability Section 1, released version 2-9.

Arguments

X, Y	REAL expressions	Coordinates of a point specified in units of the plotting scale
LTYPE	INTEGER expression	Type of broken line pattern

Description

The first call of BRKNPT executes a move to the point (x, y) without drawing anything. Subsequent calls of BRKNPT draw [1] a straight line from the previous point to the specified point, using broken line pattern LTYPE. The line is straight even on non-linear scales and polar charts.

A sequence of lines drawn by BRKNPT/JOINPT is interrupted when any other plotting subroutine is called, and the next call of BRKNPT/JOINPT is treated as a first call again. BREAK explicitly interrupts the sequence without performing any other function. MARKPT (or CP7PT/CAPPT) draws a symbol (and a caption) and then executes the equivalent to a first call of BRKNPT/JOINPT in order to move to the centre of the symbol.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

The point (x, y) is specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

$(**x, y**)^2$

See also

BREAK, BUNLPR, CLIPLV, CP7PT, JOINPT and MARKPT.

SUBROUTINE BUNLPR (CHATTR)**Name**

BUNLPR – to specify the order of priority of bundled line-drawing attributes.

Availability Section 1, released version 2-13.

Argument

CHATTR CHARACTER*3 Attributes to be bundled

CHATTR	Attribute	Cyclic order
'C'	Colour	1, 2, 3, ... NPENS
'S'	Style	0, -1, -2 ... , 1, 2 ...
'T'	Thickness	1, 2, 3, 4

Description

By default, SIMPLEPLOT associates only one attribute, colour, with pen numbers. BUNLPR may be called to specify which attributes are to be combined to distinguish pens used for line drawing; text, marker symbols and shading are not affected.

CHATTR can consist of the initials (upper- or lower-case) of one, two or three attributes in their order of priority.

The total number of attribute combinations in the current bundle is device dependent; the effect of selecting a pen number beyond the total is undefined.

Line Styles specified explicitly as arguments (*eg.* . LTYPE) override the bundled Style without affecting the other bundled attributes. The bundled Style may be specified by LTYPE=-999.

Default

CALL BUNLPR('C') restores the default.

See also

PEN, SETPNS, SQPEN, THCKMG and WFPNS.

SUBROUTINE CHDESC (IHGHT, ITAIL, ITHCK, ITILT)

Name

CHDESC – to specify characteristics of adjustable software characters.

Availability Section 4, released before version 2-5.

Arguments

IHGHT	INTEGER expression	Height of characters relative to width	
ITAIL	INTEGER expression	Size of serifs	
ITHCK	INTEGER expression	Character line thickness	
ITILT	INTEGER expression	Slope of characters	
	–1	0 (<i>default</i>)	1
IHGHT	Squat characters	Normal height	Tall characters
ITAIL	No serifs	Small serifs	Large serifs
ITHCK	Single line characters	Lightly thickened characters	Thick characters
ITILT	Backwards slope	Upright	Forwards slope

Description

CHDESC specifies a preferred combination of characteristics of the adjustable software characters selected by CHSET with ISET=51 or 52. The relationships between argument values and the characteristics are summarized in the table below.

CHDESC has no effect on hardware or other software characters (*eg.* Hershey fonts).

Default

CALL CHDESC(0,0,0,0) restores the default.

See also

CHSET.

SUBROUTINE CHMASK (TORF)**Name**

CHMASK – to specify whether text is to be masked.

Availability Section 4, released version 2-9.

Argument

TORF LOGICAL expression Whether text is to be masked

Description

By default, SIMPLEPLOT draws anywhere within the page unless specific areas have been reserved for specific activities. CHMASK specifies that the area immediately around text is to be masked from any further drawing.

After a call of CHMASK(.TRUE.) text is masked; this means that the text itself looks no different from unmasked text, but any subsequent drawing over the text is omitted as it crosses the text.

Masking of text is currently limited to horizontal and vertical text only.

The limit to the number of masked areas which can be used for individual symbols and text strings is 50. When this limit is reached a diagnostic is issued and subsequent masked areas take the place of the oldest areas and overdrawing of these areas may occur.

Diagnostics

(Maximum no. of masked areas reached)¹

Default

CALL CHMASK(.FALSE.) restores the default.

See also

MKMASK.

SUBROUTINE CHSET (ISET)**Name**

CHSET – to specify an alternative source of character sets or fonts.

Availability Section 1, released version 2-8.

Argument

ISET INTEGER expression Character set source

ISET Font source

≤ -1	Alternative hardware/firmware sets (if available)
0	Hardware/firmware font (if available)
1	Simple device independent software font
2–19	Hershey fonts (SIMPLEPLOT-PLUS)
20	Solid font (SIMPLEPLOT-PLUS)
21	Outline font (SIMPLEPLOT-PLUS)
22	Mathematical symbols (SIMPLEPLOT-PLUS)
23	Large mathematical symbols (SIMPLEPLOT-PLUS)
51	Adjustable ANSI characters (Section 4)
52	Adjustable UK characters (Section 4)

Description

For efficiency and clarity, SIMPLEPLOT is set up to draw text on pictures using characters from device hardware or firmware wherever possible. CHSET selects an alternative character set (or font). The Hershey fonts are only available with SIMPLEPLOT-PLUS.

Default

CALL CHSET(0) restores the default.

See also

FFSET, LINSET, MKSET and SHSET.

SUBROUTINE CHUNDL (NLINES)**Name**

CHUNDL – to specify the number of times text is underlined.

Availability Section 4, released version 2-9.

Argument

NLINES INTEGER expression Number of lines under text (0–3)

Description

After a call of CHUNDL, every time text is drawn, NLINES lines are drawn underneath. CHUNDL is currently limited to horizontal text.

Single underlining of text can also be achieved by using embedded sub-commands within the text string (see STRCHS and STRLV).

Default

CALL CHUNDL(0) restores the default.

See also

STRCHS and STRLV.

SUBROUTINE CLIPLV (ILEVEL)**Name**

CLIPLV – to specify the clipping region for all plotting.

Availability Section plus, released version 2-12.

Argument

ILEVEL INTEGER expression Level of clipping

ILEVEL	Clipping region
0	Default (see above)
1	Picture limits
2	SIMPLEPLOT page limits

Description

By default, plotting is clipped as follows:

- Text (including axis annotation and tick marks) is clipped to limits of SIMPLEPLOT page;
- Arrows are clipped to picture limits;
- Boxes are clipped to picture limits;
- Plotting of lines and shaded areas is clipped to picture limits;
- Marker symbols are plotted only when the point on which symbol is centred is on, or inside, the picture limits; in a similar way, range bars can spill over the picture limits.

CLIPLV specifies the all plotting is to be clipped to the specified limits.

Diagnostics

The following diagnostics may be produced by graphics subroutines that draw text and/or marker symbols:

(No. of incomplete page tasks=*n*)¹

(Symbol clipped)²

(Text clipped)²

Default

CALL CLIPLV(0) restores the default.

SUBROUTINE COORDS (IUNITS)**Name**

COORDS – to change the interpretation of coordinates.

Availability Section 1, released version 2-12.

Argument

IUNITS INTEGER expression Type of units

IUNITS Coordinate interpretation

0	Cartesian (x, y)
1	polar, $z = f(r, \theta)$, θ in degrees
2	polar, $z = f(r, \theta)$, θ in radians
3	polar – user-defined angular scale (see POLRNG)

Description

COORDS specifies coordinate interpretation as Cartesian, polar (in degrees) or polar (in radians). This interpretation remains in place until reset by COORDS or EQSCAL.

If EQSCAL has not been called, COORDS controls the type of the next new picture started by NEWPIC or AXES7. If EQSCAL is active, each new picture is started with the units specified by EQSCAL regardless of any call of COORDS; once a picture has been started, COORDS changes coordinate interpretation.

EQSCAL overrides COORDS but COORDS only modifies EQSCAL (saved scale ranges are converted).

Default

The default can be restored by CALL COORDS(-1).

See also

AXES7, EQSCAL, NEWPIC, POLAR7 and POLRNG.

SUBROUTINE CP7LB (X, Y, CAP)
SUBROUTINE CAPLB (X, Y, CAP, NCAP)

Name

CP7LB – to draw a caption at (x, y) .

Availability Section 4, released version 2-6.

Arguments

X, Y	REAL expressions	Coordinates of a point, specified in units of the plotting scales
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

CP7LB/CAPLB draws [2] the caption, CAP, at the point (x, y) .

The point (x, y) is specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine KXYXY. REAL and INTEGER values can be converted to text strings using the conversion subroutines KREAL and KNUMB respectively.

By default, if the caption is too long to fit within the SIMPLEPLOT page, it is clipped such that only whole characters appear; if coordinates exceed the limits of the SIMPLEPLOT page, the caption is omitted. Both these occurrences contribute to the number of incomplete page tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Text clipped)²

See also

CLIPLV, CP7PT, CP7XC, CP7YC, LABJST, LABANG, KNUMB and KREAL.

SUBROUTINE CP7PT (X, Y, MKTYPE, CAP)
SUBROUTINE CAPPT (X, Y, MKTYPE, CAP, NCAP)

Name

CP7PT – to draw a marker symbol at (x, y) with a caption.

Availability Section 1, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point specified in units of the plotting scales
MKTYPE	INTEGER expression	Type of marker symbol
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

CP7PT/CAPPT draws [3] the symbol, MKTYPE, centred at point (x, y) and draws [2] the caption, CAP, to the right of the symbol.

After drawing the specified symbol and text, the pen is left at the centre of the symbol to allow a line to be drawn from the symbol to another point by a succeeding call of BRKNPT/JOINPT. BREAK should be called if a line is not required to join symbol and point.

The point (x, y) is specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine KXYXY. REAL and INTEGER values can be converted to text strings using the conversion subroutines KREAL and KNUMB respectively.

By default, if the caption is too long to fit within the SIMPLEPLOT page, it is clipped such that only whole characters appear; if coordinates exceed the limits of the SIMPLEPLOT page, the caption is omitted. Both these occurrences contribute to the number of incomplete page tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Symbol clipped)²
 (Symbol spills over boundary)²
 (Text clipped)²

See also

BREAK, CLIPLV, CP7LB, MARKPT, MKMASK, MKSIZE, KREAL and KNUMB.

SUBROUTINE CP7XC (X1, X2, Y, CAP)
SUBROUTINE CAPXC (X1, X2, Y, CAP, NCAP)

Name

CP7XC – to draw a horizontally centred caption.

Availability Section 4, released version 2-6.

Arguments

X1, X2	REAL expressions	x coordinates between which the label is centred
Y	REAL expression	Vertical position of the caption
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

CP7XC/CAPXC draws [2] the caption, CAP, centred between x_1 and x_2 at vertical position y .

All coordinates are specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine KXYXY. REAL and INTEGER values can be converted to text strings using the conversion subroutines KREAL and KNUMB respectively.

By, default, if the caption is too long to fit within the SIMPLEPLOT page, it is clipped such that only whole characters appear; if coordinates exceed the limits of the SIMPLEPLOT page, the caption is omitted. Both these occurrences contribute to the number of incomplete page tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Text clipped)²

See also

CLIPLV, CP7LB, CP7PT, CP7YC, LABJST, LABANG, KNUMB and KREAL.

SUBROUTINE CP7YC (Y1, Y2, X, CAP)
SUBROUTINE CAPYC (Y1, Y2, X, CAP, NCAP)

Name

CP7YC – to draw a vertically centred caption.

Availability Section 4, released version 2-6.

Arguments

Y1, Y2	REAL expressions	y coordinates, between which the label is centred
X	REAL expression	Horizontal position of the label
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

CP7YC/CAPYC draws [2] the caption, CAP, centred between y_1 and y_2 at horizontal position x .

All coordinates are specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine KXYXY. REAL and INTEGER values can be converted to text strings using the conversion subroutines KREAL and KNUMB respectively.

By default, if the caption is too long to fit within the SIMPLEPLOT page, it is clipped such that only whole characters appear; if coordinates exceed the limits of the SIMPLEPLOT page, the caption is omitted. Both these occurrences contribute to the number of incomplete page tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Text clipped)²

See also

CLIPLV, CP7LB, CP7PT, CP7XC, LABJST, LABANG, KNUMB and KREAL.

SUBROUTINE CTBRKN (LTYPE)**Name**

CTBRKN – to specify the broken line pattern used for contours and surface sections.

Availability Section 2, released before version 2-5.

Argument

LTYPE INTEGER expression Type of broken line pattern

Description

Individual contour curves and surface sections are drawn with the bundled attributes of the current pen (by default, this is normally a solid line); CTBRKN selects an alternative broken line pattern, LTYPE.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

CTBRKN controls the line pattern used by *CNTS, *CONT, *CUT, ZEDGE, ZZEDGE, ZELEM, ZELEMS and ZZELMS. CTBRKN has no effect on the subroutines for 2-D charts and graphs.

Default

CALL CTBRKN(-999) restores the default.

See also

BUNLPR, LINSET and SQBRKN.

SUBROUTINE CTCURV (ITYPE)**Name**

CTCURV – to specify the curve type used for drawing contours.

Availability Section 2, released before version 2-5.

Argument

ITYPE INTEGER expression Method of curve drawing

ITYPE	Curve type
1	Tight fitting smooth curve
2	Looser fitting smooth curve
3	Straight lines from point to point

Description

Contour curves are drawn by joining interpolated points with some sort of curve; CTCURV specifies the method which is to be used for drawing contour curves.

The three types correspond exactly to the first three options of CVTYPE (used to control 2-D curve drawing).

Contours which change rapidly may not be suitable for loose fitting curves (ITYPE=2) because the curvature assigned by the curve drawing may produce intersections of contour curves.

CTCURV controls the curve type used for all subroutines related to contour pictures (*CNTS, *CONT and *CUT). CTCURV has no effect on shaded contours nor on the subroutines for charts and graphs.

Default

CALL CTCURV(1) restores the default.

See also

CVTYPE and SFMESH.

SUBROUTINE CTHOLD (ICODE)

Name

CTHOLD – to specify whether coordinates of internally generated curves are to be saved.

Availability Section plus, released version 2-13.

Argument

ICODE INTEGER expression Behaviour of subsequent curve
drawing

ICODE	<i>Graphics output</i>	<i>Coordinates of contour</i>
1	Yes	Forgotten (default)
2	No	Stored
3	Yes	Stored

Description

By default, the contour drawing subroutines (*CONT) plot the curves corresponding to a single contour level and the coordinates of these curves are forgotten. CTHOLD specifies that the coordinates are remembered and stored within SIMPLEPLOT for subsequent inquiry by QCURVE.

The coordinates of other curves are also remembered:

- Cross-sectional curves drawn by *CUT,
- Element boundaries drawn by ZZELMS and ZELEMS, and
- Ungridded data boundaries drawn by ZZEDGE and ZEDGE.

Default

CALL CTHOLD(1) restores the default.

See also

*CONT, *CUT, QCURVE, ZEDGE, ZELEMS, ZZEDGE and ZZELMS.

SUBROUTINE CTLABS (IFREQ)**Name**

CTLABS – to specify the frequency of labels included with contour curves.

Availability Section 2, released version 2-6.

Argument

IFREQ INTEGER expression Frequency of labels

Description

By default, contour curves are not labelled. CTLABS specifies the frequency at which labels are to be included.

After a call of CTLABS(IFREQ), the z value associated with each contour curve is drawn near the curve when a sequence of IFREQ or more points is joined in one operation.

For more frequent labelling, reduce IFREQ and for less frequent labelling, increase IFREQ; the exception to this rule is that a frequency of 0 results in no labels at all.

A call of CTLABS(10) is equivalent to a call of CTNUMB(.TRUE.) and a call of CTLABS(0) is equivalent to CALL CTNUMB(.FALSE.).

Default

CALL CTLABS(0) restores the default.

See also

CTNUMB and SQZLAB.

SUBROUTINE CTNUMB (TORF)

Name

CTNUMB – to specify whether contour curves are to be labelled.

Availability Section 2, released before version 2-5.

Argument

TORF LOGICAL expression Whether labelling is required

Description

By default, contour curves are not labelled. CTNUMB specifies whether or not contours are to be labelled.

After a call of CTNUMB(.TRUE.), the z value associated with each contour curve is drawn near the curve when a sequence of 10 or more points is joined in one operation.

A call of CTNUMB(.TRUE.) is equivalent to a call of CTLABS(10) and a call of CTNUMB(.FALSE.) is equivalent to CALL CTLABS(0).

Default

CALL CTNUMB(.FALSE.) restores the default.

See also

CTLABS and SQZLAB.

SUBROUTINE CVLBJS (VJUST, HJUST)**Name**

CVLBJS – to specify the justification of the label drawn on a labelled curve.

Availability Section 4, released version 2-13.

Arguments

VJUST CHARACTER*1 Vertical justification of label
HJUST CHARACTER*1 Horizontal justification of label

VJUST Vertical justification

'D'	Default
'B'	Bottom of the letters level with the curve
'C'	Centre of the letters level with the curve (default)
'T'	Top of the letters level with the curve

HJUST Horizontal justification

'D'	Default
'C'	Label is centred on the reference point
'L'	Label starts at the reference point (default)
'R'	Label ends at the reference point

Description

By default, curves drawn by LABCV/LABCV7 are vertically centred on the curve, and left-justified relative to the reference point for the curve (see CVLBPS). CVLBJS specifies an alternative justification of the label.

VJUST and HJUST are similar to the arguments of LABJST.

If either ordinate of the reference point is equal to the current no-data value, the label is justified against the next valid point. If horizontal justification is 'L'eft or 'C'entre, the next point is to the right of the reference point; if justification is 'R'ight, the next point is to the left of the reference point.

Default

CALL CVLBJS('D','D') restores the default.

See also

CVLBPS, LABCV7 and LIMIDX.

SUBROUTINE CVLBPS (IPOS)**Name**

CVLBPS – to specify the reference point for the label drawn on a labelled curve.

Availability Section 4, released version 2-13.

Argument

IPOS	INTEGER expression	Position of label, given as an index of data arrays
------	--------------------	--------------------------------------------------------

Description

By default, curves drawn by LABCV/LABCV7 are positioned relative to the mid-point of the curve. CVLBPS specifies an alternative reference point for the label.

Labels are drawn relative to the point (XARR(IPOS),YARR(IPOS)), where XARR and YARR are the parallel arrays of coordinates which are passed as arguments to LABCV7. Labels can be drawn relative to the highest or lowest point on the curve by setting IPOS to a value evaluated using LIMIDX.

If either XARR(IPOS) or YARR(IPOS) is equal to the current no-data value, the label is justified against the next valid point. If horizontal justification is 'L'eft or 'C'entre, the next point is IPOS+1; if justification is 'R'ight, the next point is IPOS – 1.

If there are no valid points between IPOS and the end of the curve, the label is omitted.

If IPOS is greater than NARR (the number of points in XARR and YARR) or less than 1, the default is restored.

Default

CALL CVLBPS(0) restores the default.

See also

CVLBJS, LABCV7 and LIMIDX.

SUBROUTINE CVTYPE (ITYPE)

Name

CVTYPE – to specify the type of curve to be drawn on 2-D graphs.

Availability Section 1, released before version 2-5.

Argument

ITYPE INTEGER expression Method for curve construction

ITYPE *Curve type*

- | | |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | A tight fitting smooth curve through every data point, which is confined between the same limits as the data. Sudden changes in the data result in sharp corners in the curve. A Cartesian curve drawn by this method is not invariant under rotation |
| 2 | A looser fitting smooth curve through every data point, which will probably extend higher or lower than the data at turning points, but should not have sharp corners; a Cartesian curve drawn by this method is invariant under rotation |
| 3 | Straight lines from point to point through the data, even on non-linear scales and polar charts |
| 4 | Linear regression * |
| 5 | Quadratic regression * |
-

* If ITYPE=4 or 5, the curve drawn covers the range of the x scale defined by FNRNGE.

Description

By default, the 2-D composite graph drawing subroutines (*eg.* BRKNCV, DRAWAR, SHDEC2) draw curves using a tight fitting curve to interpolate between the data points. CVTYPE specifies an alternative methods of curve fitting.

CVTYPE has no effect on surface pictures, contour maps or cross-sections (see CTCURV).

Default

CALL CVTYPE(1) restores the default.

See also

CTCURV, FNRNGE, POLOUT and POLY.

SUBROUTINE DDDATA (IPTR)**Name**

DDDATA – to pass device driver specific information from the application to a device driver.

Availability Section plus, released version 2-14.

Argument

IPTR	INTEGER array	array with 8 elements holding required value. All elements of the array must be defined
------	---------------	-----------------------------------------------------------------------------------------------

Description

Some applications have a requirement to pass data to a device driver. The information to be passed is usually of non-standard type and may be many bytes in length. Driver-specific data include widgets, lists of pixel values, points to bitmaps and pasteboard IDs.

Rather than provide a subroutine which could directly handle every possible type and quantity of data, a simple value is passed. It is expected that in the majority of cases this will be a pointer to the actual data.

An array of eight integers is used to allow for systems where **INTEGER**s are shorter than addresses. The exact conversion between a pointer and the **INTEGER** array is system dependent. Typically it will be the union (equivalence) of a pointer and the **INTEGER** array.

This subroutine may be called at any time. Data passed to this subroutine are stored until a device driver reads it or the device driver sub-system goes through a final closedown.

It is the responsibility of the calling code to ensure that the routine is called at an appropriate time and for an appropriate device driver.

See also

IOCHAN and device driver specific information.

SUBROUTINE DEFCAP (ITYPE, VCHAR, HCHAR, NROWS, NCOLMS)**Name**

DEFCAP – to define an area for captions.

Availability Section 1, released version 2-11.

Arguments

ITYPE	INTEGER expression	Type of reservation
VCHAR	CHARACTER*1	Vertical position of area
HCHAR	CHARACTER*1	Horizontal position of area
NROWS	INTEGER expression	Number of lines in area
NCOLMS	INTEGER expression	Maximum number of characters in any line of a caption

Description

DEFCAP defines an area for captions which is large enough for NROWS lines of text containing NCOLMS characters; the size is calculated using the nominal text width of the current font.

VCHAR and HCHAR are single characters representing the initial letters of vertical and horizontal positions. These determine the position of the area and also whether it is associated with a picture or the SIMPLEPLOT page; this in turn effects the limits of the area, the size of the text and therefore the size of the area.

The possible interpretations of VCHAR, HCHAR and ITYPE are listed in Appendix T of the *SIMPLEPLOT Supplement*.

ITYPE determines the behaviour of the caption area.

If BOXCAP has been used, a box is drawn around the caption area.

Diagnostics

(Key/caption attempted with no page)²
 (Key/caption attempted with no picture)²
 (Key/caption height reduced)²
 (Key/caption width reduced)²
 (Maximum no. of keys/captions reached)²
 (No room for key/caption area)²

See also

ADDCP7, BLNKY, BOXCAP, DEFKEY, DEFPOS, KPOSXY, PUTCP7, QKYCAP and TITLE7.

SUBROUTINE DEFKEY (ITYPE, VCHAR, HCHAR, NROWS, NCOLMS)**Name**

DEFKEY – to define an area for a key box.

Availability Section 1, released version 2-11.

Arguments

ITYPE	INTEGER expression	Type of reservation
VCHAR	CHARACTER*1	Vertical position of area
HCHAR	CHARACTER*1	Horizontal position of area
NROWS	INTEGER expression	Number of lines in area
NCOLMS	INTEGER expression	Maximum number of characters in any key caption

Description

DEFKEY defines an area for a key which is large enough for NROWS lines of text containing NCOLMS characters when written alongside a key sample. The size is calculated using the nominal text width of the current font.

A box is drawn [1] around the key unless cancelled by BOXKY. If ITYPE=1 or 2, the key is associated with the current picture, and the box is drawn immediately. If ITYPE=3, a key box is drawn with each subsequent new picture.

VCHAR and HCHAR are single characters representing the initial letters of vertical and horizontal positions. ITYPE is an integer between 1 and 3. The possible interpretations of VCHAR, HCHAR and ITYPE are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Key/caption attempted with no page)²
 (Key/caption attempted with no picture)²
 (Key/caption height reduced)²
 (Key/caption width reduced)²
 (Maximum no. of keys/captions reached)²
 (No room for key/caption area)²

See also

BLNKKY, BOTHK7, BOXKY, DEFCAP, DEFKYW, DEFPOS, FILLK7, KPOSXY, LINEK7, MARKK7, QKYCAP and SHDEK7.

SUBROUTINE DEFKYW (NCHARS)

Name

DEFKYW – to specify the width of samples in a key box.

Availability Section 4, released version 2-12.

Argument

NCHARS INTEGER expression Width of sample in equivalent
number of characters (or columns)

Description

By default, the space allocated for a key sample is 12 characters wide. This is sufficient to illustrate uniquely the thirteen standard SIMPLEPLOT software broken line patterns (–6..6), but can appear too wide for samples of shading pattern and marker symbols.

DEFKYW specifies the width of the space in terms of the equivalent number of characters (or columns).

Default space	Reduced space
— — — — — LINEK7	— — — — — LINEK7
— — — — — BOTHK7	— — — — — BOTHK7
⊖ MARKK7	⊖ MARKK7
█ SHDEK7	█ SHDEK7
█ FILLK7	█ FILLK7

DEFKYW takes effect when the key is set up. This depends on the type of key defined by CALL DEFKEY(ITYPE, ...):

ITYPE	Box drawn
1	when a new key is defined by DEFKEY
2	when a new key is defined by DEFKEY
3	whenever a new picture is started

MPK7H, MPK7V and SHKEYS correspond to ITYPE=2.

Default

CALL DEFKYW(0) restores the default.

See also

DEFKEY and SHKEYS.

SUBROUTINE DEFPOS (VCMS, VJST, HCMS, HJST, ITYPE)

Name

DEFPOS – to specify page coordinates of the movable descriptor, 'M'.

Availability Section plus, released version 2-12.

Arguments

VCMS	REAL expression	y (or vertical) coordinate
VJST	CHARACTER*1	Vertical justification of area
HCMS	REAL expression	x (or horizontal) coordinate
HJST	CHARACTER*1	Horizontal justification of area
ITYPE	INTEGER expression	Intended use of text

ITYPE *Text usage*

0	Default – determined by SIMPLEPLOT*
1	Titles, keys or captions relating to pictures
2	Titles, keys or captions relating to groups/pages

* Page usage is assumed, unless 'M' is used in conjunction with a descriptor specifically relating to pictures (*eg.* 'C'entre or 'T'op).

Description

The movable picture descriptor, 'M', is an additional descriptive position for titles, keys and caption areas. DEFPOS specifies a position for annotation by defining a point (HCMS,VCMS), and justification with respect to this point (VJST,HJST)

VCMS and HCMS are specified in centimetres relative to the bottom left-hand corner of the current SIMPLEPLOT page. The possible interpretations of VJST and HJST are listed in Appendix T if the *SIMPLEPLOT Supplement*.

Please note that a call to DEFPOS terminates a multi-line sequence of titles whether or not the defined position is used for a title.

The conversion subroutine, KXYXY, can be used to convert user coordinates (ICODE1=5), normalized page coordinates (ICODE1=4) or device coordinates (ICODE1=0, 1, 2) into physical page coordinates in centimetres (ICODE2=3).

Default

CALL DEFPOS(0.0, 'D', 0.0, 'D', 0) restores the default.

See also

DEFCAP, DEFKEY, KPOSXY, KXYXY, MPK7H, MPK7V, SHKEYS and TITLE7.

SUBROUTINE DEVNAM (STR)**Name**

DEVNAM – to specify a graphics device by name.

Availability Section plus, released version 2-11.

Argument

STR STRING expression Site or absolute name of device

Description

If SIMPLEPLOT is used with a multiple device driver system (*eg.* the Single Entry Point system), a graphics output device can be specified by a number of alternative methods. DEVNAM specifies a graphics device when a program is executed.

If the program has not yet started plotting, DEVNAM nominates the device which will be opened when plotting starts. Only one device can be open at any time therefore, if a device is already open, the current page is terminated (graphics buffers are flushed) and the device is closed. The device identified by STR is nominated as the device which is to be opened when plotting resumes.

DEVNAM is only applicable at installations which offer SIMPLEPLOT with a multiple device driver system. With the S.E.P. system, STR represents either the *site name* or the *absolute name* of a device driver option; STR is assumed to be a site name unless it is preceded by a '/' which identifies an absolute name.

Diagnostics

(DEVICE CLOSED)¹

Default

CALL DEVNAM(' ') restores the device selection menu.

See also

DEVNO and QDEV.

SUBROUTINE DEVNO (IDEV)**Name**

DEVNO – to specify a graphics device by number.

Availability Section 1, released before version 2-5.

Argument

IDEV INTEGER expression Number to identify device

Description

If SIMPLEPLOT is used with a multiple device driver system (*eg.* the Single Entry Point system), a graphics output device can be specified by a number of alternative methods. DEVNO specifies a graphics device when a program is executed.

If the program has not yet started plotting, DEVNO nominates the device which will be opened when plotting starts. Only one device can be open at any time; therefore, if a device is already open, the current SIMPLEPLOT page is terminated (graphics buffers are flushed) and the device is closed. The device identified by IDEV is nominated as the device which is to be opened when plotting resumes.

DEVNO is only applicable at installations which offer SIMPLEPLOT with a multiple device driver system. With the S.E.P. system, IDEV is interpreted either as a *site number* or an *absolute number* of a device driver option; site numbers are in the range 1–999 and absolute numbers are in the range 1000–32767.

Diagnostics

(DEVICE CLOSED)¹

Default

CALL DEVNO(0) restores the device selection menu.

See also

DEVNAM, QDEV and REDRAW.

SUBROUTINE DIAGDD (ILEVEL)**Name**

DIAGDD – to specify the level of device driver diagnostics.

Availability Section 1, released version 2-13.

Argument

ILEVEL INTEGER expression Level of device driver diagnostics

ILEVEL *Diagnostics level*

0	No device driver diagnostics
1	Device driver error messages (default)
2	Level 1 + device driver warning messages
3	Level 2 + device driver informative messages

Description

The S.E.P. device driver system issues diagnostic messages which are classified as either error messages, warning messages or informative messages, and, by default, only error messages are issued. **DIAGDD** specifies an alternative level of device driver diagnostics, independently of the **SIMPLEPLOT** library messages.

For example,

CALL DIAGDD(0) switches off all device driver diagnostics.

CALL DIAGDD(3) switches on all device driver diagnostics.

Please refer to host specific information about how to control the destination of diagnostic messages.

Default

CALL DIAGDD(1) restores the default.

See also

DIAGLV and DIAGOP.

SUBROUTINE DIAGLV (ILEVEL)**Name**

DIAGLV – to specify the level of diagnostics.

Availability Section plus, released version 2-9.

Argument

ILEVEL INTEGER expression Level of diagnostics

ILEVEL	Description	Messages
0	No messages output at all	None
1	Brief messages (default)	Type 1
2	Level 1 messages plus fuller details	Type 1+2
3	Level 1 messages plus subroutine trace	Type 1+3
4	Level 2 messages plus subroutine trace	Type 1+2+3

Description

By default, SIMPLEPLOT issues diagnostic messages to provide information about progress, to warn of omissions, and for fatal errors. **DIAGLV** specifies an alternative level of diagnostic information. Three types of diagnostic output can be generated:

1. Brief messages about key events during program execution
2. Fuller details whenever any omission has been necessary
3. Trace of each SIMPLEPLOT subroutine called

Five diagnostic levels are available, according to the value of **ILEVEL**, to output combinations of these.

Please refer to Appendix M of the *SIMPLEPLOT Supplement* for further information about diagnostic messages, and to host specific information about how to control the destination of diagnostic messages.

Default

CALL DIAGLV(1) restores the default.

See also

DIAGDD, DIAGOP and QSTAT.

SUBROUTINE DIAGOP (STR, ITYPE)**Name**

DIAGOP – to output a message to the SIMPLEPLOT diagnostics channel.

Availability Section 1, released version 2-13.

Arguments

STR	STRING expression	Message
ITYPE	INTEGER expression	Type of message

ITYPE	<i>Suggested type of message</i>
-------	----------------------------------

-
- | | |
|---|---------------------------------------------------------------------|
| 1 | Brief messages about key events during the execution of the program |
| 2 | Fuller details whenever any omission has been necessary |
| 3 | Trace of each subroutine called |
-

Description

DIAGOP outputs the specified message, **STR**, on the SIMPLEPLOT diagnostic I/O channel according to the value of **ITYPE** and the current diagnostic level.

It is not necessary to follow these descriptions exactly but, if you do, **DIAGOP** interacts with **DIAGLV** such that user-defined messages behave in the same way as SIMPLEPLOT diagnostic messages. For example, after **CALL DIAGLV(3)** user-defined messages of type 1 and 3 are output, but type 2 messages are omitted (see **DIAGLV** for further details).

Please refer to Appendix M of the *SIMPLEPLOT Supplement* for further information about diagnostic messages, and to host specific information about how to control the destination of diagnostic messages.

See also

DIAGDD and DIAGLV.

SUBROUTINE DRAWAR (X1, DX, DARR, NARR)**Name**

DRAWAR – to draw a curve from an array of values.

Availability Section 4, released version 2-11.

Arguments

X1	REAL expression	Value of independent variable for plotting DARR(1)
DX	REAL expression	Independent variable interval between function values
DARR	REAL array	Function values for plotting
NARR	INTEGER expression	Number of points

Description

Using the bundled line-drawing attributes of the current pen, DRAWAR draws [1] the curve which connects the following points:

(X1,DARR(1)), (X1+DX,DARR(2)),...
(X1+(NARR-1)*DX,DARR(NARR))

These points represent a set of values from a single array where the array elements hold function values $y_i = f(x_i)$ and $x_i = x_1 + (i - 1)dx$. The type of curve depends on CVTYPE.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

BRKNAR, BUNLPR, CLIPLV, CVTYPE, MARKAR, RIDDLE and SHDEAR.

SUBROUTINE DRAWBX (X1, Y1, X2, Y2)**Name**

DRAWBX – to draw a box.

Availability Section 1, released version 2-8.


Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of opposite corners of the box, in units of the plotting scales
----------------	------------------	-----------------------------------------------------------------------------

Description

Using the bundled line-drawing attributes of the current pen, DRAWBX draws [1] the box extending from x_1 to x_2 by y_1 to y_2 . If $x_1=x_2$ or $y_1=y_2$, then nothing is drawn.

The points (x_1, y_1) and (x_2, y_2) are specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.



By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

$(**x_1, y_1, x_2, y_2**)^2$
 (Null box, nothing drawn)²

See also

BRKNBX, BUNLPR, CLIPLV and SHDEBX.

SUBROUTINE DRAWCL (XCENT, YCENT, RADIUS)**Name**

DRAWCL – to draw a circular function with specified centre and radius.

Availability Section 1, released before version 2-5.

Arguments

XCENT,	REAL expressions	Coordinates of the centre of the
YCENT		circle in units of the plotting scales
RADIUS	REAL expression	Circle radius in plotting scale units

Description

Using the bundled line-drawing attributes of the current pen, DRAWCL draws [1] the circle (or the part of the circle which lies within the range of the plotting scales) centred at point (x_{cent}, y_{cent}) , with radius RADIUS. The resulting shape is only geometrically circular when both scales are equal and linear.

The centre point and the radius are both specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.

By default, all drawing is restricted by the limits of the picture scales; if it exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Circle exceeds scales)²

See also

BRKNCL, BUNLPR, CLIPLV, KXYXY, SCALES and SHDECL.

SUBROUTINE DRAWCV (XARR, YARR, NARR)**Name**

DRAWCV – to draw a curve from a set of coordinates in parallel arrays.

Availability Section 1, released before version 2-5.

Arguments

XARR, YARR	REAL arrays	Coordinates of points, in units of the plotting scales
NARR	INTEGER expression	Number of points

Description

Using the bundled line-drawing attributes of the current pen, DRAWCV draws [1] the curve corresponding to the following points:

(XARR(1), YARR(1)), (XARR(2), YARR(2)), ...
(XARR(NARR), YARR(NARR))

A closed curve can be obtained by using data in which XARR(NARR)=XARR(1) and YARR(NARR)=YARR(1). The type of curve drawn depends on CVTYPE.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

BRKNCV, BUNLPR, CLIPLV, CVTYPE, MARKCV, RIDDLE and SHDECV.

SUBROUTINE DRAWFN (FUNX)

Name

DRAWFN – to draw a curve of a user-defined function, $y = f(x)$ (or $r = f(\theta)$).

Availability Section 1, released before version 2-5.

Argument

FUNX	function name	REAL function with one REAL argument, also declared in an EXTERNAL statement
------	---------------	------------------------------------------------------------------------------

Description

DRAWFN evaluates and draws [1] the curve of the specified function, FUNX using the bundled line-drawing attributes of the current pen.

With Cartesian coordinates, the specified function, FUNX, must calculate y given x , and with polar coordinates FUNX must calculate r given θ . The intervals of the independent variable over which DRAWFN evaluates the function, vary with the curvature of the curve.

Care must be taken in the programming of FUNX to ensure that it is continuous and cannot fail for any arguments within the plotting range. Discontinuities may cause SIMPLEPLOT to loop indefinitely.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Function curve exceeds scales)²

See also

BRKNFN, BUNLPR, CLIPLV, FNRNGE, POLY, RIDDLE and SHDEFN.

SUBROUTINE DRAWLN (X, Y)**Name**

DRAWLN – to draw a straight line between a point and zero.

Availability Section 1, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point specified in units of the plotting scales
------	------------------	---------------------------------------------------------------------

Description

Using the bundled line-drawing attributes of the current pen, DRAWLN draws [1] a straight line between the point (x, y) and $(x, 0.0)$ in Cartesian plotting, or between $z = f(r, \theta)$ and $(0.0, \theta)$ in polar plotting. Nothing is drawn when DRAWLN is called with a Cartesian picture whose vertical scale excludes zero.

The point (x, y) is specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

$(**x, y**)^2$

See also

BRKNPT, BUNLPR, CLIPLV and RANGE.

SUBROUTINE DRAWPR (SUBR, T1, T2)**Name**

DRAWPR – to draw the user-defined parametric function.

Availability Section 4, released version 2-9.

Arguments

SUBR	subroutine name	Subroutine with three REAL arguments, also declared in an EXTERNAL statement
T1, T2	REAL expressions	Values of the function parameter between which curve is to be drawn

Description

DRAWPR evaluates and draws [1] the curve of a user-defined parametric function using the bundled line-drawing attributes of the current pen.

The parametric function is specified in subroutine SUBR. SUBR must have three **REAL** arguments: T, the value of the function argument, and VARX and VARY, to receive coordinates corresponding to T. SUBR is called by DRAWPR with values of T ranging from T1 to T2.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Parametric function exceeds scales)²

See also

BRKNPR, BUNLPR, CLIPLV, RIDDLE and SHDEPR.

SUBROUTINE ENDPAG**Name**

ENDPAG – to finish a picture and group separately from starting another picture.

Availability Section 4, released version 2-11.

Arguments

None.

Description

A SIMPLEPLOT page consists of a group of pictures (if **GROUP** has been called) or an individual picture otherwise. By default, when a SIMPLEPLOT program produces more than one page, each page is automatically finished by the start of another or the close down of graphics. If the graphics device is a remote device, an individual page may not be accessible until the page is terminated; in this case, it may be necessary to finish a page before the program starts another.

ENDPAG finishes the current page by flushing graphics buffers, performing the device page termination procedures, and outputting any diagnostic messages associated with the page. If **GROUP** has not been called, ENDPAG has a similar effect to ENDPIC; if **GROUP** has been called and ENDPAG is called before a requested group is full, the group is terminated and the next new picture starts a new group on a new page.

After ENDPAG, all attempts to output graphics are ignored until the start of another page.

Diagnostics

(END OF GROUP)¹

(END OF PICTURE)¹

(No. of incomplete page tasks=*n*)¹

See also

ENDPIC, ENDPLT, NEWPAG, OUTBUF, OWNIO and OWNNEW.

SUBROUTINE ENDPIC**Name**

ENDPIC – to finish a picture separately from starting another picture.

Availability Section 4, released version 2-7.

Arguments

None.

Description

By default, when a SIMPLEPLOT program produces more than one picture, each picture is automatically finished by the start of another or the close down of graphics. **ENDPIC** finishes the current picture by flushing any graphics buffers, and outputting any diagnostic messages associated with the picture.

If **GROUP** has been called, and the latest picture does not complete the group, **ENDPIC** leaves it in a state to continue the group when the next picture is started.

If the group is completed, the next picture starts a new SIMPLEPLOT page but any titles, keys or captions positioned relative to the page or group will be drawn on the current page.

Diagnostics

(END OF PICTURE)¹

(No. of incomplete picture tasks=*n*)¹

See also

ENDPAG, ENDPLT, MOVEON, OUTBUF, OWNIO and OWNNEW.

SUBROUTINE ENDPLT**Name**

ENDPLT – to close the plotting device and SIMPLEPLOT at the end of plotting.

Availability Section 1, released before version 2-5.

Arguments

None.

Description

ENDPLT flushes any graphics output buffers, closes the current graphics device (if open) and closes any permanent and temporary files opened by SIMPLEPLOT.

Every SIMPLEPLOT program should call ENDPLT when all plotting is complete. Failure to close the device may result in loss of some or all of the last picture, and the associated diagnostics. Failure to close down SIMPLEPLOT may result in temporary and/or permanent files being left open. ENDPLT should be called even if a SIMPLEPLOT program does no plotting, *eg.* if it only manipulates data.

If plotting is attempted when SIMPLEPLOT has been closed, SIMPLEPLOT is automatically re-opened.

Diagnostics

(DEVICE CLOSED)¹

(SIMPLEPLOT CLOSED)¹

See also

DEVNO and DEVNAM.

SUBROUTINE EQSCAL (XSTART, XSTOP, YSTART, YSTOP, IUNITS)

Name

EQSCAL – to specify similar linear scales for Cartesian or polar plotting.

Availability Section 1, released version 2-10.

Arguments

XSTART	REAL expression	Value at start of x (or r) scale
XSTOP	REAL expression	Value at end x (or r) scale
YSTART	REAL expression	Value at start of y (or θ) scale
YSTOP	REAL expression	Value at end of y (or θ) scale
IUNITS	INTEGER expression	Type of units

IUNITS	Units	XSTART, XSTOP	YSTART, YSTOP
–1	Cartesian	<i>Values ignored, centimetres used</i>	
0	Cartesian	Horizontal units	Vertical units
		RSTART, RSTOP	THSTR, THSTOP
1	Polar	Radial units	Angles in degrees
2	Polar	Radial units	Angles in radians
3	Polar	Radial units	User-defined scale

Description

EQSCAL specifies the limits and units of the current plotting scales, ensuring that 1 unit in x is the same physical length as 1 unit in y . The ranges of the scales, XSTART to XSTOP and YSTART to YSTOP can be expressed in different units, indicated by the value of IUNITS.

The plotting units can be switched by COORDS within the plotting of a picture, without cancelling EQSCAL.

When scaling is controlled by EQSCAL default axes are drawn from XSTART to XSTOP and YSTART to YSTOP. over the requested ranges rather than the extended ranges used to fit the picture size.

Default

Calling EQSCAL with XSTART=XSTOP or YSTART=YSTOP restores the default or IUNITS=–1 can be used to set dissimilar linear scales.

See also

AXES7, COORDS, NEWPIC, POLAR7, SCALES, XSCALE and YSCALE.

SUBROUTINE FFSIZE (ISET)**Name**

FFSET – to specify an alternative source of fast area-fill characters.

Availability Section plus, released version 2-11.

Argument

ISET INTEGER expression Fast area-fill character source

ISET Fast area-fill character source

≤ -1 Alternative hardware/firmware sets (if available)

0 Default (see above)

1 Shaded rectangles using currently selected area-fill shading method (see SHSET)

2 Currently selected text characters (see CHSET)

3 Currently selected broken line patterns (see LINSET)

Description

For efficient operation and clarity, SIMPLEPLOT is set up to use the most appropriate source of fast area-fill characters for each device. FFSIZE selects an alternative source of fast area-fill characters to be used for fast area-fill shaded contour maps (MPTYPE(2) or MPTYPE(3)) and shaded surfaces (RASTER(1)).

By default, hardware (or firmware) fast area-fill characters are used if they are available; when no hardware/firmware characters are available, the most efficient alternative on the current device is used for ISET=0.

If the number of fast area-fill characters required exceeds the number available, shaded rectangles are used for additional characters; these rectangles are drawn using the currently selected area-fill shading method (see SHSET) and correspond in size to the current fast-area fill characters (see FFSIZE).

Default

CALL FFSIZE(0) restores the default.

See also

CHSET, FFSIZE, LINSET, MPTYPE, RASTER and SHSET.

SUBROUTINE FFSIZE (WCMS, HCMS)**Name**

FFSIZE – to specify the size of fast area-fill characters.

Availability Section plus, released version 2-11.

Arguments

WCMS	REAL expression	Character width (in cms)
HCMS	REAL expression	Character height (in cms)

Description

By default, the size of fast area-fill characters depends on the type of picture being drawn:

Shaded contour maps: the target height and width of fast area-fill characters are equal to the default target width of text characters which is related to picture size (see TEXTSZ).

Shaded pictures using raster process: (*eg.* shaded surfaces) the target height and width of fast area-fill characters are 75 dots per inch.

If different sizes of fast area-fill characters are available, FFSIZE can be used to specify a target size; the size nearest $WCMS \times HCMS$ (in centimetres) is used.

If ordinary text characters are used as fast area-fill characters, SIMPLEPLOT attempts to scale them to achieve the size specified by FFSIZE; if FFSIZE has not been called, their size is affected by the TEXT* subroutines in the same way as other text.

On colour (or grey-scale) pixel devices, the minimum fast area-fill character size is one pixel. The physical size of a single pixel can be calculated (see QPAGE and QPIXLS) and used to specify the finest resolution.

Default

Call FFSIZE with WCMS=0.0 or HCMS=0.0 restores the default width or height respectively.

See also

FFSET, MPTYPE, QFFSIZ, RASTER and TEXTSZ.

SUBROUTINE FIGFMT (CHFORM, NUMINT, NDEC)

Name

FIGFMT – to specify the format of REAL numbers drawn on pictures.

Availability Section 1, released version 2-11.

Arguments

CHFORM	CHARACTER*1	Type of format
NUMINT	INTEGER expression	Number of digits before point
NDEC	INTEGER expression	Number of decimal places

CHFORM Effect

'F'	for fixed-point representation of all values
'E'	for floating-point representation of all values
'G'	'E' for very small or large values, 'F' otherwise

Description

By default, the format of REAL numbers (either drawn on pictures or converted to text strings by KREAL) is chosen to produce the smallest number of characters while still representing the value of the number. FIGFMT specifies an alternative format.

CHFORM corresponds to FORTRAN format specifiers. If CHFORM='G', the number of characters taken to represent the value in both 'E' and 'F' format is calculated and the format which takes up least space is used; in the case of these being equal, 'F' format is used.

NUMINT specifies how many digits are required before the decimal point in the mantissa of floating-point representations but has no effect on fixed-point representations. NUMINT=0 forces zero mantissa, but this is not omitted from the written form (*eg.* 0.123E4).

NDEC specifies how many decimal places are to be included – by default this depends on the value of the number. NDEC=0 indicates no decimal places, NDEC=-1 indicates no decimal places and no decimal point, and NDEC=-2 restores the default.

FIGFMT can be used to control the format of axis annotation: CHFORM controls whether a fixed-point or floating-point format is used for numerical axis labels but values of NUMINT and NDEC are ignored.

Default

CALL FIGFMT('G',1,-2) restores the default.

See also

FIGSGN, KREAL and PIINCL.

SUBROUTINE FIGSGN (SIGN, ESIGN)**Name**

FIGSGN – to specify the sign conventions for positive numbers and exponents.

Availability Section 1, released version 2-11.

Arguments

SIGN	CHARACTER*1	Representation of sign of positive number
ESIGN	CHARACTER*1	Representation of sign of positive exponent

SIGN or ESIGN	Description	Examples	
'+'	Always include sign	+12.4	+0.123E+4
' '	Space before +ve values	12.4	0.123E 4
'D'	Default (no + sign)	12.4	0.124E4

Description

By default, REAL numbers (either drawn on pictures or converted to text strings by KREAL) are preceded by a sign only if the value is negative or it is part of an exponent; FIGSGN specifies alternative conventions for the signs of positive numbers and/or exponents.

Default

CALL FIGSGN('D', 'D') restores the default.

See also

FIGFMT, KREAL and PIINCL.

**SUBROUTINE FILLK7 (ISHADE, CAP)
SUBROUTINE FILLKY (ISHADE, CAP, NCAP)**

Name

FILLK7 – to draw an annotated sample of fast area-fill characters in a key.

Availability Section plus, released version 2-10.

Arguments

ISHADE	INTEGER expression	Shading pattern number
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

FILLK7/FILLKY inserts a key to fast area-fill characters (as used on the shaded contour maps or raster pictures) in the next empty space in the current key or caption area (defined by DEFKEY/DEFCAP or selected by RESNXT).

A rectangular sample of the fast-area fill characters, corresponding to shading pattern ISHADE, is drawn on the left of the entry; the caption, CAP, is drawn [2] alongside the sample.

REAL and INTEGER values can be converted to text strings using the conversion subroutines, KREAL and KNUMB respectively.

Diagnostics

(Caption truncated)²
 (Key/caption area full)²
 (No active key/caption area)²

See also

ADDJST, BLNKKY, DEFKEY, FFSET, MPK7H, MPK7V, MPTYPE, RASTER, SHDEK7, SHPATT and SQSHAD.

SUBROUTINE FITPAG (ITYPE)**Name**

FITPAG – to specify the interpretation of **PAGE** on fixed picture devices.

Availability Section 4, released version 2-8.

Argument

ITYPE INTEGER expression Interpretation of **PAGE**

ITYPE *Device usage*

-
- | | |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0 | Output constrained to fit device, device size used as page size. The arguments of PAGE are only used to determine the orientation (portrait or landscape) of an area which can be rotated. |
| 1 | Page proportions as in specified by PAGE . The arguments of PAGE are observed on all devices; if the requested page size does not fit within a fixed picture device, the page is shrunk, but its proportions are retained, ensuring comparability of layout between output on different graphics devices. |
| 2 | Device independent layout, text, <i>ie.</i> WYSIWYG (what you see is what you get) output. All attempts to accommodate device differences are bypassed so that output looks similar on different devices. For example, software text is used if the exact size cannot be achieved with hardware text. |
| 3 | WYSIWYG output which may be rotated on all devices to honour page size. |
-

Description

FITPAG specifies the interpretation of the arguments to **PAGE**.

Default

CALL FITPAG(0) restores the default.

See also

PAGE and **PAGVW**.

SUBROUTINE FNAREA (XMIN, XMAX, YMIN, YMAX)**Name**

FNAREA – to specify the x - y plotting ranges for 3-D functions, $z = f(x, y)$.

Availability Section 2, released before version 2-5.

Arguments

XMIN	REAL expression	Minimum x value included
XMAX	REAL expression	Maximum x value included
YMIN	REAL expression	Minimum y value included
YMAX	REAL expression	Maximum y value included

Description

By default, contours of functions drawn by **FN*** are plotted over the ranges of the data of the current picture, and surface pictures are plotted over ranges 0.0 to 10.0 in both x and y . **FNAREA** specifies the ranges **XMIN** to **XMAX** and **YMIN** to **YMAX** over which 3-D functions $z = f(x, y)$ are plotted.

FNAREA can also be used to specify the x and y scales to be used on a null isometric picture (see **ISNEW**) and subsequent plotting (*via* **KISXY**); **SFZSCL** specifies z scale. This is because **SIMPLEPLOT** assumes that if there is no data to be drawn, a function is to be drawn.

Default

Calling **FNAREA** with **XMIN=XMAX** and/or **YMIN=YMAX** restores the default (if equal, the values are otherwise ignored).

See also

ISNEW, **KISXY** and **SFZSCL**.

SUBROUTINE FNCNTS (FUNXY)**Name**

FNCNTS – to draw a contour map from a 3-D function $z = f(x, y)$.

Availability Section 2, released before version 2-5.

Argument

FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement
-------	---------------	-------------------------------------------------------------------------------

Description

FNCNTS draws a contour map on the current picture representing values of the specified 3-D function. Contours are drawn for equally-spaced z values within the range of values of FUNXY. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

When plotting the function FUNXY with parameters X and Y, the value of FUNXY(X,Y) is interpreted as the surface height, z , at the point (x, y) .

The contours drawn by FNCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

CTBRKN overrides the bundled line-drawing attributes of pens associated with the four pen pointers.

Diagnostics

(Contour map not all in range)²

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, FNAREA, FNCONT, LIMSFN, RIDDLE, SFMESH, SQBRKN, SQPEN, SQZLAB and SQZVAL.

SUBROUTINE FNCONT (ZLEV, FUNXY)**Name**

FNCONT – to draw a contour curve from a 3-D function $z = f(x, y)$.

Availability Section 2, released before version 2-5.

Arguments

ZLEV	REAL expression	Contour level
FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement

Description

FNCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z = \text{ZLEV}$ from the specified function **FUNXY**.

When plotting the function **FUNXY** with parameters **X** and **Y**, the value of **FUNXY(X,Y)** is interpreted as the surface height, z , at the point (x, y) .

Diagnostics

(Contour curve not all in range)²

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, FNAREA, FNCNTS, LIMSFN, QCURVE, RIDDLE and SFMESH.

SUBROUTINE FNCUT (X1, Y1, X2, Y2, FUNXY)**Name**

FNCUT – to draw a 2-D curve of a surface section from a function $z = f(x, y)$.

Availability Section 2, released before version 2-5.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of two points
FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement

Description

If the surface represented by the function FUNXY were cut along the straight line from (x_1, y_1) to (x_2, y_2) , the side view of the section would show as a two-dimensional curve of the variation of the function along that line.

FNCUT draws [1] the curve of surface height *vs.* distance from (x_1, y_1) on the current picture – suitable scales must be set up before attempting to draw a section.

When plotting the function FUNXY with parameters X and Y, the value of FUNXY(X, Y) is interpreted as the surface height, z , at the point (x, y) .

Diagnostics

(Surface section not all in range)²

See also

CTBRKN, CTCURV, CTHOLD, FNAREA, LIMSFN and QCURVE.

SUBROUTINE FNRNGE (START, STOP)**Name**

FNRNGE – to specify a restricted x range over which to plot 2-D functions $y = f(x)$.

Availability Section 1, released before version 2-5.

Arguments

START,	REAL expressions	Values of the independent variable
STOP		between which function to be drawn

Description

By default, DRAWFN, BRKNFN and SHDEFN plot the curve of a function over the complete range of the scale of the independent variable. FNRNGE specifies an alternative range. On polar pictures, FNRNGE specifies the θ range over which to plot the function $r = f(\theta)$. By default, the first cycle (0–360°) of a complete polar graph is used or the range of scale of the independent variable.

FNRNGE is essential for functions which would become infinite within the default range, or which would produce multi-cycle polar function curves.

If the 2-D composite graph drawing subroutines (*eg.* BRKNVCV, DRAWAR, SHDEC2, *etc.*) linear or quadratic regression curves (see CVTYPE), the curve drawn covers the range of the x scale defined by FNRNGE.

Default

Calling FNRNGE with START=STOP restores the default.

See also

BRKNFN, CVTYPE, DRAWFN, EQSCAL, SCALES and SHDEFN.

SUBROUTINE FNSHAD (ZLEV1, ZLEV2, ISHADE, FUNXY)**Name**

FNSHAD – to draw the shaded area between two contour levels from a 3-D function $z = f(x, y)$.

Availability Section plus, released version 2-5.

Arguments

ZLEV1, ZLEV2	REAL expressions	Contour levels
ISHADE	INTEGER expression	Shading pattern number
FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement

Description

FNSHAD shades the area between contour levels $z=\text{ZLEV1}$ and ZLEV2 for the function FUNXY ; the area is drawn on the current picture using shading pattern ISHADE . By default, the contours themselves are not drawn (see **SHEDGE**).

When plotting the function FUNXY with parameters X and Y , the value of $\text{FUNXY}(X, Y)$ is interpreted as the surface height, z , at the point (x, y) . If function values, z , coincide with contour levels, only those equal to z_{\min} are included within the shaded region, *ie.* $z_{\min} \leq z < z_{\max}$, where $z_{\min} = \min(\text{ZLEV1}, \text{ZLEV2})$ and $z_{\max} = \max(\text{ZLEV1}, \text{ZLEV2})$.

Diagnostics

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, FNAREA, FNSHDS, LIMSFN, MPTYPE, SFMESH and SHEDGE.

SUBROUTINE FNSHDS (FUNXY)**Name**

FNSHDS – to draw a shaded contour map from a 3-D function $z = f(x, y)$.

Availability Section plus, released version 2-5.

Argument

FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement
-------	---------------	-------------------------------------------------------------------------------

Description

FNSHDS draws a shaded contour map on the current picture from the specified function FUNXY. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of values of FUNXY; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

When plotting the function FUNXY with parameters X and Y, the value of FUNXY(X,Y) is interpreted as the surface height, z , at the point (x, y) .

Diagnostics

(Shaded contours not all in range)²

See also

CTLABS, CTNUMB, FNAREA, FNCNTS, FNSHAD, LIMSFN, MPTYPE, SFMESH, SHEDGE, SHPATT and SQ*.

SUBROUTINE FNSURF (FUNXY)

Name

FNSURF – to start a new picture and draw a surface from a 3-D function $z = f(x, y)$.

Availability Section 2, released before version 2-5.

Argument

FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement
-------	---------------	-------------------------------------------------------------------------------

Description

FNSURF starts a new picture and draws a surface of the specified function over the ranges of x and y specified by the latest call of FNAREA. If FNAREA has not been called, or has been used to indicate that the default ranges are required, the defaults (x from 0.0 to 10.0, y from 0.0 to 10.0) are used by FNSURF.

When plotting the function FUNXY with parameters X and Y, the value of FUNXY(X, Y) is interpreted as the surface height, z , at the point (x, y) .

In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling FNSURF.

FNSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

Diagnostics

(Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

FNAREA, IS*, ISSHAD, LIMSFN, RIDDLE, SFEQZ, SFEQZD, SFLIMS, SFMESH and SFZSCL.

SUBROUTINE GETXY (VARX, VARY, ICODE)**Name**

GETXY – to input the coordinate of a data point from an interactive device.

Availability Section 4, released version 2-7.

Arguments

VARX, VARY	REAL variables	To receive coordinates of a point
ICODE	INTEGER variable	To receive value identifying method of input

Description

Some graphics devices, when used interactively, are capable of allowing graphics input, *ie.* a device operation can be initiated to allow the user to select a point on the display area, and the coordinates of the point be transmitted to the computer. GETXY inputs the coordinates, (x, y) , of a point on an interactive device.

VARX and VARY must be names of REAL variables to receive the user coordinates of a point, and ICODE must be the name of an INTEGER variable to receive the code number of the key used for input. A command is sent to the terminal to prepare to receive graphics input, then a reply is requested in whatever form the device allows.

When the input is received by SIMPLEPLOT, the code of the key pressed (*eg.* which keyboard key was used, or which button was pressed) is placed in ICODE, and the coordinates are converted to (x, y) user coordinates and placed in VARX and VARY. The conversion subroutine KXYXY can be used to convert user coordinates into page coordinates or device coordinates.

Please note that GETXY only operates on devices with input capability, and which have suitable device drivers and the necessary physical connections.

Diagnostics

(Graphics input failed)¹

(Graphics input not available)¹

See also

KXYXY.

SUBROUTINE GROUP (NHORIZ, NVERT)**Name**

GROUP – to specify how pictures are to be grouped on the SIMPLEPLOT page.

Availability Section 1, released before version 2-5.

Arguments

NHORIZ	INTEGER expression	Number of pictures to be placed horizontally
NVERT	INTEGER expression	Number of pictures to be placed vertically

Description

By default, SIMPLEPLOT positions pictures one per page. GROUP specifies that pictures are to be grouped together on a page in a configuration of NHORIZ pictures across by NVERT down.

After GROUP has been called, the next *new picture* subroutine positions the picture in the top left of a new SIMPLEPLOT page; subsequent new pictures fill the group left to right, top to bottom. When enough pictures have been drawn to fill the group, the next new picture automatically starts a new group (on a new SIMPLEPLOT page).

If either the margins or the picture size is changed after a group has been started, subsequent pictures are drawn using the changed sizes but the total group area remains fixed. Such changes may therefore affect the number of pictures which can be accommodated in the group.

GROUP finishes the plotting on the current SIMPLEPLOT page if a picture has been started on it; this is to avoid any confusion due to the resetting of page layout.

There are no explicit limits to the number of pictures in a group but there may be practical constraints due to other elements of the layout.

Diagnostics

(Grouping discontinued)¹

Default

Calling GROUP with either argument set to zero or both arguments set to 1 restores the default.

See also

BOXGRP, ENDPAG, NEWPIC, NEWPAG and PAGVW.

SUBROUTINE HSTCLC (DARR, NDARR, X1, DX, FARR, NFARR)**Name**

HSTCLC – to calculate data frequencies from raw data.

Availability Section 1, released before version 2-5.

Arguments

DARR	REAL array	Raw data
NDARR	INTEGER expression	Number of elements in DARR
X1	REAL variable	Offset value for subdivisions
DX	REAL variable	Frequency interval
FARR	REAL array	To receive frequency table
NFARR	INTEGER expression	Number of elements in FARR

Description

HSTCLC scans the array DARR and builds a frequency table in the array FARR. The value in DX when HSTCLC is called is used as the frequency interval unless it is found that the number of intervals would exceed NFARR, in which case a suitable frequency interval is chosen and the value of DX is reset. Interval subdivisions are placed at X1 plus integer multiples of DX, and X1 is reset to the DARR value at the interval subdivision at the start of FARR(1). DX and X1 must be names of variables which have already been given values before HSTCLC is called because their values are used, and may be changed.

See also

HSTCUM and HSTPLT.

SUBROUTINE HSTCUM (X1, DX, FARR, NARR)**Name**

HSTCUM – to draw a cumulative histogram from frequencies.

Availability Section 1, released before version 2-5.

Arguments

X1	REAL expression	Offset value for subdivisions
DX	REAL expression	Frequency interval
FARR	REAL array	Frequency table
NARR	INTEGER expression	Number of elements in FARR

Description

HSTCUM draws a cumulative histogram on the current picture from frequency values in FARR. Frequencies can be calculated from raw data using HSTCLC.

Diagnostics

(HISTOGRAM OMITTED: ZERO INTERVAL)¹

See also

HSTSHD, HSTCLC and HSTPLT.

SUBROUTINE HSTDIR (XTORF, FTORF)**Name**

HSTDIR – to specify the directions of scales for histograms drawn by HSTGRM.

Availability Section 4, released version 2-11.

Arguments

XTORF	LOGICAL expression	Whether to reverse direction of x scale
FTORF	LOGICAL expression	Whether to reverse direction of frequency scale

Description

By default, the scales on a histogram drawn by HSTGRM are calculated to fit the data exactly and are configured such that scales go from a small value to a larger value. HSTDIR specifies any combination of scale directions, by indicating for each whether to reverse the x scale and/or the frequency (or y) scale; the range of the scales can be specified by HSTRNG.

Default

CALL HSTDIR(.FALSE., .FALSE.) restores the default.

See also

HSTRNG and HSTGRM.

SUBROUTINE HSTGRM (DARR, NARR, X1, DX, CAPX, CAPY)**Name**

HSTGRM – to draw a histogram from raw data on the current picture.

Availability Section 4, released version 2-11.

Arguments

DARR	REAL array	Raw data
NARR	INTEGER expression	Number of elements in DARR
X1	REAL expression	Offset value for subdivision
DX	REAL expression	Frequency interval
CAPX	STRING expression	<i>x</i> -axis caption
CAPY	STRING expression	<i>y</i> -axis caption

Description

HSTGRM builds a frequency table from the values in the array DARR, and draws a histogram with annotated axes on the current picture.

DX specifies the required frequency interval; if DX=0.0, a suitable frequency interval is chosen internally. Interval subdivisions are placed at all values of the form $x_1 + n, dx$ (where n is any INTEGER and dx is the frequency interval) within the range of values in the array DARR.

HSTGRM draws an *x*-axis and a *y*-axis which can be configured using appropriate AX* subroutines with CHAXIS='XC' and 'YC' respectively. The *x*-axis is labelled with CAPX and the *y*-axis labelled with the caption CAPY. By default, the number of *x*-axis subdivisions relates directly to the frequency interval, DX, therefore AXSBDV should be used with care.

By default, a histogram displaying frequencies is drawn and the boxes are unshaded; the scales are calculated to fit the data exactly and both scales run in the natural direction of the corresponding axis. These default settings can be altered by HSTTYP, HSTSHD, HSTRNG and HSTDIR respectively.

Current plotting scales are ignored by HSTGRM but not reset.

See also

HSTDIR, HSTRNG, HSTTYP and HSTSHD.

SUBROUTINE HSTPLT (X1, DX, FARR, NARR)**Name**

HSTPLT – to draw a histogram from frequencies.

Availability Section 1, released before version 2-5.

Arguments

X1	REAL expression	Offset value for subdivisions
DX	REAL expression	Frequency interval
FARR	REAL array	Frequency table
NARR	INTEGER expression	Number of elements in FARR

Description

HSTPLT draws a histogram on the current picture from frequency values in FARR. Frequencies can be calculated from raw data using HSTCLC.

Diagnostics

(HISTOGRAM OMITTED: ZERO INTERVAL)¹

See also

HSTSHD, HSTCLC and HSTCUM.

SUBROUTINE HSTRNG (XMIN, XMAX, FMIN, FMAX)**Name**

HSTRNG – to specify the range of scales for histograms drawn by HSTGRM.

Availability Section 4, released version 2-11.

Arguments

XMIN	REAL expression	Minimum horizontal scale value
XMAX	REAL expression	Maximum horizontal scale value
FMIN	REAL expression	Minimum vertical scale value
FMAX	REAL expression	Maximum vertical scale value

Description

By default, the scales of a histogram drawn by HSTGRM are calculated to accommodate the data exactly. HSTRNG specifies alternative range of scales (the direction of scales can be specified separately by HSTDIR).

If the specified scales can not accommodate the entire histogram, part of the picture cannot be drawn. This contributes to the number of incomplete picture tasks and a diagnostic is issued at the end of the picture.

Current plotting scales are ignored by HSTGRM but not reset.

Default

Calling HSTRNG with $XMAX \leq XMIN$ and/or $FMAX \leq FMIN$ restores the default. *eg.* CALL HSTRNG(0.0,0.0,0.0,0.0).

See also

HSTGRM and HSTDIR.

SUBROUTINE HSTSHD (ISHADE)**Name**

HSTSHD – to specify a shading pattern for the boxes used to draw a histogram.

Availability Section 4, released version 2-11.

Argument

ISHADE INTEGER expression Shading pattern number

Description

By default, histograms are drawn with unshaded boxes. To draw a shaded histogram (using HSTGRM, HSTPLT or HSTCUM) a single shading pattern can be selected by HSTSHD.

Default

CALL HSTSHD(-1) restores the default.

See also

SHSET and SHEDGE.

SUBROUTINE HSTTYP (ITYPE)**Name**

HSTTYP – to specify the type of histogram to be plotted by HSTGRM.

Availability Section 4, released version 2-11.

Argument

ITYPE INTEGER expression Type of histogram

ITYPE	Type of histogram
1	Standard histogram
2	Cumulative histogram
3	Complementary (or inverse) cumulative histogram

Description

By default, HSTGRM draws a standard histogram in which the boxes represent the frequencies calculated from the raw data. HSTTYP changes the type of histogram drawn.

HSTTYP must be called before HSTGRM.

Default

CALL HSTTYP(1) restores the default.

See also

HSTGRM.

SUBROUTINE INITBL**Name**

INITBL – to cancel all current blanked areas.

Availability Section 1, released version 2-14.

Arguments

None.

Description

INITBL cancels all areas blanked by CHMASK, DEFCAP and MKMASK. Subsequent drawing is only masked against newly defined blanked areas.

The use of masked areas affects the speed of a plot, so INITBL results in faster output.

See also

CHMASK, DEFCAP and MKMASK.

SUBROUTINE INITSP

Name

INITSP – to reset all SIMPLEPLOT defaults.

Availability Section 1, released version 2-5.

Arguments

None.

Description

All *specification* or *reset* subroutines change SIMPLEPLOT's default behaviour.

The documentation for each specification subroutine includes details of how to restore this default behaviour individually.

INITSP restores the default behaviour of all subroutines simultaneously. There are a few exceptions to this rule: the specification subroutines which control characteristics of the I/O interface such as the diagnostic level and the current device are not reset by INITSP. The subroutines in this category include DIAGLV, DEVNAM, DEVNO, IOCHAN, OWNNEW, OWNFIL. Similarly, INITSP does not reset the device palette (defined by PENRGB or PENHLS) nor does it affect metafile I/O.

INITSP finishes the plotting on the current SIMPLEPLOT page regardless of whether it contains a picture. This is to avoid any confusion due to the resetting of page layout.

See also

ENDPLT.

SUBROUTINE IOCHAN (ITYPE, ICHAN)**Name**

IOCHAN – to specify a value to be associated with a SIMPLEPLOT internal I/O channel.

Availability Section plus, released version 2-12.

Arguments

ITYPE	INTEGER expression	Type of channel usage
ICHAN	INTEGER expression	Value to be associated with that channel

ITYPE Channel usage

1	Diagnostics
2	Prompt output
3	Prompt input
4	Graphics output
5	Graphics input
6	Configuration
8	Scratch file used for shading
9	Hershey font file
10	Scratch file used for metafiles

Description

By default, SIMPLEPLOT allocates all input and output channels internally. IOCHAN specifies an alternative value (*eg.* FORTRAN logical unit number, GKS connection identifier *etc.*) for the type of usage described by ITYPE.

Valid values of ICHAN and their effect may depend on the host processor, device driver system and (where ITYPE=4, 5 or 6) the individual device driver in use.

In order to allow IOCHAN to be used repeatedly before SIMPLEPLOT is fully initialized, it does not trigger the initial diagnostic message:

(SIMPLEPLOT Mark 2-15(nnn)X)

Default

CALL IOCHAN(ITYPE,-1) restores the default.

The default is not restored by INITSP.

See also

MTFIL, OWNFIL and Appendix H, *Host Specific Information*.

SUBROUTINE ISANG (ANGLE)

Name

ISANG – to specify the angle at which surface pictures are drawn.

Availability Section 2, released before version 2-5.

Argument

ANGLE REAL expression Angle in degrees

Description

By default, surfaces are drawn such that the angle between the horizontal plane and the base plane is 15.0°. ISANG specifies an alternative angle.

The viewing corner of the data (see ISVIEW) is positioned at the front of the picture before rotation is performed, and therefore will not be at the front of the picture for angles between 90.0° and 270.0°.

Default

CALL ISANG(15.0) restores the default.

See also

ISVIEW.

SUBROUTINE ISAXD7 (CAPX, CAPY, CAPZ)
SUBROUTINE ISAXDR (CAPX, NCAPX, CAPY, NCAPY, CAPZ, NCAPZ)

Name

ISAXD7 – to draw 3-D axes on an isometric picture.

Availability Section plus, released version 2-9.

Arguments

CAPX	STRING expression	x -axis caption
CAPY	STRING expression	y -axis caption
CAPZ	STRING expression	z -axis caption
NCAPX	INTEGER expression	Number of characters in CAPX
NCAPY	INTEGER expression	Number of characters in CAPY
NCAPZ	INTEGER expression	Number of characters in CAPZ

Description

By default, the surface pictures drawn by the *SURF subroutines do not include axes. ISAXDR/ISAXD7 draws x - y - z axes on the current surface picture.

The x - y - z diagram indicating the directions of change of x , y and z , can be omitted by calling ISDIAG.

Diagnostics

(Isometric axes inappropriate)²

See also

AXIS7, ISAXES and ISDIAG.

SUBROUTINE ISAXES (TORF)**Name**

ISAXES – to specify whether surface pictures are to include 3-D axes.

Availability Section plus, released version 2-9.

Argument

TORF LOGICAL expression Whether axes required

Description

By default, surface pictures drawn by FNSURF, RGSURF, XSURF, XYSURF, YSURF, ZSURF and ZZSURF do not have axes on them. ISAXES specifies whether or not x - y - z axes are to be drawn as part of a surface picture.

Captions 'X', 'Y' and 'Z' are automatically given to the x -axis, y -axis and z -axis respectively.

If ISAXES is active, the x - y - z diagram normally controlled by ISDIAG is omitted.

Default

CALL ISAXES(.FALSE.) restores the default.

See also

AXIS7, ISAXD7 and ISDIAG.

SUBROUTINE ISAXFC (IXFIX, IYFIX, IZFIX)**Name**

ISAXFC – to specify the colours for filled rear planes of *SIMPLEPLOT Isometric* pictures.

Availability Section plus, released version 2-14.

Arguments

IXFIX	INTEGER expression	Fill index for rear x plane
IYFIX	INTEGER expression	Fill index for rear y plane
IZFIX	INTEGER expression	Fill index for rear z plane

Description

ISAXFC specifies colour indices for filling the rear planes of *SIMPLEPLOT Isometric* pictures. If a non-negative value is specified for any plane, it is filled whenever a new image is started. ISAXFC must therefore be called before ISNEW.

IXFIX specifies the colour index for the rear plane(s) with x constant, IYFIX specifies the colour index for the rear plane(s) with y constant, and IZFIX specifies the colour index for the rear plane(s) with z constant.

If colour index -1 is specified, the associated plane is not filled. This is the default.

Default

CALL ISAXFC($-1, -1, -1$) restores the default.

Diagnostics

[INTEGER out of range]¹

See also

ISAXGC.

SUBROUTINE ISAXGC (IXCIX, IYCIX, IZCIX)**Name**

ISAXGC – to specify the colour indices for grid lines on the rear planes of *SIMPLEPLOT Isometric* pictures.

Availability Section plus, released version 2-14.

Arguments

IXCIX	INTEGER expression	Colour index for x
IYCIX	INTEGER expression	Colour index for y
IZCIX	INTEGER expression	Colour index for z

Description

ISAXGC specifies colour indices for grid lines on the rear planes of the *SIMPLEPLOT Isometric* picture. When grids have been requested, they are drawn in the raster image whenever a new image is started. ISAXGC must therefore be called before ISNEW.

IXCIX specifies the colour index for grid lines on the rear plane(s) with x constant, IYCIX specifies the colour index for grid lines on the rear plane(s) with y constant, and IZCIX specifies the colour index for grid lines on the rear plane(s) with z constant.

If index -1 is specified, the associated grids are omitted. This is the default.

Default

CALL ISAXGC($-1, -1, -1$) restores the default.

Diagnostics

[ISAXGC: Colour index I out of range]¹

See also

ISAXFC.

SUBROUTINE ISBRBZ (ZVAL)**Name**

ISBRBZ – to specify the base z value for bars in *SIMPLEPLOT Isometric* 3-D barcharts.

Availability Section plus, released version 2-14.

Argument

ZVAL	REAL expression	Required base z value
------	-----------------	-------------------------

Description

By default, *SIMPLEPLOT Isometric* 3-D barcharts show each bar extending from zero z , to a z value from an array. ISBRBZ can be called before ISBRFL to set an alternative base z value.

Default

CALL ISBRBZ(0.0) restores the default.

See also

ISBRFL.

SUBROUTINE ISBRFC (ICODE)**Name**

ISBRFC – to specify how colour sequences should be used on subsequent *SIMPLEPLOT Isometric* 3-D barcharts.

Availability Section plus, released version 2-14.

Arguments

ICODE INTEGER expression Usage (see below)

ICODE Different colours

0	Faces of bars distinguished by pen pointers (Default)
1	Data Rows distinguished by colour sequence
2	Data Columns distinguished by colour sequence
3	Data Sets distinguished by colour sequence
4	Data magnitudes distinguished by colour sequence

Description

ISBRFL fills a *SIMPLEPLOT ViSualization* 3-D barchart. ISBRFC can be called before ISBRFL, to specify how colours are used for the bars.

When ICODE = 0, three colour indices distinguish the three planes of each bar: the *x* plane uses the first colour index, the *y* plane uses the second, and the *z* plane uses the third.

When ICODE > 0, all planes of a bar are shaded with the same colour index. SQSHAD may be called to specify the sequence of colour indices. When SQSHAD has not been called, the colour indices are used in the natural sequence 1, 2, 3, ...

The edges of each plane are drawn using pen pointer [4]. Pen pointer values are controlled by SETPNS.

Default

CALL ISBRFC(0) restores the default.

See also

SQSHAD.

SUBROUTINE ISBRFL (D3ARR, NX, NY, NSETS)**Name**

ISBRFL – to fill a *SIMPLEPLOT Isometric* 3-D barchart.

Availability Section plus, released version 2-14.

Arguments

D3ARR	REAL 3-D array	$NX \times NY \times NSETS$ array of user (z) values
NX, NY, NSETS	INTEGER expressions	Dimensions of 3-D data array

Description

ISBRFL starts a new picture and draws a *SIMPLEPLOT Isometric* 3-D barchart. The barchart represents NSETS sets of values in array D3ARR, stacked on top of each other. The sets may be stacked downward with the first set at the top, or upward with the first set at the bottom, as specified by ISBRUP.

Different colours may be used to distinguish between data columns, data rows, or data sets, or data magnitudes, as specified by ISBRFC.

If all the values in D3ARR are equal to the base z value set by ISBRBZ, a diagnostic is issued and nothing is drawn.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
(BAR CHART OMITTED: NULL RANGE)¹

See also

ISBRBZ, ISBRFC and ISBRSZ.

SUBROUTINE ISBRSZ (X1, X2, Y1, Y2)**Name**

ISBRSZ – to specify the widths of bars in *SIMPLEPLOT Isometric* 3-D barcharts.

Availability Section plus, released version 2-14.

Arguments

X1, X2	REAL expressions	Limits of bars in x direction
Y1, Y2	REAL expressions	Limits of bars in y direction

Description

By default, each bar in *SIMPLEPLOT Isometric* 3-D barcharts extends from 0.1 to 0.9 of the space available in both x and y . ISBRSZ can be called to specify alternative limits.

When X2 is not greater than X1, or either lies outside the range 0.0 to 1.0, the default in x is restored; when Y2 is not greater than Y1, or either lies outside the range 0.0 to 1.0, the default in y is restored.

Default

CALL ISBRSZ(0.0, 0.0, 0.0, 0.0) restores the default.

See also

ISBRFL.

SUBROUTINE ISBRUP (IUP)**Name**

ISBRUP – to specify the stacking direction for *SIMPLEPLOT Isometric* 3-D barcharts.

Availability Section plus, released version 2-14.

Arguments

IUP INTEGER expression Whether bars stack upwards

IUP	Direction
0	Downward (Default)
1	Upward

Description

ISBRUP is called before ISBRFL to specify whether multiple data sets should be stacked downward with the first set at the top, or upward with the first set at the bottom.

Diagnostics

[ISBRUP: Integer *I* out of range]¹

Default

CALL ISBRUP(0) restores the default.

See also

ISBRFL.

SUBROUTINE ISCURV (NSTEPS)**Name**

ISCURV – to specify the smoothness of curves on crosshatched and cascade surface pictures.

Availability Section 2, released before version 2-5.

Argument

NSTEPS INTEGER expression Number of steps

Description

Outline surfaces are drawn as rapidly as possible using straight lines between points on an underlying grid; however, the curves used to draw the mesh lines on crosshatched and cascaded pictures (see **ISTYPE**) are interpolated between mesh intersections to improve the picture. By default, the number of steps used depends on the picture size; fewer steps are used on smaller pictures. **ISCURV** specifies the number of steps when interpolating between grid intersections.

After **ISCURV** has been called, each piece of curve between intersections is drawn in **NSTEPS** steps, interpolated on a smooth curve through the intersections. Small values of **NSTEPS** lead to faster processing, but less smooth drawings.

The fineness of the underlying mesh can be controlled by **ISMESH** or **SFMESH**.

Default

Calling **ISCURV** with **NSTEPS** less than 2 (the minimum value possible) restores the default.

See also

ISMESH and **SFMESH**.

SUBROUTINE ISDIAG (TORF)**Name**

ISDIAG – to specify whether surface pictures are to include an x - y - z diagram.

Availability Section 2, released version 2-6.

Argument

TORF LOGICAL expression Whether a diagram is required

Description

By default, a diagram is drawn alongside surfaces with arrows indicating the directions of change of the 3 variables, x , y and z . ISDIAG specifies whether or not an x - y - z diagram is to be drawn as part of a surface picture. ISDIAG must be called before a surface is drawn.

If ISAXES is active, the x - y - z diagram is omitted regardless of ISDIAG.

Default

CALL ISDIAG(.TRUE.) restores the default.

See also

ISAXES.

SUBROUTINE ISFULL (TORF)**Name**

ISFULL – to specify whether surface pictures fill the space available.

Availability Section 2, released version 2-7.

Argument

TORF LOGICAL expression Whether to fill the space

Description

By default, surface pictures are drawn such that all rotations of the surface can be drawn to the same scale within the picture size. This allows comparisons of rotated pictures but can result in a very small picture with a large empty area around it. ISFULL specifies whether or not surfaces are to be drawn to reach the picture limits.

After a call of ISFULL(.TRUE.), each surface picture is drawn on a scale to make the surface as big as possible within the picture limits but without changing the aspect ratio.

Default

CALL ISFULL(.FALSE.) restores the default.

See also

ISRISE.

SUBROUTINE ISMESH (MXY)**Name**

ISMESH – to specify the fineness of detail in surface pictures.

Availability Section 2, released before version 2-5.

Argument

MXY	INTEGER expression	Total number of mesh lines used in x and y
-----	--------------------	---------------------------------------------------

Description

The processing of all surface pictures is based on the same mesh of lines at equally-spaced x values and equally-spaced y values as are drawn on crosshatched (and cascaded) surfaces. By default, for data on a regular grid the data grid is used, and for all other types of data MXY=20 is used. ISMESH can be to specify the total number of x lines and y lines ($MXY = MX + MY$).

The relative values of MX and MY determine the relative lengths of the x scale and y scale in the picture. The distribution of MXY between MX and MY depends on the data type and the x - y ranges of the data. For equally-spaced gridded data, if either of the x - y scales has not been specified, MX and MY are given values proportional to the numbers of data values in the x and y directions; if both of the x - y scales are known, MX and MY are set in a similar ratio to x -range: y -range, unless that ratio would produce either MX or MY less than 5, in which case $MX=MY=MXY/2$.

Larger values of MX and MY produce surfaces with finer detail, and cross-hatched pictures with a closer mesh, but the processing is necessarily slower.

ISMESH has no effect while SFMESH is active.

Default

Calling ISMESH with MXY less than 4 restores the default.

See also

ISCURV and SFMESH.

SUBROUTINE ISNEW**Name**

ISNEW – to start a null isometric picture.

Availability Section 2, released before version 2-5.

Arguments

None.

Description

ISNEW starts a new picture and sets up scales for three-dimensional plotting. The scales are the same as would be set for surface pictures – the x - y scales cover the ranges specified by a previous call of **FNAREA** (or default to 0.0 to 10.0 for both x and y); the z scale is as specified by a previous call of **SFZSCL** (or the same default, 0.0 to 10.0).

ISNEW is a *graphics* subroutine but, by default, does no drawing. If one of the **BOX*** subroutines has been called to generate boxes around pictures, groups or pages, these are drawn [1] when a new picture is started.

Any point (x, y, z) on this new isometric picture can be addressed as a Cartesian pair (x, y) using the conversion subroutine **KISXY**. Hence, any of the graph drawing subroutines (*eg.* **CP7PT**, **BRKNPT**, **MARKPT**) can be used on an isometric picture.

See also

FNAREA, **SFZSCL** and **KISXY**.

SUBROUTINE ISRISE (FACTOR)**Name**

ISRISE – to specify the proportions of surface pictures.

Availability Section 2, released before version 2-5.

Argument

FACTOR	REAL expression	Specifies the maximum height of the surface above the base plane
--------	-----------------	------------------------------------------------------------------

Description

By default, the z scale of surface pictures is set by assigning some length on the picture to cover the range of surface heights to be represented. ISRISE specifies that the length to cover the range of surface heights on surface pictures is to be $\text{FACTOR} \times \text{picture width} \times \cos(\text{ANGLE})$ where ANGLE is the angle (in degrees) between the horizontal plane and the base plane as specified by ISANG.

Default

CALL ISRISE(0.4) restores the default.

See also

ISANG and ISFULL.

SUBROUTINE ISSBAS (IBASE)**Name**

ISSBAS – to specify the type of base on shaded surface pictures.

Availability Section plus, released version 2-13.


Argument

IBASE INTEGER expression Type of shading used for base

IBASE	Type of shading used
0	None (default)
1	Solid shading but only when skirts are also drawn
2	Solid shading (see ISSPAT)

Description

By default, shaded surfaces are drawn with neither a skirt, a backdrop nor a base. ISSBAS specifies the method used for drawing a base.



IBASE specifies the type of shading to be used for drawing the base at the foot of the skirts.

By default, shading pattern 0 (rub-out) is used for solid shading but an alternative pattern can be selected using ISSPAT.

Default

CALL ISSBAS(0) restores the default.

See also

ISSBCK, ISSHAD, ISSKRT, ISSPAT, ISTYPE, RASTER and SQSHAD.

SUBROUTINE ISSBCK (IBACK)

Name

ISSBCK – to specify the type of backdrops on shaded surface pictures.

Availability Section plus, released version 2-13.


Argument

IBACK INTEGER expression Type of shading used for backdrop

IBACK	Type of shading used
0	None (default)
1	Solid shading; default pattern 0 (see ISSPAT)
2	Vertical lines
3	Horizontal lines parallel to the x - y plane
4	Shaded horizontal bands, parallel to the x - y plane

Description

IBACK specifies the type of shading used for the *backdrop*, the area behind the surface which covers the full range of the z -axis.



By default, shading pattern 0 (rub-out) is used for solid shading but an alternative pattern can be selected using ISSPAT.

Default

CALL ISSBCK(0) restores the default.

See also

ISSBAS, ISSHAD, ISSKRT, ISSPAT, ISTYPE, RASTER and SQSHAD.

SUBROUTINE ISSHAD (IMETHD)**Name**

ISSHAD – to specify the method of shading used on shaded surface pictures.

Availability Section plus, released version 2-13.

Argument

IMETHD INTEGER expression Method of shading

IMETHD Shading method

- | | |
|---|---------------------------------------------------------------|
| 0 | No shading (default) |
| 1 | Shading in whole quadrilaterals (fastest) |
| 2 | Quadrilaterals split into 2 |
| 3 | Quadrilaterals split into 4 |
| 4 | Shading corresponding to contours (slowest but most accurate) |
-

Description

By default, the *SURF subroutines draw a surface represented by lines but with no shading. ISSHAD specifies the method for shading subsequent surfaces according to the value of IMETHD.

By default, the shaded surface is drawn as a raster picture (see RASTER) using the currently selected fast area-fill characters. Shaded surfaces may include lines according to a prior call of ISTYPE (eg. outlines, crosshatching). Axes, text and keys are not drawn as part of this raster picture. The fineness of detail of the raster image is controlled by FFSIZE.

Default

CALL ISSHAD(0) restores the default.

See also

ISSBAS, ISSBCK, ISSKRT, ISSPAT, ISTYPE and RASTER.

SUBROUTINE ISSKRT (ISKIRT)**Name**

ISSKRT – to specify the type of skirts on shaded surface pictures.

Availability Section plus, released version 2-13.


Argument

ISKIRT INTEGER expression Type of shading used for skirts

ISKIRT	Type of shading used
0	None (default)
1	Solid shading; default pattern 9 (see ISSPAT)
2	Vertical lines superimposed over solid shading
3	Horizontal lines parallel to the x - y plane
4	Shaded horizontal bands, parallel to the x - y plane

Description

ISKIRT specifies the type of shading used for *skirts*, the area on the picture between the edge of the surface and the plane of the x and y axes.

**Default**

CALL ISSKRT(0) restores the default.

See also

ISSBAS, ISSBCK, ISSHAD, ISSPAT, ISTYPE, RASTER and SQSHAD.

SUBROUTINE ISSPAT (CHFACE, ISHADE)**Name**

ISSPAT – to specify the shading patterns to be used on shaded surfaces.

Availability Section plus, released version 2-13.

Arguments

CHFACE	CHARACTER*2	Face of skirt, backdrop or base
ISHADE	INTEGER expression	Shading pattern of the face

Description

By default, shaded surfaces are drawn without skirts, backdrops or a base. If ISSBAS, ISSBCK or ISSKRT has been called to specify shaded skirts, backdrops and/or base, the default shading pattern used is pattern 0 (rub-out). ISSPAT selects an alternative.

Individual faces can be selected for shading, with the 2 character string CHFACE. The first character of CHFACE refers to the face ('A' to 'D' for skirts/backdrops, 'G' for bases). The second character refers to the position ('I' inner, 'O' outer or 'B' backdrop). The possible interpretations of CHFACE are listed in Appendix T of the *SIMPLEPLOT Supplement*.

For ungridded data, or rectangular data with no-data values, skirts do not necessarily occur at the rectangular faces; skirts dropped from holes and from surfaces where the boundary is not along a face, are identified by CHFACE='ND'.

A wildcard character, '*', can be used in place of either character of CHFACE to denote a set of faces. For example, CHFACE='**' for all faces of skirts, backdrops and the base; '*B' for all backdrops; 'A*' for the inner skirt, outer skirt and backdrop associated with face A.

If no skirt, backdrop nor base is drawn, or shaded contour bands are drawn, ISSPAT has no effect.

Diagnostics

(Invalid shading area: XX)¹

Default

CALL ISSPAT('*',0) restores the default.

See also

ISSBAS, ISSBCK, ISSKRT, ISSHAD, RASTER, SHSET and SQSHAD.

SUBROUTINE ISTYPE (ITYPE)

Name

ISTYPE – to specify the type of surface picture.

Availability Section 2, released before version 2-5.

Argument

ITYPE INTEGER expression Type of picture

ITYPE	Type of surface picture
0	No lines drawn
1	Surface outline (default)
2	Surface outline and a set of contours
3	Crosshatched picture
4	Set of curves of z against x for a set of equally-spaced y values
5	Set of curves of z against y for a set of equally-spaced x values

Description

By default, the *SURF subroutines draw a surface outline with no shading. ISTYPE specifies an alternative type of surface picture. The number of curves drawn in crosshatched and cascaded pictures (ITYPE=3, 4 or 5) can be controlled by ISMESH or SFMESH.

Default

CALL ISTYPE(1) restores the default.

See also

ISMESH, ISSHAD and SFMESH.

SUBROUTINE ISVIEW (ICORNR)**Name**

ISVIEW – to specify the view point for surface pictures.

Availability Section 2, released before version 2-5.


Argument

ICORNR INTEGER expression Viewing corner

Description

Each surface picture covers a rectangular region of the x - y plane, even when the data structure plotted by *SURF is non-rectangular. By default, surface pictures represent the surface viewed with one of the corners of the rectangle at the front, and the opposite corner at the back.

By default, the minimum x and minimum y are at the front. ISVIEW specifies an alternative corner to be at the front. ICORNR specifies the viewing corner; corners are numbered 0, 1, 2, 3 in a clockwise direction, starting from 0 at the first data point.



The viewing corner of the data is positioned at the front of the picture before any rotation is performed (see ISANG), and therefore will not be at the front of the picture for angles between 90.0° and 270.0° .

Default

CALL ISVIEW(0) restores the default.

See also

ISANG and ISYUP.

SUBROUTINE ISYUP (TORF)

Name

ISYUP – to specify the direction of change of y on surface pictures.

Availability Section 2, released before version 2-5.

Argument

TORF LOGICAL expression Whether y increases upwards

Description

On Cartesian pictures, x is conventionally represented as increasing from left to right, and y as increasing from the bottom upwards. Tabulated data is also presented with x increasing from left to right, but y usually increases downwards.

By default, on surface pictures, data is treated in a conventional Cartesian sense with y values increasing upwards. ISYUP specifies the direction of change of y on surface pictures. If TORF=.FALSE., then y values are represented as increasing downwards, as is conventional for tables.

Default

CALL ISYUP(.TRUE.) restores the default.

See also

ISVIEW.

SUBROUTINE JOINPT (X, Y)**Name**

JOINPT – to draw a straight line to the point (x, y) (or (R, θ)).

Availability Section 1, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point specified in units of the plotting scales
------	------------------	---------------------------------------------------------------------

Description

JOINPT draws a straight line to the point (x, y) , or (R, θ) if the polar coordinates have been specified by COORDS, EQSCAL or POLAR7. The line uses using the bundled line-drawing attributes of the current pen.

A line is started by the first call to JOINPT, or BRKNPT. The first call of JOINPT/BRKNPT moves to (x, y) without drawing anything; subsequent calls draw a straight line from the previous point to the specified point. The line is straight even on non-linear scales and polar charts.

A line is interrupted explicitly by BREAK, or if any other plotting subroutine is called. The next call of JOINPT/BRKNPT moves to the first point of a new line. MARKPT and CP7PT draw a symbol/caption at a specified (x, y) , followed by the equivalent to the first call to JOINPT/BRKNPT. A sequence of symbols joined by straight lines can be drawn by repeating the following calls for a sequence of points:

```
CALL JOINPT(X,Y)
CALL MARKPT(X,Y,MKTYPE)
```

The point (x, y) is specified in units of the current plotting scales (user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

$(**x, y**)^2$

See also

BREAK, BRKNPT, BUNLPR, CLIPLV, CP7PT and MARKPT.

SUBROUTINE KISXY (X3, Y3, Z3, X2, Y2)**Name**

KISXY – to convert a point (x, y, z) on a surface picture to its 2-D equivalent.

Availability Section 2, released version 2-11.

Arguments

X3, Y3, Z3	REAL expressions	Coordinates of a point, specified in 3-D picture units
X2, Y2	REAL variables	To receive the coordinates of a point specified in internal 2-D picture units

Description

On surface pictures, user coordinates are described by 3 variables (x, y, z) but the underlying coordinate system remains Cartesian and can be addressed as such. Any of the general plotting subroutines can be used by first converting a 3-D user coordinate into a 2-D picture coordinate using KISXY.

If any of the isometric coordinates, X3, Y3 or Z3, is equal to the current no-data value, then both X2 and Y2 are set to this no-data value. All plotting subroutines ignore coordinates for which either ordinate corresponds to the no-data value.

Diagnostics

(Isometric coordinates inappropriate)¹

See also

BRKNPT, CP7LB, CP7PT, CP7XC, CP7YC, JOINPT, MARKPT and NODATA.

SUBROUTINE KNUMB (IVAL, STR)

Name

KNUMB – to convert an **INTEGER** value to the equivalent text string.

Availability Section 1, released version 2-11.

Arguments

IVAL	INTEGER expression	Value to be converted
STR	STRING variable	To receive text string

Description

KNUMB converts an **INTEGER** value into the equivalent **CHARACTER** representation.

STR should be declared as a **CHARACTER** variable long enough to represent **IVAL**. **CHARACTER*10** should be sufficient for most **INTEGER**s. If **STR** is not long enough to contain the converted **INTEGER**, **SIMPLEPLOT** places as much of the number as possible into **STR** and issues a diagnostic.

Diagnostics

(String too short for **INTEGER**)¹

See also

CP7LB, CP7PT, CP7XC, CP7YC and KREAL.

SUBROUTINE KPOSXY (ITYPE, VCHAR, HCHAR, VCMS, VJST, HCMS, HJST)**Name**

KPOSXY – to convert a descriptive position into page coordinates.

Availability Section plus, released version 2-12.

Arguments

ITYPE	INTEGER expression	Intended use of position
VCHAR	CHARACTER*1	Vertical position of area
HCHAR	CHARACTER*1	Horizontal position of area
VCMS	REAL variable	To receive vertical coordinate
VJST	CHARACTER*1 variable	To receive vertical justification
HCMS	REAL variable	To receive horizontal coordinate
HJST	CHARACTER*1 variable	To receive horizontal justification

ITYPE Text usage

1	Titles
2	Key or captions areas

Description

KPOSXY returns coordinates (HCMS,VCMS) and justification (VJST,HJST) corresponding to a descriptive position (VCHAR,HCHAR) on the current page.

HCMS and VCMS describe the horizontal and vertical page coordinates of a title, key or caption area, specified in centimetres relative to the bottom left-hand corner of the current SIMPLEPLOT page. HCHAR, VCHAR, HJST and VJST are all single characters, whose possible interpretations are listed in Appendix T of the *SIMPLEPLOT Supplement*.

KPOSXY can only return sensible values for a picture or page which has already been started. If no picture/page has been started, or if ITYPE is not equal to 1 or 2, a diagnostic is issued and VCMS, HCMS, VJST, and HJST are returned with values 0.0, 0.0, 'B', and 'L' respectively.

Diagnostics

(KPOSXY argument invalid)¹

(KPOSXY called in wrong state)¹

See also

DEFPOS and KXYXY.

SUBROUTINE KREAL (RVAL, STR)**Name**

KREAL – to convert a REAL value to the equivalent text string.

Availability Section 1, released version 2-11.

Arguments

RVAL	REAL expression	Value to be converted
STR	STRING variable	To receive text string

Description

KREAL converts any REAL value into the equivalent CHARACTER representation.

STR should be declared as a CHARACTER variable long enough to represent RVAL. Most REAL numbers can be represented by a relatively small number of characters but, if STR is declared as a CHARACTER*30 variable, it should be able to accommodate even exceptionally large or small values. If STR is not long enough to contain the converted REAL, SIMPLEPLOT places as much of the number as possible into STR and issues a diagnostic.

Diagnostics

(String too short for REAL)¹

See also

CP7LB, CP7PT, CP7XC, CP7YC, FIGFMT and KNUMB.

SUBROUTINE KSCALE (START, STOP, DIV, VSTART, VSTOP, VDIV)**Name**

KSCALE – to convert scale limits such that they span whole subdivisions.

Availability Section 1, released version 2-12.

Arguments

START	REAL expression	Value required near beginning of scale
STOP	REAL expression	Value required near end of scale
DIV	REAL expression	Subdivision required
VSTART	REAL variable	To receive value to use at beginning of scale
VSTOP	REAL variable	To receive value to use at end of scale
VDIV	REAL variable	To receive subdivision value to use

Description

KSCALE takes the values **START**, **STOP** and **DIV** which describe the scale requirements, and converts them to **VSTART**, **VSTOP** and **VDIV** which satisfy the requirements and, if necessary, extend the scales to coincide with whole multiples of the scale subdivision. KSCALE does not affect scales directly, but it computes values which may be used to set scales or axis subdivisions as arguments for **SCALES**, **EQSCAL**, **AXSBDV**.

DIV is the requested subdivision; if **DIV** is zero, **SIMPLEPLOT** allocates a subdivision size related to the range of the scale, and its value is placed in **VDIV**; if **DIV** is non-zero, **VDIV** is given the magnitude of **DIV** and the sign of **STOP – START**.

If the physical length of an axis is too small for annotations at all multiples of **VDIV** to fit, the annotation interval is a multiple of **VDIV**; KSCALE knows nothing about axis length.

If **START = STOP**, then **VSTART**, **VSTOP** and **VDIV** are returned with values **START**, **STOP** and **DIV** respectively.

See also

AXSBDV and **SCALES**.

SUBROUTINE KTREAL (UNITS, IVAL1, IVAL2, RVAL, VALUE)

Name

KTREAL – to convert *time-date* value from external *time-date* triple to internal REAL form.

Availability Section plus, released version 2-12.

Arguments

UNITS	CHARACTER*1	'T'ime, 'M'onths or 'W'eeks
IVAL1	INTEGER expression	<i>Hours</i> or <i>years</i>
IVAL2	INTEGER expression	<i>Minutes</i> , <i>months</i> or <i>week number</i>
RVAL	REAL expression	<i>Seconds</i> , <i>date</i> or <i>day of week</i>
VALUE	REAL variable	To receive encoded <i>time-date</i> value

UNITS	IVAL1	IVAL2	RVAL
'T'ime	Hours	Minutes	Seconds
'M'onths	Year	Month	Date
'W'eeks	Year	Week no.	Day of week

Description

Time and *date* based data can be converted from the values of the three components (hours, minutes, seconds or year, month, day) to a single REAL value which can be used by SIMPLEPLOT for plotting coordinates and for setting picture scales. KTREAL converts such values.

Years in this century can be abbreviated to two digits – any year in the range 0–99 received by KTREAL has 1900 added to it in the conversion.

Days of the week are interpreted such that RVAL=1.0 represents Sunday, 2.0 represents Monday, *etc.*

Values encoded by KTREAL should be used first to set up suitable plotting scales, and then as coordinates for plotting.

If UNITS \neq 'T', 'M' or 'W', then VALUE is returned with value 0.0.

Diagnostics

(Invalid time-date units: X)¹

See also

KTSTR and KTTRI.

SUBROUTINE KTSTR (COMPNT, VALUE, STR, LENGTH)

Name

KTSTR – to convert one component of encoded *time-date* value from internal REAL to text.

Availability Section plus, released version 2-12.

Arguments

COMPNT	CHARACTER*2	<i>Time-date</i> component
VALUE	REAL expression	Encoded <i>time-date</i>
STR	STRING variable	To receive text string
LENGTH	INTEGER variable	To receive number of characters used in STR

COMPNT	Meaning	COMPNT	Meaning
'YE'	Year	'DE'	Days elapsed
'MO'	Month	'HO'	Hour
'WE'	Week number	'MI'	Minute
'DM'	Day of the month	'SE'	Second
'DW'	Day of the week		

Description

KTSTR converts the internal REAL representation of a *time-date* value into the text representation of one component of *time-date* annotations.

VALUE is interpreted as an encoded *time-date*, and STR is set to the text representation of the component of VALUE identified by COMPNT.

If COMPNT does not correspond to these values, a diagnostic is issued. In this case, or if VALUE corresponds to the current no-data value, STR is returned as ' ' and LENGTH=0.

The format of STR is affected by TIMFMT, TIMLDA and TIMLDC. LENGTH is set to the number of significant characters in STR.

If STR is not long enough to contain the converted component, SIMPLEPLOT places as much of the component as possible into STR and issues a diagnostic.

Diagnostics

(Invalid component type: XX)¹

(String too short for component)¹

See also

KTREAL, KTTRI, TIMFMT, TIMLDA and TIMLDC.

SUBROUTINE KTTRI (UNITS, VALUE, IVAL1, IVAL2, RVAL)

Name

KTTRI – to convert encoded *time-date* value from internal REAL to external triple form.

Availability Section plus, released version 2-12.

Arguments

UNITS	CHARACTER*1	'T'ime, 'M'onths or 'W'eeks
VALUE	REAL expression	Encoded <i>time-date</i> value
IVAL1	INTEGER variable	To receive <i>hours</i> or <i>years</i>
IVAL2	INTEGER variable	To receive <i>minutes</i> , <i>months</i> or <i>week number</i>
RVAL	REAL variable	To receive <i>seconds</i> , <i>date</i> or <i>day of week</i>

UNITS	IVAL1	IVAL2	RVAL
'T'ime	Hours	Minutes	Seconds
'M'onths	Year	Month	Date
'W'eeks	Year	Week no.	Day of week

Description

KTTRI converts *time-date* data encoded into a REAL value into the external form consisting of three components.

Days of the week are interpreted such that RVAL=1.0 represents Sunday, 2.0 represents Monday, *etc.*

If UNITS \neq 'T', 'M' or 'W', then IVAL1, IVAL2 and RVAL are returned with values 0, 0 and 0.0 respectively.

Diagnostics

(Invalid time-date units: X)¹

See also

KTREAL and KTSTR.

SUBROUTINE KVXYD (X3D, Y3D, Z3D, VARX2D, VARY2D, VARDEP)**Name**

KVXYD – to convert a three-dimensional point (x, y, z) to its two-dimensional equivalent plus depth.

Availability Section 7, released version 2-13.

Arguments

X3D, Y3D, Z3D	REAL expressions	Coordinates of a point, specified in 3-D units before transformation
VARX2D, VARY2D	REAL variables	To receive the coordinates of the projected point
VARDEP	REAL variable	To receive the distance of the projected point from the Viewing Plane

Description

KVXYD converts a three-dimensional point (X3D,Y3D,Z3D) to (VARX2D,VARY2D), the equivalent 2-D coordinates once transformation and projection have been applied. VARX2D and VARY2D are measured in terms of the underlying SIMPLEPLOT scales.

KVXYD also calculates the value of the depth, VARDEP. By default, if a point is within the limits specified by VS3DLM, its depth lies in the range $-\sqrt{3} \leq \text{VARDEP} \leq \sqrt{3}$. Points between the Origin and the Viewing Position have negative depths – the greater the depth, the further away a point is from the Viewing Position.

The permissible range of depths is altered following a call to VSFULL.

See also

QVDPLM, QVSCAL, VS3DLM, VSFULL, VSVRTP and VSVXYZ.

SUBROUTINE KWZVAL (ICURVE, ZVAL, RVAL)**Name**

KWZVAL – to convert a z value on a waterfall chart to its equivalent in terms of the label scale.

Availability Section plus, released version 2-13.

Arguments

ICURVE	INTEGER expression	Number of relevant curve
ZVAL	REAL expression	Coordinate of a point specified in data units
RVAL	REAL variable	Equivalent value in units of the label scale

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. There is an underlying numerical scale controlling the label scale. KWZVAL delivers the value in the underlying scale corresponding to a given data value ZVAL in a particular curve ICURVE.

The returned value, RVAL, can be used as an ordinate to the general point-by-point plotting sub-routines to augment a waterfall chart.

KWZVAL can not return a sensible value if no waterfall scales exist. If WFCHT, WFDRAW or WFZSCL has not been called already, a diagnostic is issued and the current no-data value returned in RVAL.

If ZVAL is equal to the current no-data value, RVAL is set to the no-data value.

Diagnostics

(No current waterfall Z scale)¹

See also

QWZSCL, WFCHT, WFDRAW and WFZSCL.

SUBROUTINE KXYXY (ICODE1, XIN, YIN, ICODE2, XOUT, YOUT)**Name**

KXYXY – to convert coordinates of a point to other units.

Availability Section plus, released version 2-11.

Arguments

ICODE1	INTEGER expression	Code for units of (x_{in}, y_{in})
XIN	REAL expression	x coordinate of a point
YIN	REAL expression	y coordinate of a point
ICODE2	INTEGER expression	Code for units of (x_{out}, y_{out})
XOUT	REAL variable	To receive x coordinate
YOUT	REAL variable	To receive y coordinate

ICODE	Units	Origin
0	Device units	Bottom left of device plotting area
1	Pixels	Bottom left of device plotting area
2	Centimetres	Bottom left of device plotting area
3	Centimetres	Bottom left of SIMPLEPLOT page
4	Normalized units	Bottom left of SIMPLEPLOT page
5	User coordinates	User origin of picture/graph

Description

A point on the plotting area can be described by a Cartesian pair specified in various different units; KXYXY converts the coordinates of a point between any of the units specified by ICODE. *Normalized* units (code 4) are in the range 0.0 to 1.0 on the SIMPLEPLOT page.

If the code for either pair is between 0 and 2, the device must have been opened. For codes 3 and 4, a SIMPLEPLOT page must have been started, and for code 5 a new picture must have been started. If KXYXY is called when the relevant information is not available, a diagnostic is issued.

If ICODE1=5, and XIN or YIN is equal to the current no-data value, XOUT and YOUT are set to no-data, and will be ignored by plotting subroutines.

The orientation of the SIMPLEPLOT page and the device are not necessarily the same. The orientation of (x, y) for codes 3–5 can be affected by calls to FITPAG, GROUP, PAGE and PAGVW.

Diagnostics

(KXYXY not viable)¹

See also

KISXY, KPVXY and NODATA.

KZRG

SUBROUTINE KZRG (XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELEMS, Z2ARR, NX, NY)

Name

KZRG – to generate a regular grid of values from ungridded (x, y, z) coordinates.

Availability Section 2, released version 2-11.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements
Z2ARR	REAL 2-D array	To receive values over a regular grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

KZRG converts the ungridded data held in ZARR into a regular grid of values in the array Z2ARR(NX,NY) using interpolation. Before using KZRG, the element array I2ARR(NNODES,NELEMS) must be set up; ZORDER or ZORDEN can be used for this purpose.

In this way, surface pictures of randomly positioned (x, y, z) coordinates can be drawn either directly by ZSURF, or indirectly by KZRG followed by RGSURF. As ZSURF is very slow, conversion to a regular grid for surface pictures is advisable whenever there is sufficient storage available for the extra array Z2ARR.

KZZRG is more efficient than KZRG.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

KZZRG.

SUBROUTINE KZZRG (XARR, YARR, ZARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS, Z2ARR, NX, NY)

Name

KZZRG – to generate a regular grid of values from ungridded (x, y, z) coordinates.

Availability Section 2, released version 2-11.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements
Z2ARR	REAL 2-D array	To receive values over a regular grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

KZZRG converts the ungridded data held in ZARR into a regular grid of values in the array Z2ARR(NX,NY) using interpolation.

Before using KZZRG, the element array I2ARR(NNODES,NELEMS) and the neighbour array N2ARR(NNODES,NELEMS) must be set up; ZZORDR or ZZORDN can be used for this purpose.

In this way, surface pictures of randomly positioned (x, y, z) coordinates can be drawn either directly by ZZSURF, or indirectly by KZZRG and RGSURF. As ZZSURF can be slow, conversion to a regular grid for surface pictures is advisable whenever there is sufficient storage available for the extra array Z2ARR.

KZZRG is more efficient than KZRG.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

KZRG.

SUBROUTINE LABANG (IDEGS)

Name

LABANG – to specify the angle of labels drawn by CP7LB, CP7XC or CP7YC.

Availability Section 4, released version 2-6.

Argument

IDEGS INTEGER expression Angle in degrees

Description

By default, the labels drawn by CP7LB, CP7XC or CP7YC are drawn horizontally. LABANG specifies the angle at which they are to be drawn.

The effect of LABANG on hardware text varies according to capabilities of the device. For example, if text can only be drawn horizontally, each character will be staggered to emulate the effect of angled text.

Default

CALL LABANG(0) restores the default.

See also

LABJST, CP7LB, CP7XC and CP7YC.

**SUBROUTINE LABCV7 (XARR, YARR, NARR, LTYPE, CAP)
SUBROUTINE LABCV (XARR, YARR, NARR, LTYPE, CAP, NCAP)**

Name

LABCV7 – to draw a labelled curve.

Availability Section 4, released version 2-13.

Arguments

XARR, YARR	REAL arrays	Coordinates of points, in units of the plotting scales
NARR	INTEGER expression	Number of points
LTYPE	INTEGER expression	Type of broken line pattern
CAP	STRING expression	Label for curve
NCAP	INTEGER expression	Number of characters in CAP

Description

Using broken line pattern LTYPE, LABCV/LABCV7 draws [1] the curve corresponding to (XARR(1), YARR(1)), (XARR(2), YARR(2)), ... (XARR(NARR), YARR(NARR)). The label, CAP, is drawn [2] along the curve. By default, the label is vertically centred on the curve, and left justified to point (XARR(NARR/2), YARR(NARR/2)). An alternative justification and position can be specified by CVLBJS/CVLBPS.

The base of each letter is parallel to the curve and the label is drawn in the direction of the curve. If the label is too long, it is truncated. LABCV7 will not interpret embedded commands specified by STRLV.

A closed curve can be obtained by using data in which XARR(NARR) = XARR(1) and YARR(NARR) = YARR(1). The curve is drawn through all points which are not equal to the current no-data value. If fewer than 2 points are valid, a diagnostic is issued and nothing is drawn.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness). If LTYPE = -999, all the bundled line-drawing attributes of the current pen are used.

Diagnostics

(Data curve exceeds scales)²
 (Insufficient number of valid points)¹
 (Requested point unavailable)¹
 (Text truncated on curve label)²

See also

BRKNCV, BUNLPR, CLIPLV, CVLBJS and CVLBPS.

SUBROUTINE LABJST (VJUST, HJUST)**Name**

LABJST – to specify the justification of labels drawn by CP7LB, CP7LBM, CP7XC or CP7YC.

Availability Section 4, released version 2-6.

Arguments

VJUST CHARACTER*1 Vertical justification of label
HJUST CHARACTER*1 Horizontal justification of label

VJUST Vertical justification

'D' Default
'T' Top of letters
'C' Halfway between 'T' and 'B'
'B' Bottom of letters (not including descenders)

HJUST Horizontal justification

'D' Default
'L' At the left (beginning) of the label
'C' Halfway between 'L' and 'R'
'R' At the right (end) of the label
'P' Preceding the label
'F' Following the label

Description

By default, the labels drawn by CP7LB, CP7XC and CP7YC are positioned such that the bottom, left-hand corner of the label coincides with the specified (x, y) coordinates. Labels drawn by CP7LBM/CP7LBM are justified 'B'ottom 'P'receding by default. LABJST specifies the position of the label relative to the point.

This (x, y) point is interpreted as one of nine possible positions described by combinations of values of VJUST and HJUST.

Default

CALL LABJST('D', 'D') restores the default.

See also

LABANG, CP7LB, CP7XC and CP7YC.

SUBROUTINE LIMEXC (DARR, NARR, VARMIN, VARMAX)**Name**

LIMEXC – to find the minimum and maximum values in a **REAL** array.

Availability Section 1, released before version 2-5.

Arguments

DARR	REAL array	Data values
NARR	INTEGER expression	Number of elements of DARR to be examined
VARMIN	REAL variable	To receive minimum value
VARMAX	REAL variable	To receive maximum value

Description

LIMEXC (LIMits EXclusive) searches through array DARR from DARR(1) to DARR(NARR) and sets VARMIN to the minimum value, VARMAX to the maximum value.

VARMIN and VARMAX must be the names of variables because LIMEXC assigns values to them.

LIMEXC ignores any values which are equal to the current no-data value.

See also

LIMINC and NODATA.

SUBROUTINE LIMIDX (DARR, NARR, IMIN, IMAX)**Name**

LIMIDX – to find the position of each of the minimum and maximum values of a **REAL** array.

Availability Section 1, released version 2-13.

Arguments

DARR	REAL array	Data values
NARR	INTEGER expression	Number of elements in DARR to be examined
IMIN	INTEGER variable	Position of minimum value
IMAX	INTEGER variable	Position of maximum value

Description

LIMIDX finds the position of the minimum and maximum values in a **REAL** array. If the array is indexed from 1 to NARR, DARR(IMIN) is the lowest value in the array, and DARR(IMAX) is the highest value.

If DARR contains more than one value equal to the minimum or maximum, IMIN or IMAX refer to the position of the first occurrence.

LIMIDX ignores any values which are equal to the current no-data value. If all the values correspond to the current no-data value, IMIN and IMAX are set to zero.

See also

LIMEXC, LIMINC and NODATA.

SUBROUTINE LIMINC (DARR, NARR, VARMIN, VARMAX)

Name

LIMINC – to find the minimum and maximum values in a REAL array.

Availability Section 1, released before version 2-5.

Arguments

DARR	REAL array	Data values
NARR	INTEGER expression	Number of elements of DARR to be examined
VARMIN	REAL variable	To be reset to minimum value
VARMAX	REAL variable	To be reset to maximum value

Description

LIMINC (LIMits INclusive) searches through array DARR from DARR(1) to DARR(NARR). If the minimum is less than the existing value of VARMIN, VARMIN is set to the minimum value; otherwise, VARMIN is left unaltered. If the maximum is greater than the existing value of VARMAX, VARMAX is set to the maximum value; otherwise VARMAX is left unaltered.

VARMIN and VARMAX must be the names of variables which have already been given values, because LIMINC uses the existing values, and may assign new values to them.

LIMINC ignores any values which are equal to the current no-data value.

See also

LIMEXC and NODATA.

SUBROUTINE LIMSFN (FUNXY, VARMIN, VARMAX)**Name**

LIMSFN – to find the range of function values to be used for contours of a 3-D function $z = f(x, y)$.

Availability Section 2, released version 2-11.

Arguments

FUNXY	function name	REAL function with two REAL arguments, also declared in an EXTERNAL statement
VARMIN, VARMAX	REAL variables	To receive values of limits

Description

LIMSFN evaluates the function **FUNXY**, which must be a **REAL** function with two **REAL** arguments, at every point which would be used for plotting the function, and sets **VARMIN** and **VARMAX** to the minimum and maximum respectively.

The values returned by LIMSFN can be affected by the range of the independent variables (see **FNAREA**), and the underlying grid used to calculate the function (see **SFMESH**).

See also

FNAREA, **SFLIMS** and **SFMESH**.

SUBROUTINE LINEK7 (LTYPE, CAP)
SUBROUTINE LINEKY (LTYPE, CAP, NCAP)

Name

LINEK7 – to draw an annotated sample of a broken line pattern in a key.

Availability Section 1, released before version 2-5.

Arguments

LTYPE	INTEGER expression	Type of broken line pattern
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

LINEKY/LINEK7 inserts a key to a broken line pattern (as used by the BRKN* subroutines) in the next empty space in the current key or caption area (defined by DEFKEY/DEFCAP or selected by RESNXT). A sample of the broken line pattern is drawn [1] on the left of the entry; the caption, CAP, is drawn [2] alongside the sample.

If line style has been requested as a bundled attribute, LTYPE overrides the line style of the bundle (but not colour or thickness) unless

LTYPE = -999 which indicates that all the bundled line-drawing attributes of the current pen are to be used.

REAL and INTEGER values can be converted to text strings using the conversion subroutines, KREAL and KNUMB respectively.

Diagnostics

(Caption truncated)²
 (Key/caption area full)²
 (No active key/caption area)²

See also

ADDJST, BLNKKY, BOTHK7, BUNLPR, DEFKEY and LINSET.

SUBROUTINE LINSET (ISET)**Name**

LINSET – to specify an alternative source of broken line patterns.

Availability Section 1, released version 2-8.

Argument

ISET INTEGER expression Broken line pattern source

ISET	Pattern source
0	Hardware/firmware broken lines (if available)
1	Device independent software broken line patterns

Description

For efficient operation and clarity, SIMPLEPLOT is set up to draw some broken lines on pictures using device hardware or firmware if possible. LINSET can be used to select an alternative source of patterned lines.

Hardware broken line patterns are chosen to correspond as much as possible to the SIMPLEPLOT software line patterns.

Default

CALL LINSET(0) restores the default.

See also

CHSET, FFSET, MKSET and SHSET.

SUBROUTINE MARGDV (PICTYP)

Name

MARGDV – to specify the distribution of picture margins.

Availability Section 1, released version 2-12.

Argument

PICTYP CHARACTER*1 Type of picture

PICTYP	<i>Picture type</i>	<i>Margin distribution</i>
'D'	Default	Large left-hand and bottom, small right-hand and top
'C'	Cartesian (x - y) plot	Large on 'XC' and 'YC' axis sides, small on other
'B'	Bar chart	Large on 'LB' and 'NB' axis sides, small on other
'I'	Isometric picture	Large on 'XI', 'YI', 'ZI' axis sides, small on other
'W'	Waterfall chart	Large on 'LW' and 'NW' axis sides, small on other
'O'	Other, <i>eg.</i> polar plot, pie chart	Equal distribution on all sides

Description

By default, margins are distributed such that the gap allocated to the right-hand side and the top is approximately the size of a single character, and the larger residue is allocated to the left-hand side and bottom.

MARGDV specifies that, while PICMRG is not active, subsequent new pictures should be set up with the margins distributed to suit the specified type of picture.

MARGDV must be called before the new picture to which it refers is started.

Default

CALL MARGDV('D') restores the default.

See also

MARGIN and PICMRG.

SUBROUTINE MARGIN (CMS)**Name**

MARGIN – to specify the overall size of the margin around individual pictures.

Availability Section 1, released before version 2-5.

Argument

CMS REAL expression Width of margin (in cms)

Description

MARGIN specifies the size of the margin around individual pictures.

If MARGIN has not been called, SIMPLEPLOT calculates the following using the current minimum size of text:

$$\text{SPACE} = 5 \times \text{character width} + 3.3 \times \text{character height}$$

The maximum default value of SPACE is 2cm.

SIMPLEPLOT imposes minimum and maximum values on picture margins. The maximum size allowed for a margin is half the smaller dimension of the picture, and the minimum margin is 0.01cm.

The distribution of the overall margin depends on the current text size. If the total margin size is less than 2 text characters, it is distributed equally on all sides of the picture. With larger margins, the gap allocated to the top and right-hand side is approximately the size of 1 character, and the larger residue is allocated to the bottom and left-hand side. TEXTSZ, TEXTMN and CHSET change text characteristics which can indirectly change margin sizes.

MARGIN overrides PICMRG and vice versa.

Diagnostics

(v_1 requested)²
 (v_2 used)²
 (Margin modified)¹

Default

Calling MARGIN with a negative argument restores the default.

See also

MARGDV and PICMRG.

SUBROUTINE MARKAR (X1, DX, DARR, NARR, MKTYPE, NSTEP)**Name**

MARKAR – to draw marker symbols at a set of values held in an array.

Availability Section 4, released version 2-11.

Arguments

X1	REAL expression	Value of independent variable for plotting DARR(1)
DX	REAL expression	Independent variable interval between function values
DARR	REAL array	Function values for plotting
NARR	INTEGER expression	Number of points
MKTYPE	INTEGER expression	Type of marker symbol
NSTEP	INTEGER expression	Interval between points marked

Description

MARKAR draws [3] a set of marker symbols, MKTYPE, centred on the following points:

(X1,DARR(1)), (X1+(NSTEP*DX),DARR(1+NSTEP)),
(X1+(2*NSTEP*DX),DARR(1+(2*NSTEP))),...

These points represent a set of values from a single array where the array elements hold function values $y_i = f(x_i)$ and $x_i = x_1 + (i - 1)dx$.

By default, all drawing is restricted by the limits of the picture scales; marker symbols can spill over the edge of a picture but the coordinates at the centre of the symbol must not exceed these limits. If coordinates exceed these limits, the symbol is omitted and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Symbol clipped)²
(Symbol spills over boundary)²

See also

BRKNAR, CLIPLV, MARKCV, MKSIZE, and SHDEAR.

SUBROUTINE MARKCV (XARR, YARR, NARR, MKTYPE, NSTEP)**Name**

MARKCV – to draw marker symbols at a set of coordinates.

Availability Section 1, released version 2-11.

Arguments

XARR, YARR	REAL arrays	Coordinates of points, in units of the plotting scales
NARR	INTEGER expression	Number of points
MKTYPE	INTEGER expression	Type of marker symbol
NSTEP	INTEGER expression	Interval between points marked

Description

MARKCV draws [3] a set of marker symbols, MKTYPE, centred on the following points:

```
(XARR(1), YARR(1)),
(XARR(1+NSTEP), YARR(1+NSTEP)), ...
(XARR(1+(2*NSTEP)), YARR(1+(2*NSTEP))), ...
```

By default, all drawing is restricted by the limits of the picture scales; marker symbols can spill over the edge of a picture but the coordinates at the centre of the symbol must not exceed these limits. If coordinates exceed these limits, the symbol is omitted and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

```
(Symbol clipped)2
(Symbol spills over boundary)2
```

See also

BRKNCV, CLIPLV, MARKAR, MKSIZE and SHDECV.

**SUBROUTINE MARKK7 (MKTYPE, CAP)
SUBROUTINE MARKKY (MKTYPE, CAP, NCAP)**

Name

MARKK7 – to draw an annotated sample of a marker symbol in a key.

Availability Section 1, released before version 2-5.

Arguments

MKTYPE	INTEGER expression	Type of marker symbol
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

MARKKY/MARKK7 inserts a key to a marker symbol (as used by MARK*) in the next empty space in the current key or caption area (defined by DEFKEY/DEFCAP or selected by RESNXT).

A sample of the marker symbol, MKTYPE, is drawn [3] on the left of the entry; the caption, CAP, is drawn [2] alongside the sample.

REAL and INTEGER values can be converted to text strings using the conversion subroutines, KREAL and KNUMB respectively.

Diagnostics

(Caption truncated)²
 (Key/caption area full)²
 (No active key/caption area)²

See also

ADDJST, BLNKY, BOTHK7, DEFKEY, LINEK7 and MKSET.

SUBROUTINE MARKPT (X, Y, MKTYPE)**Name**

MARKPT – to draw a marker symbol at a specified point.

Availability Section 1, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point specified in units of the plotting scales
MKTYPE	INTEGER expression	Type of marker symbol

Description

MARKPT draws [3] a marker symbol, MKTYPE, centred on the point (x, y) . After drawing the specified symbol, MARKPT leaves the pen at the centre of the symbol to allow a line to be drawn from the symbol to another point by a succeeding call of BRKNPT/JOINPT. For example, a sequence of symbols joined by straight lines can be drawn by repeating the following calls for a sequence of points:

```
CALL BRKNPT(X,Y,LTYPE)
CALL MARKPT(X,Y,MKTYPE)
```

BREAK should be called between MARKPT and a succeeding call of BRKNPT/JOINPT if a line is not required joining symbol and point.

The point (x, y) is specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, KXYXY.

By default, all drawing is restricted by the limits of the picture scales; marker symbols can spill over the edge of a picture but the coordinates at the centre of the symbol must not exceed these limits. If coordinates exceed these limits, the symbol is omitted and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Symbol clipped)²

(Symbol spills over boundary)²

See also

BREAK, BRKNPT, CLIPLV, CP7PT, MKMASK, MKSIZE, MARKCV and MARKAR.

SUBROUTINE MKMASK (TORF)**Name**

MKMASK – to specify whether marker symbols are to be masked.

Availability Section 4, released version 2-11.

Argument

TORF LOGICAL expression Whether symbols are to be masked

Description

By default, SIMPLEPLOT draws anywhere within the page unless specific areas have been reserved for specific activities. MKMASK specifies that the area immediately around marker symbols is to be masked from any further drawing.

After a call of MKMASK(.TRUE.) symbols are masked; this means that the symbols themselves look no different from unmasked symbols, but any subsequent drawing over the symbols is omitted as it crosses each symbol.

The limit to the number of masked areas which can be used for individual symbols and text strings is 50. When this limit is reached a diagnostic is issued and subsequent masked areas take the place of the oldest areas and overdrawing of these areas may occur.

Diagnostics

(Maximum no. of masked areas reached)¹

Default

CALL MKMASK(.FALSE.) restores the default.

See also

CHMASK.

SUBROUTINE MKSET (ISET)**Name**

MKSET – to specify an alternative source of marker symbols.

Availability Section 1, released version 2-8.

Argument

ISET INTEGER expression Marker symbol source

ISET Marker symbol source

- | | |
|---|------------------------------------------|
| 0 | Hardware/firmware symbols (if available) |
| 1 | Device independent software symbols |
| 2 | Hershey Odd Shapes |
| 3 | Hershey Graph Markers |
| 4 | Hershey Solid Graph Markers |
| 5 | Hershey Map Symbols |
| 6 | Hershey Small Astronomy |
| 7 | Hershey Astronomy |
| 8 | Hershey Zodiac |
-

Description

For efficient operation and clarity, SIMPLEPLOT is set up to mark points on pictures using symbols from device hardware or firmware wherever possible. MKSET can be used to select an alternative source of symbols.

Individual Hershey symbols can also be selected by MKTYPE greater than 16. The Hershey symbols are only available with SIMPLEPLOT-PLUS.

Default

CALL MKSET(0) restores the default.

See also

CHSET, FFSET, LINSET and SHSET.

SUBROUTINE Mysize (CMS)**Name**

Mysize – to specify a fixed size of marker symbols independent of text size.

Availability Section 4, released version 2-11.

Argument

CMS REAL expression Size of marker symbols (in cms)

Description

By default, the size of marker symbols is controlled by the same mechanism that controls the size of text. That is to say, TEXTSZ, TEXTMN and TEXTMG normally affect the size of both characters and symbols. Mysize specifies the size of marker symbols which is independent of text size.

Default

CALL Mysize(0.0) restores the default.

See also

TEXTSZ, TEXTMG.

SUBROUTINE MOVEON (TORF)**Name**

MOVEON – to specify whether to superimpose pictures.

Availability Section 4, released version 2-8.

Argument

TORF	LOGICAL expression	Whether next picture is to be drawn in the next clear space
------	--------------------	----------------------------------------------------------------

Description

By default, each new picture is automatically positioned either in the next clear space within the group or on a new SIMPLEPLOT page. MOVEON(.FALSE.) suspends the automatic moving on for each new picture, therefore allowing pictures to be superimposed. PICPOS also suspends automatic picture layout.

CALL MOVEON(.TRUE.) restores the normal state, with each new picture starting on a clear space.

Diagnostics

(MOVEON cancelled)¹

Default

CALL MOVEON(.TRUE.) restores the default.

See also

ENDPAG, ENDPIC and PICPOS.

**SUBROUTINE MPK7H (VCHAR, HCHAR, ZLEFT, ZRIGHT, CAP)
SUBROUTINE MPKYH (VCHAR, HCHAR, ZLEFT, ZRIGHT, CAP, NCAP)**

Name

MPK7H – to draw a complete horizontal key to a shaded contour map.

Availability Section plus, released version 2-10.

Arguments

VCHAR	CHARACTER*1	Vertical position of key
HCHAR	CHARACTER*1	Horizontal position of key
ZLEFT	REAL expression	z value at left of key
ZRIGHT	REAL expression	z value at right of key
CAP	STRING expression	Single caption for key
NCAP	INTEGER expression	Number of characters in CAP

Description

MPK7H/MPKYH draws a complete key to the current shading patterns that represent the data range ZLEFT to ZRIGHT. Samples of the patterns are drawn side-by-side, with the key numbers above. CAP provides a heading which is, by default, centred at the top of the key (see ADDJST). A box is drawn [1] around the key unless cancelled by BOXKY.

The key area is associated only with the current picture/page but is masked to prevent overdrawing. To avoid the key being overdrawn by other plotting, it is best to call MPK7H after NEWPIC but before the main picture is drawn. The order of key entries can be reversed by interchanging ZLEFT with ZRIGHT. The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Key/caption attempted with no page)²
 (Key/caption attempted with no picture)²
 (Key/caption height reduced)²
 (Key/caption width reduced)²
 (MAP KEY OMITTED: CONSTANT DATA)¹
 (MAP KEY OMITTED: NULL RANGE)¹
 (Maximum no. of keys/captions reached)²
 (No room for key/caption area)²

See also

ADDJST, BOXKY, MPK7V, MPTYPE, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SHPATT and SQ*.

**SUBROUTINE MPK7V (VCHAR, HCHAR, ZTOP, ZBOTTM, CAP)
SUBROUTINE MPKYV (VCHAR, HCHAR, ZTOP, ZBOTTM, CAP, NCAP)**

Name

MPK7V – to draw a complete vertical key to a shaded contour map.

Availability Section plus, released version 2-10.

Arguments

VCHAR	CHARACTER*1	Vertical position of key
HCHAR	CHARACTER*1	Horizontal position of key
ZTOP	REAL expression	z value at top of key
ZBOTTM	REAL expression	z value at bottom of key
CAP	STRING expression	Single caption for key
NCAP	INTEGER expression	Number of characters in CAP

Description

MPK7V/MPKYV draws a complete key to the current shading patterns that represent the data range ZTOP to ZBOTTM. Samples of the patterns are drawn in a vertical list, with the key numbers alongside. CAP provides a heading which is, by default, centred at the top of the key (see ADDJST). A box is drawn [1] around the key unless cancelled by BOXKY.

The key area is associated only with the current picture/page but is masked to prevent overdrawing. To avoid the key being overdrawn by other plotting, it is best to call MPK7V after NEWPIC but before the main picture is drawn. The order of key entries can be reversed by interchanging ZTOP with ZBOTTM. The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Key/caption attempted with no page)²
 (Key/caption attempted with no picture)²
 (Key/caption height reduced)²
 (Key/caption width reduced)²
 (MAP KEY OMITTED: CONSTANT DATA)¹
 (MAP KEY OMITTED: NULL RANGE)¹
 (Maximum no. of keys/captions reached)²
 (No room for key/caption area)²

See also

ADDJST, BOXKY, MPK7H, MPTYPE, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SHPATT and SQPEN.

SUBROUTINE MPTYPE (IMETHD)

Name

MPTYPE – to specify the shading method used for shaded contour maps and map keys.

Availability Section plus, released version 2-10.

Argument

IMETHD INTEGER expression Shading method

IMETHD *Shading method used*

- | | |
|---|--------------------------------------------|
| 1 | Generalized shading between contour curves |
| 2 | Fast area-fill showing data configuration |
| 3 | Fast area-fill with interpolation |
-

Description

SIMPLEPLOT offers two separate approaches to drawing shaded contour maps from data which represents a function of two variables, $z = f(x, y)$. By default, the *SHDS subroutines perform generalized shading between contour curves but SIMPLEPLOT can also use an alternative technique known as *fast area-fill*. MPTYPE specifies which technique is used.

In fast area-fill pictures, the picture is built up by working out a data value for each part of the picture in order to allocate a fill character; method 2 uses the value of the nearest data point, and method 3 interpolates between surrounding data points.

MPTYPE also determines the shading method used for map key samples (see MPK7H and MPK7V). MPTYPE has no effect on raster pictures (see RASTER) but it may be necessary to call MPTYPE with IMETHD=3 to draw a key to the patterns used on a raster picture.

Default

CALL MPTYPE(1) restores the default.

See also

FFSET, FFSIZE, MPK7H, MPK7V, RASTER and *SHDS.

SUBROUTINE MTCLOS**Name**

MTCLOS – to terminate metafile redrawing.

Availability Section plus, released version 2-11.

Arguments

None.

Description

A SIMPLEPLOT metafile can be completely redrawn by calling REDRAW or it can be drawn line-by-line using the following procedure:

1. Open the metafile.
2. Initiate redrawing by CALL MTOPEN.
3. For each line of the metafile:
 - Read line from metafile.
 - Redraw line by CALL MTDRAW(STR).
4. Terminate redrawing by CALL MTCLOS.

If any SIMPLEPLOT subroutine other than MTDRAW is called after MTOPEN but before MTCLOS, redrawing is abandoned and a diagnostic is issued.

This method of redrawing may be useful when the metafile is on a remote system from which it can be read line by line under program control.

Diagnostics

(REDRAWING ABANDONED)¹

See also

MTDRAW and MTOPEN.

SUBROUTINE MTCOMM (STR)**Name**

MTCOMM – to output a comment line to a metafile.

Availability Section plus, released version 2-11.

Argument

STR STRING expression Metafile comment line

Description

A comment line can be inserted into a metafile as it is being written by calling MTCOMM with the comment as argument. In the metafile, the comment is preceded by the identifying letters **COMM** and all such lines are ignored when the metafile is redrawn using **REDRAW**.

The maximum length of comments is 75 characters; if a longer string is passed to MTCOMM, it is truncated.

See also

MTFILE.

SUBROUTINE MTDRAW (STR)

Name

MTDRAW – to redraw a single line of a SIMPLEPLOT metafile.

Availability Section plus, released version 2-11.

Argument

STR	STRING expression	A single line from a SIMPLEPLOT metafile
-----	-------------------	------------------------------------------

Description

A SIMPLEPLOT metafile can be completely redrawn by calling REDRAW or it can be drawn line-by-line using the following procedure:

1. Open the metafile.
2. Initiate redrawing by CALL MTOPEN.
3. For each line of the metafile:
 - Read line from metafile.
 - Redraw line by CALL MTDRAW(STR).
4. Terminate redrawing by CALL MTCLOS.

If any SIMPLEPLOT subroutine other than MTDRAW is called after MTOPEN but before MTCLOS, redrawing is abandoned and a diagnostic is issued.

This method of redrawing may be useful when the metafile is on a remote system from which it can be read line by line under program control.

Diagnostics

(REDRAWING ABANDONED)¹

See also

MTCLOS, MTOPEN and REDRAW.

SUBROUTINE MTFILE (ICHAN)**Name**

MTFILE – to request metafile output.

Availability Section plus, released version 2-8.

Argument

ICHAN INTEGER expression FORTRAN channel number

Description

A SIMPLEPLOT metafile, containing a complete reproducible record of all the graphics output from a program, can be created at the same time as output to a graphics device, using the following procedure:

1. Open a FORTRAN I/O channel for formatted, serial output.
2. Call MTFILE specifying this I/O channel, before any plotting occurs (*ie.* before a graphics device is opened).
- :
3. Close FORTRAN I/O channel.

The metafile information is directed to a scratch file as the program runs. As each SIMPLEPLOT page is completed the whole scratch file is copied to ICHAN and deleted, and a diagnostic message is issued. Thus, if a program terminates prematurely for any reason, the metafile only contains details of complete pages.

The metafile produced in this way reflects the limitations of the device, such that the drawing and positioning of text may only be acceptable when reproduced on the device to which it is related, or on one which is less limited. When producing a metafile to be used on different devices, it is advisable to relate it to the device with the lowest resolution. Device *independent* metafiles can be produced using the META device driver.

If a program which uses MTFILE is run with the META device driver, the output file nominated by ICHAN takes precedence over the file usually selected by the META device driver.

A call of MTFILE with ICHAN < 0, terminates metafile output.

Diagnostics

(PAGE COPIED TO METAFILE)¹

See also

MTCOMM, MTMISS and MTONLY.

SUBROUTINE MTMISS**Name**

MTMISS – to omit the current SIMPLEPLOT page from a metafile.

Availability Section plus, released version 2-8.

Arguments

None.

Description

If SIMPLEPLOT metafile output has been requested, the metafile details of each SIMPLEPLOT page are first written to a scratch file, and only transferred to the metafile when the page is finished; a complete page can be omitted from the metafile by calling MTMISS anywhere in the program between the start and end of the page. When a page is finished, but omitted from an active metafile as a result of calling MTMISS, a diagnostic is issued.

Please note that the end of a page occurs when ENDPAG or ENDPLT is called, or, in the absence of such calls, when a new page is started by a *new picture* subroutine.

With MTFIL and MTMISS it is possible to adapt a program to enable it to inquire whether or not it should save pages in metafiles. Separation of pages into individual files can be achieved by using CLOSE and OPEN between page ends, to change the file addressed by ICHAN.

Diagnostics

(PAGE OMITTED FROM METAFIL)¹

See also

MTFIL and MTONLY.

SUBROUTINE MTONLY**Name**

MTONLY – to specify that only metafile output is to be produced.

Availability Section plus, released version 2-8.

Arguments

None.

Description

By default, metafile output is produced simultaneously with device output. MTONLY suppresses the device output.

A SIMPLEPLOT metafile, containing a complete reproducible record of all the graphics output from a program, can be created without simultaneous output to a graphics device, using the following procedure:

1. Open a FORTRAN I/O channel for formatted, serial output.
2. Call MTFILF specifying this I/O channel, before any plotting occurs (*ie.* before a graphics device is opened).
3. Call MTONLY to suppress output to the selected graphics device.
:
4. Call SIMPLEPLOT plotting subroutines.
:
5. Call ENDPLT.
6. Close FORTRAN I/O channel.

Default

The default cannot be restored except by CALL INITSP.

See also

MTFILE and MTMISS.

SUBROUTINE MTOPEN

Name

MTOPEN – to start metafile redrawing.

Availability Section plus, released version 2-11.

Arguments

None.

Description

A SIMPLEPLOT metafile can be completely redrawn by calling REDRAW or it can be drawn line-by-line using the following procedure:

1. Open the metafile.
2. Initiate redrawing by CALL MTOPEN.
3. For each line of the metafile:
 - Read line from metafile.
 - Redraw line by CALL MTDRAW(STR).
4. Terminate redrawing by CALL MTCLOS.

If any SIMPLEPLOT subroutine other than MTDRAW is called after MTOPEN but before MTCLOS, redrawing is abandoned and a diagnostic is issued.

This method of redrawing may be useful when the metafile is on a remote system from which it can be read line by line under program control.

Diagnostics

(REDRAWING ABANDONED)¹

See also

MTCLOS and MTDRAW.

SUBROUTINE NEWPAG**Name**

NEWPAG – to start a new SIMPLEPLOT page without starting a new picture.

Availability Section plus, released version 2-12.

Arguments

None.

Description

By default, a new SIMPLEPLOT page is created when the first picture is started, but sometimes it is desirable to draw page titles *etc* before any part of a picture has been drawn. NEWPAG starts a new SIMPLEPLOT page without starting a picture. Descriptive positions relative to the picture and user coordinates are undefined until a new picture is started.

NEWPAG finishes the current page and, if BOXPAG has been called to specify boxed pages, the box is drawn [1] when the new page is started.

Diagnostics

(DEVICE OPENED: *device name*)¹

See also

ENDPAG and NEWPIC.

SUBROUTINE NEWPIC

Name

NEWPIC – to start a new 2-D picture without drawing an axis framework.

Availability Section 1, released before version 2-5.

Arguments

None.

Description

NEWPIC is used to start a new picture when a standard axis framework is not required. NEWPIC is a graphics subroutine but, by default, does no drawing. If one of the BOX* subroutines has been called to generate boxes around pictures, groups or pages, these are drawn [1] when a new picture is started.

NEWPIC does not reset the underlying coordinate system. If EQSCAL has not been called, COORDS controls the type of new picture. If EQSCAL is active, each new picture is started with the units specified by EQSCAL regardless of any call of COORDS; once a picture has been started, COORDS can be called to change coordinate interpretation.

See also

AXES7, COORDS, EQSCAL, ISNEW, NEWPAG and POLAR7.

SUBROUTINE NODATA (RVAL)**Name**

NODATA – to specify the REAL value to be used to represent no-data values.

Availability Section 1, released version 2-10.

Argument

RVAL REAL expression No-data value

Description

SIMPLEPLOT interprets a single REAL value in plotting data as a no-data value; by default, this value is $-1.0E20$. NODATA specifies an alternative value to be used for this purpose.

Before SIMPLEPLOT draws anything, it checks whether one of the coordinates of the item to be drawn corresponds to the no-data value. If any ordinate is missing, the item is not drawn. As this check occurs at a fairly low level within SIMPLEPLOT, it affects everything which is drawn at user coordinates – marker symbols, text captions, curves joining points, boxes, axes, *etc*– any item which can be positioned.

It is advisable to have RVAL so far outside the normal range of data values that no problems arise but, awkward circumstances may arise. For example, if the no-data value is set to zero and an axis is required at either $x = 0.0$ or $y = 0.0$, no axis will be drawn if NODATA is called before the axis is drawn. In this case, NODATA should be called to set the no-data value to zero after the axes have been drawn but before the data are plotted. This solution will not resolve the case where the no-data value has been set for missing y coordinates but x coordinates also correspond to the missing value. In this case, points with legitimate y values but missing x values, will not be drawn.

Default

CALL NODATA($-1.0E20$) restores the default.

See also

QNODAT.

SUBROUTINE ONEPEN (IPEN)

Name

ONEPEN – to draw the colours of a multi-coloured picture separately.

Availability Section 1, released version 2-5.

Argument

IPEN INTEGER expression Pen number

Description

If a multi-coloured picture is to be plotted for a printed document, it may be necessary to plot each colour on a separate page. When a program has been developed to produce the desired effect with the colours together, it can then be adapted to plot the same picture with only the parts drawn by pen number **IPEN** by inserting a call of **ONEPEN(IPEN)** before the first plotting call; Pen 1 is then used for all plotting directed to Pen **IPEN**, and plotting directed to other pens is omitted.

Please note that, by default, colour is the only line-drawing attribute associated with pens, and that the distinction between pens depends on the capabilities of the current device. If **BUNLPR** has been called to specify other attributes to be associated with pens for drawing lines, the correspondence between colour and pens may be lost and **ONEPEN** can no longer produce true ‘colour separations’.

See also

BUNLPR, **PEN** and **SETPNS**.

SUBROUTINE OUTBUF**Name**

OUTBUF – to update the SIMPLEPLOT page by flushing internal graphics buffer.

Availability Section 4, released version 2-7.

Arguments

None.

Description

For some devices, the efficiency of data transfer for graphics can be maximized by accumulating sequences of drawing in a buffer, and outputting them when the buffer is full. When output is buffered in this way, at any stage of a program, the most recent part of the picture may be missing because the buffer is not yet full. Whenever it is necessary to be sure that the picture is up to date, `CALL OUTBUF` forces the output of all buffered graphics. If the buffers are already empty when `OUTBUF` is called, it does nothing.

See also

ENDPAG, ENDPIC, GETXY, OWNIO, OWNNEW and SCLEAR.

SUBROUTINE OWNFIL (ITYPE, ILEVEL, IPRIOR, STR)

Name

OWNFIL – to specify an alternative source/destination for SIMPLEPLOT input/output.

Availability Section plus, released version 2-12.

Arguments

ITYPE	INTEGER expression	Type of channel usage
ILEVEL	INTEGER expression	Type of drivers to be affected
IPRIOR	INTEGER expression	Priority over external information
STR	STRING expression	File/device name

ITYPE <i>Channel usage</i>		IPRIOR <i>Priority</i>	
1	Diagnostics	0	Never use
2	Prompt output	1	Use when not defined externally
3	Prompt input		
4	Graphics output	2	Use when defined externally
5	Graphics input		
6	Configuration	3	Always use

ILEVEL <i>Device drivers affected</i>	
0	None
1	Device drivers for interactive devices
2	Device drivers for non-interactive devices
3	All device drivers
4	Non-device driver I/O (<i>eg.</i> diagnostics file, prompt)
5	Non-device driver I/O plus interactive drivers
6	Non-device driver I/O plus non-interactive drivers
7	Non-device driver I/O plus all drivers (<i>ie.</i> everything)

Description

By default, SIMPLEPLOT allocates files and/or devices according to external information (*eg.* environment variables, logical names, *etc.*) or default values. OWNFIL specifies an alternative file (or device) to be used for a SIMPLEPLOT I/O channel (see ITYPE) and under what circumstances it takes priority over external information (see ILEVEL and IPRIOR).

The effect of OWNFIL can be restricted to certain classes of device driver or to non-device driver I/O according to the value of ILEVEL.

STR is interpreted as a file name (or file specification) and must have at least one character up to a maximum of 255. Valid file names differ from system to system and STR is interpreted as anything which would be valid where a file name is valid; on some systems this may include devices, path names, file specifications, network nodes *etc.*

For example, if you want your terminal output on your screen, but your hard-copy output to be sent to the files, MYPIC.DON, then use CALL OWNFIL(4,2,1,'MYPIC').

OWNFIL has no effect until the specified I/O channel is opened and, if the channel is already open, may have no effect at all:

- Prompt input, prompt output and diagnostic channels are allocated when SIMPLEPLOT is initialized and cannot be reassigned while SIMPLEPLOT is open. For ITYPE=1, 2 and 3, it is necessary for OWNFIL to be called before any other SIMPLEPLOT subroutine except IOCHAN.
- Graphics input and output channels are used only by individual device drivers and therefore can be re-assigned before a new device is selected.
- The configuration channel is used by both individual device drivers and the device driver system and therefore should normally be re-assigned before SIMPLEPLOT is fully initialized.

In order to allow OWNFIL to be used repeatedly before SIMPLEPLOT is fully initialized, it does not trigger the initial diagnostic message:

```
(SIMPLEPLOT Mark 2-15(nnn)X)
```

Diagnostics

```
(OWNFIL ignored: invalid argument)1
```

Default

CALL OWNFIL(ITYPE,0,0,' ') restores the default. Please note that the default is not restored by INITSP.

See also

IOCHAN and host specific information.

SUBROUTINE OWNIO (TORF)**Name**

OWNIO – to specify whether a terminal is to be used for graphics or user I/O.

Availability Section 4, released version 2-7.

Argument

TORF	LOGICAL expression	Whether terminal is to be used for user I/O
------	--------------------	------------------------------------------------

Description

Some types of graphics terminal need to be in one state for outputting graphics, and another state when processing ordinary **READ** and **WRITE** operations from and to the terminal. If a dialogue display obscures the graphics, **SIMPLEPLOT** may switch it off during graphics output. With this sort of terminal, any user program which includes terminal **READ** and **WRITE** operations among graphics output calls needs to be able to switch states itself.

CALL OWNIO(.TRUE.) switches the terminal into a suitable state for terminal **READ** and **WRITE** operations, and

CALL OWNIO(.FALSE.) switches it back into the state used for graphics output.

Default

CALL OWNIO(.FALSE.) restores the default.

See also

ENDPAG, **ENDPIC**, **GETXY**, **OWNNEW**, **OUTBUF** and **SCLEAR**.

SUBROUTINE OWNNEW (TORF)**Name**

OWNNEW – to specify whether to bypass the normal procedure between SIMPLEPLOT pages.

Availability Section 4, released version 2-7.

Argument

TORF	LOGICAL expression	Whether to use own action between pages
------	--------------------	--------------------------------------------

Description

By default, SIMPLEPLOT performs certain operations between pages of output. Device drivers for graphics terminals are usually set up so that the first SIMPLEPLOT page is started without requiring user interaction; but, before clearing the screen for subsequent pages, the device driver prompts the user (*eg.* the **Press <RETURN> to continue** message) to ensure that the page on the screen has been seen before it is erased.

If the user program performs its own interactive dialogue, there may be no need for the precaution of inviting a user prompt before starting a new SIMPLEPLOT page. After a call of **OWNNEW(.TRUE.)**, all such operations are bypassed such that each new page is started in the same way as the first.

Default

CALL OWNNEW(.FALSE.) restores the default.

See also

ENDPAG, ENDPIC, GETXY, OUTBUF, OWNIO and SCLEAR.

SUBROUTINE PAGE (WCMS, HCMS)

Name

PAGE – to specify the size of the SIMPLEPLOT page.

Availability Section 1, released before version 2-5.

Arguments

WCMS	REAL expression	Width of page (in cms)
HCMS	REAL expression	Height of page (in cms)

Description

PAGE has a different effect on packed picture and fixed picture devices:

Packed picture devices By default, the size of the SIMPLEPLOT page depends on the physical dimensions of the device and user calls to PICSIZ and GROUP.

When a picture size has not been specified, the allocated page size is related to the total available on the device (approximately 20cm×20cm). When a picture size has been specified, the page size is calculated to accommodate the current grouping. After PAGE has been called, each picture (or group) is positioned within an area of the specified size.

Fixed picture devices The fixed device area is treated like a page whether or not PAGE has been called. The arguments of PAGE are only used to set the page orientation when the device page may be rotated. The magnitudes of the arguments of PAGE are only used when FITPAG has also been called.

If the requested page size is larger than the device plotting area, a shrinkage factor is applied so that the page produced has the specified proportions. This shrinkage factor is then applied to all plotting within the page.

Diagnostics

(x_1 y_1 requested)²
 (x_2 y_2 used)²
 (PAGE cancelled)¹
 (PAGE ignored: invalid argument)¹
 (Page Size modified)¹

Default

Calling PAGE with either argument set to zero restores the default.

See also

FITPAG, PAG*, PGFULL and QPAGE.

SUBROUTINE PAGMRG (CMS, RCMS, BCMS, TCMS)

Name

PAGMRG – to specify the size and distribution of peripheral margins.

Availability Section 4, released version 2-11.

Arguments

CMS	REAL expression	Width of left margin (in cms)
RCMS	REAL expression	Width of right margin (in cms)
BCMS	REAL expression	Width of bottom margin (in cms)
TCMS	REAL expression	Width of top margin (in cms)

Description

By default, the peripheral margin around a group of pictures is treated as two pairs of complementary margins (left/right and bottom/top) and each pair is distributed in a 2 : 1 ratio, *left:right* and *bottom:top*. PAGMRG specifies the size and distribution of these peripheral margins individually.

Three combinations of values are possible for each pair of margins, m_1 and m_2 :

$m_1 \geq 0$ **and** $m_2 \geq 0$ sizes used unless shrinkage is needed when proportions used.

$m_1 \geq 0$ **and** $m_2 < 0$ (or *vice versa*) non-negative value used as the absolute margin size if page size permits; remaining space put on other side.

$m_1 < 0$ **and** $m_2 < 0$ reset default.

SIMPLEPLOT imposes minimum and maximum values on peripheries. The maximum size allowed for a periphery is half the smaller dimension of the group, The minimum periphery is 0.01cm.

PAGMRG overrides PERIPH and *vice versa*.

Default

CALL PAGMRG(-1.0,-1.0,-1.0,-1.0) restores the default size and distribution of peripheries.

See also

PERIPH, PICMRG and MARGIN.

SUBROUTINE PAGPOS (XCMS, YCMS)**Name**

PAGPOS – to specify the position of the SIMPLEPLOT page within the plotting area.

Availability Section 4, released version 2-11.

Arguments

XCMS	REAL expression	x coordinate of picture
YCMS	REAL expression	y coordinate of picture

Description

By default, if PAGE has been called to define a page size which is smaller than the device plotting area, this smaller region is positioned in the centre of the space available. PAGPOS overrides this position and cause the SIMPLEPLOT page to be placed at the point (x_{cms}, y_{cms}) centimetres relative to the bottom left hand corner of the device. The conversion subroutine, KXYXY, can be used to convert user coordinates or page coordinates to device coordinates in centimetres.

If the specified coordinates would position the page partly off the device plotting area, both the page dimensions and the position of its origin are scaled in the same proportion to ensure a SIMPLEPLOT page completely contained within the device plotting area.

PAGPOS is only applicable to fixed picture devices and is ignored until PAGE is called.

Diagnostics

(PAGPOS cancelled)¹

Default

Calling PAGPOS with either argument negative restores the default page positioning.

See also

PAGE and KXYXY.

SUBROUTINE PAGVW (ITYPE)**Name**

PAGVW – to specify the orientation of a page when page dimensions have not been specified.

Availability Section 4, released version 2-11.

Argument

ITYPE INTEGER expression The orientation of the page

ITYPE *Page orientation*

0	Default mode, determined by device and/or GROUP
1	Portrait (if page can be turned)
2	Landscape (if page can be turned)
3	Portrait
4	Landscape
5	Upside-down portrait
6	Upside-down landscape

Description

By default, SIMPLEPLOT determines the page orientation according to the dimensions of the device and the group configuration of pictures. PAGVW specifies an alternative orientation of a page for *fixed picture* devices.

ITYPE ≥ 3 may result in a rotated page even on devices which would not normally turn the SIMPLEPLOT page (*eg.* a screen). ITYPE=1 and 3 or ITYPE=2 and 4 are equivalent on devices which can be used in both portrait and landscape modes (*eg.* printers).

PAGVW is overridden by calling of PAGE to define page dimensions; if the default page dimensions are subsequently restored, any previous setting of PAGVW becomes active again.

Default

CALL PAGVW(0) restores the default.

See also

FITPAG, GROUP and PAGE.

SUBROUTINE PAPINC (CMS)**Name**

PAPINC – to specify the length of paper on a device with continuous paper feed.

Availability Section 1, released before version 2-5.

Argument

CMS REAL expression Length of paper (in cms)

Description

On devices with continuous paper feed (*eg.* drum plotter) the paper length available to an individual program can be increased from the installation default, up to any value not exceeding the installation maximum, using PAPINC.

For further information about the default and maximum, please refer to local documentation.

PAPINC must be called before plotting is started for it to be effective.

Default

CALL PAPINC(0.0) restores the default.

SUBROUTINE PEN (IPEN)**Name**

PEN – to select the pen to be used for all plotting.

Availability Section 1, released before version 2-5.

Argument

IPEN INTEGER expression Pen number

IPEN	<i>Pen usage</i>
–1	plotting is omitted on <i>all</i> devices
0	plotting is done in background colour; on some devices this produces the effect of rubbing out but on others (<i>eg.</i> pen plotters) plotting is omitted
1, 2, 3 ...	pens/bundles are selected as determined by the current device, palette (see PENHLS and PENRGB) and the current bundled attributes (see BUNLPR)

Description

By default, SIMPLEPLOT draws all graphics (*eg.* lines, text, marker symbols, *etc.*) with a single pen (IPEN=1). After PEN has been called, all plotting is performed using the specified pen (IPEN) until another change is initiated by a further call of PEN, SETPNS or WFPNS.

IPEN can have values –1, 0, 1, 2, 3, ... *etc.* CALL PEN(I) is equivalent to CALL SETPNS(I,I,I,I).

Please note that, by default, colour is the only line-drawing attribute associated with pens and the distinction between pens depends on the capabilities of the current device. BUNLPR specifies the attributes to be associated with pens when used for drawing lines (but not text, marker symbols nor software shading) to enable differentiation between pens even on monochrome devices.

Default

CALL PEN(1) restores the default.

See also

BUNLPR, PENHLS, PENRGB, SETPNS, ONEPEN, SHPEN and WFPNS.

SUBROUTINE PENHLS (ICOLOR, HUE, BRIGHT, SAT)

Name

PENHLS – to change the device palette using HLS conventions.

Availability Section plus, released version 2-11.

Arguments

ICOLOR	INTEGER expression	Colour index to be changed
HUE	REAL expression	Hue (degrees)
BRIGHT	REAL expression	Lightness (0.0–1.0)
SAT	REAL expression	Saturation (0.0–1.0)

Description

On devices which allow palette changes, **PENHLS** changes the specified colour index (or device pen) to a specified Hue-Lightness-Saturation. The HLS values required to produce specific colours are listed in Appendix T of the *SIMPLEPLOT Supplement*.

ICOLOR=−1 sets all colour indices (or device pens) to the specified colour.

The effect of defining the palette is affected by the capability of the device and the underlying graphics system. Possible effects include:

No change The device (or device driver) is unable to control the palette.

Retrospective change All graphics (*eg.* lines, text, filled areas, *etc.*) already drawn on the current **SIMPLEPLOT** page, with the specified colour index, are changed to the default palette definition.

Prospective change Only graphics subsequently drawn with the specified colour index use the default palette definition.

Deferred change The new palette definition takes effect from the start of the next **SIMPLEPLOT** page.

Unless any of these effects is actually required, the best time to change the palette is between finishing one **SIMPLEPLOT** page and starting the next (see **ENDPAG** and **NEWPAG**) or before the first page.

If **BUNLPR** has been called to change line-drawing attributes, the **SIMPLEPLOT** pen number will not necessarily correspond to **ICOLOR**.

Default

CALL PENRST(ICOLOR) restores the default. The default is not restored by **INITSP**.

See also

BUNLPR, **ENDPAG**, **NEWPAG**, **PENRST** and **PENRGB**.

SUBROUTINE PENRGB (ICOLOR, RED, GREEN, BLUE)**Name**

PENRGB – to change the device palette using RGB conventions.

Availability Section plus, released version 2-11.

Arguments

ICOLOR	INTEGER expression	Colour index to be changed
RED	REAL expression	Proportion of RED (0.0–1.0)
GREEN	REAL expression	Proportion of GREEN (0.0–1.0)
BLUE	REAL expression	Proportion of BLUE (0.0–1.0)

Description

On devices which allow palette changes, **PENRGB** changes the specified colour index (or device pen) to a specified combination of Red-Green-Blue. The RGB values required to produce specific colours are listed in Appendix T of the *SIMPLEPLOT Supplement*.

ICOLOR=−1 sets all colour indices (or device pens) to the specified colour.

The effect of defining the palette is affected by the capability of the device and the underlying graphics system. Possible effects include:

No change The device (or device driver) is unable to control the palette.

Retrospective change All graphics (*eg.* lines, text, filled areas, *etc.*) already drawn on the current **SIMPLEPLOT** page, with the specified colour index, are changed to the default palette definition.

Prospective change Only graphics subsequently drawn with the specified colour index use the default palette definition.

Deferred change The new palette definition takes effect from the start of the next **SIMPLEPLOT** page.

Unless any of these effects is actually required, the best time to change the palette is between finishing one **SIMPLEPLOT** page and starting the next (see **ENDPAG** and **NEWPAG**) or before the first page.

If **BUNLPR** has been called to change line-drawing attributes, the **SIMPLEPLOT** pen number will not necessarily correspond to **ICOLOR**.

Default

CALL PENRST(ICOLOR) restores the default. The default is not restored by **INITSP**.

See also

BUNLPR, **ENDPAG**, **NEWPAG**, **PENRST** and **PENHLS**.

SUBROUTINE PENRST (ICOLOR)

Name

PENRST – to reset the the device palette.

Availability Section plus, released version 2-11.

Argument

ICOLOR INTEGER expression Colour index to be changed

Description

On devices which allow palette changes, PENRGB or PENHLS can be called to change the colour indices; PENRST resets the colour index, ICOLOR, to the value defined in the device driver to be the default colour for that index. This can only take account of user-defined settings if the device driver can interrogate the device.

The effect of resetting the palette may cause different visual effects depending on the capability of the device or the underlying graphics system.

Possible effects include **No change** – the device (or device driver) is not able to control the palette therefore resetting has no effect; **Retrospective change** – all graphics (*eg.* lines, text, filled areas, *etc.*) already drawn on the current SIMPLEPLOT page, with the specified colour index, are changed to the default palette definition; **Prospective change** – only graphics subsequently drawn with the specified colour index use the default palette definition; **Deferred change** – the default palette definition takes effect from the start of the next SIMPLEPLOT page.

Unless any of these effects is actually required, the best time to change the palette is when there is no active SIMPLEPLOT page (*ie.* after finishing one SIMPLEPLOT page but before starting the next (see ENDPAG and NEWPAG) or before the first page).

Please note that, by default, colour is the only line-drawing attribute associated with pens and the distinction between pens depends on the capabilities of the current device. If BUNLPR has been called to change line-drawing attributes, the SIMPLEPLOT pen number (IPEN) does not necessarily correspond to the colour index (ICOLOR).

Default

CALL PENRST(-1) restores all colour indices.

See also

BUNLPR, ENDPAG, NEWPAG, PENRGB and PENHLS.

SUBROUTINE PERIM

Name

PERIM – to draw a rectangular box around the current picture.

Availability Section 1, released version 2-5.

Arguments

None.

Description

PERIM draws [1] a rectangular box around the perimeter of the picture which has already been started.

If scales have been extended to provide similar linear scales in x and y (see **EQSCAL**), the box is drawn around the full extent of the scales at the picture limits. If a box is required to fit the requested range of scales, and the axes drawn to annotate such scales, **DRAWBX** can be used.

See also

BOXPIC and DRAWBX.

SUBROUTINE PERIPH (CMS)**Name**

PERIPH – to specify the overall size of the periphery around a group of pictures.

Availability Section 4, released version 2-7.

Argument

CMS REAL expression Size of periphery (in cms)

Description

If neither PERIPH nor PAGMRG has been called, SIMPLEPLOT controls both the size and distribution of the periphery; PERI is calculated using the current minimum size of text:

$$\text{PERI} = 14 \times \text{character width} + 1.5 \times \text{margin size}$$

If the calculated default value of PERI is less than 3cm, a 3cm periphery is allocated, otherwise, PERI is used as the periphery size.

SIMPLEPLOT imposes minimum and maximum values on peripheries. The maximum size allowed for a periphery is half the smaller dimension of the group. The a minimum periphery is 0.01cm.

The overall peripheral margin is distributed in a 2 : 1 ratio, *left:right* and *bottom:top*.

PERIPH overrides PAGMRG and *vice versa*.

Diagnostics

(v_1 requested)²
 (v_2 used)²
 (Periphery modified)¹

Default

Calling PERIPH with a negative argument restores the default.

See also

PGFULL and PAGMRG.

SUBROUTINE PGFULL (TORF)

Name

PGFULL – to specify whether picture space is to be maximized.

Availability Section 1, released version 2-9.

Argument

TORF LOGICAL expression Whether page is to be filled

Description

By default, the periphery around a group of pictures surround the margins on the picture(s). After a call of PGFULL(.TRUE.), the periphery and the picture margins coincide, allowing bigger pictures to be included in the page.

Default

CALL PGFULL(.FALSE.) restores the default.

See also

MARGIN, PAGMRG, PERIPH and PICMRG.

SUBROUTINE PIBOXL (TORF)**Name**

PIBOXL – to specify whether a box is to be drawn around pie chart labels.

Availability Section 4, released before version 2-5.

Argument

TORF LOGICAL expression Whether a box is to be drawn

Description

By default, labels for pie chart segments are enclosed in a rectangular box. PIBOXL changes to no boxes, or back to drawing boxes. PIBOXL must be called before PIECHT.

Default

CALL PIBOXL(.TRUE.) restores the default.

See also

PIECHT.

SUBROUTINE PICMRG (CMS, RCMS, BCMS, TCMS)

Name

PICMRG – to specify the size of individual picture margins.

Availability Section 4, released version 2-11.

Arguments

CMS	REAL expression	Width of left margin (in cms)
RCMS	REAL expression	Width of right margin (in cms)
BCMS	REAL expression	Width of bottom margin (in cms)
TCMS	REAL expression	Width of top margin (in cms)

Description

By default, the picture margin is treated as two pairs of complementary margins (left/right and bottom/top) and each pair is distributed such that there is enough clearance round pictures for normal plotting requirements (*ie.* with more space to the left and bottom of the picture). PICMRG changes the size and distribution of these picture margins.

Three combinations of values are possible for each pair of margins, m_1 and m_2 :

$m_1 \geq 0$ **and** $m_2 \geq 0$ sizes used unless shrinkage is needed when proportions used.

$m_1 \geq 0$ **and** $m_2 < 0$ (or *vice versa*) non-negative value used as the absolute margin size if page size permits; remaining space put on other side.

$m_1 < 0$ **and** $m_2 < 0$ reset default.

SIMPLEPLOT imposes minimum and maximum values on picture margins. The maximum size allowed for a margin is half the smaller dimension of the picture, and the minimum margin is 0.01cm.

PICMRG overrides MARGIN and *vice versa*.

Default

CALL PICMRG(-1.0,-1.0,-1.0,-1.0) restores default margin sizes and distribution.

See also

MARGDV, MARGIN, PAGMRG and PERIPH.

SUBROUTINE PICPOS (XCMS, YCMS)**Name**

PICPOS – to specify the coordinate position of each new picture.

Availability Section 4, released version 2-8.

Arguments

XCMS	REAL expression	x coordinate of picture
YCMS	REAL expression	y coordinate of picture

Description

By default, each new picture is automatically positioned either in the next clear space within the group or on a new SIMPLEPLOT page. PICPOS specifies the coordinates, (x_{cms}, y_{cms}) , at which the bottom left-hand corner of each new picture is to be positioned. XCMS and YCMS are specified in centimetres relative to the bottom left hand corner of the current SIMPLEPLOT page; if there is no current page, a page is automatically started.

PICPOS overrides the automatic layout (there is an implicit call of MOVEON(.FALSE.)) and while PICPOS is active, ENDPAG terminates the page.

If either XCMS or YCMS exceed the page limits, or if the picture is too big to fit within the page limits at the specified position, the position is moved in one or both directions, until the picture is completely within the page, and a diagnostic is issued.

The picture size can be specified with PICSIZ. If PICPOS is active but no picture size has been specified, a 12cm \times 12cm picture is used.

Diagnostics

$(x_1 \ y_1 \text{ requested})^2$
 $(x_2 \ y_2 \text{ used})^2$
 (PICPOS cancelled)¹
 (Picture position modified)¹

Default

CALL PICPOS(XCMS,YCMS) with either argument negative.

CALL MOVEON(.TRUE.) also cancels PICPOS.

See also

ENDPAG, ENDPIC, KXYXY and MOVEON.

SUBROUTINE PICRST (N)

Name

PICRST – to reset the current picture to the size, position and scales saved as number N.

Availability Section 1, released version 2-14.

Argument

N INTEGER expression Picture identifier (1 to 10)

Description

PICRST and PICSAV facilitate simultaneous drawing on separate picture. Following a call to PICSAV(N), CALL PICRST(N) switches drawing to the picture associated with N.

Diagnostics

[PICRST: argument invalid]¹

See also

PICSAV.

SUBROUTINE PICSAV (N)

Name

PICSAV – to save the size, position and scales of the current picture as number N.

Availability Section 1, released version 2-14.

Argument

N INTEGER expression Picture identifier (1 to 10)

Description

PICSAV facilitates simultaneous drawing on separate picture. Following a call to PICSAV(N), CALL PICRST(N) switches drawing to the picture associated with N.

Diagnostics

[PICSAV: argument invalid]¹

See also

PICRST.

SUBROUTINE PICSIZ (WCMS, HCMS)

Name

PICSIZ – to specify the size of pictures.

Availability Section 1, released before version 2-5.

Arguments

WCMS	REAL expression	Width of pictures (in cms)
HCMS	REAL expression	Height of pictures (in cms)

Description

By default, SIMPLEPLOT calculates the picture size from the page size as follows:

1. Subtract the periphery (if any),
2. Divide by the group size,
3. Subtract the margins, and
4. Apply a shrinkage factor (if necessary) to fit the space available on the device.

PICSIZ specifies the target size of all pictures. If the requested picture size is larger than the space available, a shrinkage factor is applied so that the proportions (or aspect ratio) of the specified dimensions are retained.

If PICPOS is active but no picture size has been specified, a 12cm × 12cm picture is used.

Diagnostics

$(x_1 \ y_1 \text{ requested})^2$
 $(x_2 \ y_2 \text{ used})^2$
 (PICSIZ cancelled)¹
 (PICSIZ ignored: invalid argument)¹
 (Picture Size modified)¹

Default

Calling PICSIZ with either argument set to zero restores the default.

See also

GROUP, PAGE and PICPOS.

SUBROUTINE PIDIAM (CMS)**Name**

PIDIAM – to specify a reduced diameter for pie charts.

Availability Section 4, released before version 2-5.

Argument

CMS REAL expression Diameter (in cms)

Description

By default, the diameter of pie charts is the largest which can be accommodated with the required configuration of exploded segments and labels, within the picture size. PIDIAM sets the pie diameter in centimetres. PIDIAM must be called before PIECHT.

Default

CALL PIDIAM(0.0) restores the default.

See also

PIECHT.

SUBROUTINE PIECHT (DARR, LABARR, NARR)**Name**

PIECHT – to draw a pie chart on the current picture.

Availability Section 4, released version 2-11.

Arguments

DARR	REAL array	Data values
LABARR	STRING array	Names for each segment
NARR	INTEGER expression	Number of segments and number of elements in DARR and LABARR

Description

PIECHT draws a pie chart on the current picture showing the distribution of data among the NARR values in array DARR. The details of labelling, shading patterns, tilt of pie, positions of separate segments *etc.* can all be controlled by prior calls of PI* or SG* subroutines or, in the absence of such calls, defaults are used.

The number of segments of a pie chart is unlimited but the limit on the maximum number of segments which can be omitted or exploded is 32.

Diagnostics

(PIE CHART OMITTED: LESS THAN 1 SEGMENT)¹

(PIE CHART OMITTED: -VE AND +VE VALUES)¹

See also

PIBOXL, PIDIAM, PIEXPL, PIINCL, PIOMIT, PIPOSL, PITILT, SGEXPL, SGOMIT and SHKEYS.

SUBROUTINE PIEXPL (IARR, NARR)**Name**

PIEXPL – to specify the amount by which each pie chart segment is to be exploded.

Availability Section 4, released before version 2-5.

Arguments

IARR	INTEGER array	Percentage (0–50%) explosion for each segment
NARR	INTEGER expression	Number of elements in IARR

Description

By default, pie charts are drawn with all segments touching, and meeting in the centre of the pie. PIEXPL indicates the amount (percentage of the radius) by which each segment is to be displaced from the centre of the pie, along the radius bisecting the segments' angles. PIEXPL must be called before PIECHT.

The number of segments of a pie chart is unlimited but the limit on the maximum number of segments which can be omitted or exploded is 32.

The effect of PIEXPL can be overridden by SGEXPL and *vice versa*.

Default

Calling PIEXPL with all elements of IARR set to zero restores the default.

See also

PIECHT and SGEXPL.

SUBROUTINE PIINCL (LTORF, VTORF, PTORF)**Name**

PIINCL – to specify what elements are to be included in pie chart segment labels.

Availability Section 4, released before version 2-5.

Arguments

LTORF	LOGICAL expression	Whether segment names are to be included in labels
VTORF	LOGICAL expression	Whether segment values are to be included in labels
PTORF	LOGICAL expression	Whether segment percentages are to be included in labels

Description

By default, PIECHT draws each pie segment labelled with the name supplied in the argument array LABARR. PIINCL specifies any combination of segment name, segment value and segment percentage, to be used for labelling all segments. PIINCL must be called before PIECHT.

By default, percentages are specified to 2 decimal places (see FIGFMT) and labels are left-justified (see ADDJST).

Default

CALL PIINCL(.TRUE.,.FALSE.,.FALSE.) restores the default.

See also

ADDJST, FIGFMT, PIECHT, PIBOXL and PIPOSL.

SUBROUTINE PIOMIT (LARR, NARR)**Name**

PIOMIT – to specify which segments are to be omitted from pie charts.

Availability Section 4, released before version 2-5.

Arguments

LARR	LOGICAL array	Specifies for each segment whether or not it is to be omitted
NARR	INTEGER expression	Number of elements in LARR

Description

By default, all segments of pie charts are drawn by PIECHT. PIOMIT indicates that specific segments for which the value LARR(ISEG) is `.TRUE.`, are to be included in the calculations, but omitted from the picture. PIOMIT must be called before PIECHT.

The number of segments of a pie chart is unlimited but the limit on the maximum number of segments which can be omitted or exploded is 32.

The effect of PIOMIT can be overridden by SGOMIT and *vice versa*.

Default

Calling PIOMIT with all elements of LARR set to `.FALSE.` restores the default.

See also

PIECHT and SGOMIT.

SUBROUTINE PIPOSL (IPOS)**Name**

PIPOSL – to specify the position of segment labels on pie charts.

Availability Section 4, released before version 2-5.

Argument

IPOS INTEGER expression Label position

IPOS *Label position*

- | | |
|---|----------------------------------------------------------------------------------------------|
| 1 | Labels equally-spaced down sides of picture, with arrows if there is room (default) |
| 2 | Labels alongside segments, down sides of picture, with arrows if there is room |
| 3 | Labels next to segments (no arrows) |
| 4 | Labels inside segments, or next to segment when there is not enough space inside (no arrows) |
-

Description

By default, PIECHT draws segment labels equally spaced down the sides of the picture. PIPOSL selects any of the four options for label positions.

Default

CALL PIPOSL(1) restores the default.

See also

PIECHT, PIBOXL and PIINCL.

SUBROUTINE PITILT (IWDTH, IHGHT)**Name**

PITILT – to specify the tilt of pie charts.

Availability Section 4, released before version 2-5.

Arguments

IWDTH, INTEGER expressions Width to height ratio
IHGHT

Description

By default, circular pie charts are drawn by PIECHT. Tilted pie charts are drawn by adjusting the width:height ratio to produce elliptical pies. PITILT indicates the required ratio; both IWDTH and IHGHT must be positive integers, and only values with $IWDTH > IHGHT$ are accepted. PITILT must be called before PIECHT.

Default

CALL PITILT(0,0) restores the default.

See also

PIECHT.

**SUBROUTINE POLAR7 (RADIUS, CAP)
SUBROUTINE POLAR (RADIUS, CAP, NCAP)**

Name

POLAR7 – to start a new polar picture and draw axis framework.

Availability Section 1, released before version 2-5.

Arguments

RADIUS	REAL expression	Maximum value of radial scale
CAP	STRING expression	Caption for radial axis
NCAP	INTEGER expression	Number of characters in CAP

Description

POLAR/POLAR7 starts a new picture, sets linear scales from $-\text{RADIUS}$ to $+\text{RADIUS}$ in both horizontal and vertical directions, draws [1] a radial axis annotated [2] with the scale, and draws [1] an angular axis annotated [2] with the angular scale of degrees.

POLAR7 sets the underlying coordinate system to be polar (in degrees). Even if Cartesian units have been specified by EQSCAL, when a new picture is started by POLAR7, a polar axis framework is drawn over complete quadrants and the plotting units are switched to degrees.

Diagnostics

(POLAR OMITTED: ZERO RADIUS)¹

See also

AXES7, AXIS7, COORDS, EQSCAL, NEWPIC, POLRNG and POLZER.

SUBROUTINE POLIN (PARR, NP)**Name**

POLIN – to transfer polynomial coefficients before plotting curves of polynomial functions.

Availability Section 1, released before version 2-5.

Arguments

PARR	REAL array	Polynomial coefficients
NP	INTEGER expression	Number of polynomial coefficients (1–20)

Description

POLIN copies the values of PARR(1) to PARR(NP) into storage within SIMPLEPLOT for later use in calculating the polynomial function:

$$\text{PARR}(1) + \text{PARR}(2)x + \text{PARR}(3)x^2 + \dots + \text{PARR}(\text{NP})x^{\text{NP}-1}$$

using POLY, normally with DRAWFN/BRKNFN/SHDEFN.

See also

POLOUT and POLY.

SUBROUTINE POLOUT (PARR)

Name

POLOUT – to transfer polynomial coefficients after plotting regression curves.

Availability Section 1, released before version 2-5.

Argument

PARR REAL array To receive polynomial coefficients

Description

POLOUT copies values of polynomial coefficients from within SIMPLEPLOT into PARR. If CVTYPE has been called with argument 4 or 5 to cause BRKNAR/DRAWAR/SHDEAR or BRKNCV/DRAWCV/SHDECV to draw regression curves, the program can obtain the regression coefficients by calling POLOUT afterwards. PARR(I) is used as the coefficient of x^{i-1} .

See also

CVTYPE, POLIN and POLY.

SUBROUTINE POLRNG (THSTRT, THSTOP)**Name**

POLRNG – to specify the user-defined polar coordinate system.

Availability Section plus, released version 2-12.

Arguments

THSTRT	REAL expression	Value of scale at 0°
THSTOP	REAL expression	Value of scale at 360°

Description

By default, the angular scale used when **COORDS** has been called with **IUNITS=3**, is in radians. **POLRNG** specifies an alternative coordinate system.

POLRNG defines the range of a complete cycle of the angular axis from **THSTRT** to **THSTOP**. **CALL EQSCAL(..., 3)** specifies the plotting scales for polar plotting in with respect to this cyclical range.

Default

Calling **POLRNG** with **THSTRT=THSTOP** restores the default.

See also

COORDS, **EQSCAL** and **POLZER**.

REAL FUNCTION POLY (RVAL)**Name**

POLY – to evaluate a polynomial function.

Availability Section 1, released before version 2-5.

Argument

RVAL	REAL expression	Argument of polynomial function in units of plotting scales
------	-----------------	-------------------------------------------------------------

Description

POLY calculates the value, at the specified argument value, of the polynomial function whose coefficients have already been set up using POLIN. Its primary use is as an argument of DRAWFN, BRKNFN or SHDEFN. For example,

```
CALL DRAWFN(POLY)
CALL BRKNFN(POLY,LTYPE)
```

Please note that any program segment using POLY in this way, must declare POLY as an external subroutine. For example, EXTERNAL POLY.

This mechanism is also used internally within DRAWCV, BRKNCV and SHDEFN when CVTYPE has been called to specify linear or quadratic regressions.

See also

POLIN and POLOUT.

SUBROUTINE POLZER (RZERO, IRDIR, THZERO, ITHDIR)

Name

POLZER – to specify the convention used for polar coordinates.

Availability Section 1, released version 2-12.

Arguments

RZERO	REAL expression	Radial coordinate at centre of chart
IRDIR	INTEGER expression	Direction of radial scale
THZERO	REAL expression	Angle on chart of zero angular coordinate
ITHDIR	INTEGER expression	Direction of angular scale
<hr/>		
	IRDIR or ITHDIR	<i>Direction of radial increase</i> <i>Direction of angular increase</i>
	-ve	Decreasing outwards Clockwise
	0	Increasing outwards (default) Either way depending on directions of change of x & y (default)
	+ve	Increasing outwards Anticlockwise

Description

Polar coordinates describe a point $z = f(r, \theta)$ where r is the distance of the point from an origin, and θ is the angle between a fixed line through the origin and a line joining the point to the origin. By default, SIMPLEPLOT assumes that radial units increase from zero at the Cartesian origin, ($x = 0, y = 0$), and that angles increase in the direction of increasing y from zero at a fixed horizontal line $y = 0$. POLZER specifies an alternative convention for polar coordinates.

RZERO specifies the radial scale value to correspond with the Cartesian origin. THZERO specifies the anticlockwise angle (in degrees) between the horizontal line from the origin to the right, and the chosen position for the fixed line. IRDIR and ITHDIR indicate the direction of increase of the radial scale and of angular change respectively.

After a call to POLZER, all polar pictures are drawn according to the specified convention, and all polar coordinates are interpreted similarly.

Default

CALL POLZER(0.0,0,0.0,0) restores the default.

See also

COORDS, EQSCAL and POLRNG.

SUBROUTINE PUTCP7 (IROW, ICOLM, CAP)
SUBROUTINE PUTCAP (IROW, ICOLM, CAP, NCAP)

Name

PUTCP7 – to draw a caption in a specified position in a caption area.

Availability Section 4, released before version 2-5.

Arguments

IROW	INTEGER expression	Line number
ICOLM	INTEGER expression	Character position
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

PUTCAP/PUTCP7 draws [2] the single caption, CAP, in the specified position within a caption area defined by DEFCAP (and selected by RESNXT). The position is determined as line IROW (counting down from IROW=1 at top), character position ICOLM (counting across from ICOLM=1 at left).

Diagnostics

(Caption truncated)²
 (No active key/caption area)²

See also

ADDCP7, DEFCAP, KNUMB and KREAL.

SUBROUTINE QCURVE (MAXPTS, XARR, YARR, NPTS)

Name

QCURVE – to return the coordinates of a stored curve.

Availability Section plus, released version 2-13.

Arguments

MAXPTS	INTEGER expression	Maximum points to receive per call
XARR, YARR	REAL arrays	Dimensioned at least MAXPTS to receive coordinates of points
NPTS	INTEGER variable	To receive number of points

Description

Some SIMPLEPLOT operations can remember coordinates of curves for extraction by QCURVE (see CTHOLD). Each call of QCURVE can return between 0 and MAXPTS coordinates in arrays XARR and YARR; NPTS is set to the number of points returned. The stored coordinates can constitute any number of separate curves which can be extracted by repeated calls of QCURVE. Any curves containing more than MAXPTS points will also require multiple calls of QCURVE.

NPTS	<i>Interpretation of replies</i>
NPTS=MAXPTS	The curve may be incomplete either because there are more points to this curve segment or because there is another curve segment; continuation of the current segment is signified by the first point received by next call of QCURVE duplicating the value of last point of the previous segment: (XARR(MAXPTS), YARR(MAXPTS))
0 < NPTS < MAXPTS	(XARR(NPTS), YARR(NPTS)) is the final point of a curve
NPTS=0	No coordinates retrieved – end of process

If there are no stored coordinates to retrieve, a diagnostic is issued.

Diagnostics

(Curve storage empty)¹

See also

CTHOLD, ZEDGE, ZELEMS, ZZEDGE, ZZELMS, *CONT, and *CUT.

SUBROUTINE QDEV (NDEV, NSITE, NABS, SNAME, SDESC)**Name**

QDEV – to inquire details of a menu entry for a specific device option.

Availability Section plus, released version 2-11.

Arguments

NDEV	INTEGER expression	Position of option in S.E.P. menu
NSITE	INTEGER variable	To receive <i>site number</i>
NABS	INTEGER variable	To receive <i>absolute number</i>
SNAME	STRING variable	To receive <i>site name</i>
SDESC	STRING variable	To receive <i>description</i>

NDEV *Device option*

0 the currently selected device option

>0 the NDEVth entry in the menu

Description

The SIMPLEPLOT Single Entry Point device driver system provides device options which are tabulated when interactive device selection is requested and displayed as a menu. Each device option has associated with it a *site number*, *absolute number*, *site name* and *description*. QDEV inquires the values of NSITE, NABS, SNAME and SDESC for any device option; the value of NDEV indicates which device option is required.

If no device is open and NDEV=0, or if there is no NDEVth entry in the menu, QDEV returns NSITE=0, NABS=0, and SNAME and SDESC are both filled with spaces.

In order to ensure that the full text string is received, SNAME and SDESC should be declared as CHARACTER*20 and CHARACTER*40 respectively.

See also

DEVNAM and DEVNO.

SUBROUTINE QFFSIZ (WCMS, HCMS)**Name**

QFFSIZ – to inquire the physical size of current fast area-fill characters.

Availability Section plus, released version 2-12.

Arguments

WCMS	REAL variable	To receive width (in cms)
HCMS	REAL variable	To receive height (in cms)

Description

QFFSIZ inquires the width and height (in centimetres) of the current fast area-fill characters. It is only possible to find out this information when a SIMPLEPLOT page has been started; if QFFSIZ is called when there is no page, zero width and height are returned. If QFFSIZ is to be used in order to establish a suitable picture size, first use NEWPAG to start a page.

If QFFSIZ is called without a prior call of FFSIZE, the current default size for shaded contour maps is returned. The default size for raster pictures (*eg.* shaded surfaces) can be determined by preceding a call to QFFSIZ with CALL FFSIZE(0.5,0.5).

See also

FFSET, FFSIZE and NEWPAG.

SUBROUTINE QIBRFL (D3ARR, NX, NY, NSETS, ZMIN, ZMAX)**Name**

QIBRFL – to inquire the z scale required by an *SIMPLEPLOT Isometric* 3-D barchart.

Availability Section plus, released version 2-14.

Arguments

D3ARR	REAL 3-D array	$NX \times NY \times NSETS$ array of user (z) values
NX, NY, NSETS	INTEGER expressions	Dimensions of 3-D data array
ZMIN	REAL variable	To receive minimum z
ZMAX	REAL variable	To receive maximum z

Description

QIBRFL returns the minimum and maximum values required on the z scale for ISBRFL to plot the data in array D3ARR with the current base z value. This may be used to establish the z scale to set 3-D scales before drawing a stacked barchart.

Diagnostics

(QIBRFL invalid dimensions)¹

See also

ISBRBZ and ISBRFL.

SUBROUTINE QKYCAP (LABARR, NARR, ITYPE, NROWS, NCOLMS)**Name**

QKYCAP – to inquire the size of a key or caption area to hold a set of captions.

Availability Section plus, released version 2-11.

Arguments

LABARR	STRING array	Set of labels
NARR	INTEGER expression	Number of labels in LABARR
ITYPE	INTEGER expression	Intended use of text strings
NROWS	INTEGER variable	To receive number of rows
NCOLMS	INTEGER variable	To receive nominal number of columns

ITYPE	<i>Text usage</i>
-------	-------------------

- | | |
|---|-------------------------------------------|
| 1 | Keys or captions relating to pictures |
| 2 | Keys or captions relating to groups/pages |

Description

QKYCAP inquires the number of equivalent rows and columns which a set of a text strings would fill in a key or caption area (see DEFCAP and DEFKEY). Because SIMPLEPLOT scales text according to whether the key (or caption area) relates to the picture or to the page, an additional argument, ITYPE is required to describe the text usage.

QKYCAP cannot be called until a new picture/page has been started.

See also

QSTR7, DEFCAP and DEFKEY.

SUBROUTINE QNODAT (VARW)

Name

QNODAT – to inquire the current value representing no-data.

Availability Section 1, released version 2-10.

Argument

VARW REAL variable To receive no-data value

Description

QNODAT sets the variable VARW to the REAL value which is currently in use within SIMPLEPLOT to represent the absence of a data value. The default no-data value is $-1.0E20$.

See also

NODATA.

SUBROUTINE QPAGE (WCMS, HCMS)**Name**

QPAGE – to inquire the maximum page size of the current device.

Availability Section plus, released version 2-11.

Arguments

WCMS	REAL variable	To receive page width (in cms)
HCMS	REAL variable	To receive page height (in cms)

Description

QPAGE inquires the page size of the current device; the values of WCMS and HCMS returned are centimetre values which can be used as a page size (`CALL PAGE(WCMS,HCMS)`) on the current device, with no shrinkage.

See also

PAGE.

SUBROUTINE QPIC (X0, Y0, XL, YL)**Name**

QPIC – to inquire the position and size of the current picture.

Availability Section 1, released version 2-14.

Arguments

X0, Y0	REAL variables	To receive centimetre coordinates of the bottom left corner
XL	REAL variable	To receive picture width in centimetres
YL	REAL variable	To receive picture height in centimetres

Description

QPIC inquires the position and size of the current picture. These may be useful for positioning subsequent pictures relative to this one.

A new picture must be started before QPIC is called.

SUBROUTINE QPIXLS (NX, NY)**Name**

QPIXLS – to inquire number of pixels on current device.

Availability Section plus, released version 2-11.

Arguments

NX	INTEGER variable	To receive number of pixels horizontally
NY	INTEGER variable	To receive number of pixels vertically

Description

QPIXLS inquires the numbers of pixels horizontally and vertically on the current device.

If QPIXLS is called before a device is open, the device opening procedure is performed before the reply is returned. If pixel details are not available (*eg.* on a non-pixel device) NX=0 and NY=0 are returned.

See also

QPAGE.

SUBROUTINE QSFLAB (VARMIN, VARMAX, VARSTP)

Name

QSFLAB – to inquire of the range of data and contour interval on latest 3-D plot.

Availability Section 2, released version 2-11.

Arguments

VARMIN	REAL variable	To receive first z value
VARMAX	REAL variable	To receive last z value
VARSTP	REAL variable	To receive contour interval

Description

QSFLAB inquires the limits of the z plotting range, and the interval between contours, on the latest surface plot, and place their REAL values in the variables VARMIN, VARMAX and VARSTP.

See also

SFLAB.

SUBROUTINE QSPLOT (STR)**Name**

QSPLOT – to inquire the current version of SIMPLEPLOT.

Availability Section 1, released version 2-14.

Argument

STR STRING variable to receive software version

Description

The first diagnostic message output by SIMPLEPLOT includes the current version; for example:

(SIMPLEPLOT Mark 2-15(000)F)

QSPLOT can be called to get a character representation of this version number, *eg.* 2-15(000)F.

In order to ensure that the full text string is received, STR should be declared as CHARACTER*10.

SUBROUTINE QSTAT (ISTAT)

Name

QSTAT – to inquire the status of the last SIMPLEPLOT call.

Availability Section plus, released version 2-12.

Argument

ISTAT INTEGER variable To receive status value

Description

Each SIMPLEPLOT subroutine sets a status flag to 0 before it performs any functions. During the execution of the subroutine, the status flag is changed to 1 whenever output is omitted due to lack of space or an invalid request. QSTAT returns the value of the status flag (in ISTAT) which resulted from the most recently called SIMPLEPLOT subroutine.

If QSTAT is the first SIMPLEPLOT subroutine called, ISTAT is returned with a value of -1 .

DIAGLV(2) and DIAGLV(4) produce explanatory diagnostic messages for most of the conditions which set ISTAT to 1.

See also

DIAGLV.

**SUBROUTINE QSTR7 (CAP, ITYPE, WCMS, HCMS)
SUBROUTINE QSTR (CAP, NCAP, ITYPE, WCMS, HCMS)**

Name

QSTR7 – to inquire the physical size of a text string.

Availability Section plus, released version 2-11.

Arguments

CAP	STRING expression	Text string for analysis
ITYPE	INTEGER expression	Intended use of text string
WCMS	REAL variable	To receive width of text string
HCMS	REAL variable	To receive height of string
NCAP	INTEGER expression	Number of characters in CAP

ITYPE	<i>Text usage</i>
-------	-------------------

- | | |
|---|------------------------------------------------------|
| 0 | Normal usage – <i>eg.</i> picture or axis annotation |
| 1 | Keys or captions relating to pictures |
| 2 | Keys or captions relating to pages |
| 3 | Titles relating to pictures |
| 4 | Titles relating to pages |
-

Description

QSTR/QSTR7 inquire the physical height and width of a text string. Because SIMPLEPLOT scales text according to its use, an additional argument ITYPE is required to describe the text usage.

As the size of text depends on the size of the page, QSTR7 cannot be called until a new picture/page has been started. If QSTR7 is called with no active page, the values WCMS=0.0 and HCMS=0.0 are returned.

See also

NEWPAG and QKYCAP.

SUBROUTINE QV3DLM (VARX1, VARX2, VARY1, VARY2, VARZ1, VARZ2)**Name**

QV3DLM – to inquire the three-dimensional limits for plottable data.

Availability Section 7, released version 2-13.

Arguments

VARX1	REAL variable	To receive value at start of x scale
VARX2	REAL variable	To receive value at end of x scale
VARY1	REAL variable	To receive value at start of y scale
VARY2	REAL variable	To receive value at end of y scale
VARZ1	REAL variable	To receive value at start of z scale
VARZ2	REAL variable	To receive value at end of z scale

Description

SIMPLEPLOT *ViSualization* scales are set to accommodate all data within a three-dimensional box. By default, the x , y and z limits of this box are all -1.0 to $+1.0$, although *VS3DLM* can change these limits.

QV3DLM inquires the data limits used for the current picture.

All points which lie inside the limits after transformations have been applied can be plotted. Other points may lie outside the 2-D *SIMPLEPLOT* scales.

QV3DLM may also be used to calculate the Origin, which is at the centre of the Limiting Box. This is at

$$\left(\frac{\text{VARX1}+\text{VARX2}}{2}, \frac{\text{VARY1}+\text{VARY2}}{2}, \frac{\text{VARZ1}+\text{VARZ2}}{2} \right)$$

QV3DLM gives the limits for the current picture. It must be called after the scales have been set by *VSNEW*. If *VSNEW* has not been called, all the variables are set to the current ‘no data’ value.

Diagnostics

[QV3DLM: No current *ViSualization* picture]¹

See also

VS3DLM.

SUBROUTINE QVBRFL (Z, NX, NY, NSETS, ZMIN, ZMAX)**Name**

QVBRFL – to inquire the z scale required by a *SIMPLEPLOT ViSualization* 3-D barchart.

Availability Section 7, released version 2-14.

Arguments

Z	REAL 3-D array	$NX \times NY \times NSETS$ array of user (z) values
NX, NY, NSETS	INTEGER expressions	Dimensions of 3-D data array
ZMIN	REAL variable	To receive minimum z
ZMAX	REAL variable	To receive maximum z

Description

QVBRFL returns the minimum and maximum values required on the z scale for VSBFRFL to plot the data in array Z with the current base z value. This may be used to establish the z scale to set 3-D scales before drawing a stacked barchart.

Diagnostics

[QVBRFL: Invalid array dimension]¹

See also

VS3DLM, VSBFBZ and VSBFRFL.

SUBROUTINE QVDPLM (VARMIN, VARMAX)

Name

QVDPLM – to inquire the range of depths for the current *SIMPLEPLOT ViSualization* picture.

Availability Section 7, released version 2-13.

Arguments

VARMIN	REAL variable	To receive minimum depth
VARMAX	REAL variable	To receive maximum depth

Description

QVDPLM gives the range of depths of points inside the *SIMPLEPLOT ViSualization* Limiting Box. The limits for the box are set by VS3DLM, given the current scaling mode set by VSFULL.

Depth increases away from the Viewing Position – only points which are the other side of the Viewing Plane have positive depths.

The range of depths is affected by VSFULL as follows:

- VSFULL(0) (default), $\text{VARMIN} \geq -\sqrt{3}$ and $\text{VARMAX} \leq +\sqrt{3}$.
- VSFULL(1), $\text{VARMIN} = -\sqrt{3}$ and $\text{VARMAX} = +\sqrt{3}$.
- VSFULL(2), the range of depths depends on the transformations specified by VSMAG, VSR0T, and VSTRAN.

QVDPLM gives the limits for the current picture. It must be called after the scales have been set by VSNEW. If VSNEW has not been called, all the variables are set to the current ‘no data’ value.

Diagnostics

[QVDPLM: No current ViSualization picture]¹

See also

VS3DLM, VSFULL, VSVRTP and VSVXYZ.

SUBROUTINE QVSCAL (VARXMN, VARXMX, VARYMN, VARYMX)**Name**

QVSCAL – to inquire the scale limits in SIMPLEPLOT user coordinates corresponding to the current projected plotting area.

Availability Section 7, released version 2-13.

Arguments

VARXMN	REAL variable	To receive minimum value of x scale
VARXMX	REAL variable	To receive maximum value of x scale
VARYMN	REAL variable	To receive minimum value of y scale
VARYMX	REAL variable	To receive maximum value of y scale

Description

QVSCAL returns the maximum possible plotting area for the current *SIMPLEPLOT ViSualization* picture. The plotting limits may be altered by calls to VS3DLM, VSFIT, VSFITP, VSFULL, VSVRTP or VSVXYZ.

If a point is within the limits specified by VS3DLM, the range of possible x - y values is determined by the Scaling Mode selected by VSFULL:

- VSFULL(0) (default),
 $\text{VARXMN}/\text{VARYMN} \geq -\sqrt{3}$ and $\text{VARXMX}/\text{VARYMX} \leq +\sqrt{3}$.
- VSFULL(1), $\text{VARXMN}/\text{VARYMN} = -\sqrt{3}$, and $\text{VARXMX}/\text{VARYMX} = +\sqrt{3}$.
- VSFULL(2), the 2-D limits depends on the transformations specified by VSMAG, VSR0T and VSTRAN.

QVSCAL gives the limits for the current picture. It must be called after the scales have been set by VSNEW. If VSNEW has not been called, all the variables are set to the current ‘no data’ value.

Diagnostics

[QVSCAL: No current ViSualization picture]¹

See also

VS3DLM, VSFIT, VSFITP, VSFULL, VSVRTP and VSVXYZ.

SUBROUTINE QWZSCL (ZSTART, ZSTOP)

Name

QWZSCL – to inquire the current z scales for curves on waterfall charts.

Availability Section plus, released version 2-13.

Arguments

ZSTART, REAL variables To receive range of z covered
ZSTOP

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. Each curve is drawn on a scale covering the same z range.

QWZSCL inquires the current scales for any single curve on the latest waterfall chart.

QWZSCL can not return a sensible value if no waterfall scales exist. If WFCHT, WFDRAW or WFZSCL has not been called already, a diagnostic is issued and ZSTART and ZSTOP are set to the current no-data value.

Diagnostics

(No current waterfall Z scale)¹

See also

KWZVAL and WFZSCL.

SUBROUTINE RANGE (X1, Y1, X2, Y2)**Name**

RANGE – to draw a line indicating a range of values.

Availability Section 1, released before version 2-5.

Arguments

X1, Y1	REAL expressions	Coordinates of the first point
X2, Y2	REAL expressions	Coordinates of the second point

Description

RANGE draws [1] the mathematically straight line from (x_1, y_1) to (x_2, y_2) , with a short perpendicular line across each end. This line may be represented by a curve when plotted on non-linear scales or in polar coordinates.

The points (x_1, y_1) and (x_2, y_2) are specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine KXYXY.

By default, all drawing is restricted by the limits of the picture scales; range bars can spill over the edge of a picture but the coordinates at either end must not exceed these limits. If coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

$(**x_1, y_1, x_2, y_2**)^2$

See also

CLIPLV, DRAWLN and BRKNPT.

SUBROUTINE RASTER (ICODE)

Name

RASTER – to specify the shading technique to be used for shaded surfaces.

Availability Section plus, released version 2-13.

Argument

ICODE INTEGER expression Type of shading

ICODE	Shading technique
0	Disable raster emulation (use the <i>painter's algorithm</i>)
1	Enable raster emulation

Description

By default, shaded surface pictures are plotted by building up a raster image internally which is output using the current fast area-fill characters. RASTER specifies an alternative shading technique for shaded surfaces.

Axes, text and keys are not drawn as part of this raster picture but surface lines (*eg.* outlines, crosshatching) are included in the raster image; for such lines, smaller fast area-fill characters may be desirable (see FFSIZE).

There is a limit to the number of different levels (or shading patterns) which can be represented on a raster picture; in the current implementation this limit is 126 levels.

The *painter's algorithm* is an alternative to raster emulation on devices which can overstrike shaded areas (or rub out software shading lines). This technique exploits the representation of a three-dimensional surface on a two-dimensional picture whereby some of the data values are hidden 'behind' the shape which is actually drawn. When using the painter's algorithm, data at the 'back' of the picture is plotted first and then overdrawn where appropriate.

Default

CALL RASTER(1) restores the default.

See also

FFSET, FFSIZE, ISSBAS, ISSBCK, ISSHAD, ISSKRT, ISSPAT and QFFSIZ.

SUBROUTINE REDRAW (ICHAN, IDEV)**Name**

REDRAW – to redraw the metafile from the specified I/O channel to the specified device.

Availability Section plus, released version 2-8.

Arguments

ICHAN	INTEGER expression	Channel number
IDEV	INTEGER expression	Device number

Description

A SIMPLEPLOT metafile can be created using either MTFIL or the META device driver. Once created, the metafile opened on FORTRAN I/O channel ICHAN can be redrawn in its entirety by REDRAW to the device specified by IDEV. REDRAW continues reading from channel number ICHAN until the end of file is encountered. If the metafile contains details of more than one SIMPLEPLOT page, a succession of separate plots is produced.

If REDRAW is called with ICHAN=0 while a SIMPLEPLOT page is still being assembled, the current scratch metafile is redrawn.

SIMPLEPLOT can only address one device at a time; if a different device is specified for REDRAW from the one in use, SIMPLEPLOT closes the current device, and then opens the device referenced by IDEV. Any subsequent plotting from the program automatically reverts to the original device, and diagnostic messages are issued.

IDEV can have any value which is available to DEVNO including IDEV=0 to invoke interactive selection (S.E.P. device driver system only).

Diagnostics

(DEVICE CLOSED)¹

(DEVICE OPENED: device)¹

See also

MTCOMM, MTCLOS, MTDRAW, MTFIL, MTMISS, MTONLY and MTOPEN.

SUBROUTINE RESCLR

Name

RESCLR – to cancel all areas reserved for captions and keys.

Availability Section 4, released before version 2-5.

Arguments

None.

Description

Areas reserved for sequences of captions and keys continue to be allocated with each new picture until the reservation is cancelled by another call of **DEFCAP** or **DEFKEY**. **RESCLR** cancels all reserved areas (for keys and captions) and set the number of reserved areas back to zero.

The limit on the maximum number of reserved areas for keys and captions is 9.

See also

DEFCAP and DEFKEY.

SUBROUTINE RESNXT (VCHAR, HCHAR)**Name**

RESNXT – to specify the reserved area which is to be used next.

Availability Section 4, released before version 2-5.

Arguments

VCHAR	CHARACTER*1	Vertical position of reserved area
HCHAR	CHARACTER*1	Horizontal position of reserved area

Description

When more than one area has been reserved for keys or captions, it becomes necessary to indicate which area a key entry or caption is to occupy. If RESNXT is called with arguments VCHAR and HCHAR matching those of one of the reserved areas, subsequent calls of subroutines which draw a key entry or caption are aimed at the next available space in that area. RESNXT has effect until a different area is selected by another call of RESNXT or until a new area is defined by DEFCAP or DEFKEY.

The limit on the maximum number of reserved areas for keys and captions is 9.

RESNXT only interacts with key/caption areas which have been defined using DEFKEY/DEFCAP with ITYPE=3; if RESNXT is called specifying a position for which there is no corresponding reserved area, a diagnostic is issued.

The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(RESNXT ignored, area not reserved)¹

See also

RESCLR, DEFCAP and DEFKEY.

REAL FUNCTION RGCALC (X, Y, Z2ARR, NX, NY)

Name

RGCALC – to interpolate $z = f(x, y)$ from 3-D data on a regular grid.

Availability Section 2, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

The value of z at (x, y) is evaluated by two-way linear interpolation within the rectangular cell of the grid in which (x, y) is located.

If X or Y lie outside the limits of the data, RGCALC returns the current no-data value.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

NODATA, QNODAT, SFEQX and SFEQY.

SUBROUTINE RGCNTS (Z2ARR, NX, NY)**Name**

RGCNTS – to draw a contour map from 3-D data on a regular grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

RGCNTS draws a contour map on the current picture which represents 3-D data on a regular grid. Contours are drawn for equally-spaced z values within the range of data held in Z2ARR. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

The contours drawn by RGCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

CTBRKN overrides the bundled line-drawing attributes of pens associated with the four pen pointers.

Diagnostics

(Contour map not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, RIDDLE, SFEQX, SFEQY, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SQBRKN, SQPEN, SQZLAB and SQZVAL.

SUBROUTINE RGCONT (ZLEV, Z2ARR, NX, NY)**Name**

RGCONT – to draw a contour curve from 3-D data on a regular grid.

Availability Section 2, released before version 2-5.

Arguments

ZLEV	REAL expression	Contour level
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

RGCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z=ZLEV$ from 3-D data (on a regular grid) held in Z2ARR.

Diagnostics

(Contour curve not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, QCURVE, RIDDLE, SFEQX and SFEQY.

SUBROUTINE RGCUT (X1, Y1, X2, Y2, Z2ARR, NX, NY)**Name**

RGCUT – to draw a 2-D curve of a surface section from 3-D data on a regular grid.

Availability Section 2, released before version 2-5.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of two points
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

If the surface represented by the data in Z2ARR were cut along the straight line from (x_1, y_1) to (x_2, y_2) , the side view of the section would show as a two-dimensional curve of the variation of the data along that line.

RGCUT draws [1] the curve of surface height *vs.* distance from (x_1, y_1) on the current picture – suitable scales must be set up before attempting to draw a section.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Surface section not all in range)²

See also

CTBRKN, CTCURV, CTHOLD, QCURVE, SFEQX and SFEQY.

SUBROUTINE RGSHAD (ZLEV1, ZLEV2, ISHADE, Z2ARR, NX, NY)**Name**

RGSHAD – to shade the area between two contour levels from 3-D data on a regular grid.

Availability Section plus, released version 2-5.

Arguments

ZLEV1,	REAL expressions	Contour levels
ZLEV2		
ISHADE	INTEGER expression	Shading pattern number
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

RGSHAD shades the area between contour levels $z=ZLEV1$ and $ZLEV2$ from 3-D data (on a regular grid) held in **Z2ARR**; the area is drawn on the current picture using shading pattern **ISHADE**. By default, the contours themselves are not drawn (see **SHEDGE**).

If data values, z , coincide with contour levels, only those equal to z_{min} are included within the shaded region, *ie.* $z_{min} \leq z < z_{max}$, where $z_{min} = MIN(ZLEV1, ZLEV2)$ and $z_{max} = MAX(ZLEV1, ZLEV2)$.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, RGSCHDS, SFEQX, SFEQY, SFMESH and SHEDGE.

SUBROUTINE RGSHDS (Z2ARR, NX, NY)**Name**

RGSHDS – to draw a shaded contour map from 3-D data on a regular grid.

Availability Section plus, released version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

RGSHDS draws a shaded contour map on the current picture from 3-D data on a regular grid. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of data held in Z2ARR; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contours not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, RGSHAD, RGCNTS, SFEQX, SFEQY, SHEDGE, SHPATT and SQ*.

SUBROUTINE RGSURF (Z2ARR, NX, NY)**Name**

RGSURF – to start a new picture and draw a surface from 3-D data on a regular grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR

Description

RGSURF starts a new picture, and draws a surface of the data in Z2ARR.

In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling RGSURF.

RGSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

IS*, ISSHAD, RIDDLE, SFEQX, SFEQY and SFZSCL.

SUBROUTINE RIDDLE (RVAL)

Name

RIDDLE – to specify the level of elimination of redundant points for polylines.


Availability Section 1, released version 2-12.

Argument

RVAL REAL expression Tolerance

Description

By default, no attempt is made to remove co-linear points which make up a polyline. RIDDLE specifies that a filtering process is to be applied to all polyline output which throws away intermediate points which are nearly co-linear. RVAL specifies the maximum permissible percentage error in thinning-out of polylines, that is, the tolerance to be used to determine co-linearity. RVAL must be in range 0.0 to 5.0 inclusive; any other value resets the default.



The filtering criterion relates to angles between vectors. Given a sequence of 3 points A , B and C to be joined by 2 vectors AB and BC , B is omitted if angle ABC is in the range $180 - \theta$ to $180 + \theta$ where $\tan \theta = \text{RVAL}/25.0$.

It can be shown that $BD = AC * (\tan \theta/2)/2$ where BD is the maximum perpendicular distance between the line drawn and any point omitted, and AC is the length of the line. Over the allowed range of RVAL, $(\tan \theta)/2$ approximates $\tan(\theta/2)$ so that BD is approximately $\text{RVAL}/100$.

Default

CALL RIDDLE(0.0) restores the default.

SUBROUTINE SCALES (XSTART, XSTOP, IXTYPE, YSTART, YSTOP, IYTYPE)

Name

SCALES – to specify Cartesian scales for all 2-D plotting.

Availability Section 1, released before version 2-5.

Arguments

XSTART	REAL expression	x scale value at left edge
XSTOP	REAL expression	x scale value at right edge
IXTYPE	INTEGER expression	Type of horizontal scale
YSTART	REAL expression	y scale value at bottom edge
YSTOP	REAL expression	y scale value at top edge
IYTYPE	INTEGER expression	Type of vertical scale

IXTYPE or IYTYPE	Type of scale
0	Centimetre
1	Linear
2	Logarithmic
3	Normal probability (%)

Description

By default, scales are linear in centimetres starting at zero. **SCALES** specifies the limits and types of both horizontal and vertical plotting scales. The relative values of the first and last scale values determine whether the scale increases or decreases.

SCALES resets the underlying coordinate system to Cartesian.

Scales are normally set before a picture is started and the same scales used for all relevant 2-D pictures until reset.

Diagnostics

(Range ≥ 100 ; linear scale used)¹

(Range through 0; linear scale used)¹

Default

Calling **SCALES** with XSTART=XSTOP and/or YSTART=YSTOP, or with IXTYPE=0 and/or IYTYPE=0, restores the default centimetre scaling (the values of all arguments are otherwise ignored).

See also

KSCALE, XSCALE, YSCALE and EQSCAL.

SUBROUTINE SCLEAR**Name**

SCLEAR – to clear the graphics screen independently of starting a new picture.

Availability Section 4, released version 2-7.

Arguments

None.

Description

On a screen device, SIMPLEPLOT always clears the graphics screen immediately after starting a new page. SCLEAR performs the same clearing operation.

On a non-screen device (*eg.* a pen plotter or laser printer), SCLEAR has no effect.

See also

ENDPAG, OUTBUF, OWNIO and OWNNEW.

SUBROUTINE SETPNS (IPEN1, IPEN2, IPEN3, IPEN4)

Name

SETPNS – to specify the pens associated with the four pen pointers.

Availability Section 1, released before version 2-5.

Arguments

IPEN1	INTEGER expression	Pen associated with pen pointer [1]
IPEN2	INTEGER expression	Pen associated with [2]
IPEN3	INTEGER expression	Pen associated with [3]
IPEN4	INTEGER expression	Pen associated with [4]

IPEN <i>i</i>	Pen usage
–1	plotting is omitted on all devices
0	plotting is done in background colour; this has no effect on pen plotters
1, 2, 3 ...	pens/bundles are selected as determined by the current device, palette and bundled attributes

Description

Four pen pointers are identified with different types of plotting operations, and different parts of composite operations, to enable the user to specify a combination of pen usage. The pointers identified with specific plotting operations are indicated by numbers in square brackets within the subroutine specifications. By default, all the pointers are associated with pen number 1. SETPNS specifies alternative pens to be associated with the four pen pointers. IPEN*i* can have values –1, 0, 1, 2, 3, ... *etc.*

CALL SETPNS(I,I,I,I) is equivalent to CALL PEN(I).

By default, colour is the only line-drawing attribute associated with pens and the distinction between pens depends on the capabilities of the current device. BUNLPR specifies the attributes to be associated with pens when used for drawing lines to differentiate between pens even on monochrome devices.

Default

CALL SETPNS(1,1,1,1) restores the default.

See also

BUNLPR, PEN, SHPEN, ONEPEN, PENRGB, PENHLS, PENRST and WFPNS.

SUBROUTINE SFEQX (XSTART, XSTEP)

Name

SFEQX – to specify the equally-spaced x values to be associated with gridded 3-D data.

Availability Section 2, released before version 2-5.

Arguments

XSTART	REAL expression	x value of first data column
XSTEP	REAL expression	x interval between data columns

Description

By default, data on an unspecified regular x grid relates to the current plotting scales:

Surfaces: Current plotting scales do not apply, so XSTART = 1.0 and XSTEP = 1.0 are used.

Contours: XSTART and XSTEP are allocated such that the data cover the current plotting scales; if no scales have been specified, centimetre scaling is used.

SFEQX specifies the x values corresponding to the data grid. SFEQX must be called before one of the RG* (data on a regular grid) or Y* (data on a grid of equally-spaced x values with specified y values) routines.

By default, after a call to SFEQX, an isometric x -axis displays the range of values from XSTART to $XSTART + XSTEP \times (NX - 1)$, where NX is specified as an argument to RGSURF/YSURF.

Default

Calling SFEQX with XSTEP=0.0 restores the default.

See also

SFEQY.

SUBROUTINE SFEQY (YSTART, YSTEP)

Name

SFEQY – to specify the equally-spaced y values to be associated with gridded 3-D data.

Availability Section 2, released before version 2-5.

Arguments

YSTART	REAL expression	y value of first data row
YSTEP	REAL expression	y interval between data rows

Description

By default, data on an unspecified regular y grid relates to the current plotting scales:

Surfaces: Current plotting scales do not apply, so YSTART = 1.0 and YSTEP = 1.0 are used.

Contours: YSTART and YSTEP are allocated such that the data cover the current plotting scales; if no scales have been specified, centimetre scaling is used.

SFEQY specifies the y values corresponding to the data grid. SFEQY must be called before any of the RG* (data on a regular grid) or X* (data on a grid of specified x values with equally-spaced y values) routines.

By default, after a call to SFEQY, an isometric y -axis displays the range of values from YSTART to YSTART + YSTEP \times (NY – 1), where NY is specified as an argument to RGSURF/XSURF.

Default

Calling SFEQY with YSTEP=0.0 restores the default.

See also

SFEQX.

SUBROUTINE SFEQZ (ZSTART, ZSTEP)**Name**

SFEQZ – to specify the equal spacing of contours.

Availability Section 2, released before version 2-5.

Arguments

ZSTART	REAL expression	Offset value for contour levels
ZSTEP	REAL expression	Interval between contour levels

Description

By default, subroutines which draw a set of equally-spaced contour curves or a set of shaded contour regions, allocate an offset value (ZSTART=0.0) and an interval to produce between 5 and 10 contour levels at suitable values. SFEQZ specifies an alternative offset value and interval for contour levels on both surface pictures and contour maps.

After SFEQZ has been called, sets of equally-spaced contour curves are drawn at all levels $ZSTART + N * ZSTEP$ (n , a +ve or –ve integer) lying within the z plotting range. SFEQZD overrides SFEQZ and *vice versa*.

If ZSTEP is less than $1.0E-4 \times$ contour range, the default interval is used instead and, at diagnostic level 2, a diagnostic message is issued (see below).

SFEQZ also affects the interval between the values represented on a map key (see MPK7H and MPK7V).

Diagnostics

(Too many contours: default used)²

Default

CALL SFEQZ(0.0,0.0) restores the default.

See also

ISTYPE, MPK7H, MPK7V, SFLIMS, SFEQZD, SFZSCL and SQZVAL.

SUBROUTINE SFEQZD (NSTEPS, DELTA)**Name**

SFEQZD – to specify the equal spacing of contours for discrete data.

Availability Section plus, released version 2-11.

Arguments

NSTEPS	INTEGER expression	Number of contour intervals
DELTA	REAL expression	Minimum interval between discrete data values

Description

By default, subroutines which draw a set of equally-spaced contour curves or a set of shaded contour regions, allocate an offset value and interval to produce between 5 and 10 contour levels at suitable values. SFEQZD specifies the number of contours and the interval between discrete data values, for equally-spaced contour levels on both surface pictures and contour maps.

After SFEQZD has been called, the z plotting range is divided into NSTEPS equal intervals, allowing a margin of $\text{DELTA} \times 0.5$ at each end of the range to accommodate discrete data values correctly. No attempt is made to ensure that the contour levels occur at ‘simple’ numbers.

SFEQZ overrides SFEQZD and *vice versa*.

If DELTA is less than $1.0E-4 \times$ contour range, the default interval is used instead and, at diagnostic level 2, a diagnostic message is issued (see below).

SFEQZD also affects the interval between the values represented on a map key (see MPK7H and MPK7V) and key labels are centred on samples rather than positioned between them.

Diagnostics

(Too many contours: default used)¹

Default

CALL SFEQZD(0,DELTA) restores the default.

See also

ISTYPE, MPK7H, MPK7V, SFLIMS, SFEQZ, SFZSCL and SQZVAL.

SUBROUTINE SFLAB**Name**

SFLAB – to annotate the current 3-D picture with the range of values displayed.

Availability Section 2, released before version 2-5.

Arguments

None.

Description

SFLAB draws [2] a message indicating the z plotting range on a surface picture or contour map. For example,

```
Z:-2 TO 2
```

If equally-spaced contours are included, the interval between them is also given. For example,

```
Z:-2 TO 2 CONTOUR INTERVAL=0.5
```

The message is drawn at the 'B'ottom, 'L'eft of the picture.

Diagnostics

(Surface label inappropriate)²

See also

QSFLAB.

SUBROUTINE SFLIMS (Z1, Z2)

Name

SFLIMS – to specify the z plotting range.

Availability Section 2, released before version 2-5.

Arguments

Z1	REAL expression z value at start of z range
Z2	REAL expression z value at end of z range

Description

By default, the full range of the data supplied is plotted on surface pictures and contour maps. SFLIMS specifies an alternative range. Any parts of the supplied data which lie outside the range Z1 to Z2 are omitted:

Surface pictures: Holes are left in the surface where data values lie above or below the specified limits.

The scale of the picture is not altered to make the cut-off picture fill the space available (see SFZSCL).

Contour maps: Blank areas are left in the contour map where data values lie above or below the specified limits. The default contour interval is chosen to suit the reduced data range.

SFLIMS also affects the range of values represented on a map key (see MPK7H and MPK7V): the data range of the key is the intersection of the data range (specified in the call to MPK7H or MPK7V) with that specified using SFLIMS and/or SFZSCL.

Default

Calling SFLIMS with Z1=Z2 restores the default.

See also

MPK7H, MPK7V and SFZSCL.

SUBROUTINE SFMESH (MX, MY)

Name

SFMESH – to specify a mesh to be used for constructing contours and surfaces.

Availability Section plus, released version 2-11.

Arguments

MX	INTEGER expression	Number of x mesh lines used
MY	INTEGER expression	Number of y mesh lines used

Description

In order to get smoother edges to shaded contour regions, SIMPLEPLOT needs a finer grid; SFMESH specifies this grid. By default, the amount of detail in contour curves depends on the data structure:

Surfaces: A grid is used which depends on the x - y ranges of the data, possibly modified by a call of ISMESH. SFMESH specifies a grid to be used, overriding the default for contour curves and surfaces.

Contour pictures: SFMESH can be used to change the smoothness of curves by altering the concentration of interpolated points from which curves are constructed; if the mesh used differs from the data configuration, contouring may be slower.

For surfaces, SFMESH nominates a grid which is independent of the x - y ranges of the data. Please note that the x -range is divided into MX equal steps and the y -range is divided into MY equal steps; on surfaces these x steps and y steps are plotted with equal size in the picture.

ISMESH has no effect while SFMESH is active.

Default

Calling SFMESH with MX and/or MY less than 2 restores the default.

See also

ISMESH and CTCURV.

SUBROUTINE SFZSCL (ZSTART, ZSTOP)**Name**

SFZSCL – to specify the z scale of surface pictures and contour maps independently of the data set.

Availability Section 2, released version 2-12.

Arguments

ZSTART	REAL expression	Start of z scale
ZSTOP	REAL expression	End of z scale

Description

By default, surface pictures are drawn with an increasing z scale covering the same range as the data. SFZSCL specifies an alternative z scale such that ZSTART lies at the bottom of the picture and ZSTOP at the top. This may be useful when comparable scales are needed for different pictures.

If the user-specified scale can not accommodate the entire surface, part of the picture cannot be drawn; this contributes to the number of incomplete picture tasks and a diagnostic is issued at the end of the picture.

SFZSCL also affects the range of values represented on a map key (see MPK7H and MPK7V): the data range of the key is the intersection of the data range (specified in the call to MPK7H or MPK7V) with that specified using SFZSCL and/or SFLIMS; however, if the data range of the key is null, the scale specified by SFZSCL is used instead.

Default

Calling SFZSCL with ZSTART=ZSTOP restores the default.

See also

FNAREA, MPK7H, MPK7V and SFLIMS.

SUBROUTINE SGEXPL (IVAL, ISEG)**Name**

SGEXPL – to specify the amount by which one pie chart segment is to be exploded.

Availability Section 4, released before version 2-5.

Arguments

IVAL	INTEGER expression	Percentage explosion (0–50)
ISEG	INTEGER expression	Segment number (1– <i>maximum</i>)

Description

By default, the displacement of all segments is zero. SGEXPL specifies the amount (as percentage of radius) by which segment number ISEG is to be displaced from the centre of the pie, along the radius bisecting its angle. SGEXPL must be called before PIECHT.

The number of segments of a pie chart is unlimited but the limit on the maximum number of segments which can be omitted or exploded is 32.

The effect of SGEXPL can be overridden by PIEEXPL and *vice versa*.

Default

CALL SGEXPL(0, ISEG) restores the default.

See also

PIECHT and PIEEXPL.

SUBROUTINE SGOMIT (TORF, ISEG)**Name**

SGOMIT – to specify whether a pie chart segment is to be omitted.

Availability Section 4, released before version 2-5.

Arguments

TORF	LOGICAL expression	Whether segment is to be omitted
ISEG	INTEGER expression	Segment number (<i>1–maximum</i>)

Description

By default, all data values are represented by a segment in the pie chart and every segment is displayed. SGOMIT specifies whether or not the ISEGth segment of the pie is to be omitted from the picture. All segments are included in the calculation of pie chart segments. SGOMIT must be called before PIECHT.

The number of segments of a pie chart is unlimited but the limit on the maximum number of segments which can be omitted or exploded is 32.

The effect of SGOMIT can be overridden by PIOMIT and *vice versa*.

Default

CALL SGOMIT(.FALSE., ISEG) restores the default.

See also

PIECHT and PIOMIT.

SUBROUTINE SHANGS (IDEG1, IDEG2, IDEG3, IDEG4)**Name**

SHANGS – to specify the angles used in software shading patterns.

Availability Section 4, released before version 2-5.

Arguments

IDEG1, INTEGER expressions Angles in degrees
 IDEG2,
 IDEG3,
 IDEG4

Description

Software shading patterns consist of sets of equally-spaced parallel lines of one colour. The sequence for a monochrome device is as follows:

- Pattern -1 is empty but is outlined using the pen selected by SHPEN, or currently selected for drawing lines (pen pointer 1).
- Pattern 0 fills the area with pen 0 (background). If the device cannot draw in background, pattern 0 is equivalent to pattern -1 .
- Pattern 1 fills the area with pen 1 and is not affected by settings for the angle or separation of hatching lines (SHDESC or SHGAP).
- Patterns 2–5 use the 4 shading angles with a small line separation; patterns 6–9 use the 4 shading angles with a larger line separation, *etc.*

If very large pattern numbers are chosen, very large line separation is used.

By default, four angles are used in shading patterns, 0° , 90° , 45° and 135° . SHANGS specifies alternative angles. The number of shading angles is the number of different angles set by SHANGS – for example, the number of shading angles is reduced to three if two of the arguments, IDEG n , are equal. Changing the number of shading angles also changes the relationship between shading patterns and pattern numbers – the use of fewer angles means that the cycle of patterns is repeated sooner.

Default

CALL SHANGS(0,90,45,135) restores the default.

See also

SHCOLS, SHGAP and SHDESC.

SUBROUTINE SHCOLS (NCOLS)**Name**

SHCOLS – to specify a restricted number of colours used for shading patterns.

Availability Section 4, released before version 2-5.

Argument

NCOLS **INTEGER** expression Number of colours

Description

By default, the number of colours used for shading patterns is set to the maximum number of colours available on the device. **SHCOLS** specifies an alternative number of colours to be used for shading. **SHCOLS** affects hardware and software shading patterns. **SHCOLS** must be called before a shading operation.

Changing the number of shading colours also changes the relationship between shading patterns and pattern numbers – the use of fewer colours means that the cycle of patterns is repeated sooner.

Default

CALL SHCOLS(0) restores the default. Note that this also resets **SHPEN**.

See also

SHANGS, **SHDESC**, **SHGAP** and **SHPEN**.

SUBROUTINE SHDEA2 (X1, DX, DARR1, DARR2, NARR, ISHADE)**Name**

SHDEA2 – to shade between 2 curves defined by values held in 2 arrays.

Availability Section 4, released version 2-12.

Arguments

X1	REAL expression	Value of independent variable for plotting DARR1(1) and DARR2(1)
DX	REAL expression	Independent variable interval between function values
DARR1	REAL array	Function values for first curve
DARR2	REAL array	Function values for second curve
NARR	INTEGER expression	Number of values in each array
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number ISHADE, SHDEA2 shades the area between two curves:

```
(X1,DARR1(1)), (X1+DX,DARR1(2)),...
                                (X1+(NARR-1)*DX,DARR1(NARR))
(X1,DARR2(1)), (X1+DX,DARR2(2)),...
                                (X1+(NARR-1)*DX,DARR2(NARR))
```

The type of curve depends on CVTYPE but the area is enclosed by joining the first points of each curve together by a straight line, and the last points of each curve. Whether the boundary of the area is drawn depends on SHEDGE.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

CLIPLV, CVTYPE, RIDDLE, SHDEC2, SHDEAR and SHEDGE.

SUBROUTINE SHDEAR (X1, DX, DARR, NARR, ISHADE)**Name**

SHDEAR – to draw a curve from an array of values, and shade under it.

Availability Section 4, released version 2-11.

Arguments

X1	REAL expression	Value of independent variable for plotting DARR(1)
DX	REAL expression	Independent variable interval between function values
DARR	REAL array	Function values for plotting
NARR	INTEGER expression	Number of points
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number ISHADE, SHDEAR shades the area enclosed by the curve which connects the following points:

(X1,DARR(1)), (X1+DX,DARR(2)),...
(X1+(NARR-1)*DX,DARR(NARR))

These points represent a set of values from a single array where the array elements hold function values $y_i = f(x_i)$ and $x_i = x_1 + (i - 1)dx$.

If the curve is not closed, the area shaded depends on SHTYPE; the type of curve depends on CVTYPE and whether the curve itself is drawn depends on SHEDGE.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

BRKNAR, CLIPLV, CVTYPE, RIDDLE, SHDEA2, SHDECV, SHEDGE and SHTYPE.

SUBROUTINE SHDEBX (X1, Y1, X2, Y2, ISHADE)**Name**

SHDEBX – to draw a shaded box.


Availability Section 4, released version 2-8.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of opposite corners of the box, specified in units of the plotting scales
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number **ISHADE**, **SHDEBX** shades the box extending from x_1 to x_2 by y_1 to y_2 . If $x_1=x_2$ or $y_1=y_2$, then nothing is drawn. Whether a boundary is drawn depends on **SHEDGE**. The points (x_1, y_1) and (x_2, y_2) are specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, **KXXYY**.



By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using **CLIPLV**.

Diagnostics

$(**x_1, y_1, x_2, y_2**)^2$
 (Null box, nothing drawn)²

See also

BRKNBX, CLIPLV and SHEDGE.

SUBROUTINE SHDEC2 (XARR1, YARR1, NARR1, XARR2, YARR2, NARR2, ISHADE)**Name**

SHDEC2 – to shade the area between 2 curves specified by sets of coordinates.

Availability Section 4, released version 2-5.

Arguments

XARR1, YARR1	REAL arrays	Coordinates of first curve
NARR1	INTEGER expression	Number of points in first curve
XARR2, YARR2	REAL arrays	Coordinates of second curve
NARR2	INTEGER expression	Number of points in second curve
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number ISHADE, SHDEC2 shades the area between two curves:

$(XARR1(1), YARR1(1)), \dots, (XARR1(NARR1), YARR1(NARR1))$

$(XARR2(1), YARR2(1)), \dots, (XARR2(NARR2), YARR2(NARR2))$

The type of curve depends on CVTYPE but the area is enclosed by joining the first points of each curve together by a straight line, and the last points of each curve. Whether the boundary of the area is drawn depends on SHEDGE.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

CLIPLV, CVTYPE, RIDDLE, SHDEA2, SHDECV and SHEDGE.

SUBROUTINE SHDECL (XCENT, YCENT, RADIUS, ISHADE)**Name**

SHDECL – to draw a circular function with specified centre and radius, and to shade inside it.

Availability Section 4, released before version 2-5.

Arguments

XCENT,	REAL expressions	Coordinates of the centre of the
YCENT		circle in units of the plotting scale
RADIUS	REAL expression	Circle radius in plotting scale units
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number **ISHADE**, **SHDECL** shades the circle (or the part of the circle which lies within the range of the plotting scales) centred at point (x_{cent}, y_{cent}) , with radius **RADIUS**. The resulting shape is only geometrically circular when both scales are equal and linear. Whether a boundary is drawn depends on **SHEDGE**.

The centre point and the radius are both specified in units of the current plotting scales (*ie.* user coordinates); device or page coordinates can be converted to user coordinates using the conversion subroutine, **KXYXY**.

By default, all drawing is restricted by the limits of the picture scales; if it exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using **CLIPLV**.

Diagnostics

(Circle exceeds scales)²

See also

BRKNCL, CLIPLV, EQSCAL, KXYXY and SHEDGE.

SUBROUTINE SHDECV (XARR, YARR, NARR, ISHADE)**Name**

SHDECV – to draw a curve from a set of coordinates, and shade under it.

Availability Section 4, released before version 2-5.

Arguments

XARR, YARR	REAL arrays	Coordinates of points in units of the plotting scales
NARR	INTEGER expression	Number of points
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number ISHADE, SHDECV shades the area enclosed by the curve corresponding to the following points:

(XARR(1), YARR(1)), (XARR(2), YARR(2)), ...
(XARR(NARR), YARR(NARR))

A closed curve can be obtained by using data in which XARR(NARR)=XARR(1) and YARR(NARR)=YARR(1). If the curve is not closed, the area shaded depends on SHTYPE. The type of curve drawn depends on CVTYPE and whether the curve itself is drawn depends on SHEDGE.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Data curve exceeds scales)²

See also

BRKNVCV, CLIPLV, CVTYPE, MARKCV, RIDDLE, SHEDGE and SHTYPE.

SUBROUTINE SHDEFN (FUNX, ISHADE)**Name**

SHDEFN – to draw a curve of a user-defined function, $y = f(x)$, and shade under it.

Availability Section 4, released before version 2-5.

Arguments

FUNX	function name	REAL function with one REAL argument, also declared in an EXTERNAL statement
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number ISHADE, SHDEFN shades the area enclosed by the curve of a user-defined function, FUNX, and the axes or edge of the picture. Whether a boundary is drawn depends on SHEDGE.

With Cartesian coordinates, the specified function, FUNX, must calculate y given x , and with polar coordinates FUNX must calculate r given θ . The intervals of the independent variable over which SHDEFN evaluates the function, vary with the curvature of the curve.

Care must be taken in the programming of the FUNX to ensure that it is continuous and cannot fail for any arguments within the plotting range. Discontinuities may cause SIMPLEPLOT to loop indefinitely.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using CLIPLV.

Diagnostics

(Function curve exceeds scales)²

See also

BRKNFN, CLIPLV, FNRNGE, POLY, RIDDLE and SHEDGE.

SUBROUTINE SHDEK7 (ISHADE, CAP)
SUBROUTINE SHDEKY (ISHADE, CAP, NCAP)

Name

SHDEK7 – to draw an annotated sample of a shading pattern in a key.

Availability Section 4, released before version 2-5.

Arguments

ISHADE	INTEGER expression	Shading pattern number
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

SHDEK7/SHDEKY inserts a key to a shading pattern in the next empty space in the current key or caption area (defined by DEFKEY/DEFCAP or selected by RESNXT).

A rectangular sample of shading pattern ISHADE is drawn on the left of the entry; the caption, CAP, is drawn [2] alongside the sample. Whether a boundary is drawn around the sample shading pattern depends on SHEDGE.

REAL and INTEGER values can be converted to text strings using the conversion subroutines, KREAL and KNUMB respectively.

Diagnostics

(Caption truncated)²
 (Key/caption area full)²
 (No active key/caption area)²

See also

ADDJST, BLNKKY, DEFKEY, FILLK7, MPK7H, MPK7V, SHEDGE, SHKEYS, SHPATT, SHSET and SQSHAD.

SUBROUTINE SHDEPR (SUBR, T1, T2, ISHADE)**Name**

SHDEPR – to draw the user-defined parametric function, and shade inside it.

Availability Section 4, released version 2-9.

Arguments

SUBR	subroutine name	Subroutine with three REAL arguments, also declared in an EXTERNAL statement
T1, T2	REAL expressions	Values of the function parameter between which curve is to be drawn
ISHADE	INTEGER expression	Shading pattern number

Description

Using shading pattern number **ISHADE**, **SHDEPR** shades the area enclosed by the curve of a user-defined parametric function. If the curve is not closed, a closed area is formed by joining the first and last points with a straight line; whether a boundary is drawn depends on **SHEDGE**.

The parametric function is specified in subroutine **SUBR**; **SUBR** must have three **REAL** arguments: **T**, the value of the function argument, and **VARX** and **VARY**, to receive coordinates corresponding to **T**. **SUBR** is called by **SHDEPR** with values of **T** ranging from **T1** to **T2**.

By default, all drawing is restricted by the limits of the picture scales; if coordinates exceed these limits, plotting is clipped to the picture limits and every such occurrence contributes to the number of incomplete picture tasks. An alternative clipping strategy can be specified using **CLIPLV**.

Diagnostics

(Parametric function exceeds scales)²

See also

BRKNPR, **CLIPLV**, **RIDDLE** and **SHEDGE**.

SUBROUTINE SHDESC (IDEG1, IDEG2, IDEG3, IDEG4, NCOLS, GAP)**Name**

SHDESC – to specify all characteristics of shading patterns.

Availability Section 4, released before version 2-5.

Arguments

IDEG1, IDEG2, IDEG3, IDEG4	INTEGER expressions	Angles in degrees
NCOLS	INTEGER expression	Number of colours
GAP	REAL expression	Minimum separation between shading lines (in cms)

Description

Each software shading pattern consists of a set of equally-spaced parallel lines of one colour. On a monochrome device the sequence is as follows: pattern –1 is empty but is outlined using the pen selected by SHPEN, or pen pointer 1; patterns 0 and 1 are as near to solid as the device permits – 0 uses background if the device permits, otherwise it is equivalent to pattern –1; patterns 2–5 use the 4 shading angles with a small line separation; patterns 6–9 use a larger line separation, *etc.* If very large pattern numbers are chosen, very large line separation is used.

By default, IDEG1 is equivalent to 0, IDEG2 to 90, IDEG3 to 45, IDEG4 to 135, NCOLS to the maximum number of colours available on the device, and GAP to the thickness of the lines drawn on the device.

SHDESC specifies alternatives for all these shading characteristics – the number of shading angles used is the number of different angles specified; the number of shading colours can be any positive value and the minimum separation between shading lines can be any value greater than or equal to the standard thickness of lines on the device. SHDESC must be called before a shading operation.

NCOLS also affects hardware shading patterns but the angles and line separation only affect software patterns. If fewer colours or angles are selected, the cycle of patterns is repeated sooner.

Default

CALL SHDESC(0,90,45,135,0,0.0) restores the default

See also

SHANGS, SHCOLS and SHGAP.

SUBROUTINE SHEDGE (ITYPE)

Name

SHEDGE – to specify whether to draw a boundary around a shaded area.

Availability Section plus, released version 2-11.

Argument

ITYPE INTEGER expression Boundary option

ITYPE *Shading edge*

–1	Default mode, determined by SIMPLEPLOT
0	No edge drawn
1	Edge drawn

Description

By default, SIMPLEPLOT draws some shaded areas with a boundary and some without. For example, pie charts, bar charts and two-dimensional shaded curves are drawn with a boundary, but shaded areas on a contour map are drawn without a boundary. SHEDGE overrides this default behaviour.

The boundary of a shaded area is drawn with the same pen as the shading pattern itself except for pattern –1; pattern –1 is outlined using the pen selected by SHPEN or (if none selected) the pen currently selected for drawing lines, [1]. The drawing of this boundary line is not affected by bundled line-drawing attributes.

Default

CALL SHEDGE(–1) restores the default.

See also

MPK7H, MPK7V, SHSTRT, SHSTOP, SHDE*, *SHAD and *SHDS.

SUBROUTINE SHGAP (GAP)**Name**

SHGAP – to specify the spacing of software shading lines.

Availability Section 4, released before version 2-5.

Argument

GAP	REAL expression	Minimum separation between lines (in cms)
-----	-----------------	----------------------------------------------

Description

Software shading patterns consist of sets of equally-spaced parallel lines of one colour. The sequence for a monochrome device is as follows:

- Pattern –1 is empty but is outlined using the pen selected by SHPEN, or the pen currently selected for drawing lines (pen pointer 1).
- Pattern 0 is as near to solid as the device permits, using pen 0. If the device cannot draw in background, pattern 0 is equivalent to pattern –1.
- Pattern 1 fills the area with pen 1 and is not affected by settings for the angle or separation of hatching lines.
- Patterns 2–5 use the 4 shading angles with a small line separation.
- Patterns 6–9 use the 4 shading angles with a larger line separation.
- *etc.*

If very large pattern numbers are chosen, very large line separation is used.

By default, the minimum separation between shading lines is set to the thickness of lines drawn on the device. SHGAP specifies the minimum separation between lines as any value greater than or equal to the standard thickness of lines on the device. Changing the separation between shading lines also changes the relationship between shading patterns and pattern numbers.

Default

CALL SHGAP(0.0) restores the default.

See also

SHANGS, SHCOLS and SHDESC.

SUBROUTINE SHKEYS (VCHAR, HCHAR, LABARR, NARR, CAP)**Name**

SHKEYS – to draw a complete key to a sequence of shading patterns.

Availability Section 4, released version 2-11.

Arguments

VCHAR	CHARACTER*1	Vertical position of area
HCHAR	CHARACTER*1	Horizontal position of area
LABARR	STRING array	Set of captions
NARR	INTEGER expression	Number of labels in LABARR
CAP	STRING expression	Header caption for key

Description

SHKEYS constructs a complete key to the first NARR shading patterns of the currently defined sequence (see SQSHAD and SHPATT).

The key is positioned on the SIMPLEPLOT page in the same way as other keys; VCHAR and HCHAR are single characters representing the initial letters of vertical and horizontal positions.

CAP provides a heading which, by default, is centred at the top of the key (see ADDJST). A box is drawn [1] around the key unless cancelled by BOXKY.

The key is associated only with the current picture but area is masked to prevent overdrawing. To avoid the key being overdrawn by other plotting (*eg.* if the key is positioned ‘inside’ the picture), it is best to call SHKEYS after NEWPIC but before the main picture is drawn (this may be slower because SIMPLEPLOT must check for overlapping).

The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

(Key/caption height reduced)²
 (Key/caption width reduced)²
 (Maximum no. of keys/captions reached)²
 (No room for key/caption area)²

See also

ADDJST, BOXKY, DEFKEY, DEFKYW, DEFPOS, MPK7H, MPK7V, SHDEK7, SHPATT, SHSET and SQSHAD.

SUBROUTINE SHPATT (ISHADE, IPOS)

Name

SHPATT – to specify one of a sequence of shading patterns.

Availability Section 4, released version 2-5.

Arguments

ISHADE	INTEGER expression	Pattern number
IPOS	INTEGER expression	Indicating which of the sequence is to be set (1–32)

ISHADE	Shading pattern
–1	an empty area
0	solid fill with background colour
1, 2, 3...	hardware/software patterns

Description

By default, subroutines which shade a sequence of areas to distinguish them from each other use the shading patterns in numerical order 1, 2, 3 *etc.* SHPATT specifies an alternative pattern, ISHADE, to be associated with the IPOS_{th} shaded area. SHPATT must be called before the subroutine which performs the shading.

ISHADE can have values –1, 0, 1, 2, 3, ... *etc.*

If the boundary of a shaded area is to be drawn (see SHEDGE), it is drawn with the same pen as the shading pattern itself except for pattern –1; pattern –1 is outlined using the pen selected by SHPEN or (if none selected) the pen currently selected for drawing lines, [1].

The number of shading patterns is unlimited but the limit on the *maximum* number of patterns which can be specified as a sequence is 32.

Default

CALL SHPATT(*n*,*n*) restores the default for each position, *n*.

See also

SQSHAD, SHPEN and SHEDGE.

SUBROUTINE SHPEN (IPEN)

Name

SHPEN – to specify single colour shading patterns with the specified pen.

Availability Section 4, released version 2-7.

Argument

IPEN INTEGER expression Pen number

IPEN	<i>Pen usage</i>
–1	plotting is omitted on all devices
0	plotting is done in background colour; on some devices this produces the effect of rubbing out but on others (<i>eg.</i> pen plotters) plotting is omitted
1, 2, 3 ...	pens/colours are selected as determined by the device driver

Description

By default, the number of colours used for shading patterns is set to the maximum number of colours available on the device. SHPEN requests monochromatic shading with pen number, IPEN. SHPEN must be called before a shading operation.

IPEN can have values –1, 0, 1, 2, 3, ... *etc.*

Please note that changing the number of shading colours changes the relationship between shading patterns and pattern numbers.

Software shading is not affected by bundled line-drawing attributes.

Default

CALL SHCOLS(0) restores the default.

See also

SHCOLS, SHSET, PEN and SETPNS.

SUBROUTINE SHSET (ISET)**Name**

SHSET – to specify an alternative source of area-fill patterns for polygon shading.

Availability Section 4, released version 2-8.

Argument

ISET INTEGER expression Code number for area fill source

ISET Polygon area-fill source

≤ -1 Alternative hardware/firmware sets (if available)

0 Hardware/firmware area fill (if available)

1 Device independent software shading

Description

For efficient operation and clarity, SIMPLEPLOT is set up to shade areas using area fill from device hardware or firmware wherever suitable. SHSET selects an alternative source of area fill patterns.

On devices which can use hardware area fill, the hardware patterns may be used to take the place of software shading. When no more hardware patterns are available, SIMPLEPLOT returns to the software pattern that would have occurred in this position.

Default

CALL SHSET(0) restores the default.

See also

CHSET, FFSET, LINSET and MKSET.

SUBROUTINE SHSTOP**Name**

SHSTOP – to terminate the description of a user-defined shaded shape.

Availability Section plus, released version 2-11.

Arguments

None.

Description

SHSTOP terminates a user-defined shape for shading started by SHSTRT. The graphics output of the shape is not started until the drawing has been terminated.

If the shape does not consist entirely of closed areas, nothing is drawn and a diagnostic is issued.

Diagnostics

(Unclosed shaded area)¹

See also

SHSTRT.

SUBROUTINE SHSTRT (ISHADE)**Name**

SHSTRT – to start a user-defined shaded shape.

Availability Section plus, released version 2-11.

Argument

ISHADE INTEGER expression Shading pattern number

Description

A user-defined shape which can be drawn using any of the DRAW* or BRKN* subroutines, JOINPT and BREAK is shaded if the drawing of the shape is preceded by a call of SHSTRT and followed by a call of SHSTOP. ISHADE selects the shading pattern.

The drawing of the shape for shading should normally be terminated by SHSTOP, but a call of any SIMPLEPLOT subroutine other than those allowed for drawing the shape, causes the shape to be abandoned and a diagnostic is issued.

The shape can be made up from one or more closed areas, and the boundaries traced in any order; if there are any gaps in the boundaries of the shape, the unclosed curves are omitted and a diagnostic is issued.

Whether the boundary is drawn depends on SHEDGE.

Diagnostics

(Unclosed shaded area)¹

(USER SHADING ABANDONED)¹

See also

SHSTOP and SHEDGE.

SUBROUTINE SHTYPE (ITYPE)

Name

SHTYPE – to specify the shading boundary used for unclosed curves.

Availability Section 4, released before version 2-5.

Argument

ITYPE INTEGER expression Mode of shading

<i>ITYPE Shading area for unclosed curves</i>	
0	Area contained by joining last point of curve to first with a straight line
1	Area between curve and horizontal axis or base of graph
2	Area between curve and vertical axis or left hand edge of graph

Description

By default, when SHDECV or SHDEAR defines a curve which is not closed, shading applies to the area between the curve and the x -axis or bottom horizontal boundary when no axis exists. Alternative areas can be chosen by calling SHTYPE.

SHTYPE does not apply to polar charts nor to functions drawn by SHDEFN or SHDEPR. The curves drawn by SHDEA2 and SHDEC2 are always closed and therefore unaffected by SHTYPE.

Default

CALL SHTYPE(1) restores the default.

See also

SHDECV and SHDEAR.

SUBROUTINE SHUNIF (TORF)**Name**

SHUNIF – to specify whether software shading lines are to be drawn in only one direction.

Availability Section 4, released before version 2-5.

Argument

TORF	LOGICAL expression	Whether uniform shading is required
-------------	---------------------------	-------------------------------------

Description

By default, software shading lines are drawn in alternating directions. On mechanical devices, it is faster to draw shading lines in alternate directions than to draw them all one way; but on pen plotters, the shaded area may look more uniform if the lines are all drawn the same way. After a call of **SHUNIF(.TRUE.)**, all software generated shading lines are drawn in one direction.

Default

CALL SHUNIF(.FALSE.) restores the default.

See also

SHDESC.

SUBROUTINE SQBRKN (IARR, NARR)**Name**

SQBRKN – to specify a sequence of broken line patterns.

Availability Section plus, released version 2-12.

Arguments

IARR	INTEGER array	Pattern numbers for each contour line
NARR	INTEGER expression	Number of elements in IARR (1–32)

Description

By default, subroutines which draw a sequence of contour lines use a single broken line pattern (which can be specified by CTBRKN) for every line. SQBRKN specifies a sequence of broken line patterns.

The number of software line patterns is unlimited but patterns beyond the usual range, $-6 \dots 6$, have longer patterns and may not be easily distinguishable from one another. The number of hardware broken line patterns is also unlimited in theory but, in practice, there are fewer than are available in software. Whether hardware or software patterns are used, there is a limit on the *maximum* number of patterns which can be specified as a sequence – only 32 patterns can be defined as a sequence.

If line style has been requested as a bundled attribute, the broken line patterns specified using SQBRKN override the line style of the bundles (specified by PEN, SETPNS or SQPEN) unless

$IARR(i) = -999$ which indicates that all the current bundled line-drawing attributes are to be used.

When the sequence is exhausted, the line pattern specified by CTBRKN is used.

Default

CALL SQBRKN(IARR,0) restores the default.

See also

BUNLPR, CTBRKN, LINSET and SQ*.

SUBROUTINE SQPEN (IARR, NARR)

Name

SQPEN – to specify a sequence of pens/bundles.

Availability Section plus, released version 2-12.

Arguments

IARR	INTEGER array	Pen numbers for each contour
NARR	INTEGER expression	Number of elements in IARR (1–32)

IARR(<i>i</i>) <i>Pen usage</i>	
–1	plotting is omitted on all devices
0	plotting is done in background colour; on some devices this produces the effect of rubbing out but on others (<i>eg.</i> pen plotters) plotting is omitted
1, 2, 3 ...	pens/bundles are selected as determined by the current device, palette (see PENHLS and PENRGB) and the current bundled attributes (see BUNLPR)

Description

By default, subroutines which draw a sequence of contour lines, use a single pen (specified by PEN) or use the pens assigned by pen pointers:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

SQPEN specifies an alternative sequence of pens. SQPEN also affects surface pictures which are drawn with crosshatching or contour lines (see ISTYPE, *CNTS). A different pen is used for each contour range which the crosshatched lines cross and at the edge of a surface on which contours are drawn. IARR(*i*) can have values –1, 0, 1, 2, 3, ... *etc.*

The number of pens is unlimited but the maximum number of pens which can be specified as a sequence is 32. When the sequence is exhausted, the pen pointed to by pen pointer [1] is used (see SETPNS and PEN).

Default

CALL SQPEN(IARR,0) restores the default.

See also

BUNLPR, PEN, PENHLS, PENRGB, SETPNS and SQ*.

SUBROUTINE SQSHAD (IARR, NARR)**Name**

SQSHAD – to specify a sequence of shading patterns.

Availability Section 4, released version 2-12.

Arguments

IARR	INTEGER array	Pattern numbers for each shaded area
NARR	INTEGER expression	Number of elements in IARR (1–32)
<hr/>		
IARR(<i>i</i>)	<i>Shading pattern</i>	
–1	an empty area	
0	solid fill with background colour	
1, 2, 3 ...	hardware/software patterns	

Description

By default, subroutines which shade a sequence of areas to distinguish them from each other, use the shading patterns in numerical order 1, 2, 3 *etc.* SQSHAD specifies an alternative sequence of pattern numbers.

SQSHAD must be called before the subroutine which performs the shading.

IARR can have values –1, 0, 1, 2, 3, ... *etc.*

If the boundary of a shaded area is to be drawn (see SHEDGE), it is drawn with the same pen as the shading pattern itself except for pattern –1; pattern –1 is outlined using the pen selected by SHPEN or (if none selected) the pen currently selected for drawing lines, [1].

The number of shading patterns is unlimited but the limit on the maximum number of patterns which can be specified as a sequence is 32.

SQSHAD also affects the shading pattern samples represented on map keys (see MPK7H and MPK7V) and shaded keys (see SHKEYS).

Default

CALL SQSHAD(IARR,0) restores the default.

See also

MPK7H, MPK7V, SHEDGE, SHKEYS, SHPEN and SQ*.

SUBROUTINE SQZLAB (LABARR, NARR)**Name**

SQZLAB – to specify a sequence of contour labels.

Availability Section plus, released version 2-12.

Arguments

LABARR	STRING array	Contour labels
NARR	INTEGER expression	Number of elements in LABARR (1–32)

Description

By default, contour maps are not labelled but CTLABS or CTNUMB can be called to specify that automatically generated numeric labels are to be drawn. SQZLAB specifies an alternative set of textual labels to be used. SQZLAB also determines the labels used on a map key (see MPK7H and MPK7V).

The number of contour labels is unlimited but the limit on the maximum number of labels which can be specified as a sequence is 32. Also, the length of individual labels is restricted to a maximum of 20 characters; longer labels are truncated.

When the sequence is exhausted, labelling ceases.

Default

CALL SQZLAB(LABARR,0) restores the default.

See also

CTLABS, CTNUMB, MPK7H, MPK7V, SQZVAL, *CNTS and *SHDS.

SUBROUTINE SQZVAL (DARR, NARR)**Name**

SQZVAL – to specify a sequence of contour levels.

Availability Section plus, released version 2-12.

Arguments

DARR	REAL array	Contour levels
NARR	INTEGER expression	Number of elements in DARR (1–32)

Description

By default, a set of contour curves is drawn with a regular contour interval (see SFEQZ and SFEQZD); SQZVAL specifies an alternative set of values at which to draw contours. The number of contour levels is unlimited but the limit on the maximum number of values which can be specified as a sequence is 32.

SQZVAL also affects the values represented on a map key (see MPK7H and MPK7V).

SQZVAL overrides the effects of both SFEQZ and SFEQZD.

Diagnostics

(DATA GRID NOT MONOTONIC)¹

Default

CALL SQZVAL(DARR,0) restores the default.

See also

MPK7H, MPK7V, SFEQZ, SFEQZD, SQZLAB, *CNTS and *SHDS.

SUBROUTINE STRCHS (CHESC, CHOPEN, CHCLOS)**Name**

STRCHS – to specify the three special characters to be used in escape sequences.

Availability Section plus, released version 2-11.

Arguments

CHESC	CHARACTER*1	Escape character
CHOPEN	CHARACTER*1	Opening bracket
CHCLOS	CHARACTER*1	Closing bracket

Description

By default, SIMPLEPLOT recognizes '!', '[' and ']' as the special characters used to identify embedded commands within text strings; STRCHS specifies alternative characters.

Alphanumeric characters may not be used as escape or bracketing characters; the same character can be used for both bracket characters, but the escape character must be different from both brackets.

STRCHS can be called at any time, regardless of whether STRLV has been called to enable recognition of these characters. If STRCHS is called with invalid arguments, the use of escape sequences is disabled until a valid call of STRCHS.

Default

CALL STRCHS('!', '[', ']') restores the default.

See also

QSTR7 and STRLV.

SUBROUTINE STRLV (ILEVEL)

Name

STRLV – to specify the level of interpretation of embedded commands in text strings.

Availability Section plus, released version 2-11.

Argument

ILEVEL INTEGER expression Level of interpretation

ILEVEL	Action
--------	--------

0	Disable interpretation (default)
---	----------------------------------

1	Enable interpretation of subcommands
---	--------------------------------------

Description

STRING arguments to SIMPLEPLOT subroutines which supply text to be drawn on pictures, can include embedded subcommands !N, !B, !H, !L, !U, !P, !F.

<i>Embedded subcommand</i>	<i>Action</i>
!N	new line
!B	backspace
!H[<i>text</i>]	superscript
!L[<i>text</i>]	subscript
!U[<i>text</i>]	underline
!P <i>n</i> [<i>text</i>]	colour/pen change
!F <i>n</i> [<i>text</i>]	font change

These subcommands use ordinary characters as escape sequences to distinguish them from the text to be drawn. STRLV sets the level of interpretation of these escapes sequences within text strings.

Default

CALL STRLV(0) restores the default.

See also

QSTR7 and STRCHS.

SUBROUTINE TEXTAR (RATIO)

Name

TEXTAR – to specify the aspect ratio of text characters.

Availability Section 4, released version 2-10.

Argument

RATIO REAL expression Width/height

Description

TEXTAR can be used to specify the height to width ratio of text characters. If hardware text is currently selected, TEXTAR only has effect if the following criteria are met:

- the current device is capable of adjusting the aspect ratio of text, and
- the device driver has been suitably modified.

TEXTAR affects all software text except the adjustable character sets (ISET=51 and 52).

By default, ‘Simple software’ characters (as selected by CHSET(1)) are constrained such that they are drawn using a whole number of device steps (or pixels) per step in order to achieve satisfactory shapes. If a non-default aspect ratio is specified, this constraint is removed and text may appear misshapen especially on low-resolution devices.

Default

Calling TEXTAR with $RATIO \leq 0$ restores the default.

See also

CHSET and TEXTSZ.

SUBROUTINE TEXTLF (FACTOR)**Name**

TEXTLF – to specify the vertical separation of lines of text.

Availability Section 1, released version 2-11.

Argument

FACTOR REAL expression Factor to multiply text height

Description

TEXTLF modifies the vertical spacing between successive lines of title, between entries in key and caption areas, and between multiple lines of text containing encoded linefeeds. **FACTOR** can be any REAL value greater than or equal to 1.0.

Default

CALL TEXTLF(1.2) restores the default or any call of TEXTLF with $\text{FACTOR} \leq 0.0$.

See also

TEXTSZ.

SUBROUTINE TEXTMG (FACTOR)

Name

TEXTMG – to specify the magnification of text.

Availability Section 1, released before version 2-5.

Argument

FACTOR REAL expression Magnification factor for text size

Description

By default, SIMPLEPLOT aims to produce text which is both clear and well proportioned. A target size of text used is chosen to relate to the physical size of the picture, and to be appropriate to its purpose – title, key, axis annotation *etc.* This target size can not be achieved on all devices – some devices can reproduce hardware text at any chosen size, some have a few discrete sizes, and some can only draw one size of text; software text may vary according to the pixel resolution of the device.

If TEXTMG has been called, the target size is multiplied by FACTOR; this new target size is then adjusted as described above.

Default

CALL TEXTMG(1.0) restores the default.

See also

TEXTMN and TEXTSZ.

SUBROUTINE TEXTMN (CMS)**Name**

TEXTMN – to specify the minimum text size.

Availability Section 1, released version 2-6.

Argument

CMS	REAL expression	Minimum character width (in cms)
-----	-----------------	----------------------------------

Description

By default, SIMPLEPLOT aims to produce text which is both clear and well proportioned. A target size of text used is chosen to relate to the physical size of the picture, and to be appropriate to its purpose – title, key, axis annotation *etc.* This target size can not be achieved on all devices – some devices can reproduce hardware text at any chosen size, some have a few discrete sizes, and some can only draw one size of text; software text may vary according to the pixel resolution of the device.

The target width is always forced to be no less than some minimum value. After TEXTMN has been called, the specified value is used in place of all smaller targets. If TEXTMN has not been called, a minimum set in the device driver is used; but when no minimum is set in the device driver either, 0.14 centimetres is used.

For proportionally-spaced fonts (*eg.* the Hershey fonts), the target text size is set to the width of digits which is uniform for all digits within a font.

Default

CALL TEXTMN(0.0) restores the default.

See also

TEXTMG and TEXTSZ.

SUBROUTINE TEXTSL (ANGLE)

Name

TEXTSL – to specify the slant of hardware text.

Availability Section 4, released version 2-10.

Argument

ANGLE	REAL expression	Clockwise angle of slant from the upright (in degrees)
-------	-----------------	--------------------------------------------------------

Description

TEXTSL can be used to specify the angle of slant of hardware text but only has effect if the following criteria are met:

- hardware text is currently selected,
- the current device is capable of adjusting the slope of text, and
- the device driver has been modified to implement this facility.

The slant is specified, in degrees, as the clockwise angle from the upright. Positive angles produce forward sloping characters and negative angles produce backward sloping characters. The maximum slope is device dependent.

Default

CALL TEXTSL(0.0) restores the default.

See also

CHSET and TEXTAR.

SUBROUTINE TEXTSZ (CMS)**Name**

TEXTSZ – to specify the fixed character width of all text.

Availability Section 1, released version 2-5.

Argument

CMS	REAL expression	Character width (in cms)
-----	-----------------	--------------------------

Description

By default, SIMPLEPLOT aims to produce text which is both clear and well proportioned. A target size of text used is chosen to relate to the physical size of the picture, and to be appropriate to its purpose – title, key, axis annotation *etc.* This target size can not be achieved on all devices – some devices can reproduce hardware text at any chosen size, some have a few discrete sizes, and some can only draw one size of text; software text may vary according to the pixel resolution of the device.

TEXTSZ fixes the target size of text to a value specified in centimetres. For the reasons described above, this target may not always be achieved.

For the proportionally-spaced fonts (*eg.* the Hershey fonts) the text size corresponds to the width of digits which is uniform for all digits within a font.

For subscripts and superscripts, the ordinary target size is multiplied by 0.75.

Default

CALL TEXTSZ(0.0) restores the default.

See also

TEXTMG and TEXTMN.

SUBROUTINE THCKMG (CHTYPE, FACTOR)**Name**

THCKMG – to specify the pen thickness to be used for all plotting.

Availability Section 1, released version 2-13.

Arguments

CHTYPE	CHARACTER*1	Type of plotting to be affected by FACTOR
FACTOR	REAL expression	Magnification factor for thickening

CHTYPE	Type of plotting
--------	------------------

'L'	Line drawing
'T'	Selected software text
'M'	Software marker symbols
'*'	All of the above

Description

By default, SIMPLEPLOT performs all plotting with a single pen thickness (FACTOR=1.0). After THCKMG has been called, the type of plotting specified by CHTYPE is performed using the pen thickness specified by FACTOR.

Software shading lines are not affected by THCKMG.

If line thickness has been specified as a bundled attribute (see BUNLPR), each member of the sequence of line thicknesses (1, 2, 3, 4) is multiplied by FACTOR.

Default

CALL THCKMG('*',1.0) restores the default.

See also

BUNLPR.

SUBROUTINE TIMFMT (COMPNT, LBTYPE, NCHARS)**Name**

TIMFMT – to specify the format for one component of *time-date* data.

Availability Section plus, released version 2-12.

Arguments

COMPNT	CHARACTER*2	<i>Time-date</i> component
LBTYPE	CHARACTER*1	Label type
NCHARS	INTEGER expression	Number of characters

LBTYPE	<i>Label type</i>
--------	-------------------

'N'	Number alone
'P'	Prefixed number
'S'	Suffixed number
'T'	Text – only valid for 'DW', 'DM', 'MO', and 'HO'
'D'	Default – the value of NCHARS is ignored

Description

Time-date annotations are built from combinations of components, each of which may be expressed in different formats. The possible interpretations of **COMPNT** are listed in Appendix T of the *SIMPLEPLOT Supplement*.

For text labels, if **NCHARS** > 0, the component will contain **NCHARS** characters, truncating from the right if the string is too long. If **NCHARS** ≤ 0 the whole string is used, excluding trailing spaces.

For numeric labels, if **NCHARS**=2 and the component value is a whole number, two digits are used, including zeros. Otherwise, *SIMPLEPLOT* uses as many digits as are needed to represent the value.

If **LBTYPE**='P' or 'S', a single character prefix or suffix, specified by **TIMLDC**, is appended to the numerical value of the component. The individual components of axis labels are separated by one-character separators which can be controlled independently by **AXLBSP**.

Diagnostics

(Invalid component type: *XX*)¹

(Text label unavailable: *XX*)²

Default

CALL TIMFMT(COMPNT, 'D', 0) restores the default.

See also

AXLBSP, AXLBTP, TIMLDA and TIMLDC.

SUBROUTINE TIMLDA (COMPNT, LABARR, NARR)

Name

TIMLDA – to load a new set of text labels for one component of *time-date* axis annotations.

Availability Section plus, released version 2-12.

Arguments

COMPNT	CHARACTER*2	<i>Time-date</i> component
LABARR	STRING array	Containing set of labels
NARR	INTEGER expression	Number of items in LABARR

COMPNT	Meaning	Max NARR
'MO'	Month	12
'DM'	Day of the month	31
'DW'	Day of the week	7
'HO'	Hour	24

Description

Time-date annotations are built from up to three components. All components can be labelled numerically but some components can also be labelled with text from lists stored by SIMPLEPLOT. These standard labels are listed in Appendix T of the *SIMPLEPLOT Supplement*. TIMLDA changes the contents of the list for one component.

If NARR=0, LABARR is not examined and the standard labels for that component are loaded; otherwise, up to NARR labels from array LABARR are stored for use as text labels. If a non-zero value of NARR is smaller than the maximum for that component, the first NARR labels are stored, and used in conjunction with the rest of the existing set of text labels.

Please note that TIMLDA is only used to change the text labels – TIMFMT is used to switch between the use of text labels and numeric labels.

Diagnostics

(Invalid component type: XX)¹

(Inappropriate component type: XX)²

Default

CALL TIMLDA (COMPNT, LABARR, 0) restores the default.

See also

AXLBTP, TIMFMT and TIMLDC.

SUBROUTINE TIMLDC (COMPNT, CHTYPE)**Name**

TIMLDC – to load a new prefix/suffix character for numeric labels of one component of *time-date* axis annotations.

Availability Section plus, released version 2-12.

Arguments

COMPNT	CHARACTER*2	<i>Time-date</i> component
CHTYPE	CHARACTER*1	Character to add to numeric labels

Description

Time-date annotations are built from up to three components. Each component can be labelled numerically, with a single-character prefix or suffix. TIMLDC sets the stored character for one component.

COMPNT identifies the component; the possible interpretations of COMPNT are listed in Appendix T of the *SIMPLEPLOT Supplement*. CHTYPE specifies the character to use. If CHTYPE=' ', the default character is loaded.

TIMLDC only changes the stored character; TIMFMT must be called to switch between the use of prefixed/suffixed numeric labels and alternative forms of label. The individual components of labels are separated by one-character separators controlled independently by AXLBSP.

Diagnostics

(Invalid component type: XX)¹

Default

CALL TIMLDC(COMPNT, ' ') restores the default.

See also

AXLBSP, AXLBTP, TIMFMT and TIMLDA.

**SUBROUTINE TITLE7 (VCHAR, HCHAR, CAP)
SUBROUTINE TITLE (VCHAR, HCHAR, CAP, NCAP)**

Name

TITLE7 – to draw a text string as a title to the picture, group or page.

Availability Section 1, released before version 2-5.

Arguments

VCHAR	CHARACTER*1	Vertical position of title
HCHAR	CHARACTER*1	Horizontal position of title
CAP	STRING expression	Caption
NCAP	INTEGER expression	Number of characters in CAP

Description

TITLE/TITLE7 draws [2] the caption, CAP, as a title in the specified position. Several lines of text can be drawn by successive calls of TITLE7/TITLE in the same position. The only restriction on how many titles can be drawn in any position, is when the bottom of the page is reached.

VCHAR and HCHAR are single characters representing the initial letters of vertical and horizontal positions. The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

'N'orth and 'H'igher both position titles as high as possible on a page but differ in their horizontal positioning – 'N'orth titles use the full width of the page and can be centred within the limits of the page whereas 'H'igher titles use the limits of the group.

The position of the title also determines its horizontal limit – the full width of the page, the width of the group or the width of the picture.

Diagnostics

(None of title will fit in)²
 (Text clipped)²
 (Title attempted with no page)²
 (Title attempted with no picture)²
 (Title omitted below bottom)²
 (Title too tall)²
 (Title truncated)²

See also

ADDCP7, CLIPLV, CP7LB, CP7PT, CP7XC, CP7YC, DEFCAP and KPOSXY.

SUBROUTINE VS3DLM (XSTART, XSTOP, YSTART, YSTOP, ZSTART, ZSTOP)**Name**

VS3DLM – to set the three-dimensional Limiting Box for plottable data.

Availability Section 7, released version 2-13.

Arguments

XSTART	REAL expression	Value at start of x scale
XSTOP	REAL expression	Value at end of x scale
YSTART	REAL expression	Value at start of y scale
YSTOP	REAL expression	Value at end of y scale
ZSTART	REAL expression	Value at start of z scale
ZSTOP	REAL expression	Value at end of z scale

Description

SIMPLEPLOT ViSualization scales are set to accommodate all data within a three-dimensional box. By default, the x , y and z limits of this box are all -1.0 to $+1.0$. VS3DLM changes these limits.

All points which lie inside the Limiting Box after transformation can be plotted. Note that, although a point may have (x, y, z) coordinates within the limits set by VS3DLM, it may still lie outside the Limiting Box if any transformations have been applied.

For more information about the effect of transformations on scales, see documentation on the transformation subroutines VSMAG, VSROT and VSTRAN, and the scaling subroutines VSFIT, VSFITP and VSFULL.

VS3DLM is also used to set the Origin, which is at the centre of the Limiting Box. By default, this is at $(0.0, 0.0, 0.0)$, although after

CALL VS3DLM(XSTART, XSTOP, YSTART, YSTOP, ZSTART, ZSTOP)

it is at

$$\left(\frac{XSTART+XSTOP}{2}, \frac{YSTART+YSTOP}{2}, \frac{ZSTART+ZSTOP}{2} \right)$$

VS3DLM does not take effect until the next call of VSNEW.

Default

Calling VS3DLM with XSTART=XSTOP, YSTART=YSTOP or ZSTART=ZSTOP restores the default for all scales.

See also

QV3DLM, VSFIT, VSFITP, VSFULL and VSINIT.

SUBROUTINE VSAXDR (CAPX, CAPY, CAPZ)**Name**

VSAXDR – to draw 3-D axes on a *SIMPLEPLOT ViSualization* picture.

Availability Section 7, released version 2-14.

Arguments

CAPX	STRING expression	<i>x</i> -axis caption
CAPY	STRING expression	<i>y</i> -axis caption
CAPZ	STRING expression	<i>z</i> -axis caption

Description

VSAXDR can be called to draw *x-y-z* axes for the current *SIMPLEPLOT ViSualization* picture. VSAXDR must be called after 3-D scales have been applied by VSNEW. The axes are drawn directly on the picture, not into the raster image. It is preferable to draw axes after the image has been transmitted by VSOUT, to avoid the axis being overdrawn.

Diagnostics

[VSAXDR: No current ViSualization picture]¹

See also

AX*, VSAXFC, VSNEW and VSOUT.

SUBROUTINE VSAXFC (IXFIX, IYFIX, IZFIX)**Name**

VSAXFC – to specify the colours for filled rear planes of *SIMPLEPLOT ViSualization* pictures.

Availability Section 7, released version 2-14.

Arguments

IXFIX	INTEGER expression	Fill index for rear x plane
IYFIX	INTEGER expression	Fill index for rear y plane
IZFIX	INTEGER expression	Fill index for rear z plane

Description

VSAXFC specifies colour indices for filling the rear planes of the *SIMPLEPLOT ViSualization* Limiting Box. If a non-negative value is specified for any plane, it is filled whenever a new image is started. VSAXFC must therefore be called before VSNEW.

IXFIX specifies the colour index for the rear plane(s) with x constant, IYFIX specifies the colour index for the rear plane(s) with y constant, and IZFIX specifies the colour index for the rear plane(s) with z constant.

If colour index -1 is specified (default), the associated plane is not filled. Zero, one or two planes may be filled for each variable, depending on the Viewing Position set by VSVRTP/VSVXYZ.

In this release of the software, data may be mapped onto colour indices 0 to 95 inclusive.

Default

CALL VSAXFC(-1,-1,-1) restores the default.

Diagnostics

[VSAXFC: Colour index I out of range]¹

See also

VSAXGC, VSOUT, VSVRTP and VSVXYZ.

SUBROUTINE VSAXGC (IXCIX, IYCIX, IZCIX)**Name**

VSAXGC – to specify the colour indices for grid lines on the rear planes of *SIMPLEPLOT ViSualization* pictures.

Availability Section 7, released version 2-14.

Arguments

IXCIX	INTEGER expression	Colour index for x
IYCIX	INTEGER expression	Colour index for y
IZCIX	INTEGER expression	Colour index for z

Description

VSAXGC specifies colour indices for grid lines on the rear planes of the *SIMPLEPLOT ViSualization* Limiting Box. When grids have been requested, they are drawn in the raster image whenever a new image is started. VSAXGC must therefore be called before VSNEW.

IXCIX specifies the colour index for grid lines on the rear plane(s) with x constant, IYCIX specifies the colour index for grid lines on the rear plane(s) with y constant, and IZCIX specifies the colour index for grid lines on the rear plane(s) with z constant.

If index -1 is specified, grids on the associated planes are not drawn, and if rear planes are filled, grid lines are formed by gaps in the filling. If index -2 is specified, the associated grids are omitted. This is the default.

Default

CALL VSAXGC($-2, -2, -2$) restores the default.

Diagnostics

[VSAXGC: Colour index I out of range]¹

See also

VSAXFC.

SUBROUTINE VSBLFL (X1, X2, Y1, Y2, Z1, Z2)**Name**

VSBLFL – to fill a 3-D block on a *SIMPLEPLOT ViSualization* picture.

Availability Section 7, released version 2-14.

Arguments

X1, X2	REAL expressions	Range of x values
Y1, Y2	REAL expressions	Range of y values
Z1, Z2	REAL expressions	Range of z values

Description

VSBLFL draws a single block on the current *SIMPLEPLOT ViSualization* picture. This block is filled with the current fill index set by VSFILC, and subject to edge visibility and colour.

If the range of any dimension is zero (X1=X2, Y1=Y2 or Z1=Z2) nothing is drawn.

Diagnostics

[VSBLFL: No current ViSualization picture]¹

See also

VSBLTN, VSBFL, VSEDGC, VSEDGV and VSFILC.

SUBROUTINE VSBLTN (X1, X2, Y1, Y2, Z1, Z2, U1, U2)**Name**

VSBLTN – to tint a 3-D block on a *SIMPLEPLOT ViSualization* picture.

Availability Section 7, released version 2-14.

Arguments

X1, X2	REAL expressions	Range of x values
Y1, Y2	REAL expressions	Range of y values
Z1, Z2	REAL expressions	Range of z values
U1, U2	REAL expressions	Range of u values

Description

VSBLTN draws a single block on the current *SIMPLEPLOT ViSualization* picture. The block is tinted with colours ranging from the colour derived from U1 at $z = Z1$ to the colour derived from U2 at $z = Z2$. The block is subject to edge visibility and colour.

Diagnostics

[VSBLTN: No current ViSualization picture]¹

See also

VSBLFL, VSBRTN, VSEDGC and VSEDGV.

SUBROUTINE VSB RBZ (ZVAL)**Name**

VSB RBZ – to specify the base z value for bars in *SIMPLEPLOT ViSualization* 3-D barcharts.

Availability Section 7, released version 2-14.

Argument

ZVAL	REAL expression	Required base z value
------	-----------------	-------------------------

Description

By default, *SIMPLEPLOT ViSualization* 3-D barcharts show each bar extending from $z = 0.0$, to a z value from an array. VSB RBZ can be called before VSB RFL or VSB RTN to set an alternative base z value.

Default

CALL VSB RBZ(0.0) restores the default.

See also

VSB RFL and VSB RTN.

SUBROUTINE VSBRFC (ICODE)

Name

VSBRFC – to specify how colour sequences should be used on subsequent *SIMPLEPLOT Visualization* 3-D barcharts.

Availability Section 7, released version 2-14.

Arguments

ICODE INTEGER expression Specify use of colour (see below)

ICODE *Different colours*

- | | |
|---|-------------------------------------------------------|
| 0 | Faces of bars distinguished by pen pointers (default) |
| 1 | Data Rows distinguished by colour sequence |
| 2 | Data Columns distinguished by colour sequence |
| 3 | Data Sets distinguished by colour sequence |
| 4 | Data magnitudes distinguished by colour sequence |
-

Description

VSBRFC fills a *SIMPLEPLOT Visualization* 3-D barchart. VSBRFC can be called before VSBFL, to specify how colours are used for the bars.

When ICODE = 0, three colour indices distinguish the three planes of each bar: the x plane uses the first colour index, the y plane uses the second, and the z plane uses the third.

When ICODE > 0, all planes of a bar are shaded with the same colour index. SQSHAD may be called to specify the sequence of colour indices. When SQSHAD has not been called, the colour indices are used in the natural sequence 1, 2, 3, ...

Diagnostics

[VSBRFC: Integer I out of range]¹

Default

CALL VSBRFC(0) restores the default.

See also

SQSHAD and VSBFL.

SUBROUTINE VSBRFL (Z, NX, NY, NSETS)**Name**

VSBRFL – to fill a *SIMPLEPLOT ViSualization* 3-D barchart.

Availability Section 7, released version 2-14.

Arguments

Z	REAL 3-D array	$NX \times NY \times NSETS$ array of user (z) values
NX, NY, NSETS	INTEGER expressions	Dimensions of 3-D data array

Description

A *SIMPLEPLOT ViSualization* 3-D barchart is drawn representing NSETS sets of values in array Z, stacked on top of each other. The sets may be stacked downward with the first set at the top, or upward with the first set at the bottom, as specified by VSBRUP.

Different colours may be used to distinguish between data columns, data rows, or data sets, or data magnitudes, as specified by VSBRFC.

Diagnostics

[VSBRFL: No current ViSualization picture]¹
 [VSBRFL: Invalid array dimension]¹

See also

QVBRFL, VSBRBZ, VSBRFC, VSBRSZ, VSBRTN and VSBRUP.

SUBROUTINE VSBRSZ (X1, X2, Y1, Y2)

Name

VSBRSZ – to specify the widths of bars in *SIMPLEPLOT ViSualization* 3-D barcharts.

Availability Section 7, released version 2-14.

Arguments

X1, X2	REAL expressions	Limits of bars in x direction
Y1, Y2	REAL expressions	Limits of bars in y direction

Description

By default, each bar in *SIMPLEPLOT ViSualization* 3-D barcharts extends from 0.1 to 0.9 of the space available in both x and y . VSBRSZ can be called to specify alternative limits.

When X2 is not greater than X1, or either lies outside the range 0.0 to 1.0, the default in x is restored; when Y2 is not greater than Y1, or either lies outside the range 0.0 to 1.0, the default in y is restored.

Default

CALL VSBRSZ(0.0, 0.0, 0.0, 0.0) restores the default.

See also

VSBRFL and VSBRTN.

SUBROUTINE VSBR TN (Z, NX, NY)

Name

VSBR TN – to tint a *SIMPLEPLOT ViSualization* 3-D barchart.

Availability Section 7, released version 2-14.

Arguments

Z	REAL 2-D array	NX×NY user (<i>z</i>) values
NX, NY	INTEGER expressions	Dimensions of 2-D data array

Description

VSBR TN draws a *SIMPLEPLOT ViSualization* 3-D barchart representing the values in array Z. The colours representing different *z* values are controlled by VSUTOC, and by default map onto colour indices 1 to 15.

Diagnostics

[VSBR TN: No current ViSualization picture]¹
 [VSBR TN: Invalid array dimension]¹

See also

VSBRBZ, VSBFL, VSBRSZ and VSUTOC.

SUBROUTINE VSBRUP (IUP)

Name

VSBRUP – to specify the stacking direction for *SIMPLEPLOT Visualization* 3-D barcharts.

Availability Section 7, released version 2-14.

Arguments

IUP INTEGER expression Whether bars stack upwards

IUP <i>Direction</i>	
0	Downward (default)
1	Upward

Description

VSBRUP is called before VSBFL to specify whether multiple data sets should be stacked downward with the first set at the top, or upward with the first set at the bottom:

Diagnostics

[VSBRUP: Integer *I* out of range]¹

Default

CALL VSBRUP(0) restores the default.

See also

VSBRFL and VSBRTN.

SUBROUTINE VSCHLS (ICIX, HUE, BRIGHT, SATN)**Name**

VSCHLS – to set hue, lightness and saturation levels for the *SIMPLEPLOT ViSualization* palette.

Availability Section 7, released version 2-13.

Arguments

ICIX	INTEGER expression	Colour index to be changed
HUE	REAL expression	Hue (degrees)
BRIGHT	REAL expression	Lightness (0.0–1.0)
SATN	REAL expression	Saturation (0.0–1.0)

Description

SIMPLEPLOT ViSualization maintains its own target palette for output. Palette requests on devices with limited colour capabilities are rendered using Error Diffusion techniques.

BRIGHT and SATN must be between 0.0 and 1.0. If they are not, a diagnostic is issued and the palette is unchanged.

VSCHLS sets the device palette if palette control is available.

Diagnostics

[VSCHLS: Colour index *I* out of range]¹

[VSCHLS: Colour specification *R* out of range]¹

See also

VSCRGB and VSCRNG.

SUBROUTINE VSCRGB (ICIX, RED, GREEN, BLUE)**Name**

VSCRGB – to specify red, green and blue levels for the *SIMPLEPLOT ViSualization* palette.

Availability Section 7, released version 2-13.

Arguments

ICIX	INTEGER expression	Colour index to be specified
RED	REAL expression	Proportion of Red (0.0–1.0)
GREEN	REAL expression	Proportion of Green (0.0–1.0)
BLUE	REAL expression	Proportion of Blue (0.0–1.0)

Description

SIMPLEPLOT ViSualization maintains its own target palette for output. Palette requests on devices with limited colour capabilities are rendered using Error Diffusion techniques.

RED, GREEN and BLUE must be between 0.0 and 1.0. If they are not, a diagnostic is issued and the palette is unchanged.

VSCRGB sets the device palette if palette control is available.

Diagnostics

[VSCRGB: Colour index *I* out of range]¹

[VSCRGB: Colour specification *R* out of range]¹

See also

VSCHLS and VSCRNG.

SUBROUTINE VSCRNG (ICIX1, ICIX2)**Name**

VSCRNG – to set a graded range of colours in the *SIMPLEPLOT ViSualization* palette.

Availability Section 7, released version 2-14.

Arguments

ICIX1	INTEGER expression	first pen index of graded range
ICIX2	INTEGER expression	last pen index of graded range

Description

VSCRNG sets the colours for all indices between ICIX1 and ICIX2. The existing values of colours ICIX1 and ICIX2 are left unchanged and a graded range of colours is interpolated for all indices between them.

See also

VSCHLS and VSCRGB.

SUBROUTINE VSEDGC (ICIX)**Name**

VSEDGC – to specify the colour index for the edge of filled areas.

Availability Section 7, released version 2-13.

Argument

ICIX INTEGER expression Colour index for edge of filled areas

Description

VSEDGC sets the colour index for the edge of *SIMPLEPLOT Visualization* filled areas. This value is then applied if the edge visibility is set to ON by VSEDGV(1). In this release of software, data may be mapped on to colour indices 0 to 95 inclusive.

If colour index -1 is specified, subsequent edges are omitted. This differs from selecting colour index 0, which draws the edge in background, and from VSEDGV(0) which fills the interior up to and including the edge.

Diagnostics

[VSEDGC: Colour index I out of range]¹

Default

CALL VSEDGC(1) restores the default.

See also

VSBLFL, VSBLTN, VSBFL, VSBRTN, VSEDGV, VSPGFL, VSRG, VSRGU, VSPGTN, VSXYZ, VSXYZU, VSZ and VSZU.

SUBROUTINE VSEDGV (LEVEL)**Name**

VSEDGV – to specify whether the edge of polygons is to be drawn.

Availability Section 7, released version 2-13.

Argument

LEVEL INTEGER expression Whether to draw the edge in edge
 colour index

LEVEL	<i>Drawn</i>
0	OFF – no edge drawn
1	ON – edge drawn

Description

By default, the edge visibility is OFF, and the edge of filled areas is drawn in the same colour as the interior. By setting the edge visibility ON, the edge of each polygon is drawn in the edge colour index (see VSEDGC). By drawing the edge of polygons separately from the interior, the underlying data structure can be displayed.

Diagnostics

[VSEDGV: Integer *I* out of range]¹

Default

CALL VSEDGV(0) restores the default.

See also

VSBLFL, VSBLTN, VSBFL, VSBRTN, VSEDGC, VSEDGI, VSIS, VSISU, VSPGFL, VSPGTN, VSRG, VSRGU, VSXYZ, VSXYZU, VSZ and VSZU.

SUBROUTINE VSEQX (XSTART, XSTEP)**Name**

VSEQX – to specify the equally-spaced x values to be associated with *SIMPLEPLOT ViSualization* gridded 3-D data.

Availability Section 7, released version 2-13.

Arguments

XSTART	REAL expression	x value of first data column
XSTEP	REAL expression	Interval between data columns

Description

By default, data on a regular grid drawn by VSRG, VSRGU, VSIS or VSISU are scaled to fit within the current Limiting Box specified by VS3DLM.

VSEQX specifies the x values corresponding to the data grid, and may be used in conjunction with VS3DLM to position the $y-z$ plane in 3-D space. XSTART specifies the x coordinate to be associated with the first column of the data array, and XSTEP specifies the interval between columns.

VSEQX has no effect if VS3DLM has not been called to set the *SIMPLEPLOT ViSualization* 3-D scales explicitly.

Default

Calling VSEQX with XSTEP=0.0 restores the default.

See also

VSEQY, VSEQZ, VSRG, VSRGU, VSIS, and VSISU.

SUBROUTINE VSEQY (YSTART, YSTEP)**Name**

VSEQY – to specify the equally-spaced y values to be associated with *SIMPLEPLOT ViSualization* gridded 3-D data.

Availability Section 7, released version 2-13.

Arguments

YSTART	REAL expression	y value of first data row
YSTEP	REAL expression	Interval between data rows

Description

By default, data on a regular grid drawn by VSRG, VSRGU, VSIS or VSISU are scaled to fit within the current Limiting Box specified by VS3DLM.

VSEQY specifies the y values corresponding to the data grid, and may be used in conjunction with VS3DLM to position the $x-z$ plane in 3-D space. YSTART specifies the y coordinate to be associated with the first row of the data array, and YSTEP specifies the interval between rows.

VSEQY has no effect if VS3DLM has not been called to set the *SIMPLEPLOT ViSualization* 3-D scales explicitly.

Default

Calling VSEQY with YSTEP=0.0 restores the default.

See also

VSEQX, VSEQZ, VSRG, VSRGU, VSIS and VSISU.

SUBROUTINE VSFILC (ICIX)**Name**

VSFILC – to specify the colour index to be used by *SIMPLEPLOT ViSualization* area fill sub-routines.

Availability Section 7, released version 2-13.

Argument

ICIX INTEGER expression Colour index for filling

Description

VSFILC sets the colour index for subsequent filling by VSPGFL or VSBLFL. In this release of software, data may be mapped on to colour indices 0 to 95 inclusive. If colour index -1 is specified, subsequent areas are not filled.

Diagnostics

[VSFILC: Colour index I out of range]¹

Default

CALL VSFILC(1) restores the default.

See also

VSBLFL, VSCHLS, VSCRGB and VSPGFL.

SUBROUTINE VSFIT (CHAXES)

Name

VSFIT – to specify which axis scales are measured in similar units.

Availability Section 7, released version 2-13.

Argument

CHAXES STRING expression axes which are related

CHAXES *similar axes*

'XYZ' all scales in same units (default)

'XY' x and y scales are similar

'XZ' x and z scales are similar

'YZ' y and z scales are similar

' ' all scales are unrelated

Description

2-D SIMPLEPLOT scales are set to accommodate all data within the three-dimensional box specified by VS3DLM. By default, each of these scales is measured in the same units. If the ranges of these scales are of different magnitudes, the resulting picture is distorted.

VSFIT specifies which scales are comparable. If scales are unrelated, each axis defines the edge of a cube which contains the data. If only 2 scales are similar, the length of the third axis is equal to the longer of the other two.

CHAXES may be in upper or lower case, but if it does not correspond to one of the strings above, an error message is written and nothing is altered.

If non-default scales are used, the relationship between axes is affected by the transformation routines, VSMAG, VSR0T and VSTRAN.

Diagnostics

[VSFIT: Invalid string *XX*]¹

Default

CALL VSFIT('XYZ') restores the default.

See also

VS3DLM and VSFITP.

SUBROUTINE VSFITP (XLEN, YLEN, ZLEN)**Name**

VSFITP – to specify the relative lengths of the x , y and z axes.

Availability Section 7, released version 2-14.

Argument

XLEN	REAL expression	Length of x -axis
YLEN	REAL expression	Length of y -axis
ZLEN	REAL expression	Length of z -axis

Description

By default, the lengths of the *SIMPLEPLOT Visualization* scales are proportional to the data range they cover. This means that if the ranges are not comparable, the picture is unduly distorted.

VSFITP specifies that the axis lengths are in proportion to each other. After `CALL VSFITP(1.0,1.0,1.0)`, for example, all axes are of the same length. After `CALL VSFITP(1.0,2.0,4.0)`, the x -axis is half the length of the y -axis, which is half the length of the z -axis.

If any argument is non-zero, the default is restored – scales are proportional to data range.

Default

`CALL VSFITP(0.0,0.0,0.0)` restores the default.

See also

VS3DLM and VSFIT.

SUBROUTINE VSFULL (MODE)**Name**

VSFULL – to specify how the Limiting Box is to fill the SIMPLEPLOT picture.

Availability Section 7, released version 2-13.

Argument

MODE INTEGER expression Scaling Mode used

Description

By default, the 2-D SIMPLEPLOT scales are set to accommodate the extent of the Limiting Box. The underlying SIMPLEPLOT scales are Linear Cartesian with 1 unit in x the same as 1 unit in y .

If a point or object is *Transformed* (Rotated, Translated or Magnified), its (x, y, z) coordinates change. This means that it may no longer fit on the picture, even though before transformation it lies within the limits specified by VS3DLM. After **CALL VSFULL(1)**, VSNEW sets scales to allow all possible rotations. The relative size of the image is comparable for successive pictures.

After **CALL VSFULL(2)**, VSNEW sets all points within the 3-D limits to be plottable after the current requested Transformations. The resulting images are larger than those produced by Scaling Mode 1, but the scales of successive pictures are not directly comparable.

VSFULL does not take effect until the next call of VSNEW.

Diagnostics

[VSFULL: Integer I out of range]¹

Default

CALL VSFULL(0) restores the default.

See also

VS3DLM, VSINIT, VSMAG, VSROT and VSTRAN.

SUBROUTINE VSINIT (LEVEL)**Name**

VSINIT – to reset *SIMPLEPLOT ViSualization* defaults.

Availability Section 7, released version 2-13.

Argument

LEVEL INTEGER expression Level of initialization

LEVEL *Initializes*

-
- | | |
|---|-----------------------------------------|
| 1 | Rotation, Translation and Magnification |
| 2 | Scales |
| 4 | Drawing attributes |
-

Description

VSINIT may be called to restore some or all defaults of attributes set in *SIMPLEPLOT ViSualization*:

The following subroutines are affected by VSINIT:

LEVEL *Subroutines affected*

-
- | | |
|---|----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | VSMAG, VSROT, VSTRAN |
| 2 | VS3DLM, VSEQX, VSEQY, VSEQZ, VSFIT,
VSFITP, VSFULL, VSVRTP, VSVXYZ |
| 4 | VSAXFC, VSAXGC, VSB RBZ, VSB RFC, VSB RSZ, VSB RUP,
VSCRGB, VSEDGC, VSEDGC, VSEDGV, VSFILC, VSCHLS,
VSLBOX,
VSLINC, VSPMC, VSPMMG, VSUTOC |
-

VSINIT(2) takes effect at the next call to VSNEW. VSINIT(1) and VSINIT(4) take effect immediately.

Multiple categories of attributes may be set by adding the appropriate values of LEVEL, *eg.* CALL VSINIT(3) is equivalent to calling VSINIT(1) and VSINIT(2). CALL VSINIT(7) restores all defaults.

Diagnostics

[VSINIT: Integer *I* out of range]¹

See also

VSNEW.

SUBROUTINE VSK7H (VCHAR, HCHAR, ULEFT, URIGHT, CAP)**Name**

VSK7H – to draw a horizontal key.

Availability Section 7, released version 2-14.

Arguments

VCHAR	CHARACTER*1	Vertical position of key
HCHAR	CHARACTER*1	Horizontal position of key
ULEFT	REAL expression	<i>u</i> value at left of key
URIGHT	REAL expression	<i>u</i> value at right of key
CAP	STRING expression	Single caption for key

Description

VSK7H draws a key to the current patterns representing user data values on tinted *SIMPLEPLOT ViSualization* plots. A horizontal rectangle gives a sample of colours, and a *u*-axis, labelled with the caption CAP, gives the data values.

The rectangle is drawn as a *SIMPLEPLOT ViSualization* image, and VSK7H should not be called between VSNEW and VSOUT. A box is drawn round the key unless cancelled by CALL BOXKY(.FALSE.).

VCHAR and HCHAR are the single character initial letters of vertical and horizontal positions of the key. The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

[VSK7H: Key omitted – active ViSualization picture]¹

See also

BOXKY, VSBLTN, VSBRTN, VSK7V, VSPGTN, VSPLTN, VSRG, VSRGU, VSUTOC, VSXYZ, VSXYZU, VSZ and VSZU.

SUBROUTINE VSK7V (VCHAR, HCHAR, UTOP, UBOTTM, CAP)**Name**

VSK7V – to draw a vertical key.

Availability Section 7, released version 2-14.

Arguments

VCHAR	CHARACTER*1	Vertical position of key
HCHAR	CHARACTER*1	Horizontal position of key
UTOP	REAL expression	<i>u</i> value at top of key
UBOTTM	REAL expression	<i>u</i> value at bottom of key
CAP	STRING expression	Single caption for key

Description

VSK7V draws a key to the current patterns representing user data values on tinted *SIMPLEPLOT ViSualization* plots. A vertical rectangle gives a sample of colours, and a *u*-axis, labelled with the caption CAP, gives the data values.

The rectangle is drawn as a *SIMPLEPLOT ViSualization* image, and VSK7V should not be called between VSNEW and VSOUT. A box is drawn round the key unless cancelled by CALL BOXKY(.FALSE.).

VCHAR and HCHAR are the single character initial letters of vertical and horizontal positions of the key. The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

Diagnostics

[VSK7V: Key omitted – active ViSualization picture]¹

See also

BOXKY, VSBLTN, VSBRTN, VSK7H, VSPGTN, VSPLTN, VSRG, VSRGU, VSUTOC, VSXYZ, VSXYZU, VSZ and VSZU.

SUBROUTINE VSKEYS (VCHAR, HCHAR, LABARR, NARR, CAP)**Name**

VSKEYS – to draw a complete key to a sequence of distinct shading patterns.

Availability Section 7, released version 2-14.

Arguments

VCHAR	CHARACTER*1	Vertical position of area
HCHAR	CHARACTER*1	Horizontal position of area
LABARR	STRING array	Set of captions
NARR	INTEGER expression	Number of labels in LABARR
CAP	STRING expression	Header caption for key

Description

VSKEYS constructs a complete key to the first NARR shading patterns of the currently defined sequence (see SQSHAD and SHPATT).

The key is positioned on the SIMPLEPLOT page in the same way as other keys; VCHAR and HCHAR are single characters representing the initial letters of vertical and horizontal positions. The possible interpretations of VCHAR and HCHAR are listed in Appendix T of the *SIMPLEPLOT Supplement*.

CAP provides a heading which, by default, is centred at the top of the key. The key is associated only with the current picture but area is masked to prevent overdrawing.

VSKEYS should not be called between VSNEW and VSOUT. A box is drawn round the key unless cancelled by CALL BOXKY(.FALSE.).

See also

ADDJST, BOXKY, DEFKEY, DEFKYW, DEFPOS, SHPATT, SHSET SQSHAD, VSK7H, VSK7V.

SUBROUTINE VSLBOX (LEVEL)**Name**

VSLBOX – to specify whether Limiting Boxes are to be drawn around *SIMPLEPLOT* *ViSualization* images.

Availability Section 7, released version 2-13.

Argument

LEVEL INTEGER expression Whether images are to be boxed

LEVEL	Action taken
0	No box drawn
1	Box is drawn

Description

By default, images are not boxed. VSLBOX specifies whether or not a 3-D box is to be drawn around every subsequent image.

After CALL VSLBOX(1), a 3-D box is drawn around the area defined by the Limiting Box whenever VSNEW is called to start a new image. The box is drawn in the current Line Colour Index set by VSLINC. If an image has already been started, no box is drawn until the next image.

Default

CALL VSLBOX(0) restores the default.

Diagnostics

[VSLBOX: Integer *I* out of range]¹

See also

VS3DLM, VSFULL, VSLINC and VSNEW.

SUBROUTINE VSLINC (ICIX)**Name**

VSLINC – to specify the colour index to be used by line drawing subroutines.

Availability Section 7, released version 2-13.

Argument

ICIX INTEGER expression Colour index for line drawing

Description

VSLINC sets the colour index for subsequent line drawing by VSLBOX or VSPLDR. In this release of software, data may be drawn in colour indices 0 to 95 inclusive. If colour index -1 is specified, subsequent lines are omitted.

Diagnostics

[VSLINC: Colour index I out of range]¹

Default

CALL VSLINC(1) restores the default.

See also

VSCHLS, VSLBOX, VSPLDR and VSCRGB.

SUBROUTINE VSMAG (XFACT, YFACT, ZFACT)**Name**

VSMAG – to magnify *SIMPLEPLOT ViSualization* coordinates along any or all of the x - y - z axes.

Availability Section 7, released version 2-13.

Arguments

XFACT	REAL expression	Magnification factor along the x -axis
YFACT	REAL expression	Magnification factor along the y -axis
ZFACT	REAL expression	Magnification factor along the z -axis

Description

By default, *SIMPLEPLOT ViSualization* interprets (x, y, z) coordinates literally. However, following a call to VSMAG, a magnification factor is applied to subsequent coordinates.

For example, following a call to VSMAG(XFACT, 1.0, 1.0), the point (x, y, z) is interpreted as $(x \times \text{XFACT}, y, z)$, and all subsequent objects are magnified by XFACT along the x -axis.

Similar magnification can be applied to the y and z -axes by setting YFACT and ZFACT to values other than 1.0.

After a point has been magnified, its (x, y, z) position changes. This means that it may not fit on the current picture, even if it lies within the limits specified by VS3DLM. VSFULL(2) may be called before VSNEW to ensure that (x, y, z) points within the Limiting Box before transformation stay on the picture.

Transformation is cumulative, so two successive calls to VSMAG(2.0, 2.0, 2.0) quadruple the size along each axis.

The transformed coordinate is a combination of the affects of VSMAG, VSROT and VSTRAN, which means that default magnification cannot be restored on its own. All transformation variables are restored by CALL VSINIT(1).

See also

VSFULL, VSINIT, VSROT and VSTRAN.

SUBROUTINE VSNEW**Name**

VSNEW – to start a new *SIMPLEPLOT ViSualization* picture.

Availability Section 7, released version 2-13.

Arguments

None.

Description

VSNEW starts a new *SIMPLEPLOT ViSualization* picture and updates the variables which affect scaling. These are attributes set by VS3DLM, VSEQX, VSEQY, VSEQZ, VSFIT, VSFITP, VSFULL, VSVRTP and VSVXYZ.

VSNEW sets the underlying SIMPLEPLOT scales which are used by the internal *SIMPLEPLOT ViSualization* subroutines when constructing and transmitting an image. If another type of graph is drawn after a call to VSNEW, the SIMPLEPLOT scales should be set explicitly by SCALES or EQSCAL.

Backdrops and grids specified by VSAXFC and VSAXGC are drawn into the raster image when VSNEW is called.

Diagnostics

[VSNEW: Radius too short - no perspective applied]¹

See also

VS3DLM, VSAXFC, VSAXGC, VSFIT, VSFITP, VSFULL, VSVRTP and VSVXYZ.

SUBROUTINE VSOUT

Name

VSOUT – to flush the raster image.

Availability Section 7, released version 2-13.

Arguments

None.

Description

VSOUT sends the raster image to the display device. With this release of *SIMPLEPLOT ViSualization* the internal raster image is not retained for subsequent re-processing, and VSNEW must be called before starting a new image.

Diagnostics

[VSOUT: *n* incomplete tasks]¹

See also

VSNEW.

SUBROUTINE VSPGFL (XARRAY, YARRAY, ZARRAY, NPTS)**Name**

VSPGFL – to fill a planar polygon with the current fill index in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

XARRAY	REAL array	NPTS x values
YARRAY	REAL array	NPTS y values
ZARRAY	REAL array	NPTS z values
NPTS	INTEGER expression	Number of points in polygon

Description

The current transformations are applied to the x - y - z data. Successive points are joined by a straight line, and the interior area is filled with the current fill colour index. If the Edge Visibility is ON, following a call to **VSEDGV(1)**, the edge is drawn in the current Edge Colour Index.

Polygons must be planar, convex and between 3 and 200 points. If $NPTS < 3$, a diagnostic is issued and nothing is drawn.

Hidden line and surface removal are applied to all drawing.

Diagnostics

[VSPGFL: No current ViSualization picture]¹
 [VSPGFL: Invalid array dimension]¹

See also

VSEDGC, VSEDGV, VSFILC and VSPGTN.

SUBROUTINE VSPGTN (XARRAY, YARRAY, ZARRAY, UARRAY, NPTS)**Name**

VSPGTN – to tint a planar polygon from user data values in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

XARRAY	REAL array	NPTS x values
YARRAY	REAL array	NPTS y values
ZARRAY	REAL array	NPTS z values
UARRAY	REAL array	NPTS user data values
NPTS	INTEGER expression	Number of points in polygon

Description

The current transformations are applied to the x - y - z data. Successive points are joined by a straight line, and the interior area is filled by changing colours interpolated from the corresponding user data values. If the Edge Visibility is ON, following a call to **VSEMGV(1)**, the edge is drawn in the current Edge Colour Index.

Polygons must be planar, convex and between 3 and 200 points. If $NPTS < 3$, a diagnostic is issued and nothing is drawn.

Hidden line removal is applied to all drawing.

Diagnostics

[VSPGTN: No current ViSualization picture]¹

[VSPGTN: Invalid array dimension]¹

See also

VSEMG, VSEMGV, VSPGFL and VSUTOC.

SUBROUTINE VSPLDR (XARRAY, YARRAY, ZARRAY, NPTS)**Name**

VSPLDR – to draw a polyline through a succession of (x, y, z) data points in a *SIMPLEPLOT* *ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

XARRAY	REAL array	NPTS x values
YARRAY	REAL array	NPTS y values
ZARRAY	REAL array	NPTS z values
NPTS	INTEGER expression	Number of points in polyline

Description

The current transformations are applied to the input data and successive points are joined by a straight line, using the current line colour index. Hidden line removal is applied to all drawing.

If $NPTS < 2$, a diagnostic is issued and nothing is drawn.

Diagnostics

[VSPLDR: No current ViSualization picture]¹
 [VSPLDR: Invalid array dimension]¹

See also

VSLINC and VSPLTN.

SUBROUTINE VSPLTN (XARRAY, YARRAY, ZARRAY, UARRAY, NPTS)**Name**

VSPLTN – to tint a polyline based on user data values in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

XARRAY	REAL array	NPTS x values
YARRAY	REAL array	NPTS y values
ZARRAY	REAL array	NPTS z values
UARRAY	REAL array	NPTS user data values
NPTS	INTEGER expression	Number of points in polyline

Description

The current *SIMPLEPLOT ViSualization* transformations are applied to the x - y - z data. Successive points are joined by a straight line, using changing colours interpolated from the corresponding user data values.

If $\text{VSPLTN} < 2$, a diagnostic is issued and nothing is drawn.

Hidden line removal is applied to all drawing.

Diagnostics

[VSPLTN: No current ViSualization picture]¹

[VSPLTN: Invalid array dimension]¹

See also

VSPLDR and VSUTOC.

SUBROUTINE VSPMC (ICIX)**Name**

VSPMC – to specify the colour index for subsequent markers.

Availability Section 7, released version 2-14.

Argument

ICIX INTEGER expression Colour index for markers

Description

VSPMC sets the colour index for subsequent marker symbols. In this release of software, data may be drawn in colour indices 0 to 95 inclusive. If colour index -1 is specified, subsequent markers are omitted.

Diagnostics

[VSPMC: Colour index I out of range]¹

Default

CALL VSPMC(1) restores the default.

See also

VSCHLS, VSPMDR and VSCRGB.

SUBROUTINE VSPMDR (XARRAY, YARRAY, ZARRAY, NPTS, MKTYPE)**Name**

VSPMDR – to draw a set of markers of type MKTYPE in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-14.

Arguments

XARRAY	REAL array	NPTS <i>x</i> coordinates
YARRAY	REAL array	NPTS <i>y</i> coordinates
ZARRAY	REAL array	NPTS <i>z</i> coordinates
NPTS	INTEGER expression	Number of points in polymarker
MKTYPE	INTEGER expression	Marker type

Description

VSPMDR draws a polymarker – a set of marker symbols – of type MKTYPE, centred on each of the points held in the *x-y-z* arrays. The current transformations are applied to the *x-y-z* data.

Markers are drawn in the current marker colour with the current marker magnification factor applied by VSPMMG. Markers are drawn face on to the viewer, orthogonal to the line of sight.

By default, markers are scaled to occupy 2% of the smaller of the width or height of the picture size, with a minimum size of 0.14cm. When perspective is applied to the *SIMPLEPLOT ViSualization* image, the target marker size applies at a point half way between the front and back of the image. The size of markers decreases away from the viewer.

Diagnostics

[VSPMDR: No Current ViSualization picture]¹
 [VSPMDR: Invalid array dimension]¹
 [VSPMDR: Integer *I* out of range]¹

See also

VSPMC and VSPMMG.

SUBROUTINE VSPMMG (FACTOR)**Name**

VSPMMG – to specify the scaling factor for subsequent markers.

Availability Section 7, released version 2-14.

Argument

FACTOR	REAL expression	Factor by which marker size to be scaled
--------	-----------------	------------------------------------------

Description

By default, markers are scaled to occupy 2% of the smaller of the width or height of the picture size, with a minimum marker size of 0.14cm. When perspective is applied to the *SIMPLEPLOT Visualization* image, the target marker size applies at a point half way between the front and back of the image. The size of markers decreases away from the viewer.

After `CALL VSPMMG(FACTOR)`, the size of markers is increased by a factor of `FACTOR`. `FACTOR` must be greater than 0.0. If it is not, the default is used.

Diagnostics

[VSPMMG: Value *R* out of range]¹

Default

`CALL VSPMMG(0.0)` restores the default.

See also

VSPMDR.

SUBROUTINE VSRG (Z2ARR, NX, NY)**Name**

VSRG – to draw a perspective surface picture from a 2-D array in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

Z2ARR	REAL 2-D array	NX×NY array of user (z) values
NX, NY	INTEGER expression	Dimensions of 2-D data array

Description

The data values held in the array **Z2ARR** are drawn as a filled surface. The colours representing different heights are controlled by **VSUTOC**.

By default, the x , y and z ranges of the data are mapped onto the Limiting Box. If **VS3DLM** has been called to set the scales explicitly, the z values map onto the specified limits, and the x and y scales can be controlled by **VSEQX** and **VSEYQ**.

Diagnostics

[VSRG: No current ViSualization picture]¹
 [VSRG: Invalid array dimension]¹

See also

VS3DLM, VSEDGC, VSEDGV, VSEQX, VSEYQ, VSRGU and VSUTOC.

SUBROUTINE VSRGU (Z2ARR, U2ARR, NX, NY)**Name**

VSRGU – to draw contours of data from one 2-D array on a surface picture from another 2-D array in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

Z2ARR	REAL 2-D array	NX×NY array of (z) values
U2ARR	REAL 2-D array	NX×NY array of data values
NX, NY	INTEGER expressions	Dimensions of 2-D arrays

Description

Contours representing U2ARR are drawn on the surface defined by Z2ARR. The colours representing different contour levels are controlled by VSUTOC.

By default, the x , y and z ranges of the data are mapped onto the Limiting Box. If VS3DLM has been called to set the scales explicitly, the z values map onto the specified limits, and the x and y scales can be controlled by VSEQX and VSEQY.

Diagnostics

[VSRGU: No current ViSualization picture]¹
 [VSRGU: Invalid array dimension]¹

See also

VS3DLM, VSEDGC, VSEDGV, VSEQX, VSEQY, VSRG and VSUTOC.

SUBROUTINE VSROT (CHAXIS, ROTATE)

Name

VSROT – to rotate *SIMPLEPLOT ViSualization* coordinates around one of the x - y - z axes.

Availability Section 7, released version 2-13.

Arguments

CHAXIS CHARACTER*2 Axis type
 ROTATE REAL expression Rotation (in degrees)

CHAXIS *Type of axis*

'X3' 3-D perspective x -axis

'Y3' 3-D perspective y -axis

'Z3' 3-D perspective z -axis

Description

By default, *SIMPLEPLOT ViSualization* interprets (x, y, z) coordinates literally. However, following a call to VSROT, subsequent coordinates are rotated around one of the axes.

CHAXIS signifies axis type. If you are looking down the axis in a positive direction, rotation is clockwise.

Following a call to VSROT('X3',45.0), the point (x, y, z) is rotated by 45° around the x -axis. Transformation is cumulative, so two successive calls to VSROT('Y3',30.0) rotate points 60° around the y -axis.

After a point has been rotated, its (x, y, z) position changes. This means that it may not fit on the current picture, even if it lies within the limits specified by VS3DLM. VSFULL(1) or VSFULL(2) may be called before VSNEW to ensure that (x, y, z) points within the Limiting Box before transformation stay on the picture.

The transformed coordinate is a combination of the effects of VSMAG, VSROT and VSTRAN, which means that default rotation cannot be restored on its own. All transformation variables are restored by CALL VSINIT(1).

Diagnostics

[VSROT: Invalid string *XX*]¹

See also

VSFULL, VSINIT, VSMAG and VSTRAN.

SUBROUTINE VSTRAN (XTRANS, YTRANS, ZTRANS)

Name

VSTRAN – to translate *SIMPLEPLOT ViSualization* coordinates along any or all of the x - y - z axes.

Availability Section 7, released version 2-13.

Arguments

XTRANS	REAL expression	Translation along the x -axis
YTRANS	REAL expression	Translation along the y -axis
ZTRANS	REAL expression	Translation along the z -axis

Description

By default, *SIMPLEPLOT ViSualization* interprets (x, y, z) coordinates literally. However, following a call to VSTRAN, a translation value is applied to subsequent coordinates.

For example, following a call to VSTRAN(XTRANS,0.0,0.0), the point (x, y, z) is interpreted as $(x + \text{XTRANS}, y, z)$, and all subsequent objects are translated by XTRANS along the x -axis.

Similar translation can be applied to the y and z -axes by setting YTRANS and ZTRANS to non-zero values.

After a point has been translated, its (x, y, z) position changes. This means that it may not fit on the current picture, even if it lies within the limits specified by VS3DLM. VSFULL(2) may be called before VSNEW to ensure that (x, y, z) points within the Limiting Box before transformation stay on the picture.

Transformation is cumulative, so two successive calls to VSTRAN(2.0,2.0,2.0) move points 4.0 units along each axis.

The transformed coordinate is a combination of the effects of VSMAG, VSR0T and VSTRAN, which means that default translation cannot be restored on its own. All transformation variables are restored by CALL VSINIT(1).

See also

VSFULL, VSINIT, VSMAG and VSR0T.

SUBROUTINE VSUTOC (UMIN, UMAX, ICIX1, ICIX2)**Name**

VSUTOC – to define mapping from user data values to colour indices.

Availability Section 7, released version 2-13.

Arguments

UMIN, UMAX	REAL expressions	Range of user data values to be mapped
ICIX1, ICIX2	INTEGER expressions	Corresponding range of colour indices

Description

By default, *SIMPLEPLOT ViSualization* maps the full range of user data given in output sub-routines on to colour indices 1 to 15. VSUTOC selects different ranges of colour associated with a *SIMPLEPLOT ViSualization* picture.

VSUTOC maps data within a given range onto a specified set of pen indices. After CALL VSUTOC(UMIN,UMAX,ICIX1,ICIX2), each index from ICIX1 to (ICIX2 – 1) is associated with an equal range of data between UMIN and UMAX. Each range measures $\frac{UMAX-UMIN}{ICIX2-ICIX1}$ units.

Index ICIX2 represents all data values greater than or equal to UMAX. Index ICIX1 is also used for data less than UMIN.

The default action may be restored by setting UMIN greater than UMAX.

In this release of software, data may be mapped on to colour indices 0 to 95 inclusive.

Diagnostics

[VSUTOC: Colour index *I* out of range]¹

Default

CALL VSUTOC(0.0, -1.0, 0, 0) restores the default.

See also

VSCRGB and VSCHLS.

SUBROUTINE VSVRTP (RADIUS, THETA, PHI)**Name**

VSVRTP – to set the Viewing Position in terms of a radius and 2 angles for a projected picture.

Availability Section 7, released version 2-13.

Arguments

RADIUS	REAL expression	Distance of the Viewing Position from the Origin
THETA	REAL expression	Horizontal angle
PHI	REAL expression	Vertical angle

Description

VSVRTP sets a Viewing Position for *SIMPLEPLOT ViSualization* in terms of a radius and 2 angles. RADIUS is the distance between the Viewing Position and the Origin, where the maximum possible distance from the Origin to any point in the Limiting Box is $\sqrt{3}$. The Origin and Limiting Box are set by VS3DLM.

RADIUS is interpreted as being positive. A radius of $-R$ is equivalent to a radius of $+R$.

If the Viewing Position is too close to the Origin, points could be projected to infinity, or be otherwise unplotable. To prevent this happening, if the absolute value of $\text{RADIUS} \leq \sqrt{3}$, a diagnostic is issued at the next call to VSNEW, and no perspective is applied.

THETA is the horizontal angle in degrees between the Viewing Position and the Origin on the x - y plane; PHI is the vertical angle in degrees between this plane and the Line of Sight. By default, THETA=30.0, and PHI=15.0.

THETA = 0.0 along the x -axis (*ie.* at $y = 0.0$). PHI = 0.0 on the x - y plane (*ie.* at $z = 0.0$).

The change in Viewing Position does not take effect until the next call of VSNEW. VSVRTP overrides any previous call to VSVXYZ.

Default

CALL VSVRTP(0.0, 30.0, 15.0) restores the default.

See also

VS3DLM, VSINIT, VSNEW and VSVXYZ.

SUBROUTINE VSVXYZ (XVIEW, YVIEW, ZVIEW)**Name**

VSVXYZ – to set the Viewing Position for a projected picture in terms of (x, y, z) .

Availability Section 7, released version 2-13.

Arguments

XVIEW	REAL expression	x component of Viewing Position
YVIEW	REAL expression	y component of Viewing Position
ZVIEW	REAL expression	z component of Viewing Position

Description

VSVXYZ sets a Viewing Position for *SIMPLEPLOT* *ViSualization* in terms of (x, y, z) .

XVIEW, YVIEW and ZVIEW are in the underlying three-dimensional coordinates before transformation.

If the Viewing Position is too close to the Origin, points could be projected to infinity, or be otherwise unplotable. To prevent this from happening, the distance from (XVIEW, YVIEW, ZVIEW) to the Origin should be greater than the radius of the Bounding Sphere specified by VS3DLM.

If

$$XVIEW^2 + YVIEW^2 + ZVIEW^2 < \left(\frac{XSTOP - XSTART}{2}\right)^2 + \left(\frac{YSTOP - YSTART}{2}\right)^2 + \left(\frac{ZSTOP - ZSTART}{2}\right)^2$$

a diagnostic is issued at the next call to VSNEW, and no perspective is applied.

The change in Viewing Position does not take effect until the next call of VSNEW. VSVXYZ overrides any previous call to VSVRTP.

Default

See VSVRTP.

See also

VS3DLM, VSINIT, VSNEW and VSVRTP.

SUBROUTINE VSXYZ (X2ARR, Y2ARR, Z2ARR, NX, NY)**Name**

VSXYZ – to draw a surface picture from three 2-D arrays in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

X2ARR, Y2ARR, Z2ARR	REAL 2-D arrays	NX×NY arrays of user (x, y, z) values
NX, NY	INTEGER expression	Dimensions of 2-D arrays

Description

The quadrilateral data structure held in the x - y - z arrays is represented by a surface. Elements are constructed from each of the 4 adjacent elements in the 2-D arrays. The colours representing different z -values are controlled by VSUTOC.

Diagnostics

[VSXYZ: No current ViSualization picture]¹
 [VSXYZ: Invalid array dimension]¹

See also

VS3DLM, VSEDGC, VSEDGV, VSUTOC and VSXYZU.

SUBROUTINE VSXYZU (X2ARR, Y2ARR, Z2ARR, U2ARR, NX, NY)**Name**

VSXYZU – to draw contours of data in one 2-D array on a surface picture from three 2-D arrays in a *SIMPLEPLOT ViSualization* image.

Availability Section 7, released version 2-13.

Arguments

X2ARR,	REAL 2-D arrays	NX×NY arrays of user (x, y, z) values
Y2ARR,		
Z2ARR		
U2ARR	REAL 2-D array	NX×NY User data values
NX, NY	INTEGER expression	Dimensions of 2-D arrays

Description

The quadrilateral data structure held in the x - y - z arrays is represented by a surface. Contours from the corresponding U2ARR array are drawn on this surface. Elements are constructed from each of the four adjacent elements in the x - y - z arrays. The colours representing different u values are controlled by VSUTOC.

Diagnostics

[VSXYZU: No current ViSualization picture]¹
 [VSXYZU: Invalid array dimension]¹

See also

VS3DLM, VSEDGC, VSEDGV, VSUTOC and VSXYZ.

SUBROUTINE VSZ (XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELS)**Name**

VSZ – to draw a surface from 3-D data structured into elements.

Availability Section 7, released version 2-13.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELS	INTEGER expression	Number of elements

Description

VSZ draws a surface representing data structured into elements and held in parallel arrays, XARR(NPTS), YARR(NPTS) and ZARR(NPTS).

Before using VSZ, the element array I2ARR(NNODES,NELS), must be set up. The SIMPLEPLOT-PLUS subroutines ZZORDR or ZZORDN can only be used for this purpose if the surface is such that there is a single function value z for any (x, y) , otherwise the user must construct an index array identifying the indices in the x , y and z arrays to each node in each element.

The colours representing different contour levels are controlled by VSUTOC.

Diagnostics

[VSZ: No current ViSualization picture]¹
 [VSZ: Invalid array dimension]¹

See also

VSEDGC, VSEDGV, VSUTOC, and VSZU.

SUBROUTINE VSZU (XARR, YARR, ZARR, UARR, NPTS, I2ARR, NNODES, NELS)**Name**

VSZU – to draw contours of data in an array on a surface from 3-D data structured into elements.

Availability Section 7, released version 2-13.

Arguments

X2ARR, Y2ARR, Z2ARR	REAL arrays	(x, y, z) coordinates of data values in parallel arrays
U2ARR	REAL array	NPTS user data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELS	INTEGER expression	Number of elements

Description

VSZU draws a contour map of the data values in UARR(NPTS), on the surface representing data structured into planar elements and held in parallel arrays XARR(NPTS), YARR(NPTS) and ZARR(NPTS).

Before using VSZU, the element array I2ARR(NNODES,NELS) must have been set up. The SIMPLEPLOT-PLUS subroutines ZZORDR or ZZORDN can be used for this purpose if the surface is such that there is a single function value z for any (x, y) . Otherwise, the user must construct an index array identifying the indices in the x , y and z arrays to each node in each element.

The colours representing different contour levels are controlled by VSUTOC.

Diagnostics

[VSZU: No current ViSualization picture]¹

[VSZU: Invalid array dimension]¹

See also

VSEDCG, VSEEDGV, VSUTOC and VSZ.

SUBROUTINE WFCHT (Z2ARR, NPTS, NCURVS, CAPN, CAPL)**Name**

WFCHT – to draw a waterfall chart on the current picture.

Availability Section plus, released version 2-13.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NPTS	INTEGER expression	Number of columns in Z2ARR
NCURVS	INTEGER expression	Number of rows in Z2ARR
CAPN	STRING expression	Numeric axis caption
CAPL	STRING expression	Label axis caption

Description

A waterfall chart has a numeric scale for an independent variable and a label scale over which a series of staggered curves are plotted. WFCHT draws a waterfall chart on the current picture of data held in the two-dimensional array, Z2ARR(NPTS,NMAX), where NMAX is greater or equal to NCURVS, the number of curves to be plotted. Each curve corresponding to the points Z2ARR(1,n) to Z2ARR(NPTS,n) is offset from the last by an equal step and masked by curves already drawn on the waterfall chart.

NPTS and NCURVS must both be positive INTEGERS; if they are not, a diagnostic is generated and nothing is drawn. A waterfall curve must have between 2 and 1024 points.

WFCHT draws numeric and label axes which can be configured using appropriate AX* subroutines with CHAXIS='NW' and 'LW' respectively. Other characteristics of a waterfall chart can be specified using prior calls of WF*.

WFCHT draws a waterfall chart on the current 2-D picture and should therefore be preceded by the *new picture* subroutine, NEWPIC.

Diagnostics

(Constant data: default z scale used)¹
 (Too many points in waterfall curve)¹
 (Waterfall chart not all in range)²
 (WATERFALL OMITTED: INVALID DIMENSIONS)¹

See also

WF*.

SUBROUTINE WFDRAW (ZARR, NPTS)

Name

WFDRAW – to draw a single curve on a waterfall chart.

Availability Section plus, released version 2-13.

Arguments

ZARR	REAL array	Data values of curve
NPTS	INTEGER expression	Number of points in ZARR

Description

WFDRAW draws a single waterfall curve on the current picture. Each curve corresponding to the points ZARR(1) to ZARR(NPTS) is offset from the last by an equal step, and masked by waterfall curves already drawn.

Different parts of the curves are drawn using different pen pointers so that independent changes to the visibility or appearance of the parts can be achieved through pointer adjustments:

Pointer	Pen usage
---------	-----------

[1]	Unmasked part of curve with $z \geq \text{ZLEVEL}$
[2]	Masked part of curve with $z \geq \text{ZLEVEL}$
[3]	Unmasked part of curve with $z < \text{ZLEVEL}$
[4]	Masked part of curve with $z < \text{ZLEVEL}$

The first CALL WFDRAW(NPTS) on a chart sets the number of points for curve on the whole chart. Subsequent curves on the same chart are either short or incomplete if they have different values of NPTS. NPTS must be a positive INTEGER; if it is not, a diagnostic is generated and nothing is drawn. The maximum number of points per waterfall curve is limited to 1024.

WFDRAW draws a waterfall curve on the current 2-D picture therefore the first call to WFDRAW must be preceded by the *new picture* subroutine, NEWPIC.

Diagnostics

(Constant data: default z scale used)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Too many waterfall curves on picture)¹
 (Too many points in waterfall curve)¹
 (Waterfall curve not all in range)²

See also

WFEQL, WFEQN, WFNCVS, WFPNS, WFSTEP, WFZLEV and WFZSCL.

SUBROUTINE WFEQL (CSTART, CSTEP)**Name**

WFEQL – to specify the equally-spaced values on the label scale of a waterfall chart.

Availability Section plus, released version 2-13.

Arguments

CSTART	REAL expression	Minimum scale value
CSTEP	REAL expression	Interval between curves

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. Standard SIMPLEPLOT calls may be used to add axes to annotate the chart. By default, the label scale is defined to identify the curves by 1.0, 2.0, 3.0 *etc.* in the order of drawing.

WFEQL may be called to specify CSTART, the scale value to associate with the beginning of the span of the first curve, and CSTEP, the scale interval between curves.

The label scale defined by WFEQL affects axis annotations, but has no effect on the curves.

WFEQL takes effect at the start of the next waterfall chart.

Default

Calling WFEQL with CSTEP=0.0 restores the default.

See also

AXIS7, WFCHT and WFDRAW.

SUBROUTINE WFEQN (ESTART, ESTEP)**Name**

WFEQN – to specify the equally-spaced values on the numeric scale of a waterfall chart.

Availability Section plus, released 2-13.

Arguments

ESTART	REAL expression	Value of first data column
ESTEP	REAL expression	Interval between data columns

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves is plotted. By default, curves cover the full range of the numeric scale.

By default, the numeric scale on a waterfall chart is 1.0 to `REAL(NPTS)`, where `NPTS` is the number of points in the first curve drawn. `WFEQN` relates the numeric scale to the data values. `WFEQN` must be called before a waterfall chart has been started.

After a call to `WFEQN`, the numeric waterfall axis displays the range of values from `ESTART` to `ESTART + ESTEP × (NPTS − 1)`, where `NPTS` is specified as an argument to `WFCHT`/`WFDRAW`.

Default

Calling `WFEQN` with `ESTEP=0.0` restores the default.

See also

`WFCHT`, `WFDRAW`, `WFEQL` and `WFNSCL`.

SUBROUTINE WFINIT**Name**

WFINIT – to reset all defaults for waterfall charts.

Availability Section plus, released version 2-13.

Arguments

None.

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. The characteristics of waterfall charts can be controlled by various specification subroutines to change values used when plotting waterfall charts.

WFINIT cancels the effects of calls of all the waterfall specification subroutines, resetting all values to their defaults.

WFINIT has no effect on the axis characteristics of a waterfall chart.

See also

INITSP, WFEQL, WFEQN, WFNCVS, WFPNS, WFSTEP, WFZLEV and WFZSCL.

SUBROUTINE WFNCVS (NCURVS)**Name**

WFNCVS – to specify the number of curves to be accommodated on waterfall charts.

Availability Section plus, released version 2-13.

Argument

NCURVS INTEGER expression Total number of waterfall curves

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. The curves drawn on the chart can all be plotted by a single call of WFCHT, or by a succession of calls of WFDRAW.

By default, a waterfall chart drawn by WFCHT is scaled to accommodate the number of curves in the supplied data; if only one waterfall curve is drawn by WFDRAW, the scale accommodates this single curve. WFNCVS specifies an alternative number of curves, NCURVS.

Following a call to WFNCVS, the label scale is calculated to accommodate NCURVS curves for each waterfall chart. In this case, a waterfall chart drawn by WFCHT is scaled to accommodate NCURVS curves and only this number are drawn. Similarly, NCURVS curves can be drawn on the same picture by NCURVS successive calls of WFDRAW.

NCURVS must be a positive INTEGER; if not, the default is restored. The maximum number of curves that can be accommodated on a waterfall chart is 1024.

Default

CALL WFNCVS(0) restores the default.

See also

WFCHT, WFDRAW and WFSTEP.

SUBROUTINE WFNSCL (START, STOP)**Name**

WFNSCL – to specify the numeric scale for waterfall charts.

Availability Section plus, released version 2-13.

Arguments

START	REAL expression	Value at start of numeric scale
STOP	REAL expression	Value at end of numeric scale

Description

By default, the numeric scale on a waterfall chart is 1.0 to $\text{REAL}(\text{NPTS})$, where NPTS is the number of points in the first curve drawn. If WFEQN has been called to relate the plotting scales to the data values, the default numeric scale is ESTART to $\text{ESTART} + (\text{ESTEP} \times (\text{NPTS} - 1))$. WFNSCL sets an alternative scale from START to STOP . These new scale limits can extend beyond the default limits or restrict the default limits; also, the direction of the scale can be reversed by making START greater than STOP .

Default

Calling WFNSCL with $\text{START}=\text{STOP}$ restores the default.

See also

WFEQL and WFEQN .

SUBROUTINE WFPNS (IPEN1, IPEN2, IPEN3, IPEN4)**Name**

WFPNS – to specify the pens used in waterfall charts.

Availability Section plus, released version 2-13.

Arguments

IPEN1	INTEGER expression	Pen associated with [1]
IPEN2	INTEGER expression	Pen associated with [2]
IPEN3	INTEGER expression	Pen associated with [3]
IPEN4	INTEGER expression	Pen associated with [4]

Pointer Pen usage

[1]	Unmasked part of curve with $z \geq \text{ZLEVEL}$
[2]	Masked part of curve with $z \geq \text{ZLEVEL}$
[3]	Unmasked part of curve with $z < \text{ZLEVEL}$
[4]	Masked part of curve with $z < \text{ZLEVEL}$

*IPEN*i* Pen usage*

-1	plotting is omitted on all devices
0	drawn in background colour
1, 2, 3 ...	pens/bundles as specified by PENHLS/PENRGB and BUNLPR

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. Different parts of the curves are distinguished by the use of different pen pointers.

IPEN*i* can have values -1, 0, 1, 2, 3, ... *etc.*

Pointers set by WFPNS are used for waterfall curves independently of pointers set by SETPNS. This allows different defaults, and simultaneous setting of one set of pointers for the waterfall charts for axes.

Default

CALL WFPNS(1,-1,1,-1) restores the default.

See also

AXIS7, BUNLPR, SETPNS, WFCHT and WFDRAW.

SUBROUTINE WFSTEP (ZDISP)**Name**

WFSTEP – to specify the displacement between waterfall curves.

Availability Section plus, released version 2-13.

Argument

ZDISP	REAL expression	Displacement between curves relative to the span of a curve
-------	-----------------	----------------------------------------------------------------

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. Each curve is scaled to occupy an equal portion of the label scale, and the curves are displaced from each other by an equal step. By default, each curve is displaced from the next by one third of the span of a curve.

WFSTEP specifies an alternative value for ZDISP. Subsequently, label scales are calculated to cover a range dependent on a function of ZDISP, the number of curves being accommodated, and the physical length of the scale.

The value of ZDISP must be greater than -1.0 (the value of ZDISP for which the next curve would be completely obscured); if $ZDISP \leq -1.0$ the default is restored.

Default

CALL WFSTEP(-1.0) restores the default.

See also

WFCHT, WFDRAW and WFNCVS.

SUBROUTINE WFZLEV (ZLEVEL)**Name**

WFZLEV – to specify the data value at which waterfall curves can change pens.

Availability Section plus, released version 2-13.

Argument

ZLEVEL REAL expression Data value for pen change

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. If pen pointers are used to discriminate between parts of the curves, a switch of pens is made at a particular data value. By default, the switch occurs at 0.0; WFZLEV may be called to specify an alternative value, ZLEVEL, for switching pens.

Default

CALL WFZLEV(0.0) restores the default.

See also

WFCHT, WFDRAW and WFPNS.

SUBROUTINE WFZSCL (ZSTART, ZSTOP)**Name**

WFZSCL – to specify the z scales for curves on subsequent waterfall charts.

Availability Section plus, released version 2-13.

Arguments

ZSTART, REAL expressions Range of z covered
ZSTOP

Description

A waterfall chart has a numeric scale for an independent variable, and a label scale over which a series of staggered curves are plotted. Each curve is drawn on a scale covering the same z range.

By default, the z scale extends from the minimum z to the maximum z of the data as it is known at the start of a waterfall chart. This involves all the data when WFCHT is used for the chart, but only the first curve of a chart drawn by WFDRAW. WFZSCL specifies an alternative z scale to be used for all the curves on a waterfall chart. WFZSCL only takes effect when the next waterfall chart is started.

Default

Calling WFZSCL with ZSTART=ZSTOP restores the default scaling.

See also

KSCALE, KWZVAL, WFCHT and WFDRAW.

REAL FUNCTION XCALC (X, Y, Z2ARR, NX, NY, XARR)**Name**

XCALC – to interpolate $z = f(x, y)$ from 3-D data on an x -specified grid.

Availability Section 2, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

The value of z at (x, y) is evaluated by two-way linear interpolation within the rectangular cell of the grid in which (x, y) is located. If X or Y lie outside the limits of the data, XCALC returns the current no-data value.

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values, x_i , are supplied in increasing or decreasing order (*ie.* $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and the current no-data value is returned.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

NODATA, QNODAT and SFEQY.

SUBROUTINE XCNTS (Z2ARR, NX, NY, XARR)**Name**

XCNTS – to draw a contour map from 3-D data on an x -specified grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

XCNTS draws a contour map on the current picture representing 3-D data on an x -specified tartan grid. Contours are drawn for equally-spaced z values within the range of data held in Z2ARR. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

The contours drawn by XCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

CTBRKN overrides the bundled line-drawing attributes of pens associated with the four pen pointers.

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values, x_i , are supplied in increasing or decreasing order (*ie.* $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no contours are drawn.

Diagnostics

(Contour map not all in range)²
 (DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, RIDDLE, SFEQY, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SQBRKN, SQPEN, SQZLAB and SQZVAL.

SUBROUTINE XCONT (ZLEV, Z2ARR, NX, NY, XARR)

Name

XCONT – to draw a contour curve from 3-D data on an x -specified grid.

Availability Section 2, released before version 2-5.

Arguments

ZLEV	REAL expression	Contour level
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

XCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z = \text{ZLEV}$ from 3-D data (on an x -specified tartan grid) held in Z2ARR.

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values, x_i , are supplied in increasing or decreasing order (*ie.* $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no contour is drawn.

Diagnostics

(Contour curve not all in range)²
 (DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, QCURVE, RIDDLE and SFEQY.

SUBROUTINE XCUT (X1, Y1, X2, Y2, Z2ARR, NX, NY, XARR)**Name**

XCUT – to draw a 2-D curve of a surface section from 3-D data on an x -specified grid.

Availability Section 2, released before version 2-5.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of two points
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

If the surface represented by the data in Z2ARR were cut along the straight line from (x_1, y_1) to (x_2, y_2) , the side view of the section would show as a two-dimensional curve of the variation of the data along that line.

XCUT draws [1] the curve of surface height *vs.* distance from (x_1, y_1) on the current picture – suitable scales must be set up before attempting to draw a section.

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values in XARR are supplied in increasing or decreasing order (*ie.* they are *monotonic*). If the grid values are not monotonic, a diagnostic is issued and no curve is drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface section not all in range)²

See also

CTBRKN, CTCURV, CTHOLD, QCURVE and SFEQY.

SUBROUTINE XSCALE (XSTART, XSTOP, IXTYPE)**Name**

XSCALE – to specify the Cartesian horizontal scale for all 2-D plotting.

Availability Section 1, released before version 2-5.

Arguments

XSTART	REAL expression	Horizontal scale value at left edge
XSTOP	REAL expression	Horizontal scale value at right edge
IXTYPE	INTEGER expression	Type of horizontal scale

IXTYPE	Type of scale
--------	---------------

0	Centimetre
---	------------

1	Linear
---	--------

2	Logarithmic
---	-------------

3	Normal probability (%)
---	------------------------

Description

By default, the horizontal scale is linear in centimetres starting at zero. XSCALE can be used to specify the horizontal scale of a 2-D picture, leaving the vertical scale unchanged. The scale increases in the conventional direction when $x_{start} < x_{stop}$.

XSCALE resets the underlying coordinate system to Cartesian.

The same scale is used for all relevant 2-D pictures until reset.

Diagnostics

(Range ≥ 100 ; linear scale used)¹

(Range through 0; linear scale used)¹

Default

Calling XSCALE with XSTART=XSTOP, or IXTYPE=0, restores the default (the values of all arguments are otherwise ignored).

See also

EQSCAL, SCALES and YSCALE.

SUBROUTINE XSHAD (ZLEV1, ZLEV2, ISHADE, Z2ARR, NX, NY, XARR)**Name**

XSHAD – to shade the area between two contour levels from 3-D data on an x -specified grid.

Availability Section plus, released version 2-5.

Arguments

ZLEV1, ZLEV2	REAL expressions	Contour levels
ISHADE	INTEGER expression	Shading pattern number
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

XSHAD shades the area between contour levels z =ZLEV1 and ZLEV2 from 3-D data (on an x -specified grid) held in Z2ARR; the area is drawn on the current picture using shading pattern ISHADE. By default, the contours themselves are not drawn (see SHEDGE).

If data values, z , coincide with contour levels, only those equal to z_{min} are included within the shaded region, *ie.* $z_{min} \leq z < z_{max}$, where $z_{min} = \min(\text{ZLEV1}, \text{ZLEV2})$ and $z_{max} = \max(\text{ZLEV1}, \text{ZLEV2})$.

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values, x_i , are supplied in increasing or decreasing order (*ie.* $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no contours are drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, XSHDS, MPTYPE, SFEQY, SFMESH and SHEDGE.

SUBROUTINE XSHDS (Z2ARR, NX, NY, XARR)

Name

XSHDS – to draw a shaded contour map from 3-D data on an x -specified grid.

Availability Section plus, released version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

XSHDS draws a shaded contour map on the current picture from 3-D data on a x -specified grid. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of data held in Z2ARR; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values, x_i , are supplied in increasing or decreasing order (*ie.* $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no contours are drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Shaded contours not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SFEQY, SHEDGE, SHPATT, SQ*, XSHAD and XCNTS.

SUBROUTINE XSURF (Z2ARR, NX, NY, XARR)**Name**

XSURF – to start a new picture and draw a surface from 3-D data on an x -specified grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid

Description

XSURF starts a new picture, and draws a surface of the data in Z2ARR.

In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling XSURF.

XSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

SIMPLEPLOT can only interpret data on an x -specified grid if the grid values, x_i , are supplied in increasing or decreasing order (*ie.* $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no surface is drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

IS*, ISSHAD, RIDDLE, SFEQY, SFEQZ, SFEQZD, SFLIMS, SFMESH and SFZSCL.

REAL FUNCTION XYCALC (X, Y, Z2ARR, NX, NY, XARR, YARR)**Name**

XYCALC – to interpolate $z = f(x, y)$ from 3-D data on an x - y specified grid.

Availability Section 2, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

The value of z at (x, y) is evaluated by two-way linear interpolation within the rectangular cell of the grid in which (x, y) is located. If X or Y lie outside the limits of the data, XYCALC returns the current no-data value.

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values, y_i and x_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$, and $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and the current no-data value is returned.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

NODATA and QNODAT.

SUBROUTINE XYCNTS (Z2ARR, NX, NY, XARR, YARR)**Name**

XYCNTS – to draw a contour map from 3-D data on an x - y specified grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

XYCNTS draws a contour map on the current picture representing 3-D data on an x - y specified tartan grid. Contours are drawn for equally-spaced z values within the range of data held in Z2ARR. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

The contours drawn by XYCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

CTBRKN overrides the bundled line-drawing attributes of pens associated with the four pen pointers.

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values, y_i and x_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$, and $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no curves are drawn.

Diagnostics

(Contour map not all in range)²
 (DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, RIDDLE, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SQBRKN, SQPEN, SQZLAB and SQZVAL.

SUBROUTINE XYCONT (ZLEV, Z2ARR, NX, NY, XARR, YARR)**Name**

XYCONT – to draw a contour curve from 3-D data on an x - y specified grid.

Availability Section 2, released before version 2-5.

Arguments

ZLEV	REAL expression	Contour level
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

XYCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z=ZLEV$ from 3-D data (on an x - y specified tartan grid) held in Z2ARR.

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values, y_i and x_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$, and $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no curve is drawn.

Diagnostics

(Contour curve not all in range)²
 (DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, QCURVE and RIDDLE.

SUBROUTINE XYCUT (X1, Y1, X2, Y2, Z2ARR, NX, NY, XARR, YARR)**Name**

XYCUT – to draw a 2-D curve of a surface section from 3-D data on an x - y specified grid.

Availability Section 2, released before version 2-5.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of two points
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

If the surface represented by the data in Z2ARR were cut along the straight line (x_1, y_1) to (x_2, y_2) , the side view of the section would show as a two-dimensional curve of the variation of the data along that line.

XYCUT draws [1] the curve of surface height *vs.* distance from (x_1, y_1) on the current picture – suitable scales must be set up before attempting to draw a section.

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values in XARR and YARR are each supplied in increasing or decreasing order (*ie.* they are *monotonic*). If the grid values are not monotonic, a diagnostic is issued and no curve is drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface section not all in range)²

See also

CTBRKN, CTCURV, CTHOLD and QCURVE.

SUBROUTINE XYSHAD (ZLEV1, ZLEV2, ISHADE, Z2ARR, NX, NY, XARR, YARR)**Name**

XYSHAD – to shade the area between two contour levels from 3-D data on an x - y specified grid.

Availability Section plus, released version 2-5.

Arguments

ZLEV1, ZLEV2	REAL expressions	Contour levels
ISHADE	INTEGER expression	Shading pattern number
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

XYSHAD shades the area between contour levels z =ZLEV1 and ZLEV2 from 3-D data (on an x - y specified grid) held in Z2ARR; the area is drawn on the current picture using shading pattern ISHADE. By default, the contours themselves are not drawn (see SHEDGE).

If data values, z , coincide with contour levels, only those equal to z_{min} are included within the shaded region, *ie.* $z_{min} \leq z < z_{max}$, where $z_{min} = \min(\text{ZLEV1}, \text{ZLEV2})$ and $z_{max} = \max(\text{ZLEV1}, \text{ZLEV2})$.

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values, y_i and x_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$, and $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no curves are drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SFMESH, SHEDGE and XYSHDS.

SUBROUTINE XYSHDS (Z2ARR, NX, NY, XARR, YARR)**Name**

XYSHDS – to draw a shaded contour map from 3-D data on an x - y specified grid.

Availability Section plus, released version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

XYSHDS draws a shaded contour map on the current picture from 3-D data on a x - y specified grid. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of data held in Z2ARR; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values, y_i and x_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$, and $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no curves are drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Shaded contours not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SHEDGE, SHPATT, SQ*, XYSHAD and XYCNTS.

SUBROUTINE XYSURF (Z2ARR, NX, NY, XARR, YARR)**Name**

XYSURF – to start a new picture and draw a surface from 3-D data on an x - y specified grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
XARR	REAL array	NX x values of the grid
YARR	REAL array	NY y values of the grid

Description

XYSURF starts a new picture, and draws a surface of the data in Z2ARR.

In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling XYSURF.

XYSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

SIMPLEPLOT can only interpret data on an x - y specified grid if the grid values, y_i and x_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$, and $x_1 < x_2 < \dots < x_n$ or $x_1 > x_2 > \dots > x_n$). If the grid values are not monotonic, a diagnostic is issued and no surface is drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

IS*, ISSHAD, RIDDLE, SFEQZ, SFEQZD, SFLIMS, SFMESH and SFZSCL.

REAL FUNCTION YCALC (X, Y, Z2ARR, NX, NY, YARR)**Name**

YCALC – to interpolate $z = f(x, y)$ from 3-D data on a y -specified grid.

Availability Section 2, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

The value of z at (x, y) is evaluated by two-way linear interpolation within the rectangular cell of the grid in which (x, y) is located. If X or Y lie outside the limits of the data, YCALC returns the current no-data value.

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values, y_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$). If the grid values are not monotonic, a diagnostic is issued and the current no-data value is returned.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

NODATA, QNODAT and SFEQX.

SUBROUTINE YCNTS (Z2ARR, NX, NY, YARR)**Name**

YCNTS – to draw a contour map from 3-D data on a y -specified grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

YCNTS draws a contour map on the current picture representing 3-D data on a y -specified grid. Contours are drawn for equally-spaced z values within the range of data held in Z2ARR. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

The contours drawn by YCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

CTBRKN overrides the bundled line-drawing attributes of pens associated with the four pen pointers.

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values, y_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$). If the grid values are not monotonic, a diagnostic is issued and no contours are drawn.

Diagnostics

(Contour map not all in range)²
 (DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, RIDDLE, SFEQX, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SQBRKN, SQPEN, SQZLAB and SQZVAL.

SUBROUTINE YCONT (ZLEV, Z2ARR, NX, NY, YARR)**Name**

YCONT – to draw a contour curve from 3-D data on a y -specified grid.

Availability Section 2, released before version 2-5.

Arguments

ZLEV	REAL expression	Contour level
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

YCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z=ZLEV$ from 3-D data (on a y -specified tartan grid) held in Z2ARR.

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values, y_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$). If the grid values are not monotonic, a diagnostic is issued and no contour is drawn.

Diagnostics

(Contour curve not all in range)²
 (DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, QCURVE, RIDDLE and SFEQX.

SUBROUTINE YCUT (X1, Y1, X2, Y2, Z2ARR, NX, NY, YARR)**Name**

YCUT – to draw a 2-D curve of a surface section from 3-D data on a y -specified grid.

Availability Section 2, released before version 2-5.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of two points
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

If the surface represented by the data in Z2ARR were cut along the straight line joining (x_1, y_1) to (x_2, y_2) , the side view of the section would show as a two-dimensional curve of the variation of the data along that line.

YCUT draws [1] the curve of surface height *vs.* distance from (x_1, y_1) on the current picture – suitable scales must be set up before attempting to draw a section.

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values in YARR are supplied in increasing or decreasing order (*ie.* they are *monotonic*). If the grid values are not monotonic, a diagnostic is issued and no curve is drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface section not all in range)²

See also

CTBRKN, CTCURV, CTHOLD, QCURVE and SFEQX.

SUBROUTINE YSCALE (YSTART, YSTOP, IYTYPE)**Name**

YSCALE – to specify the Cartesian vertical scale for all 2-D plotting.

Availability Section 1, released before version 2-5.

Arguments

YSTART	REAL expression	y scale at bottom edge
YSTOP	REAL expression	y scale value at top edge
IYTYPE	INTEGER expression	Type of vertical scale

IYTYPE	Type of scale
--------	---------------

0	Centimetre
---	------------

1	Linear
---	--------

2	Logarithmic
---	-------------

3	Normal probability (%)
---	------------------------

Description

By default, the vertical scale is linear in centimetres starting at zero. YSCALE can be used to specify the vertical scale of a 2-D picture, leaving the horizontal scale unchanged. The scale increases in the conventional direction when $y_{start} < y_{stop}$.

YSCALE resets the underlying coordinate system to Cartesian.

The same scale is used for all relevant 2-D pictures until reset.

Diagnostics

(Range ≥ 100 ; linear scale used)¹

(Range through 0; linear scale used)¹

Default

Calling YSCALE with YSTART=YSTOP, or IYTYPE=0, restores the default (the values of all arguments are otherwise ignored).

See also

EQSCAL, SCALES and XSCALE.

SUBROUTINE YSHAD (ZLEV1, ZLEV2, ISHADE, Z2ARR, NX, NY, YARR)**Name**

YSHAD – to shade the area between two contour levels from 3-D data on a y -specified grid.

Availability Section plus, released version 2-5.

Arguments

ZLEV1, ZLEV2	REAL expressions	Contour levels
ISHADE	INTEGER expression	Shading pattern number
Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

YSHAD shades the area between contour levels z =ZLEV1 and ZLEV2 from 3-D data (on a y -specified grid) held in Z2ARR; the area is drawn on the current picture using shading pattern ISHADE. By default, the contours themselves are not drawn (see SHEDGE).

If data values, z , coincide with contour levels, only those equal to z_{min} are included within the shaded region, *ie.* $z_{min} \leq z < z_{max}$, where $z_{min} = \min(\text{ZLEV1}, \text{ZLEV2})$ and $z_{max} = \max(\text{ZLEV1}, \text{ZLEV2})$.

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values, y_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$). If the grid values are not monotonic, a diagnostic is issued and no contours are drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SFEQX, SFMESH, SHEDGE and YSHDS.

SUBROUTINE YSHDS (Z2ARR, NX, NY, YARR)**Name**

YSHDS – to draw a shaded contour map from 3-D data on a y -specified grid.

Availability Section plus, released version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

YSHDS draws a shaded contour map on the current picture from 3-D data on a y -specified grid. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of data held in Z2ARR; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values, y_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$). If the grid values are not monotonic, a diagnostic is issued and no contours are drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Shaded contours not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SFEQX, SHEDGE, SHPATT, SQ*, YSHAD and YCNTS.

SUBROUTINE YSURF (Z2ARR, NX, NY, YARR)

Name

YSURF – to start a new picture and draw a surface from 3-D data on a y -specified grid.

Availability Section 2, released before version 2-5.

Arguments

Z2ARR	REAL 2-D array	Data values over a grid
NX, NY	INTEGER expressions	Number of columns and rows in Z2ARR
YARR	REAL array	NY y values of the grid

Description

YSURF starts a new picture, and draws a surface of the data in ZARR.

In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling YSURF.

YSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

SIMPLEPLOT can only interpret data on a y -specified grid if the grid values, y_i , are supplied in increasing or decreasing order (*ie.* $y_1 < y_2 < \dots < y_n$ or $y_1 > y_2 > \dots > y_n$). If the grid values are not monotonic, a diagnostic is issued and no surface is drawn.

Diagnostics

(DATA GRID NOT MONOTONIC)¹
 (INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

IS*, RIDDLE, SFEQX, SFEQZ, SFEQZD, SFLIMS, SFMESH and SFZSCL.

REAL FUNCTION ZCALC (X, Y, XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZCALC – to interpolate $z = f(x, y)$ from ungridded 3-D data (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point
XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

The value of z at (x, y) is interpolated on a plane triangle across 3 data points surrounding (x, y) . The data points are selected from the the ungridded 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR.

If NNODES is greater than 3, an extra point in each element is generated by taking the mean of each of the coordinates of the data points of the element, and triangular sub-elements are constructed by joining each of the nodes to this extra point.

If X or Y lies outside the limits of the data, ZCALC returns the current no-data value.

Before using ZCALC, the element array I2ARR(NNODES, NELEMS) must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZCALC is more efficient than ZCALC.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

NODATA, QNODAT, ZORDEN, ZORDER and ZZCALC.

SUBROUTINE ZCNTS (XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZCNTS – to draw a contour map from ungridded 3-D data (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZCNTS draws a contour map on the current picture representing ungridded 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR. Contours are drawn for equally-spaced z values within the range of data held in ZARR. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

The contours drawn by ZCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

CTBRKN overrides the bundled line-drawing attributes of pens associated with the four pen pointers.

Before using ZCNTS the element array, I2ARR(NNODES, NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZCNTS is more efficient than ZCNTS.

Diagnostics

(Contour map not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, SFEQZ, SFLIMS, SQBRKN, SQPEN, SQZLAB, SQZVAL, ZORDEN, ZORDER and ZZCNTS.

SUBROUTINE ZCONT (ZLEV, XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZCONT – to draw a contour curve from ungridded 3-D data (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

ZLEV	REAL expression	Contour level
XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z=ZLEV$ from the ungridded 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR.

Before using ZCONT the element array, I2ARR(NNODES,NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZCONT is more efficient than ZCONT.

Diagnostics

(Contour curve not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, QCURVE, RIDDLE, ZORDEN, ZORDER and ZZCONT.

**SUBROUTINE ZCUT (X1, Y1, X2, Y2, XARR, YARR, ZARR, NPTS, I2ARR, NNODES,
NELEMS)**

Name

ZCUT – to draw a 2-D curve of a surface section from ungridded 3-D data (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

X1, Y1, X2, Y2	REAL expressions	Coordinates of two points
XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

If the surface represented by the 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR, was cut along the straight line from (x_1, y_1) to (x_2, y_2) , the side view of the section would show as a two-dimensional curve of the variation of the data along that line.

ZCUT draws [1] the curve of surface height *vs.* distance from (x_1, y_1) on the current picture – suitable 2-D scales must be set up before attempting to draw a section.

Before using ZCUT the element array, I2ARR(NNODES, NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Surface section not all in range)²

See also

CTBRKN, CTCURV, CTHOLD, QCURVE, ZORDEN and ZORDER.

SUBROUTINE ZEDGE (XARR, YARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZEDGE – to draw around the boundary of the data area covered by a set of elements (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZEDGE searches the (x, y) coordinates held in parallel arrays, XARR and YARR, and draws [1] straight lines between all pairs of nodes which are adjacent in only one element. These straight lines constitute the boundary of the area in which ZCNTS and ZCONT can draw contours with this element structure.

Before using ZEDGE the element array, I2ARR(NNODES, NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZEDGE is more efficient than ZEDGE.

Diagnostics

(Element boundary not all in range)²
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTHOLD, QCURVE, ZORDEN, ZORDER and ZZEDGE.

SUBROUTINE ZELEM (JELE, XARR, YARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZELEM – to draw a single area element.

Availability Section 2, released before version 2-5.

Arguments

JELE	INTEGER expression	Element number to be drawn
XARR, YARR	REAL arrays	(x, y) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZELEM draws [1] the boundary of the JELEth area element on the current 2-D picture.

Before using ZELEM, the element array I2ARR(NNODES, NELEMS) must be set up; ZORDER or ZORDEN can be used for this purpose.

If any part of the element is off the current picture scales, this part is omitted and a diagnostic is issued.

Diagnostics

(Element not all in range)²
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, ZELEMS, ZNUMB, ZORDEN, ZORDER and ZZELMS.

SUBROUTINE ZELEMS (XARR, YARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZELEMS – to draw the configuration of a set of area elements (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZELEMS draws [1] the boundaries of all the area elements on the current 2-D picture. The elements represent the 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR.

Before using ZELEMS the element array, I2ARR(NNODES, NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

If any part of the element is off the current picture scales, this part is omitted and a diagnostic is issued.

ZZELMS is more efficient than ZELEMS.

Diagnostics

(Elements not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTHOLD, QCURVE, ZELEM, ZORDEN, ZORDER and ZZELMS.

SUBROUTINE ZNEIGH (I2ARR, N2ARR, NNODES, NELEMS)**Name**

ZNEIGH – to set up an array of neighbours from an array of elements.

Availability Section 2, released version 2-5.

Arguments

I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	To receive element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

Some computations with ungridded data are slow because of the need to search repeatedly through the elements. Considerable savings in searching time are made possible by the introduction of an additional INTEGER array, the array of neighbours, with the same dimensions as the array of elements. ZNEIGH sets up an array of neighbours N2ARR(NNODES,NELEMS,f) from the array of elements I2ARR(NNODES,NELEMS).

For each subroutine, Z*, operating on ungridded (x, y, z) coordinates, a more efficient ZZ* subroutine is available; each ZZ* subroutine has the array N2ARR in addition to the arguments of the corresponding ZZ* subroutine.

If an array of elements needs to be set up as well as an array of neighbours, ZZORDR (or ZZORDN) is more efficient than using ZORDER (or ZORDEN) and ZNEIGH separately.

Memory for N2ARR is allocated internally, and must be freed using SPCA_free.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

ZZORDN and ZZORDR.

SUBROUTINE ZNUMB (NTORF, ETORF)**Name**

ZNUMB – to specify whether nodes and/or elements are to be numbered.

Availability Section 2, released before version 2-5.

Arguments

NTORF	LOGICAL expression	Whether to number nodes
ETORF	LOGICAL expression	Whether to number elements

Description

ZNUMB modifies the actions of subsequent calls to ZELEM, ZELEMS or ZZELMS – in addition to drawing element boundaries, they will also label each node drawn with the node number (*ie.* its position in XARR and YARR) if NTORF = .TRUE., and/or label the centre of each element drawn with the element number (*ie.* its position in the element array) if ETORF = .TRUE..

Default

CALL ZNUMB(.FALSE., .FALSE.) restores the default.

See also

LABANG, ZELEM, ZELEMS and ZZELMS.

SUBROUTINE ZORDEN (XARR, YARR, NPTS, I2ARR, NVAR, ISIZE)**Name**

ZORDEN – to reconfigure (x, y) coordinates into triangular area elements using normalized values.

Availability Section 2, released version 2-9.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	To receive data element structure, I2ARR(3, ISIZE)
NVAR	INTEGER variable	To receive number of elements
ISIZE	INTEGER expression	second dimension of I2ARR

Description

ZORDEN organizes a set of (x, y) coordinates, held in parallel arrays XARR and YARR, into a structure of non-overlapping triangular area elements covering the data, in a similar way to ZORDER. Unlike ZORDER, ZORDEN allows for dissimilar orders of magnitude in x and y , by triangulating x and y values normalized over identical ranges; the values in the arrays are not altered.

The number of triangles generated is placed into NVAR. If NVAR reaches ISIZE before the process is complete, triangulation is incomplete – a diagnostic is issued and I2ARR is filled with the partial structure and NVAR=ISIZE.

Memory for I2ARR is allocated internally, and must be freed using SPCA_free.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Triangulation data duplicated)¹
 (Triangulation incomplete)¹
 (Triangulation failed)¹
 (Triangulation impossible)¹

See also

ZORDER, ZZORDN and ZZORDR.

SUBROUTINE ZORDER (XARR, YARR, NPTS, I2ARR, NVAR, ISIZE)**Name**

ZORDER – to reconfigure (x, y) coordinates into triangular area elements.

Availability Section 2, released before version 2-5.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	To receive data element structure, I2ARR(3, ISIZE)
NVAR	INTEGER variable	To receive number of elements
ISIZE	INTEGER expression	second dimension of I2ARR

Description

ZORDER organizes a set of (x, y) coordinates, held in parallel arrays XARR and YARR, into a structure of non-overlapping triangular area elements covering the data; three node numbers (*ie.* their positions in XARR and YARR) for each triangle are placed in I2ARR.

For example, $I2ARR(1, n) = i$, $I2ARR(2, n) = j$, $I2ARR(3, n) = k$, means that the n th triangle consists of $(XARR(i), YARR(i))$, $(XARR(j), YARR(j))$ and $(XARR(k), YARR(k))$.

The number of triangles generated is placed into NVAR. If NVAR reaches ISIZE before the process is complete, triangulation is incomplete – a diagnostic is issued and I2ARR is filled with the partial structure and NVAR=ISIZE.

Memory for I2ARR is allocated internally, and must be freed using SPCA_free.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Triangulation data duplicated)¹
 (Triangulation incomplete)¹
 (Triangulation failed)¹
 (Triangulation impossible)¹

See also

ZORDEN, ZZORDN and ZZORDR.

**SUBROUTINE ZSHAD (ZLEV1, ZLEV2, ISHADE, XARR, YARR, ZARR, NPTS, I2ARR,
NNODES, NELEMS)**

Name

ZSHAD – to shade the area between two contour levels from ungridded 3-D data (without neighbours).

Availability Section plus, released version 2-5.

Arguments

ZLEV1, ZLEV2	REAL expressions	Contour levels
ISHADE	INTEGER expression	Shading pattern number
XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZSHAD shades the area between contour levels $z = \text{ZLEV1}$ and ZLEV2 from ungridded 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR. The area is drawn on the current picture using shading pattern ISHADE. By default, the contours themselves are not drawn (see SHEDGE).

If data values, z , coincide with contour levels, only those equal to z_{min} are included within the shaded region, *ie.* $z_{min} \leq z < z_{max}$, where $z_{min} = \min(\text{ZLEV1}, \text{ZLEV2})$ and $z_{max} = \max(\text{ZLEV1}, \text{ZLEV2})$.

Before using ZSHAD the element array, I2ARR(NNODES, NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZSHAD is more efficient than ZSHAD.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SFMESH, SHEDGE, ZORDEN, ZORDER, ZSHDS and ZZSHAD.

SUBROUTINE ZSHDS (XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZSHDS – to draw a shaded contour map from ungridded 3-D data (without neighbours).

Availability Section plus, released version 2-5.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZSHDS draws a shaded contour map on the current picture from ungridded 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of data held in ZARR; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

Before using ZSHDS the element array, I2ARR(NNODES,NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZSHDS is more efficient than ZSHDS.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contours not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SHEDGE, SHPATT, SQ*, ZCNTS, ZORDEN, ZORDER, ZSHAD and ZZSHDS.

SUBROUTINE ZSURF (XARR, YARR, ZARR, NPTS, I2ARR, NNODES, NELEMS)**Name**

ZSURF – to start a new picture and draw a surface from ungridded 3-D data (without neighbours).

Availability Section 2, released before version 2-5.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZSURF starts a new picture, and draws a surface representing the ungridded data (without neighbours) held in parallel arrays, XARR, YARR and ZARR.

In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling ZSURF.

ZSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

Before using ZSURF the element array, I2ARR(NNODES, NELEMS), must be set up; ZORDER or ZORDEN can be used for this purpose.

ZZSURF is more efficient than ZSURF.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

IS*, RIDDLE, SFEQZ, SFEQZD, SFLIMS, SFMESH, SFZSCL, ZORDEN, ZORDER and ZZSURF.

REAL FUNCTION ZZCALC (X, Y, XARR, YARR, ZARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)

Name

ZZCALC – to interpolate $z = f(x, y)$ from ungridded 3-D data (with neighbours).

Availability Section 2, released version 2-5.

Arguments

X, Y	REAL expressions	Coordinates of a point
XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

The value of z at (x, y) is interpolated on a plane triangle across 3 data points surrounding (x, y) . The data points are selected from the the ungridded 3-D data (without neighbours) held in parallel arrays, XARR, YARR and ZARR.

If NNODES is greater than 3, an extra point in each element is generated by taking the mean of each of the coordinates of the data points of the element, and triangular sub-elements are constructed by joining each of the nodes to this extra point.

If X or Y lies outside the limits of the data, ZZCALC returns the current no-data value.

Before using ZZCALC the element array, I2ARR(NNODES,NELEMS), and the neighbour array, N2ARR(NNODES,NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose.

ZZCALC is more efficient than ZCALC.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

NODATA, QNODAT, ZZORDN and ZZORDR.

SUBROUTINE ZZCNTS (XARR, YARR, ZARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)

Name

ZZCNTS – to draw contours from ungridded 3-D data (with neighbours).

Availability Section 2, released version 2-5.

Arguments

XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZCNTS draws a contour map on the current picture representing ungridded 3-D data (with neighbours) held in parallel arrays, XARR, YARR and ZARR. Contours are drawn for equally-spaced z values within the range of data held in ZARR. By default, an interval is allocated to give between 5 and 10 contour levels over the range.

The contours drawn by ZZCNTS use the four pen pointers as follows:

- [1] positive levels except lowest and highest of set
- [2] highest level when more than one level drawn
- [3] lowest level of set
- [4] negative and zero levels except lowest and highest of set

The element data structures specified by I2ARR and N2ARR may be created by ZZORDR or ZZORDN if required.

ZZCNTS is more efficient than ZCNTS.

Diagnostics

(Contour map not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTLABS, CTNUMB, SFEQZ, SFEQZD, SFLIMS, SFZSCL, SQBRKN, SQPEN, SQZLAB, SQZVAL, ZZORDN, ZZORDR and ZZSHDS.

SUBROUTINE ZZCONT (ZLEV, XARR, YARR, ZARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)

Name

ZZCONT – to draw a contour curve from ungridded 3-D data (with neighbours).

Availability Section 2, released version 2-5.

Arguments

ZLEV	REAL expression	Contour level
XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZCONT draws [1] a contour curve on the current picture. The contour curve corresponds to $z=ZLEV$ from the ungridded 3-D data (with neighbours) held in parallel arrays, XARR, YARR and ZARR

Before using ZZCONT the element array, I2ARR(NNODES,NELEMS), and the neighbour array, N2ARR(NNODES,NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose.

ZZCONT is more efficient than ZCONT.

Diagnostics

(Contour curve not all in range)²
(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTCURV, CTHOLD, CTLABS, CTNUMB, QCURVE, RIDDLE, ZZORDN and ZZORDR.

SUBROUTINE ZZEDGE (XARR, YARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)**Name**

ZZEDGE – to draw around the boundary of the data area covered by a set of elements (with neighbours).

Availability Section 2, released version 2-5.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZEDGE searches the (x, y) coordinates held in parallel arrays, XARR and YARR, and draws [1] straight lines between all pairs of nodes which are adjacent in only one element. These straight lines constitute the boundary of the area in which ZZCNTS and ZZCONT can draw contours with this element structure.

Before using ZZEDGE the element array, I2ARR(NNODES,NELEMS), and the neighbour array, N2ARR(NNODES,NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose.

ZZEDGE is more efficient than ZEDGE.

Diagnostics

(Element boundary not all in range)²

(INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTHOLD, QCURVE, ZZORDN and ZZORDR.

SUBROUTINE ZZELMS (XARR, YARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)**Name**

ZZELMS – to draw the configuration of a set of area elements (with neighbours).

Availability Section 2, released version 2-5.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZELMS draws [1] the boundaries of all the area elements on the current 2-D picture. The elements represent the 3-D data (with neighbours) held in parallel arrays, XARR, YARR and ZARR.

Before using ZZELMS the element array, I2ARR(NNODES,NELEMS), and the neighbour array, N2ARR(NNODES,NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose.

ZZELMS is more efficient than ZELEMS.

Diagnostics

(Elements not all in range)²
 (INVALID ARGUMENT: ARRAY SIZE)¹

See also

CTBRKN, CTHOLD, QCURVE, ZELEM, ZNUMB, ZZORDN and ZZORDR.

SUBROUTINE ZZORDN (XARR, YARR, NPTS, I2ARR, N2ARR, NVAR, ISIZE)**Name**

ZZORDN – to reconfigure (x, y) coordinates into triangular elements and an array of neighbours (using normalized values).

Availability Section 2, released version 2-9.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values in parallel arrays
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	To receive data element structure, I2ARR(3, ISIZE)
N2ARR	INTEGER 2-D array	To receive neighbour array, N2ARR(3, ISIZE)
NVAR	INTEGER variable	To receive number of elements
ISIZE	INTEGER expression	second dimension of I2ARR and N2ARR

Description

ZZORDN organizes a set of (x, y) coordinates, held in parallel arrays XARR and YARR, into a structure of non-overlapping triangular area elements covering the data. The element numbers of neighbouring elements are placed into N2ARR for use by the ZZ* subroutines.

Unlike ZZORDR, ZZORDN allows for dissimilar orders of magnitude in x and y , by triangulating x and y values normalized over identical ranges.

If NVAR reaches ISIZE before completion, a diagnostic is issued, I2ARR is filled with the partial structure and NVAR=ISIZE.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Triangulation data duplicated)¹
 (Triangulation incomplete)¹
 (Triangulation failed)¹
 (Triangulation impossible)¹

See also

ZNEIGH, ZORDEN, ZORDER and ZZORDR.

SUBROUTINE ZZORDR (XARR, YARR, NPTS, I2ARR, N2ARR, NVAR, ISIZE)**Name**

ZZORDR – to reconfigure (x, y) coordinates into triangular elements and an array of neighbours.

Availability Section 2, released version 2-5.

Arguments

XARR, YARR	REAL arrays	(x, y) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	To receive data element structure, I2ARR(3, ISIZE)
N2ARR	INTEGER 2-D array	To receive neighbour array, N2ARR(3, ISIZE)
NVAR	INTEGER variable	To receive number of elements
ISIZE	INTEGER expression	second dimension of I2ARR and N2ARR

Description

ZZORDR organizes a set of (x, y) coordinates, held in parallel arrays XARR and YARR, into a structure of non-overlapping triangular area elements covering the data. Three node numbers (*ie.* their positions in XARR and YARR) for each triangle are placed in I2ARR. At the same time, the element numbers of neighbouring elements are placed in N2ARR for use by the ZZ* subroutines.

If NVAR reaches ISIZE before the process is complete, a diagnostic is issued, I2ARR is filled with the partial structure and NVAR=ISIZE.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Triangulation data duplicated)¹
 (Triangulation incomplete)¹
 (Triangulation failed)¹
 (Triangulation impossible)¹

See also

ZNEIGH, ZORDEN, ZORDER and ZZORDN.

**SUBROUTINE ZZSHAD (ZLEV1, ZLEV2, ISHADE, XARR, YARR, ZARR, NPTS, I2ARR,
N2ARR, NNODES, NELEMS)**

Name

ZZSHAD – to shade the area between two contour levels from ungridded 3-D data (with neighbours).

Availability Section plus, released version 2-5.

Arguments

ZLEV1,	REAL expressions	Contour levels
ZLEV2		
ISHADE	INTEGER expression	Shading pattern number
XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZSHAD shades the area between contour levels $z = \text{ZLEV1}$ and ZLEV2 from ungridded 3-D data (with neighbours) held in parallel arrays, XARR, YARR and ZARR. The area is filled with shading pattern ISHADE. By default, the contours themselves are not drawn (see SHEDGE).

If data values, z , coincide with contour levels, only those equal to z_{min} are included within the shaded region, *ie.* $z_{min} \leq z < z_{max}$, where $z_{min} = \min(\text{ZLEV1}, \text{ZLEV2})$ and $z_{max} = \max(\text{ZLEV1}, \text{ZLEV2})$.

Before using ZZSHAD the element array, I2ARR(NNODES, NELEMS), and the neighbour array, N2ARR(NNODES, NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose.

ZZSHAD is more efficient than ZSHAD.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contour not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SFMESH, SHEDGE, ZZORDN, ZZORDR and ZZSHDS.

SUBROUTINE ZZSHDS (XARR, YARR, ZARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)**Name**

ZZSHDS – to draw a shaded contour map from ungridded 3-D data (with neighbours).

Availability Section plus, released version 2-5.

Arguments

XARR, YARR, ZARR	REAL arrays	(x, y, z) coordinates of data values
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZSHDS draws a shaded contour map on the current picture from ungridded 3-D data (with neighbours) held in parallel arrays, XARR, YARR and ZARR. By default, the contour curves are drawn at equally-spaced z values using an interval chosen to give between 5 and 10 contours levels over the range of data held in ZARR; each of the contour intervals is shaded with a sequence of shading patterns; the contours themselves are not drawn (see SHEDGE).

Before using ZZSHDS the element array, I2ARR(NNODES,NELEMS), and the neighbour array, N2ARR(NNODES,NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose.

ZZSHDS is more efficient than ZSHDS.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹

(Shaded contours not all in range)²

See also

CTLABS, CTNUMB, MPTYPE, SHEDGE, SHPATT, SQ*, ZCINTS, ZZORDN, ZZORDR and ZZSHAD.

SUBROUTINE ZZSURF (XARR, YARR, ZARR, NPTS, I2ARR, N2ARR, NNODES, NELEMS)**Name**

ZZSURF – to start a new picture and draw a surface from ungridded 3-D data (with neighbours).

Availability Section 2, released version 2-5.

Arguments

XARR,	REAL arrays	(x, y, z) coordinates of data values
YARR, ZARR		
NPTS	INTEGER expression	Number of data points
I2ARR	INTEGER 2-D array	Data element structure
N2ARR	INTEGER 2-D array	Element numbers of neighbours
NNODES	INTEGER expression	Number of nodes per element
NELEMS	INTEGER expression	Number of elements

Description

ZZSURF starts a new picture, and draws a surface representing the ungridded data (with neighbours) held in parallel arrays, XARR, YARR and ZARR. In order to draw a surface picture of polar data, $z = f(r, \theta)$, specify polar units with COORDS before calling ZZSURF.

ZZSURF uses the four pens pointers as follows:

- [1] $z \geq 0$, on underside of surface.
- [2] $z < 0$, on underside of surface.
- [3] $z \geq 0$, top side of surface.
- [4] $z < 0$, on top side of surface.

A shaded surface can be drawn according to a prior call of ISSHAD.

Before using ZZSURF the element array, I2ARR(NNODES,NELEMS), and the neighbour array, N2ARR(NNODES,NELEMS), must be set up; ZZORDR or ZZORDN can be used for this purpose. ZZSURF is more efficient than ZSURF.

Diagnostics

(INVALID ARGUMENT: ARRAY SIZE)¹
 (Surface not all within picture)²
 (SURFACE OMITTED: CONSTANT DATA)¹

See also

IS*, RIDDLE, SFEQZ, SFEQZD, SFLIMS, SFMESH, SFZSCL, ZZORDN and ZZORDR.

- Hershey
 - marker symbols, 174
- x - y plots
 - inquire limits, 245
- (x, y)
 - for single (x, y, z) point, 153
- x - y - z
 - comparable scales
 - proportional lengths, 334
 - similar units, 333
 - inquire limits, 242
 - specify limits, 313
- (x, y, z)
 - equivalent (x, y) and Depth, 153
 - specify Viewing Position, 358
- 2-D limits, 245
- 3-D axes, 314
- 3-D barchart, 127, 321
 - base z value, 125, 319
 - colour sequences, 126, 320
 - direction of data, 129, 324
 - inquire height, 232, 243
 - single block, 317
 - single tinted block, 318
 - size of bars, 128, 322
 - tinted, 323
- 3-D limits
 - inquire limits, 242
 - specify limits, 313
- 4-D data
 - add contours to surface, 353, 360, 362
- ADDCP7, 4
- ADDJST, 5
- ADDTOP, 6
- Angle of
 - labels, 158
 - software shading lines, 273
 - surface, 120
- Angular scale
 - convention, 227
 - user-defined, 225
- ARHEAD, 7
- Array limits
 - array index, 162
 - exclusive, 161
 - inclusive, 163
- ARROW, 8
- Arrows
 - draw, 8
 - specify
 - shafts, 9
 - size of head, 7
- ARSHFT, 9
- AXCLR, 10
- AXCRSS, 11
- Axes
 - x - y - z on surface picture, 121
 - individual, 14
 - with barchart, 33
 - with histogram, 112
 - with new picture
 - x - y axes, 12
 - polar, 222
 - surface picture, 122
 - with waterfall chart, 363
- AXES7, 12
- AXGRID, 13
- Axis
 - 3-D, 314
 - annotation
 - at intersection, 17
 - draw set of, 32
 - individual, 15
 - justification, 18
 - non-linear, 19
 - omission, 17
 - position, 16
 - style, 16
 - text direction, 20
 - time-date, 23
 - draw
 - 3-D axes, 314
 - complete axis, 14
 - individual label, 15
 - major subdivision, 25
 - minor subdivision, 26
 - set of labels, 32
 - grids
 - broken line, 13
 - draw, 13
 - intersection, 11
 - location, 24
 - non-linear annotation, 19
 - position, 11, 24
 - range, 27
 - rear plane
 - fill colour, 123, 315
 - grid colour, 124, 316
 - subdivisions
 - base value, 28
 - cancellation, 10
 - interval, 28
 - major, 25
 - minor, 26

- offset, 28
- subinterval, 31
- tick marks
 - position, 29, 30
 - style, 29, 30
- time-date
 - alternative labels, 310
 - alternative prefix/suffix, 311
 - annotation, 23
 - separators, 21
 - specify format, 309
- AXIS7, 14
- AXLAB7, 15
- AXLBAN, 16
- AXLBGP, 17
- AXLBJS, 18
- AXLBLV, 19
- AXLBSL, 20
- AXLBSP, 21
- AXLBTM, 22
- AXLBTP, 23
- AXLOCN, 24
- AXMAJ, 25
- AXMIN, 26
- AXRNGE, 27
- AXSBDV, 28
- AXSBMN, 29
- AXSBTK, 30
- AXSUBS, 31
- AXTXT7, 32
- Backspace within text string, 301
- Bar chart, 33
 - 3-D, 127, 321
 - base z value, 125, 319
 - colour sequences, 126, 320
 - composite key, 287
 - direction of data, 129, 324
 - draw axes, 33
 - individual axis, 14
 - inquire height of stacked barchart, 232, 243
 - single block, 317
 - single tinted block, 318
 - size of bars, 128, 322
 - specify
 - direction of scales, 34
 - justification, 35
 - range of scales, 36
 - type, 37
 - width of bars, 35
 - tinted, 323
- BARCMT, 33
- BARDIR, 34
- BARFMT, 35
- BARRNG, 36
- BARTYP, 37
- Base z for 3-D barcharts, 125, 319
- Blank line
 - caption area, 38
 - key, 38
 - within text string, 301
- Blanked areas
 - reset, 117
- BLNKKY, 38
- Block
 - draw a 3-D block, 317
 - draw a tinted 3-D block, 318
- BOTHK7, 39
- Box
 - boundary
 - caption areas, 40
 - current picture only, 206
 - groups of pictures, 41
 - keys, 42
 - pages, 43
 - picture, 44
 - pie chart labels, 209
 - rectangle
 - broken line, 47
 - shaded, 277
 - solid line, 83
- BOXCAP, 40
- BOXGRP, 41
- BOXKY, 42
- BOXPG2, 43
- BOXPIC, 44
- BREAK, 45
- BRKNAR, 46
- BRKNEX, 47
- BRKNCL, 48
- BRKNCV, 49
- BRKNFN, 50
- BRKNPR, 51
- BRKNPT, 52
- Broken line
 - axis grids, 13
 - box, 47
 - circle, 48
 - contours, 64
 - curve through data
 - set of coordinates, 49
 - single data set, 46
 - draw to point, 52
 - function, 50
 - hardware/software, 166
 - key entry
 - line pattern only, 165
 - with symbol, 39
 - parametric function, 51
 - sequence for contours, 295
 - thickness, 308
- Buffer flushing, 191
- Bundles, 53
- BUNLPR, 53
- BUSS Logo, 43
- Caption area
 - boundary box, 40
 - define, 73
 - entry
 - blank, 38
 - by row and column, 228

- in next space, 4
 - justification, 5
- inquire required size, 233
- reserve, 73
- reuse, 6
- user-defined position, 76
- Channel
 - specify input/output value, 119
- Characters
 - adjustable, 54
 - alternative fonts, 56
 - aspect ratio, 302
 - magnify, 304
 - masked, 55
 - minimum width, 305
 - slant (hardware only), 306
 - underlined, 57
 - width, 307
- CHDESC, 54
- CHMASK, 55
- CHSET, 56
- CHUNDL, 57
- Circle
 - broken line, 48
 - shaded area, 279
 - solid line, 84
- Clear graphics screen, 261
- CLIPLV, 58
- Clipping strategy, 58
- Close
 - SIMPLEPLOT, 91
- Close device, 91
- Clustered bar chart, 37
- Coefficients
 - polynomial input, 223
 - regression output, 224
- Colour
 - according to data values, 356
 - bundles, 53
 - edge of filled areas, 328
 - grids, 124, 316
 - lines, 341
 - pen pointers, 262
 - waterfall chart, 370
 - polygons, 332
 - polymarkers, 349
 - rear plane, 123, 315
 - reset palette, 205
 - sequences on barchart, 126, 320
 - shading patterns
 - monochrome, 289
 - number to use, 274
 - specify
 - colour separation, 190
 - single pen usage, 202
 - specify palette
 - HLS, 203, 325
 - range, 327
 - RGB, 204, 326
- Comparable x - y - z scales
 - proportional lengths, 334
 - similar units, 333
- Contour curve
 - function of 2 variables, 101
 - gridded data
 - regular, 254
 - specified x , 376
 - specified x - y , 384
 - specified y , 391
 - specify
 - broken line pattern, 64
 - curve type, 65
 - fineness of mesh, 269
 - labels, 67, 68
 - store coordinates, 66
 - ungridded data
 - with neighbours, 413
 - without neighbours, 399
- Contour map
 - function of 2 variables, 100
 - gridded data
 - regular, 253
 - specified x , 375
 - specified x - y , 383
 - specified y , 390
 - sequence of
 - broken line patterns, 295
 - labels, 298
 - levels, 299
 - pens, 296
 - specify
 - z range, 268
 - z scale, 270
 - broken line pattern, 64
 - contour levels, 265
 - curve type, 65
 - discrete contour levels, 266
 - fineness of mesh, 269
 - labels, 67, 68
 - ungridded data
 - with neighbours, 412
 - without neighbours, 398
 - values
 - inquire, 238
 - label picture, 267
- Contours
 - add to surface, 353, 360, 362
- Convert
 - INTEGER to text string, 146
 - REAL to text string, 148
 - coordinates
 - device, 155
 - page, 155
 - surface, 145
 - user, 155
 - positions, 147
 - scale limits, 149
 - time-date
 - to REAL, 150
 - to text, 151
 - to triple, 152
 - ungridded data

- with neighbours, 157
 - without neighbours, 156
- waterfall z value, 154
- Coordinates
 - Cartesian, 59
 - input, 107
 - polar, 59, 222
 - angular convention, 227
 - user-defined, 225
- COORDS, 59
- CP7LB, 60
- CP7PT, 61
- CP7XC, 62
- CP7YC, 63
- Cross section
 - broken line pattern, 64
 - function of 2 variables, 102
 - gridded data
 - regular, 255
 - specified x , 377
 - specified x - y , 385
 - specified y , 392
 - store coordinates, 66
 - ungridded data, 400
- CTBRKN, 64
- CTCURV, 65
- CTHOLD, 66
- CTLABS, 67
- CTNUMB, 68
- Cumulative histogram, 110, 116
- Curve through data
 - set of coordinates
 - broken line, 49
 - marker symbols, 170
 - shaded area, 280
 - solid line, 85
 - single data set
 - broken line, 46
 - marker symbols, 169
 - shaded area, 276
 - solid line, 82
 - specify
 - curve type, 71
 - regression, 71
 - shading limits, 293
 - with label, 159
- Curve type
 - contours, 65
 - curves through data, 71
 - surface picture, 130
- CVLBJS, 69
- CVLBPS, 70
- CVTYPE, 71
- Data
 - from device driver, 72
 - specified by colour, 356
- DDDDATA, 72
- Defaults
 - 3-D, 336
 - all, 118
 - blanked areas, 117
 - raster image, 336
 - waterfall, 367
- DEFCAP, 73
- DEFKEY, 74
- DEFKYW, 75
- DEFPOS, 76
- Depth
 - inquire limits, 244
 - of single (x, y, z) point, 153
- Descriptive position, user-defined, 76
- Device
 - specify
 - by name, 77
 - by number, 78
- Device driver
 - pass on data, 72
- DEVNAM, 77
- DEVNO, 78
- DIAGDD, 79
- DIAGLV, 80
- Diagnostic
 - device driver, 79
 - inquire status, 240
 - level, 80
 - user-defined message, 81
- DIAGOP, 81
- Direction of barchart data, 129, 324
- Dotted line, see broken line
- DRAWAR, 82
- DRAWBX, 83
- DRAWCL, 84
- DRAWCV, 85
- DRAWFN, 86
- DRAWLN, 87
- DRAWPR, 88
- Edge of filled areas
 - colour, 328
 - visibility, 329
- Edge of ungridded data
 - broken line pattern, 64
 - store coordinates, 66
 - with neighbours, 414
 - without neighbours, 401
- Elements
 - draw surface, 361
 - with added contours, 362
 - quadrilateral
 - draw surface, 359
 - draw surface with added contours, 360
- Elements of ungridded data
 - broken line pattern, 64
 - configuration
 - with neighbours, 415
 - without neighbours, 403
 - individual, 402
 - store coordinates, 66
- ENDPAG, 89
- ENDPIC, 90
- ENDPLT, 91

- EQSCAL, 92
- Equally spaced x scale, 330
- Equally spaced y scale, 331
- Error diffusion, 325–327
- Error messages, see diagnostic
- Error status, inquire, 240
- Explode pie chart segments
 - composite, 217
 - individual, 271
- Fast area-fill
 - inquire character size, 231
 - key entry, 97
 - specify
 - method used, 179
 - size of characters, 94
 - software/hardware, 93
- FFSET, 93
- FFSIZE, 94
- FIGFMT, 95
- FIGSGN, 96
- Fill colour, 332
 - rear plane, 123, 315
- Fill the available picture, 335
- Filled polygon, 345
- FILLK7, 97
- FITPAG, 98
- Flush graphics buffer, 191
- FNAREA, 99
- FNCNTS, 100
- FNCONT, 101
- FNCUT, 102
- FNRNGE, 103
- FNSHAD, 104
- FNSHDS, 105
- FNSURF, 106
- Font selection
 - hardware/software, 56
 - within text string, 301
- Format
 - REAL signs, 96
 - REAL values, 95
 - time-date
 - alternative labels, 310
 - alternative prefix/suffix, 311
 - axis labels, 309
- Frame, see page
- Frequency calculation for histograms, 109
- Function of 1 variable
 - broken line, 50
 - shaded area, 281
 - solid line, 86
 - specify range of variable, 103
- Function of 2 variables
 - contour curve, 101
 - contour map, 100
 - cross section, 102
 - inquire function range, 164
 - shaded contour map, 105
 - shaded contour range, 104
 - surface picture, 106
- variable ranges, 99
- GETXY, 107
- Graph, see picture
- Graphics device
 - close, 91
 - flush buffer, 191
 - input coordinates, 107
 - inquire
 - maximum page size, 235
 - name/number, 230
 - number of pixels, 237
 - specify
 - by name, 77
 - by number, 78
- Grid lines, 13
- Gridded data
 - convert ungridded data
 - with neighbours, 157
 - without neighbours, 156
 - regular
 - contour curve, 254
 - contour map, 253
 - cross section, 255
 - interpolation, 252
 - shaded contour map, 257
 - shaded contour range, 256
 - surface picture, 258
 - specified x
 - contour curve, 376
 - contour map, 375
 - cross section, 377
 - interpolation, 374
 - shaded contour map, 380
 - shaded contour range, 379
 - surface picture, 381
 - specified x - y
 - contour curve, 384
 - contour map, 383
 - cross section, 385
 - interpolation, 382
 - shaded contour map, 387
 - shaded contour range, 386
 - surface picture, 388
 - specified y
 - contour curve, 391
 - contour map, 390
 - cross section, 392
 - interpolation, 389
 - shaded contour map, 395
 - shaded contour range, 394
 - surface picture, 396
- GROUP, 108
- Groups of pictures
 - boundary box, 41
 - define formation, 108
- Hardware/software
 - broken line patterns, 166
 - character sets, 56
 - fast area-fill, 93

- marker symbols, 174
- shading patterns, 290
- Hershey
 - characters, 56
- Histogram
 - cumulative, 116
 - draw from frequencies
 - cumulative, 110
 - standard, 113
 - draw with axes from raw data, 112
 - frequency calculation, 109
 - inverse, 116
 - specify
 - direction of range, 114
 - direction of scales, 111
 - shading pattern, 115
 - type, 116
- HLS (Hue Light Saturation)
 - set palette, 203, 325
- Horizontal
 - bar chart, 37
 - centred label, 62
 - key, 177, 337
 - scale, 260, 378
- HSTCLC, 109
- HSTCUM, 110
- HSTDIR, 111
- HSTGRM, 112
- HSTPLT, 113
- HSTRNG, 114
- HSTSHD, 115
- HSTTYP, 116
- INITBL, 117
- Initialize
 - raster image, 343
- Initialize defaults
 - 3-D, 336
 - all, 118
 - blanked areas, 117
 - raster image, 336
 - waterfall, 367
- INITSP, 118
- Input
 - graphical, 107
 - non-graphical, 194
 - polynomial coefficients, 223
 - specify filename, 192
- Input/Output channel
 - specify value, 119
- Inquire
 - 2-D limits, 245
 - 3-D limits, 242
 - contour levels, 238
 - curve coordinates, 229
 - depth limits, 244
 - device name/number, 230
 - error status, 240
 - height of stacked barchart, 232, 243
 - limits of 3-D function, 164
 - no-data value, 234
 - number of pixels, 237
 - SIMPLEPLOT version, 239
 - size of
 - current picture, 236
 - fast area-fill characters, 231
 - key/caption area, 233
 - maximum page, 235
 - text string, 241
 - waterfall z scale, 246
- INTEGER
 - convert to text string, 146
- Interpolation, $z = f(x, y)$
 - gridded data
 - regular, 252
 - specified x , 374
 - specified x - y , 382
 - specified y , 389
 - ungridded data
 - with neighbours, 411
 - without neighbours, 397
- IOCHAN, 119
- ISANG, 120
- ISAXD7, 121
- ISAXES, 122
- ISAXFC, 123
- ISAXGC, 124
- ISBRBZ, 125
- ISBRFC, 126
- ISBRFL, 127
- ISBRSZ, 128
- ISBRUP, 129
- ISCURV, 130
- ISDIAG, 131
- ISFULL, 132
- ISMESH, 133
- ISNEW, 134
- ISRISE, 135
- ISSBAS, 136
- ISSBCK, 137
- ISSHAD, 138
- ISSKRT, 139
- ISSPAT, 140
- ISTYPE, 141
- ISVIEW, 142
- ISYUP, 143
- JOINPT, 144
- Justification
 - axis annotation, 18
 - bars, 35
 - caption/key entries, 5
 - labels drawn at point, 160
 - user-defined position, 76
- Key
 - 3-D
 - distinct data values, 339
 - horizontal, 337
 - vertical, 338
 - to shaded contour map
 - horizontal, 177

- vertical, 178
- to shading patterns, 287
- Key area
 - boundary box, 42
 - define, 74
 - inquire required size, 233
 - reserve, 74
 - reuse, 6
 - sample width, 75
 - user-defined position, 76
- Key entry
 - blank, 38
 - broken line + symbol, 39
 - broken line pattern, 165
 - fast area-fill, 97
 - marker symbol, 171
 - shading pattern, 282
- KISXY, 145
- KNUMB, 146
- KPOSXY, 147
- KREAL, 148
- KSCALE, 149
- KTREAL, 150
- KTSTR, 151
- KTTRI, 152
- KVXYD, 153
- KWZVAL, 154
- KXYXY, 155
- KZRG, 156
- KZZRG, 157
- LABANG, 158
- LABCV7, 159
- Label
 - contour curves
 - frequency, 67
 - sequence, 298
 - specify, 68
 - drawn at point
 - angle of text, 158
 - centred horizontally, 62
 - centred vertically, 63
 - justification, 160
 - text only, 60
 - title, 312
 - with marker symbol, 61
- Labelled curve
 - draw, 159
 - justification, 69
 - position of label, 70
- LABJST, 160
- Landscape page, 200
- Layout
 - distribution of margins, 167
 - fixed picture device
 - orientation, 200
 - WYSIWYG, 98
 - full page, 208
 - group of pictures, 108
 - length of paper, 201
 - picture size, 214
 - size of
 - individual margins, 210
 - individual peripheries, 198
 - overall margin, 168
 - overall periphery, 207
 - page, 197
 - start page, 187
 - start picture, 188
 - superimposed pictures, 176
 - terminate page, 89
 - terminate picture, 90
 - user-defined position of
 - page, 199
 - picture, 211
- Lift pen, 45
- LIMEXC, 161
- LIMIDX, 162
- LIMINC, 163
- Limiting Box
 - colour, 341
 - draw around picture, 340
 - inquire scales, 242
 - specify scales, 313
- Limits
 - 3-D function range, 164
 - data range
 - array index, 162
 - exclusive, 161
 - inclusive, 163
- LIMSFN, 164
- Line
 - break a line, 45
 - broken line, 52
 - colour, 341
 - solid line, 144
- Line plots, 87
- Line spacing, 303
- Linear regression
 - coefficients, 224
 - curve through data, 71
- LINEK7, 165
- LINSET, 166
- Logarithmic scales, 260
- Logo
 - on boundary, 43
- Magnification, 342
 - line thickness, 308
 - text, 304
- MARGDV, 167
- MARGIN, 168
- Margin
 - page (periphery)
 - individual, 198
 - overall, 207
 - picture
 - distribution, 167
 - individual, 210
 - overall size, 168
- MARKAR, 169
- MARKCV, 170

- Marker symbol, 350
 - clipping strategy, 58
 - colour index, 349
 - draw set, 169, 170
 - drawn at point
 - symbol only, 172
 - with text label, 61
 - key entry
 - symbol only, 171
 - with broken line pattern, 39
 - masked, 173
 - size, 175, 351
 - software/hardware, 174
 - thickness, 308
- MARKK7, 171
- MARKPT, 172
- Mask
 - cancel masked areas, 117
 - characters, 55
 - marker symbols, 173
- Maximum/minimum of array
 - array index, 162
 - exclusive, 161
 - inclusive, 163
- Messages, see diagnostic
- Metafile
 - output
 - comment line, 181
 - omit page, 184
 - start, 183
 - redraw complete file, 249
 - redraw line-by-line
 - draw, 182
 - start, 186
 - terminate, 180
 - without device output, 185
- MKMASK, 173
- MKSET, 174
- MKSIZE, 175
- Moveable position, 76
- MOVEON, 176
- MPK7H, 177
- MPK7V, 178
- MPTYPE, 179
- MTCLOS, 180
- MTCOMM, 181
- MTDRAW, 182
- MTFILE, 183
- MTMISS, 184
- MTONLY, 185
- MTOPEN, 186
- Neighbours, ungridded data, 404
- New page
 - boundary box, 43
 - with new picture, 188
 - without picture, 187
- New picture
 - 3-D, 343
 - boundary box, 44
 - device control, 195
 - empty surface picture, 134
 - polar, 222
 - surface picture
 - x specified data, 381
 - x - y specified data, 388
 - y specified data, 396
 - regular gridded data, 258
 - ungridded data, 410, 420
 - with x - y axes, 12
 - without axes, 188
- NEWPAGE, 187
- NEWPIC, 188
- No-data value
 - inquire, 234
 - specify, 189
- NODATA, 189
- Normal probability scales, 260
- Omit pie chart segments
 - composite, 219
 - individual, 272
- ONEPEN, 190
- OUTBUF, 191
- Output
 - non-graphical, 194
 - polynomial coefficients, 224
 - preview, 98
 - raster image, 344
 - reduce polylines, 259
 - specify filename, 192
- Output channel
 - specify value, 119
- OWNFIL, 193
- OWNIO, 194
- OWNNEW, 195
- PAGE, 197
- Page
 - boundary box, 43
 - fixed picture device
 - layout, 98
 - orientation, 200
 - peripheral margins
 - individual, 198
 - overall, 207
 - size of
 - inquire, 235
 - specify, 197
 - start, 187
 - termination, 89
 - user-defined position, 199
- PAGMRG, 198
- PAGPOS, 199
- PAGVW, 200
- Palette
 - reset, 205
 - specify by colour range, 327
 - specify by HLS, 203, 325
 - specify by RGB, 204, 326
- PAPINC, 201
- Parametric function

- broken line, 51
- shaded area, 283
- solid line, 88
- PEN, 202
- Pen, see colour
- Pen pointers, 262
 - waterfall chart, 370
- Pen selection
 - bundles, 53
 - monochrome shading, 289
 - pen pointers, 262
 - sequence, 296
 - single, 202
 - within text string, 301
- PENHLS, 203
- PENRGB, 204
- PENRST, 205
- PERIM, 206
- PERIPH, 207
- Periphery
 - individual sizes, 198
 - minimize, 208
 - overall size, 207
- Perspective, 357, 358
- PGFULL, 208
- Phi (ϕ), 357
- PIBOXL, 209
- PICMRG, 210
- PICPOS, 211
- PICRST, 212
- PICSAV, 213
- PICSIZ, 214
- Picture
 - boundary box, 44
 - boxed individually, 206
 - group layout, 108
 - margins
 - distribution, 167
 - individual, 210
 - overall size, 168
 - restore picture, 212
 - save picture, 213
 - size
 - inquire, 236
 - specify, 214
 - start without axes, 188
 - superimposed, 176
 - termination, 90
 - user-defined position, 211
- PIDIAM, 215
- Pie chart
 - boxed labels, 209
 - composite key, 287
 - contents of labels, 218
 - diameter, 215
 - draw, 216
 - explode segments, 217, 271
 - omit segments, 219, 272
 - position of labels, 220
 - tilted, 221
- PIECHT, 216
- PIEXPL, 217
- PIINCL, 218
- PIOMIT, 219
- PIOSL, 220
- PITILT, 221
- Pixels, inquire number of, 237
- Polar plot
 - angular convention, 227
 - degrees, 59
 - individual axis, 14
 - new picture and axes, 222
 - partial plots, 92
 - radians, 59
 - user-defined scale, 225
- POLAR7, 222
- POLIN, 223
- POLOUT, 224
- POLRNG, 225
- POLY, 226
- Polygon
 - draw filled polygon, 345
 - draw tinted polygon, 346
 - edge colour, 328
 - edge visibility, 329
 - fill colour, 332
- Polyline, 347
 - colour, 341
 - draw tinted polyline, 348
- Polymarker, 350
 - colour index, 349
 - size, 351
- Polynomial
 - FUNCTION, 226
 - coefficients
 - input, 223
 - output, 224
- POLZER, 227
- Portrait page, 200
- Preview, 98
- Proportional length scales, 334
- PUTCP7, 228
- Pyramid bar chart, 37
- QCURVE, 229
- QDEV, 230
- QFFSIZ, 231
- QIBRFL, 232
- QKYCAP, 233
- QNODAT, 234
- QPAGE, 235
- QPIC, 236
- QPIXLS, 237
- QSFLAB, 238
- QSPLLOT, 239
- QSTAT, 240
- QSTR7, 241
- Quadratic regression
 - coefficients, 224
 - curve through data, 71
- Quadrilateral elements
 - draw surface, 359

- with added contours, 360
- QV3DLM, 242
- QVBRFL, 243
- QVDPLM, 244
- QVSCAL, 245
- QWZSCL, 246
- Radius, Theta, Phi
 - specify Viewing Position, 357
- RANGE, 247
- Range bars, 247
- Range of colours
 - set palette, 327
- RASTER, 248
- Raster image
 - initialize image, 343
 - output image, 344
- REAL
 - convert to text string, 148
 - sign format, 96
 - value format, 95
- Rear plane
 - fill colour, 123, 315
 - grid colour, 124, 316
- Rectangle
 - broken line, 47
 - shaded area, 277
 - solid line, 83
- REDRAW, 249
- Redraw metafile
 - complete file, 249
 - line-by-line, 182
- Reduce polylines, 259
- Regression
 - coefficients, 224
 - curve through data, 71
- Regular grid
 - draw surface, 352
 - with added contours, 353
 - equally spaced x scales, 330
 - equally spaced y scales, 331
- RESCLR, 250
- Reserved areas
 - cancel, 250
 - define
 - captions, 73
 - keys, 74
 - specify which area is used, 251
- Reset all defaults, 118
- Reset blanked areas, 117
- RESNXT, 251
- Restore picture, 212
- Reuse of caption areas/keys, 6
- RGB (Red Green Blue)
 - set palette, 204, 326
- RGCALC, 252
- RGCNTS, 253
- RGCONT, 254
- RG CUT, 255
- RGSHAD, 256
- RGSHDS, 257
- RGSURF, 258
- RIDDLE, 259
- Rotation, 354
- Save picture, 213
- SCALES, 260
- Scales
 - z scale, 270
 - 2-D limits, 245
 - angular
 - convention, 227
 - user-defined, 225
 - bar chart
 - direction, 34
 - range, 36
 - Cartesian
 - x and y scales, 260
 - x scale, 378
 - y scale, 393
 - comparable x - y - z scales
 - proportional lengths, 334
 - similar units, 333
 - convert limits, 149
 - equally spaced x scale, 330
 - equally spaced y scale, 331
 - fill the available picture, 335
 - histogram
 - direction, 111
 - range, 114
 - inquire 3-D limits, 242
 - non-linear, 260
 - polar, 92
 - restore scale, 212
 - save scale, 213
 - set scales, 343
 - similar linear x - y , 92
 - specify 3-D limits, 313
- SCLEAR, 261
- Screen clear, 261
- Segment of pie chart
 - explode
 - composite, 217
 - individual, 271
 - omit
 - composite, 219
 - individual, 272
- Sequence of
 - broken line patterns, 295
 - contour labels, 298
 - contour levels, 299
 - pens, 296
 - shading patterns, 297
- SETPNS, 262
- SFEQX, 263
- SFEQY, 264
- SFEQZ, 265
- SFEQZD, 266
- SFLAB, 267
- SFLIMS, 268
- SFMESH, 269
- SFZSCL, 270

- SGEXPL, 271
- SGOMIT, 272
- Shaded area
 - between 2 curves
 - function values, 275
 - set of coordinates, 278
 - box, 277
 - circle, 279
 - curve through data
 - set of coordinates, 280
 - single data set, 276
 - function of 1 variable, 281
 - parametric function, 283
 - specify
 - boundary drawn, 285
 - type of area, 293
 - user-defined
 - start, 292
 - terminate, 291
- Shaded contour map
 - draw contour curves, 285
 - function of 2 variables, 105
 - gridded data
 - regular, 257
 - specified x , 380
 - specified x - y , 387
 - specified y , 395
 - key
 - horizontal, 177
 - vertical, 178
 - sequence of
 - labels, 298
 - levels, 299
 - pens, 296
 - shading patterns, 297
 - shading method, 179
 - ungridded data
 - with neighbours, 419
 - without neighbours, 409
- Shaded contour range
 - draw contour curves, 285
 - function of 2 variables, 104
 - gridded data
 - regular, 256
 - specified x , 379
 - specified x - y , 386
 - specified y , 394
 - shading method, 179
 - ungridded data
 - with neighbours, 418
 - without neighbours, 408
- Shaded contours
 - add to surface, 353, 360, 362
- Shading patterns
 - draw complete key, 287
 - fast area-fill, 179
 - histogram, 115
 - key entry, 282
 - software/hardware, 290
 - specify
 - all details, 284
 - hatching angles, 273
 - individual, 288
 - number of colours, 274
 - sequence, 297
 - single colour, 289
 - software line separation, 286
 - uniform, 294
- SHANGS, 273
- SHCOLS, 274
- SHDEA2, 275
- SHDEAR, 276
- SHDEBX, 277
- SHDEC2, 278
- SHDECL, 279
- SHDECV, 280
- SHDEFN, 281
- SHDEK7, 282
- SHDEPR, 283
- SHDESC, 284
- SHEDGE, 285
- SHGAP, 286
- SHKEYS, 287
- SHPATT, 288
- SHPEN, 289
- SHSET, 290
- SHSTOP, 291
- SHSTRT, 292
- SHTYPE, 293
- SHUNIF, 294
- Similar linear x - y scales, 92
- Similar unit scales, 333
- SIMPLEPLOT
 - close, 91
 - inquire version, 239
 - reset all defaults, 118
- Size of
 - arrow heads, 7
 - bars, 128, 322
 - characters (width), 307
 - fast area-fill characters, 94
 - inquire
 - current picture, 236
 - key/caption area, 233
 - maximum page, 235
 - text string, 241
 - key sample, 75
 - margins
 - individual, 210
 - overall, 168
 - marker symbols, 175
 - page, 197
 - peripheral margins
 - individual, 198
 - overall, 207
 - pictures, 214
 - pie chart diameter, 215
 - polymarkers, 351
- Software/hardware
 - broken line patterns, 166
 - character sets, 56
 - fast area-fill, 93

- marker symbols, 174
- shading patterns, 290
- Solid line
 - box, 83
 - circle, 84
 - curve through data
 - set of coordinates, 85
 - single data set, 82
 - draw to point, 144
 - function, 86
 - line plot, 87
 - parametric function, 88
- Specifications
 - format of specifications, 3
- SPR form, 2
- SQBRKN, 295
- SQPEN, 296
- SQSHAD, 297
- SQZLAB, 298
- SQZVAL, 299
- Stacked barchart, 37
 - 3-D, 127, 321
 - base z value, 125, 319
 - direction of data, 129, 324
 - distinguish data sets by colour, 126, 320
 - inquire height, 232, 243
 - size of bars, 128, 322
 - tinted, 323
- Stacking direction, 129, 324
- Start new picture, see new picture
- Store curve coordinates, 66
- STRCHS, 300
- STRLV, 301
- Subscripts, 301
- Superimposed pictures, 176
- Superscripts, 301
- Surface
 - from elements, 361
 - with added contours, 362
 - from quadrilateral elements, 359
 - with added contours, 360
 - from regular grid, 352
 - with added contours, 353
- Surface picture
 - axes
 - on current picture, 121
 - with new picture, 122
 - convert coordinates, 145
 - draw x - y - z axes, 121
 - empty picture, 134
 - function of 2 variables, 106
 - gridded data
 - regular, 258
 - specified x , 381
 - specified x - y , 388
 - specified y , 396
 - individual axis, 14
 - shaded surface
 - backdrop, 137
 - base, 136
 - shading pattern, 140
 - skirt, 139
 - type of shading, 138
 - shading technique, 248
 - specify
 - x grid, 263
 - y grid, 264
 - z range, 268
 - z scale, 270
 - x - y - z diagram, 131
 - angle, 120
 - contour levels, 265
 - curve type, 130
 - discrete contour levels, 266
 - fineness of mesh, 133, 269
 - mirror image, 143
 - proportions, 135
 - size, 132
 - type of surface, 141
 - view point, 142
 - ungridded data
 - with neighbours, 420
 - without neighbours, 410
 - values
 - inquire, 238
 - label picture, 267
- Surface section
 - function of 2 variables, 102
 - regular, 255
 - specified x , 377
 - specified x - y , 385
 - specified y , 392
 - ungridded data, 400
- Symbol, see marker symbol, 350
- Terminate
 - page, 89
 - picture, 90
 - plotting, 91
 - user-defined shaded area, 291
- Text
 - clipping strategy, 58
 - embedded commands
 - interpretation, 301
 - special characters, 300
 - inquire physical size, 241
 - masked, 55
 - specify
 - angle, 158
 - aspect ratio, 302
 - hardware/software, 56
 - justification, 160
 - line spacing, 303
 - magnification, 304
 - minimum width, 305
 - slant (hardware only), 306
 - width, 307
 - thickness, 308
 - title, 312
- TEXTAR, 302
- TEXTLF, 303
- TEXTMG, 304

- TEXTMN, 305
- TEXTSL, 306
- TEXTSZ, 307
- THCKMG, 308
- Theta (θ), 357
- Time-date
 - axis
 - components, 22
 - separators, 21
 - axis annotation, 23
 - to REAL, 150
 - convert to text, 151
 - convert to triple, 152
 - load
 - alternative labels, 310
 - alternative prefix/suffix, 311
 - specify format, 309
- TIMFMT, 309
- TIMLDA, 310
- TIMLDC, 311
- Tinted barchart, 323
- Tinted block, 318
- Tinted polygon, 346
- Tinted polyline, 348
- Title
 - text string, 312
 - user-defined position, 76
- TITLE7, 312
- Transformation
 - magnification, 342
 - rotation, 354
 - translation, 355
- Translation, 355
- Triangulation
 - normalized
 - with neighbour generation, 416
 - without neighbours, 406
 - standard
 - with neighbour generation, 417
 - without neighbours, 407
- Underline
 - all text, 57
 - within text string, 301
- Ungridded data
 - cross section, 400
 - element, 402
 - neighbour generation, 404
 - number nodes/elements, 405
 - triangulation
 - with neighbour generation, 416, 417
 - without neighbours, 406, 407
 - with neighbours
 - boundary, 414
 - contour curve, 413
 - contour map, 412
 - convert to gridded, 157
 - element configuration, 415
 - interpolation, 411
 - shaded contour map, 419
 - shaded contour range, 418
 - surface picture, 420
 - triangulation, 416, 417
 - without neighbours
 - boundary, 401
 - contour curve, 399
 - contour map, 398
 - convert to gridded, 156
 - element configuration, 403
 - interpolation, 397
 - neighbour generation, 404
 - shaded contour map, 409
 - shaded contour range, 408
 - surface picture, 410
 - triangulation, 406, 407
- Uniform software shading, 294
- Units
 - coordinate interpretation, 59
 - similar scales, 92
- Update the picture, 191
- User-defined
 - angular scale, 225
 - descriptive position, 76
 - polynomial function, 226
 - position of
 - page, 199
 - picture, 211
 - shaded area
 - start, 292
 - terminate, 291
- Version
 - inquire SIMPLEPLOT version, 239
- Vertical
 - bar chart, 37
 - centred label, 63
 - key, 178, 338
 - scale, 260, 393
- Viewing position
 - (Radius,Theta,Phi), 357
 - (x, y, z), 358
- Visibility
 - edge of filled areas, 329
- VS3DLM, 313
- VSAXDR, 314
- VSAXFC, 315
- VSAXGC, 316
- VSBFL, 317
- VSBFLTN, 318
- VSBREBZ, 319
- VSBREFC, 320
- VSBREFL, 321
- VSBRSZ, 322
- VSBRTN, 323
- VSBRRUP, 324
- VSCHLS, 325
- VSCRGB, 326
- VSCRNG, 327
- VSEDC, 328
- VSEDCV, 329
- VSEQX, 330
- VSEQV, 331

- VSFILC, 332
- VSFIT, 333
- VSFITP, 334
- VSFULL, 335
- VSINIT, 336
- VSK7H, 337
- VSK7V, 338
- VSKEYS, 339
- VSLBOX, 340
- VSLINC, 341
- VSMAG, 342
- VSNEW, 343
- VSOUT, 344
- VSPGFL, 345
- VSPGTN, 346
- VSPLDR, 347
- VSPLTN, 348
- VSPMC, 349
- VSPMDR, 350
- VSPMMG, 351
- VSRG, 352
- VSRGU, 353
- VSROT, 354
- VSTRAN, 355
- VSUTOC, 356
- VSVRTP, 357
- VSVXYZ, 358
- VSXYZ, 359
- VSXYZU, 360
- VSZ, 361
- VSZU, 362
- Waterfall chart
 - z scale, 373
 - convert z value, 154
 - curve displacement, 371
 - draw axes, 363
 - draw complete, 363
 - draw curve, 364
 - individual axis, 14
 - initialize, 367
 - inquire z scale, 246
 - label scale, 365
 - number of curves, 368
 - numeric scale
 - interval, 366
 - limits, 369
 - pen change level, 372
 - pen usage, 370
- WFCHT, 363
- WFDRAW, 364
- WFEQL, 365
- WFEQN, 366
- WFINIT, 367
- WFNCVS, 368
- WFNSCL, 369
- WFPNS, 370
- WFSTEP, 371
- WFZLEV, 372
- WFZSCL, 373
- Width of bars, 128, 322
- WYSIWYG layout, 98
- x scale, 378
 - equal spacing between values, 330
- x-specified data
 - contour curve, 376
 - contour map, 375
 - cross section, 377
 - interpolation, 374
 - shaded contour map, 380
 - shaded contour range, 379
 - surface picture, 381
- x-y axes
 - with new picture, 12
- x-y plots
 - no-data value
 - inquire, 234
 - specify, 189
- x-y scales
 - linear and non-linear, 260
 - similar linear, 92
- x-y specified data
 - contour curve, 384
 - contour map, 383
 - cross section, 385
 - interpolation, 382
 - shaded contour map, 387
 - shaded contour range, 386
 - surface picture, 388
- x-y-z
 - diagram, 131
- XCALC, 374
- XCNTS, 375
- XCONT, 376
- XCUT, 377
- XSCALE, 378
- XSHAD, 379
- XSHDS, 380
- XSURF, 381
- XYCALC, 382
- XYCNTS, 383
- XYCONT, 384
- XYCUT, 385
- XYSHAD, 386
- XYSHDS, 387
- XYSURF, 388
- y scale, 393
 - equal spacing between values, 331
- y-specified data
 - contour curve, 391
 - contour map, 390
 - cross section, 392
 - interpolation, 389
 - shaded contour map, 395
 - shaded contour range, 394
 - surface picture, 396
- YCALC, 389
- YCNTS, 390
- YCONT, 391
- YCUT, 392

YSCALE, 393
YSHAD, 394
YSHDS, 395
YSURF, 396

z
 base value for 3-D barcharts, 125, 319
z range
 contour map, 268
 surface picture, 268
z scale
 contour map, 270
 surface picture, 270
 waterfall chart, 373

ZCALC, 397
ZCNTS, 398
ZCONT, 399
ZCUT, 400
ZEDGE, 401
ZELEM, 402
ZELEMS, 403
ZNEIGH, 404
ZNUMB, 405
ZORDEN, 406
ZORDER, 407
ZSHAD, 408
ZSHDS, 409
ZSURF, 410
ZZCALC, 411
ZZCNTS, 412
ZZCONT, 413
ZZEDGE, 414
ZZELMS, 415
ZZORDN, 416
ZZORDR, 417
ZZSHAD, 418
ZZSHDS, 419
ZZSURF, 420

